MADISOUND SPEAKER COMPONENTS

Audiophile Price List — January 2008

Central Time Hours: 9:00 a.m. to 5:00 p.m. Monday - Friday; 10:00 a.m. to 2:00 p.m. Saturday

Madisound Air Core Inductors						
mH Size		Wire gauge	$DCR\Omega$		Cost	
.10	SB/MB	20/19	.1 / .1	100	\$2.40	
.15	SB/MB	20/19	.1 / .1	100	2.50	
.20	SB/MB	20/19	.2 / .17	100	2.70	
.22	МВ	19	.18	100	2.70	
.25	SB/MB	20/19	.31 / .2	100	2.75	
.30	SB/MB	20/19	.34 / .3	100	2.95	
.33	МВ	19	.3	100	3.10	
.35	SB/MB	20/19	.38 / .3	100	3.10	
.40	SB/MB	20/19	.4 / .3	100	3.20	
.45	SB/MB	20/19	.43 / .3	100	3.25	
.47	MB	19	.34	100	3.25	
.50	SB/MB	20/19	.44 / .35	100	3.35	
.55	MB	19	.37	100	3.45	
.56	SB	20	.48	100	3.45	
.60	SB/MB	20/19	.5 / .37	100	3.60	
.67	SB/MB	20/19	.53 / .4	100	3.65	
.70	МВ	19	.41	100	3.85	
.75	МВ	19	.43	100	4.00	
.80	SB/MB	22/19	.88 / .45	100	4.20	
.85	MB	19	.48	100	4.30	
.90	MB	19	.5	100	4.35	
1.00	MB	19	.5	150	4.70	
1.25	MB	19	.7	150	5.00	
1.50	MB	19	.75	150	5.40	
1.75	LB	19	.8	150	6.50	
1.80	МВ	19	.82	150	6.75	
2.00	LB	19	.9	150	7.10	
2.25	LB	19	.95	150	7.30	
2.50	LB	19	1.0	150	7.70	
2.75	LB	19	1.05	150	8.00	
3.00	LB	19	1.1	150	8.30	
3.50	LB	19	1.2	150	9.00	
4.00	LB	19	1.3	150	9.50	

	T
N. Managara	
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
)

Madisound Iron Core Inductors						
4.5 LB	18	.75	250	\$9.75		
5.0 LB	18	.80	250	10.00		
6.0 LB	18	1.0	250	10.65		
7.0 LB	18	1.2	250	11.80		
8.0 LB	18	1.4	250	12.40		
10.0 LB	18	1.4	250	14.00		
12.0 XLB	18	1.1	250	14.50		
15.0 XLB	18	1.3	250	15.50		
18.0 XLB	18	1.5	250	16.65		
†SB bobbin 38mm Ø x 20mm tall; MB bobbin 48mm Ø x 23mm tall						


LB bobbin 59mm \emptyset x 32mm tall; XLB bobbin 54mm \emptyset x 55mm tall

Surplus Capacitors				
2.0 mfd	.35			
2.7 mfd	Panasonic mylar, 10%, 250V long leads	.30		
2.7 mfd	Richey mylar, 250V, Dipped, Red	.30		
3.0 mfd	T.I. mylar 10% 100V long leads	.30		
3.3 mfd	Panasonic Polyprop. 10% 200V radial	.60		
5.0 mfd	GE Polyprop. , 400V, 10%, axial	.75		
10.0 mfd	TYEE Polyprop. 100V, 30 x 27 x 18m	.90		

Wire-Wound Sand Cast Resistors		
15 Watt 12.5mm T x 12mm W x 46.5mm L		
25 Watt 13mm T x 14.5mm W x 60mm L		
1, 1.5, 2,2.5, 3, 3.5, 4, 4.5, 5, 5.5,6,6.5, 7, 7.5,8,9, 10, 14, 23Ω 15 W 10%	\$.45 each	
2.2, 2.7, 3.3, 3.9, 4.7, 5.6, 6.8, 8.2, 10, 12, 15, 20, 25Ω 25 Watt 10%	.65 each	

Eagle - Metal Oxide Film Non-Inductive Resistors			
5%, 10Watt, 8.5mmØ x 32mmL, 33mm leads			
1.5, 2.2, 2.5, 2.7, 3, 3.3, 3.5, 4, 4.7, 5, 5.6, 6,6.8, 7, 8, 9, 10, 12, 14, 15, 16,	\$1.20 each		
20, 30, 50 Ω			
Circuit Boards for Crossovers, Soldered Lugs, Glass Froxy			





Autosound Steel Grills with Mounting Rings						
4.5" \$3.50 6.5" \$5.00 10" \$7.00					\$7.00	
5.25"	4.00	8"	6.00	12"	10.00	





MADISOUND SPEAKER COMPONENTS, INC. 8608 UNIVERSITY GREEN P.O. BOX 44283

MADISON, WI 53744-4283 U.S.A. TEL: 608-831-3433 FAX: 608-831-3771 e-mail: info@madisound.com Web Page: http://www.madisound.com



MADISOUND LOW RESISTANCE INDUCTORS

MADISOUND is pleased to announce that we are now stocking SIDEWINDER and SLEDGEHAMMER Audio Inductors. These are audiophile grade inductors using 16 gauge wire with the following specifications:

Hard drawn copper for maximum conductivity.

Nylon-Polypropylene coating for maximum scuff and abrasion protection.

Better than 101.3 % of National Electrical and Manufacturing Association (NEMA) standard sample.

Power Handling capacity: more than 350 watts before saturation.




SIDEWINDER AUDIO INDUCTORS - 16 AWG

	RE INDU			RE INDU		AIR CO		
Bobbin:	48mmØ x	23mm tall	Bobbin:	59mmØ :	x 32mm tall	Bobbin:	59mmØ z	x 32mm tall
.1 mH	.1	\$3.55	.50mH	.22	\$7.00	1.00mH	.34	\$9.60
.15	.11	3.65	.55	.23	7.35	1.25	.38	10.50
.20	.14	4.00	.60	.24	7.50	1.50	.43	11.80
.22	.14	4.10	.65	.27	7.85	1.80	.47	12.50
.25	.15	4.25	.70	.28	8.20	2.00	.52	13.50
.30	.16	4.80	.75	.29	8.45	2.25	.54	13.80
.33	.18	5.10	.80	.30	8.70	2.50	.59	14.30
.39	.18	5.45	.85	.31	8.85	Bobbin: 5	54mmØ x	55mm tall
.45	.2	5.75	.90	.33	9.10	3.00	.72	18.00
						3.50	.76	18.25

SLEDGEHAMMER STEEL LAMINATE INDUCTORS - 15 AWG

MADISOUND is pleased to offer a line of LOW distortion inductors. We are utilizing the good magnetic characteristics of high permeable steel alloy to give you inductors with high power capability, low DCR and low distortion. The inductors show significantly lower distortion in the low frequencies and will give cleaner sound reproduction for bass drivers, especially subwoofers.

Just as you would use polypropylene capacitors for a noticeably cleaner sound in your midranges and tweeters, Madisound Sledgehammer Steel inductors will give you noticeably clearer bass. Sledgehammer Steel Laminate inductors use hard drawn 15 gauge copper wire for maximum conductivity and low DC resistance.



mН	DCR	Price	mН	DCR	Price
Dim: 32n	nm x 45mm	x 48mm	Dim: 32	mm x 45mm	x 95mm
1.0	.100	\$8.65	5.0	.242	16.00
1.25	.120	9.25	5.5	.257	16.25
1.5	.140	10.05	6.0	.272	16.65
2.0	.156	10.30	7.0	.307	17.55
2.25	.162	10.90	8.0	.345	18.55
2.5	.164	11.20	10.0	.376	20.25
2.7	.168	11.90	12.0	.426	21.75
3.0	.178	12.05	13.0	.450	23.00
3.3	.185	12.75	15.0	.505	24.00
3.7	.200	13.45	18.0	.550	24.55
4.0	.210	\$14.70	20.0	.595	27.15

Values between sizes listed are also available. Add 20% to cost of value larger than your requirement.

GOERTZ AIR CORE FOIL INDUCTORS

MADISOUND is pleased to offer Goertz air core foil inductors. Foil inductors have obvious advantages over wire wound inductors in terms of improved electrical and sonic characteristics.

- 1" wide x 0.003" 14AWG
- 99.99% pure copper foil
- 0.002" thick polypropylene film coating
- Negligible skin-effect below 100kHz
- Flat inductive reactance from 5Hz through 50kHz
- No saturation distortion

- Extremely low stored charge
- Cool operation, good heat dissipation
- High winding tension and vacuum fusing reduces FM distortion
- Negligible power loss due to skin-effect
- Tolerance 2.5%

14 AWG COPPER



			TANU	COLLE			
mH	DCR	Dia. In.	Price	mH	DCR	Dia. In.	Price
0.10	.050	1.6	\$12.60	0.75	.162	2.5	\$23.05
0.15	.054	1.7	\$13.80	0.82	.175	2.6	\$24.05
0.22	.071	1.8	\$14.60	1.00	.188	2.7	\$25.60
0.25	.076	1.8	\$14.90	1.20	.220	2.8	\$28.30
0.27	.078	1.9	\$15.10	1.50	.251	3.0	\$30.05
0.30	.082	2.0	\$15.60	1.80	.300	3.2	\$32.25
0.33	.083	2.0	\$16.40	2.00	.315	3.3	\$34.50
0.39	.095	2.1	\$17.90	2.20	.332	3.4	\$36.70
0.47	.110	2.2	\$18.40	2.70	.370	3.5	\$39.35
0.50	.118	2.2	\$19.25	3.30	.421	3.7	\$43.70
0.56	.130	2.3	\$19.80	3.90	.477	3.9	\$46.40
0.62	.148	2.3	\$20.85	4.70	.547	4.1	\$54.90
0.68	.154	2.4	\$22.00	6.00	.658	4.2	\$61.00
				•			

16 AWG COPPER

12 AWG COPPER

Air Core Foil Inductors

mH	DCR	Dia. In.	Price	mH
0.10	.078	1.3	\$10.80	0.10
0.15	.086	1.4	\$11.10	0.15
0.22	.112	1.5	\$11.65	0.22
0.25	.120	1.6	\$11.75	0.25
0.27	.124	1.6	\$11.85	0.27
0.30	.129	1.8	\$12.20	0.30
0.33	.130	1.9	\$12.55	0.33
0.39	.150	2.0	\$13.30	0.39
0.47	.173	2.1	\$13.85	0.47
0.50	.190	2.1	\$14.65	0.50
0.56	.204	2.2	\$15.15	0.56
0.62	.276	2.2	\$15.85	0.62
0.68	.242	2.3	\$16.55	0.68
0.75	.250	2.4	\$16.95	0.75
0.82	.276	2.5	\$17.35	0.82
1.00	.295	2.6	\$18.15	1.00
1.20	.343	2.7	\$19.25	1.20
1.50	.394	2.9	\$20.05	1.50
1.80	.471	3.1	\$20.65	1.80
2.00	.497	3.2	\$23.70	2.00
2.20	.522	3.3	\$25.00	3.90
2.70	.583	3.4	\$26.90	4.70
3.30	.661	3.6	\$29.90	6.00
I				

mH	DCR	Dia. In.	Price
0.10	.027	1.7	\$17.90
0.15	.032	1.8	\$19.95
0.22	.045	1.9	\$22.00
0.25	.047	2.0	\$23.15
0.27	.049	2.0	\$23.95
0.30	.052	2.0	\$25.15
0.33	.053	2.1	\$27.50
0.39	.087	2.2	\$29.40
0.47	.070	2.3	\$30.50
0.50	.075	2.4	\$32.55
0.56	.083	2.4	\$34.80
0.62	.091	2.4	\$36.35
0.68	.098	2.5	\$38.15
0.75	.105	2.6	\$39.10
0.82	.111	2.7	\$40.10
1.00	.120	2.8	\$42.05
1.20	.141	2.9	\$45.60
1.50	.160	3.1	\$50.10
1.80	.191	3.3	\$52.35
2.00	.202	3.4	\$57.40
3.90	.304	4.1	\$81.10
4.70	.348	4.4	\$97.95
6.00	.415	4.7	\$111.95
1			

Since we introduced our Air Core Inductors in 1997 they have become standard fixtures in many of the Worlds finest speakers, and thousand of audiophiles have improved their sound by personally upgrading their crossover circuits with our products.

Alpha-Core developed the combination of high grade OFC copper with polypropylene film as the dielectric, wound onto a non-hygroscopic core able to endure the sometimes high working temperature without long term shrinkage. We knew that a loose center will allow relative motion of layers due to electromagnetic forces, leading to FM distortion, so we chose LEXANTM a high strength, super stable engineering resin for our cores.

We also developed the vacuum fusing process in order to further preserve the long-term integrity of our inductors.


Research has no limits, so throughout the years we have worked on improving our product and proprietary manufacturing equipment. As a result we are now winding our inductors even tighter, to closer tolerances and at increased productivity Inductors are calibrated within 2.5% of nominal, wound with superior tightness and fused at both ends, hermetically protecting the conductor (be it copper or fine silver) against tarnishing with time.

The copper foil inductors cannot be wound down and we are not able to special order values that are not listed here. If you need a special value please order directly from Alpha-Core.

PERFECT LAY WINDING Air Core Inductors

MADISOUND is now stocking **PERFECT LAY WINDING** audio inductors from Solen Engineering. These are audio grade inductors using 14 gauge wire with the following specifications:

- Perfect Lay Hexagonal Winding. Winding Space Factor: 86.7%
- Oxygen Content: Less than 200 parts per million on surface.
- Insulation: 130 degree centigrade Single coating Nylon-Polyurethane.
- Computer Optimized Coil Dimension.
- Encapsulation: Varnish dip coating with 4 nylon ties.
- No Saturation distortion: Test voltage 1500 VAC
- No Hysteresis distortion: Test voltage 1500 VAX
- Inductance tolerance: within 1% of value listed.
- Conductivity: Better than 101.5% of National Electrical and Manufacturing Association (NEMA) standard sample.
- Wire Diameter: .064 inches; 1.63 mm. High Purity Annealed Copper.



CHATEAUROUX Polypropylene Solen Fast Caps

We are pleased to announce that we now have in stock CHATEAUROUXMETALLIZED POLYPROPYLENE CAPACITORS of exceptional quality and excellent price. This type of dielectric has been characterized by Walter Jung as "outstanding" when compared with all other dielectrics in the areas of:

DISSIPATION FACTOR PERCENTAGE-DIELECTRIC ABSORPTION PERCENTAGE-STABILITY

- Low dissipation factor
- > Low dielectric absorption factor
- > High insulation resistance
- High frequency and temperature stability
- Good self healing characteristics of polypropylene dialectic
- ➤ High Current Capacity
- Excellent Over voltage and Pulse handling capability
- > Low self inductance
- ➤ Low equivalent series resistance

- Excellent stability
- ➤ Leads: Tinned pure copper (not jacketed)
- > Superior high frequency characteristics
- > High Ionization level
- ➤ Dissipation factor @ 200 C: Less than .01 %.
- ➤ Dielectric: Polypropylene Film.
- ➤ Working Voltage: 400 VDC or higher.
- ➤ Test Voltage: 2.15 times rated voltage
- ➤ Capacitance tolerance: +/- 5%



	13 D, 23 L 16 D, 25 L 18 D, 33 L 23D, 33 L	8 ufd: 12 ufd: 15 ufd: 18 ufd: 25 ufd:	29 D, 38 L 29 D, 45 L 31D, 45 L	35 ufd: 40 ufd: 50 ufd: 60 ufd: 70 ufd:	40D, 60 L 45 D, 60 L 47 D, 65 L	80 ufd: 5- 100 ufd:50 120 ufd:60 150 ufd:60	6 D, 72 L 1 D, 72 L
1.0 ufd 1.5 2.0 2.2 2.5 3.0 3.3 4.0 4.7	\$1.85 2.15 2.35 2.50 2.55 2.65 2.75 3.05 3.25	5.0 ufd 5.6 6.0 6.8 7.0 8.0 9.0 10.0 12.0	\$3.40 3.50 3.65 3.90 3.95 4.85 5.20 5.30 5.95	15.0 ufd 18.0 20.0 22.0 25.0 30.0 35.0 40.0 45.0	\$6.75 7.45 7.65 7.90 9.90 11.25 12.75 13.95 15.60	50.0 ufd 60.0 70.0 80.0 100.0 120.0 150.0 200.0	\$16.10 18.95 20.80 23.65 29.10 35.20 40.70 52.50 It to within 1% of each

MUSICAP by H O V L A N D

Madisound is pleased to offer Hovland MusiCaps, film and foil polypropylene capacitors, for the speaker builder who can settle for nothing but the best in sound reproduction. MusiCaps have quickly become the the standard for extremely high end audio systems, allowing speakers to achieve their ultimate level of performance. MusiCaps provide a dramatic improvement in clarity, focus and dynamics. Although MusiCaps are expensive, the degree of improvement is a value compared to the cost of high end cables and interconnects. Hovland MusiCaps are the component of choice when musical realism is your goal.

- Separate layers of polypropylene film & conductive foil, deliver superior clarity of reproduction
- Custom stranded 16 gauge silver-plated copper leads
 no copper oxidation to ever degrade the sound
- Lead-free silver-bearing solder used in tinning and attachment of leads
- . Tight \pm 5% tolerances
- Hand Soldered lead termination
- Extremely low DA, DF and ESR
- 100% pre-testing for absolute quality assurance
- Consistent even winding tension assures freedom from microphonics



THOOPHOTIOS
A single capacitor = a singular sound; no time
smear from multiple sections
Manufactured entirely in the USA

Red lead should be closer to speaker in series connection.

What the reviewers say ...

"After auditioning a wide variety of caps, I find these film-and-foil capacitors to be the most musical performers—and by a large margin. The MusiCap specializes in textural liquidity (lack of grain) and delicacy of treble nuances."

Dick Olsher, Reviewer for Samadhi Acoustics

"...the extra ambiance, combined with a very clean treble delivery that seemed far less prone to ringing or sibilance than the other types does make them really quite special."

Domini Baker, HI-FI WORLD SUPPLEMENT

"If you want see-thru, high definition, detail *and* listenability, try the MusiCaps."

Joe Roberts, Editor, SOUND PRACTICES, Issue 6

"The improved signal transmission of the Hovland foil capacitors elevated the [Ariel] speakers to a new level of naturalness, clarity, and immediacy."

Lynn Olson, POSITIVE FEEDBACK, Vol. 5, No. 4

Value	WVDC	Dimensions	Price
value	VVVDC	(D x L)(Inches)	Each
0.01 µf*	1600V	0.39 x 1.17	\$11.95
0.1 <i>µ</i> f*	600V	0.50 x 1.75	\$13.90
$0.22 \mu f^*$	600V	0.62 x 2.00	\$16.55
0.33 µf*	600V	0.57 x 2.25	\$19.30
0.47 <i>u</i> f*	600V	0.80 x 2.50	\$22.05
1.0 <i>µ</i> f	100V	0.55 x 2.00	\$19.30
1.5 <i>µ</i> f	100V	0.70 x 2.00	\$22.40
$2.0 \mu f$	100V	0.70 x 2.25	\$25.50
$2.2 \mu f$	100V	0.75 x 2.25	\$26.15
$2.7 \mu f$	100V	0.80 x 2.25	\$27.65
$3.0 \mu f$	100V	0.75 x 2.88	\$28.60
$3.3 \mu f$	100V	0.82 x 2.88	\$29.45
$4.0 \mu f$	100V	0.85 x 2.88	\$31.90
$4.7 \mu f$	100V	0.95 x 2.88	\$33.85
5.0 μ f	100V	0.95 x 2.88	\$34.50
5.6 µf	100V	0.95 x 2.88	\$36.70
6.0 μ f	100V	0.95 x 2.88	\$38.15
6.8 µf	100V	1.05 x 3.25	\$41.20
7.0 <i>µ</i> f	100V	1.05 x 3.25	\$42.00
8.0 <i>µ</i> f	100V	1.10 x 3.25	\$45.75
9.0 µf	100V	1.20 x 3.25	\$49.70
$10.0\mu\mathrm{f}$	100V	1.35 x 3.25	\$53.40
12.0 μ f	100V	1.50 x 3.38	\$62.05
15.0 <i>µ</i> f	100V	1.63 x 3.38	\$73.95

Bennic Capacitors (Electrolytic & Polypropylene)

Metallized Polypropylene Capacitors, XPP Series, 160VAC/250VDC

Tolerance Range : +/- 5% Dissipation Factor : Maximum 0.07% @ 1KHz

Operating Temp.
Capacitance Drift -40°C to +105°C

Maximum 2% cycled through the operating temp. range Min. 10,000 Mega-Ohm X rated caps (mfd) at 25°C Insulating Resist. Life Test 150% of rated working voltage at 105°C for 1,000 hours

Lead Length : 40 mm minimum

: Black tape, Yellow body, White wording Color

	1 ,	3 /	0		,
Value mfd	D/Lmm	Price Each	Value mfd	D/Lmm	Price Each
0.1	6/16	\$0.30	4.7	19 / 36	\$2.15
0.47	8 / 24	\$0.50	5.6	17 / 45	\$2.40
1.0	10/31	\$0.65	6.8	18 / 45	\$2.50
1.5	12/31	\$0.80	8.2	20 / 46	\$3.40
2.2	14/31	\$1.15	10	23 / 46	\$3.75
2.7	15/31	\$1.30	12	22 / 55	\$4.05
3.3	16 / 35	\$1.60	16	24 / 55	\$5.25
3.9	16 / 35	\$1.85			

BI-POLAR ELECTROLYTIC CAPACITORS, 100WV

Tolerance Range : +/- 10% @ 1KHz

: Maximum 0.04 CV + 3 µA After Charge 5 Minutes Leakage

Temp. Range Surge Volt Lead Length -40° C to $+85^{\circ}$ C 125 for 100WV 40 mm minimum

Maximum 5% @1KHz Values 12mfd to 150mfd Max D.F.

Maximum 10% @1KHz Values 165mfd to 1000mfd

Color : Blue

Value mfd	D/Lmm	Price Each	Value mfd	D/Lmm	Price Each
12	12/31	\$0.75	140	22 / 45	\$2.95
18	12/31	\$0.85	150	22 / 45	\$3.10
22	12/31	\$0.95	165	16 / 42	\$2.90
31	16 / 34	\$1.10	180	16 / 42	\$3.00
40	16 / 34	\$1.25	200	16 / 42	\$3.05
50	16 / 34	\$1.45	250	18 / 42	\$3.75
65	16 / 34	\$1.55	280	18 / 45	\$4.20
80	16 / 42	\$1.80	330	22 / 45	\$4.50
100	18 / 42	\$2.00	500	25 / 51	\$6.15
125	22 / 45	\$2.50	1000	25 / 60	\$9.00

Carli **Metallized Polyester Film Capacitors (Mylar)**

Carl	Carli Metallized Polyester Film Capacitors (Mylar)							
Value µfd	Description	Ø mm	L mm	Price Each				
1.0	Mylar 10% 150 volt	8	19	\$0.60				
2.7	Mylar 10% 150 volt	10	31	1.00				
3.3	Mylar 10% 150 volt	11	25	1.05				
3.9	Mylar 10% 150 volt	12	31	1.15				
4.7	Mylar 10% 150 volt	13	31	1.25				
6.0	Mylar 10% 150 volt	14	31	1.50				
6.8	Mylar 10% 150 volt	14	31	1.70				
8.0	Mylar 10% 150 volt	16	31	1.95				
10.0	Mylar 10% 150 volt	16	31	2.30				

Carli Metallized Polyester Film Capacitors (Mylar)							
Value µfd	ue µfd Description Ø mm L mm Price Each						
12.0	Mylar 10% 150 volt	20	31	2.75			
15.0	Mylar 10% 150 volt	23	31	3.40			
20.0	Mylar 10% 150 volt	21	46	5.00			



Supreme Silver/Gold Capacitor The metallisation of the capacitor foil for the MCap Supreme Silver/Gold consists of 99.99% pure silver, to

D*L/mm

17*34

17*34

17*34

17*34

19*39

21*39

VDC

1200

1200

1200

1200

1200

1200

0.010

0.022

0.047

0.22

which 1% high purity gold is added. Gold alters the crystalline structure of the silver maximizes its electrical conductivity. This capacitor uses a special inductance-free winding. Two capacitor windings are interleaved (in series), so that their inductances effectively cancel. For example, two 2µf windings are used to make one 1µf capacitor. When embedded in complete silence, instruments

- 00	and	voices can	develop the	ar absolute c	elearness and	power.	I olerance ±	<u>-</u> 2%.
Price	\mathbf{mf}	VDC	D*L/mm	Price	\mathbf{mf}	VDC	D*L/mm	Price
\$40.00	0.68	1200	26*40	\$62.05	4.70	1200	45*71	\$153.00
\$40.00	1.00	1200	31*41	\$73.70	5.60	1200	46*72	\$166.65
\$40.00	2.20	1200	35*54	\$95.05	6.80	1200	51*72	\$187.15
\$44.10	2.70	1200	35*54	\$106.60	8.20	1200	51*72	\$211.45
\$50.05	3.30	1200	41*56	\$118.60	10.0	1200	51*106	\$256.40
\$56.80	3.90	1200	42*57	\$133.30				

Supreme Silver/Oil Capacitor



polypropylene dielectric capacitor. This capacitor uses a special inductance-free winding. Two capacitor windings are interleaved (in series), so that their inductances effectively cancel. For example, two 2μf windings are used to make one 1μf capacitor. High purity silver (99.99%) is used for the capacitor coating. A special oil has been chosen to contribute to an even fuller and smoother tonal richness and diversity. Mundorf Supreme Silver/Oil capacitors are arguably the best sounding audiophile capacitors available. Tolerance $\pm 2\%$.

This product is an oil impregnated, silver metallized

The Supreme capacitor uses the same special

μ f	VDC	D*L/mm	Price	$\mu \mathbf{f}$	VDC	D*L/mm	Price	$\mu \mathbf{f}$	VDC	D*L/mm	Price
0.01	1200	12*27	\$29.00	0.68	1200	25*38	\$40.50	3.90	1200	40*53	\$79.30
0.10	1200	16*34	\$29.25	0.82	1200	30*39	\$44.00	4.70	1200	40*69	\$86.20
0.15	1200	16*34	\$29.95	1.00	1200	30*39	\$47.70	5.60	1200	45*69	\$95.45
0.22	1200	18*37	\$31.05	1.50	1200	35*39	\$54.35	6.80	1200	45*69	\$106.90
0.33	1200	18*37	\$32.90	2.20	1200	40*53	\$62.90	8.20	1200	50*68	\$121.25
0.47	1200	20*37	\$35.40	2.70	1200	40*53	\$66.55	10.0	1200	45*105	\$145.25
0.56	1200	25*38	\$37.80	3.30	1200	40*53	\$72.70				

Supreme Polypropylene Capacitor The Supreme capacitor uses the same special induction-free winding technology as the Silver/Oil



capacitor. This capacitor is a metallized polypropylene film, with exceptional low loss characteristics. The Supreme is equally suited to electronics as it is for high-end loudspeakers. No matter where you use the Mcap Supreme - as a coupling capacitor in your CD player or amplifier, or in the crossover of your speakers - you always get the same surprising and impressive performance. Whether your upgrading a premium system of a price conscious configuration, Supreme will deliver a significant enhancement. Tolerance $\pm 2\%$

μ f	VDC	D*L/mm	Price	μ f	VDC	D*L/mm	Price	μf	VDC	D*L/mm	Price
0.10	1200	17*36	\$12.75	1.00	800	20*40	\$22.50	5.60	800	36*56	\$43.05
0.15	1200	19*38	\$13.95	1.50	800	25*55	\$24.60	6.80	800	41*57	\$44.25
0.22	1200	20*38	\$15.20	1.80	800	25*55	\$26.70	8.20	800	36*106	\$52.45
0.33	1200	25*52	\$17.65	2.20	800	25*55	\$27.85	10.0	800	36*106	\$59.40
0.47	800	20*39	\$18.90	2.70	800	30*56	\$29.10	15.0	800	41*102	\$75.95
0.56	800	20*39	\$20.15	3.30	800	30*56	\$31.95	22.0	800	50*106	\$104.70
0.68	800	20*39	\$20.95	3.90	800	30*56	\$34.80				
0.82	800	20*40	\$21.30	4.70	800	36*56	\$37.70				



M-Connect 105 Kit With 6mm Pure Copper Posts

Price Each Kit \$109.50

105mm Round x 8mm



M-Connect 6mm Pure Copper Posts

Red or Black \$35.60 each Includes nuts



M-Connect 122 Bi-Wire Kit With 6mm Pure Copper Posts

• Price Each Kit \$180.80

Strap not included. 122mm x 96mm x 8mm





M-Connect 130 Kit Available with Pure Copper or Brass

- Copper Posts Kit \$137.35 each
- Brass Posts Kit \$107.20 each 130mm round x 8mm

M-Connect 8mm Posts Red or Black, with nuts

- Copper Post Each \$45.60
- •Brass Post Each \$30.50



M-Connect 150 Bi-wire Kit Available with Pure Copper or Brass 8mm **Binding Posts**

- Copper Posts Kits \$226.05 each
- •Brass Posts Kits \$165.75 each

Shorting strap not included. 150mm x 124mm x 8mm

M-CONNE(





ClarityCap has been manufacturing high quality audio grade capacitors in the United Kingdom for the last 20 years. More and more people are appreciating the difference that ClarityCap makes to sound quality.

SA Range Polypropylene Capacitors

Specially developed to meet the needs of the professional audio engineer in both hi-fi and studio monitoring, these components are the result of extensive consultation between the audio industry and ClarityCap.

The capacitors are wound using a 10µm(630Vdc) rated polypropylene film. Following a special heat treatment cycle, insulated copper terminals are hand soldered to give the best possible connection.

The inherently low dissipation and dielectric absorption factors of polypropylene allied with an excellent mechanical stability results in an extremely detailed sonic performance. The construction also results in a low self-inductance and ESR and the devices are highly stable with regard to temperature and frequency.

•	~ ~ .	ъ.		~ T ()	
$\mu \mathbf{f}$	Ø x L (mm)	Price	μ f	Ø x L (mm)	Price
0.10	27 x 19	\$3.70	9.00	42 x 45	\$13.50
0.22	21 x 19	\$3.75	10.0	45 x 45	\$14.10
0.33	27 x 19	\$4.20	12.0	40. x 65	\$15.00
0.47	20 x 28	\$4.30	15.0	45 x 65	\$17.85
1.00	22 x 38	\$4.40	18.0	49 x 65	\$21.15
1.50	23 x 38	\$5.10	20.0	50 x 65	\$23.45
2.20	27 x 38	\$5.80	22.0	53 x 65	\$24.95
3.30	33 x 38	\$7.60	25.0	57 x 65	\$30.10
3.90	35 x 38	\$7.80	30.0	62 x 65	\$35.55
4.70	35 x 38	\$8.05	33.0	65 x 65	\$37.70
5.60	35 x 45	\$9.45	39.0	70 x 65	\$44.15
6.20	35 x 45	\$10.00	47.0	75 x 65	\$51.95
6.80	38 x 45	\$10.95	50.0	78 x 65	\$55.60
8.20	42 x 45	\$12.30		1'' = 25.4mm	

PX Range Polypropylene Capacitors

Constructed from a $250 \text{Vdc}(6\mu\text{m})$ rated film, this component is spindle wound. It is then given a special heat treatment before it has insulated copper terminals hand soldered to give the best possible connection.

The inherently low dissipation and dielectric absorption factors of polypropylene allied with an excellent mechanical stability results in an extremely detailed sonic performance.

The construction also results in a low self-inductance and ESR (Equivalent Series Resistance) and the devices are highly stable with regard to temperature and frequency.

$\mu \mathbf{f}$	W x H x L (mm)	Price	μ f	W x H x L (mm)	Price
0.47	14 x 9 x 19	\$1.90	12.0	28 x 26 x 45	\$7.30
1.00	15 x 10 x 28	\$2.15	15.0	35 x 30 x 45	\$9.20
1.50	13 x 18 x 28	\$2.45	18.0	37 x 34 x 45	\$10.90
2.20	19 x 15 x 28	\$2.65	20.0	37 x 35 x 45	\$11.75
3.30	23 x 19 x 28	\$2.65	22.0	40 x 38 x 45	\$12.55
3.90	23 x 18 x 33	\$3.20	25.0	43 x 40 x 45	\$13.90
4.70	25 x 20 x 33	\$3.85	30.0	42 x 37 x 60	\$15.40
5.00	25 x 20 x 33	\$4.00	39.0	47 x 43 x 60	\$18.95
5.60	27 x 22 x 33	\$4.40	47.0	52 x 46 x 60	\$22.40
6.00	27 x 23 x 33	\$4.55	50.0	52 x 50 x 60	\$25.00
6.80	25 x 28 x 33	\$4.90	68.0	60 x 57 x 60	\$30.95
8.20	27 x 22 x 45	\$5.40	82.0	65 x 65 x 60	\$37.35
9.00	27 x 23 x 45	\$5.60	100.0	71 x 71 x 60	\$46.60
10.0	28 x 25 x 45	\$5.90		1'' = 25.4mm	
			'		



- Metallized Polypropylene
- Tolerance +5%
- Dissipation factor ≤ 0.001@1kHz
- Rated Voltage 630Vdc
- Dielectric absorption ≤ 0.1%
- 10 µm polypropylene film
- Insulated copper leads; hand soldered



- Metallized Polypropylene
- Spindle wound
- Tolerance ±5%
- Dissipation factor ≤ 0.001@1kHz
- Rated Voltage 250Vdc
- Dielectric absorption $\leq 0.1\%$
- 6 μm polypropylene film
- Insulated copper leads; hand soldered





RCA TYPE CONNECTORS - RoHS COMPLIANT

ILLUSTRATIONS NOT TO SCALE

	Retail
WBT-0101 Topline	\$34.00
WBT-0101-KIT 4 Plugs, WBT™ solder, Torx™ key, boxed	\$140.00

Ultra fine machining grants smooth operation of unit. Unique plating process with final plating of 24k gold. Patented WBT™ barrel provides both adjustment and locking function. The barrel is finished in polished ruthenium. A slotted center pin allows a perfect fit. Teflon™ insulation. Strain relief captured with Torx™ T6 size set screw. Maximum cable diameter allowed is 9mm²/ 0.354 inches².



WBT-0102Ag nextgen™ Signature (hybrid)	\$59.00
WBT-0102Ag-KIT	\$240.00
4 Plugs, WBT™ solder, Torx™ key, boxed	

Contacts utilize passivated pure fine silver. The body is constructed with brass and then platinum plated to give a nice asthetic appeal. The central contact assembly is made of Ultramid® and the negative contact uses Dyneon™. The barrel is comprised of brass with a shiny black piano lacquer finish. A characteristic impedance of 75 ohms makes this a perfect match for digital audio and video. The maximum size conductor that can be used is 1.5mm² / 16-17 AWG. Maximum diameter of cable with dielectric is 9mm² / 0.354 inches². The barrel is offered in black only.



WBT-0102Cu nextgen™ Topline (hybrid)	\$39.00
WBT-0102Cu-KIT 4 Plugs, WBT™ solder, Torx™ key, boxed	\$160.00

As above with contacts manufactured from pure oxygen free copper which is plated with a thin layer of 24k gold to provide protection from oxidation. The barrel is offered in black only.



WBT-0108 Topline	\$41.00
WBT-0108-KIT 4 Plugs, Torx [™] key, boxed	\$168.00

Crimp version of the WBT-0101. It is recommended that the signal contact (maximum 16 AWG) and ground (maximum 14 AWG) conductors first be prepared with a crimp sleeve. Connection is made by fastening the conductors with the supplied TorxTM T6 size set screws. The greatest cable diameter that can be accommodated is 9mm² / 0.354 inches².





RCA TYPE CONNECTORS - RoHS COMPLIANT

ILLUSTRATIONS NOT TO SCALE

	Retail
WBT-0110Ag nextgen™ Signature (pure)	\$57.00
WBT-0110Ag-KIT 4 Plugs, WBT™ solder, Torx™ key, boxed	\$232.00

Passivated pure fine silver contacts. The body is constructed of Ultramid®, while the negative contact uses Dyneon™. The Barrel is comprised of Al/Mg alloy for improved rejection of EMI. With a characteristic impedance of 75 ohms, the WBT-0110 makes the perfect match for digital audio and video. The maximum size conductor that can be used is 1.5mm² / 16-17 AWG. Maximum diameter of cable with dielectric is 9mm² / 0.354 inches². Connector body available in nine different colors for multichannel identification. The barrel is offered in cobalt blue only.



WBT-0110Cu nextgen™ Topline (pure)	\$35.00
WBT-0110Cu-KIT 4 Plugs, WBT™ solder, Torx™ key, boxed	\$144.00

As above with contacts manufactured from pure oxygen free copper and plated with a thin layer of 24k gold to provide protection from oxidation. Barrel offered in cobalt blue only



WBT-0144 Midline	\$21.00
WBT-0144-KIT	\$88.00
4 Plugs, WBT™ solder, Torx™ key, boxed	Ψοσ.σσ

As a midline offering of the WBT-0101, this connector has all the same style and finesse. Differences include a barrel finished in matte black, lower yet efficient machining tolerances and lesser percentage oxygen free copper alloy stock. The largest outside diameter cable that can be accepted by this RCA type connector is 9mm² / 0.354 inches².



WBT-0147 Midline	\$21.00
WBT-0147-KIT 4 Plugs, WBT™ solder, Torx™ key, boxed	\$88.00

While being a compact version of the WBT-0144, shorter and thinner, this connector works well on smaller diameter cables. With a maximum cable diameter of 7.8mm² / 0.307 inches², this is the smallest RCA type plug manufactured by WBT.



RCA TYPE CONNECTORS CONTINUED - RoHS COMPLIANT

ILLUSTRATIONS NOT TO SCALE



	Retail
WBT-0150 Topline	\$39.00
WBT-0150-KIT	\$82.00
2 Plugs, WBT™ solder, Torx™ key, boxed	Ψ02.00

This connector is an oversized version of the WBT-0101 with similar construction and features. Accommodates a cable diameter between 9.1-11.3 mm² / 0.358-0.445 inches².



WBT-0152Ag nextgen™ Signature (hybrid)	\$59.00
WBT-0152Ag-KIT 4 Plugs, WBT™ solder, Torx™ key, boxed	\$240.00

A new (2007) version of the WBT-0150 connector. Improved to utilize the nextgen™ insert. Contacts utilize passivated pure fine silver. The body is constructed with brass and then platinum plated to give a nice asthetic appeal. The central contact assembly is made of Ultramid® and the negative contact uses Dyneon™. The barrel is comprised of brass and finished in a glossy piano black color. A characteristic impedance of 75 ohms makes this a perfect match for digital audio and video. The maximum size conductor that can be used is 1.5mm² / 16-17 AWG. Maximum diameter of cable with dielectric is 9.1-11.3 mm² / 0.358-0.445 inches². The barrel is offered in black only.



WBT-0152Cu nextgen™ Topline (hybrid)	\$39.00
WBT-0152Cu-KIT 4 Plugs, WBT™ solder, Torx™ key, boxed	\$160.00

As above with contacts manufactured from pure oxygen free copper which is plated with a thin layer of 24k gold to provide protection from oxidation. The barrel is offered in black only.



Retail Price List • Effective January 1, 2007 RCA TYPE PLUG COMPARISON CHART

At a Glance RCA Plug Comparison Chart							Term		•		Ava Mı	ailab ultich	le ma	arkir el id	ng co entif	lors icatio	for on
RCA PLUGS	Final body finish	External plating, layers & thickness	Metallurgic properties of signal contact area	Properties of connector body	/30		Polimo	BC Mount	0,00	/ange Vell de	MOM STE	Bluen	/ /S/S//	Whii	Green	Black	7
WBT0101	double 24k gold with polished ruthenium barrel	nickel free 5 layers Cu 11µm duplex Pd 4µm Au 0.3µm duplex	68% oxygen free copper alloy with Teflon™ insulation	68% oxygen free copper alloy 2/100 mm machining tolerance	•			•		0	•	•		0		•	
WBT0102Ag	platinum plated brass with glossy piano black lacquer finish	1 layer Pt 0.4 μm	100% fine silver passivated	68% oxygen free copper alloy 2/100 mm machining tolerance	•			•	•	0	•	•	•	0	0	•	
WBT0102Cu	24k gold plated brass with glossy piano black lacquer finish	1 layer Au 0.5µm	99.996% copper	68% oxygen free copper alloy 2/100 mm machining tolerance	•			•	0	0	•	•	•	0	0	•	
WBT0108	double 24k gold with polished ruthenium barrel	nickel free 5 layers Cu 11µm duplex Pd 4µm Au 0.3µm duplex	68% oxygen free copper alloy with Teflon™ insulation	68% oxygen free copper alloy 2/100 mm machining tolerance		•		•		0	•	•		0		•	
WBT0110Ag	color coded Ultramid™ ceramic coated Al/Mg barrel	1 layer Pt 0.4 μm	100% fine silver passivated	main body of Ultramid™ modular insert of Dyneon™	•			•	•	0	•	•	•	0	0	•	
WBT0110Cu	color coded Ultramid™ ceramic coated Al/Mg barrel	1 layer Au 0.5 μm	99.996% copper	main body of Ultramid™ modular insert of Dyneon™	•			•	•	0	•	•	•	0	0	•	
WBT0144	24k gold plating with matte black barrel	3 layers Cu 1.5 µm Ni 8.0 µm Au 0.2 µm	55% oxygen free copper alloy with Teflon™ insulation	55% oxygen free copper alloy 5/100 mm machining tolerance	•			•		0	•	•		0		•	
WBT0147	24k gold plating with matte black barrel	3 layers Cu 1.5 μm Ni 8.0 μm Au 0.2 μm	55% oxygen free copper alloy with Teflon™ insulation	55% oxygen free copper alloy 5/100 mm machining tolerance	•			•		0	•	•		0		•	
WBT0150	double 24k gold with polished ruthenium barrel	nickel free 5 layers Cu 11µm duplex Pd 4µm Au 0.3µm duplex	68% oxygen free copper alloy with Teflon™ insulation	68% oxygen free copper alloy 2/100 mm machining tolerance	•												
WBT0152Ag	platinum plated brass with glossy piano black lacquer finish	1 layer Pt 0.4 μm	100% fine silver passivated	68% oxygen free copper alloy 2/100 mm machining tolerance	•												
WBT0152Cu	24k gold plated brass with glossy piano black lacquer finish	1 layer Au 0.5μm	99.996% copper	68% oxygen free copper alloy 2/100 mm machining tolerance	•												





RCA TYPE SOCKETS - RoHS COMPLIANT

ILLUSTRATIONS NOT TO SCALE

	Retail
WBT-0201 Topline	\$29.00
WBT-0201-KIT 2 Sockets, WBT™ solder, boxed	\$62.00

This RCA type socket is a favorite among many audio enthusiasts. Featuring 99.996% high copper content, the dual prism spring loaded contact, WBT's 24k gold supra-plating process and Teflon™ dielectric. Socket tightens from the outside of a chassis using the included mounting nut. The complete unit includes insulation washers to accommodate a panel thickness from 0.1mm - 4.2mm.



WBT-0210Ag Ms nextgen™ Signature (metal nut)	\$53.00
WBT-0210Ag Ms-KIT (metal nut) 2 Sockets, WBT™ solder, boxed	\$110.00
WBT-0210Ag nextgen™ Signature (pure)	\$51.00
WBT-0210Ag-KIT (pure) 2 Sockets, WBT™ solder, boxed	\$106.00

The highest quality socket available on the market, with passivated pure fine silver contacts for both positive and negative connections. The positive contact utilizes a new tulip shaped spring loaded design to assure a secure connection. Air used as a dielectric surrounds the positive contact. The main body is comprised of 30% glass reinforced Ultramid® with the ground (negative) contact embedded within the connector. The complete unit includes removable insulation washers to accommodate a panel thickness from 0.1mm - 4.2mm.



WBT-0210Cu Ms nextgen™ Signature (metal nut)	\$31.00
WBT-0210Cu Ms-KIT (metal nut) 2 Sockets, WBT™ solder, boxed	\$66.00
WBT-0210Cu nextgen™ Signature (pure)	\$29.00
WBT-0210Cu-KIT (pure) 2 Sockets, WBT™ solder, boxed	\$62.00

As above with both contacts, positive and negative, manufactured from pure oxygen free copper and plated with a thin layer of 24k gold to provide protection from oxidation.





RCA TYPE SOCKETS - RoHS COMPLIANT

ILLUSTRATIONS NOT TO SCALE

PCB MOUNT Retail
WBT-0234 Topline \$35.00

Right angle, printed circuit board version of the WBT-0201 with a screw to secure the connection to a printed circuit board. The ground contact is made through the securing screw to the PCB and two additional solder points. The signal, or positive contact, has one solder contact point.

WBT-0244 Midline

\$29.00

The WBT-0244 is a midline version of the WBT-0201 which differs in the copper content of the main body and the machining tolerances.

PCB MOUNT

WBT-0274 Midline

\$29.00

A midline offering of the WBT-0234, this connector provides a single ground and signal or positive mounting position. The socket body is machined of a lower percentage copper alloy, but the positive contact is made of 99.996% pure copper as with all WBT sockets.


	At a Glance RCA Socket Comparison Chart							tion	,	Ava mu	ilabl Itich	e mann	arkir el id	ng c lenti	olors	s for	
RCA SOCKETS	Final body finish	External plating, layers & thickness	Maximum cable diameter size accepted	Metallurgic properties of signal contact area connector body		Crimp	PCB Mount	Red	Orange	Yellow	Green	Blue	Violet	White	Grey	Black	
WBT0201	24k gold	nickel free 2 layers Bronze 5µm Au 0.3µm	1.5mm² 16 AWG	99.996% oxygen free copper with 0.3µm 24k gold plating Teflon™ insulated	68% oxygen free copper alloy 0.1-4.2mm mounting panel thickness				•		0				0		
WBT0210Ag WBT0210Ag Ms (Ms=metal nut)	grey Ultramid™	non metal	1.5mm² 16 AWG	100% fine silver (passivated)	main body of Ultramid™ 0.1-4.2mm mounting panel thickness				•	0	0	•	•	•	0	0	•
WBT0210Cu WBT0210Cu Ms (Ms=metal nut)	grey Ultramid™	non metal	1.5mm² 16 AWG	99.996% oxygen free copper with 0.5µm 24k gold plating	main body of Ultramid™ 0.1-4.2mm mounting panel thickness				•	•	0	•	•	•	0	0	•
WBT0234	24k gold	nickel free 5 layers Cu 11µm duplex Pd 4µm Au 0.3µm duplex	printed circuit board mounting (right angle)	99.996% oxygen free copper with 0.3µm 24k gold plating Teflon™ insulated	68% oxygen free copper alloy 0.1-4.2mm mounting panel thickness	•		•	•		0				0		
WBT0244	24k gold	3 layers Cu 1.5µm Ni 8.0µm Au 0.2µm	2.5mm² 14AWG	99.996% oxygen free copper with 0.3µm 24k gold plating Teflon™Insulated	55% oxygen free copper alloy 0.1-4.2mm mounting panel thickness	•			•		0				0		
WBT0274	24k gold	3 layers Cu 1.5 μm Ni 8.0 μm Au 0.2 μm	printed circuit board mounting (right angle)	99.996% oxygen free copper with 0.3µm 24k gold plating Teflon™ insulated	55% oxygen free copper alloy 0.1-4.2mm mounting panel thickness	•		•	•		0				0		




8









Retail Price List • Effective January 1, 2007

SPEAKER CONNECTORS - RoHS COMPLIANT

ILLUSTRATIONS NOT TO SCALE

	Retail
WBT-0600 Topline	\$36.00
WBT-0600-KIT 4 Plugs, 1 Torx™ key, boxed	\$148.00

Top quality banana plug with robust design and sleeve with polished ruthenium finish. Offering high contact pressure due to an expanding inner spike ensures a solid mechanical fit. Termination fitted with two Torx™ screws size T6 for secure crimp connection as well as cable strain relief. Easy fit for wire size up to 10mm² / 8 AWG.

WBT-0644 Midline	\$24.00
WBT-0644-KIT	# 400.00
4 Plugs, 1 Torx™ key, boxed	\$100.00

A midline offering of the WBT-0600. Differences include a barrel finished in black, lower yet efficient machining tolerances and lesser grade oxygen free copper alloy stock. The largest diameter cable accepted for termination is 10mm² / 8 AWG.

CE COMPLIANT STACKABLE

WBT-0645 Midline - Safety Line	\$24.00
WBT-0645-KIT 4 Plugs, 1 Torx™ key, boxed	\$100.00

An Innovative banana plug approved worldwide as a loudspeaker cable connector due to the safety pin design. It is fully insulated using Makrolon®. A secure connection is possible through an expanding inner spike which provides high clamping power. Using only one hand, cables can be connected in tight spaces with just thumb and forefinger. The WBT-0645 is stackable for bi-wiring. Two TorxTM screws for extra tight pressure connection and additional cable strain relief. Connector can accommodate a cable diameter size of 10mm² / 8 AWG.

CE COMPLIANT

WBT-0660Cu Topline	\$22.00
WBT-0660Cu-KIT	\$92.00
4 Plugs, 1 Torx [™] key, boxed	•

High current spade lug with elastomeric shock absorber for progressive contact pressure eliminating structure born and air born noise as well as magnetostriction. Fully insulated body conforms to international safety standards. 1/4 inch / 6.4mm sandwich spade connector. Pure oxygen free copper contact is direct gold plated to protect against oxidation. Easy fit for wire sizes up to 10mm² / 8AWG.

CE COMPLIANT

WBT-0680Cu Topline	\$22.00
WBT-0680Cu-KIT 4 Plugs, 1 Torx™ key, boxed	\$92.00

Same as the WBT-0660Cu but in a larger size of 5/16 inch / 8.1mm sandwich spade connector. Easy fit for wire sizes up to 10mm² / 8AWG.






SPEAKER CONNECTORS - RoHS COMPLIANT

ILLUSTRATIONS NOT TO SCALE

CE COMPLIANT	Retail
WBT-0660Ag Signature	\$44.00
WBT-0660Ag-KIT 4 Plugs, 1 Torx™ key, boxed	\$180.00

1/4 inch / 6.4mm sandwich spade connector. Pure fine silver contact is direct platinum plated to protect against tarnish. High current spade lug with elastomeric shock absorber for progressive contact pressure eliminating structure born and air born noise as well as magnetostriction. Fully insulated body is safe to use and conforms to international safety standards. Easy fit for wire sizes up to 10mm²/8AWG.



CE COMPLIANT

WBT-0680Ag Signature	\$44.00
WBT-0680Ag-KIT 4 Plugs, 1 Torx [™] key, boxed	\$180.00

Same as the WBT-0660Ag but in a larger size of 5/16 inch / 8.1mm sandwich spade connector. Pure fine silver contact is direct platinum plated to protect contact metal from tarnish. Easy fit for wire sizes up to 10mm²/8AWG.

At	At a Glance Speaker Connector Comparison Chart								tion		Avai Mu	lable ltich	e ma anne	arkin el id	g co entifi	lors icatio	for on
SPEAKER CONNECTORS	Final body finish	External plating, layers & thickness	Metallurgic properties of signal contact area	Properties of connector body	1,000	7000k	Period	Red Mount	Oral Oral	/e///96	Green.	Blue	Violes	Whit	Greij	Black	
WBT0600	24k gold plated	nickel free 5 layers Cu 11µm duplex Pd 4µm Au 0.3µm duplex	68% oxygen free copper alloy	68% oxygen free copper alloy	•	•		•						0		•	
WBT0644	24k gold plated	3 layers Cu1.5µm Ni 8.0µm Au 0.2µm	52% oxygen free copper alloy	52% oxygen free copper alloy	•	•		•						0		•	
WBT0645	Makrolon™ over 24k gold plating	3 layers Cu 1.5µm Ni 8.0µm Au 0.2µm	55% oxygen free copper alloy	55% oxygen free copper alloy CE and IEC 65 compliant		•		•						0		•	
WBT0660Cu	Makrolon™ over 24k gold plating	24k gold plating	99.996% copper	3 part: brass cage, pure CU contact, stainless steel former CE and IEC 65 compliant		•		•						0		•	
WBT0680Cu	Makrolon™ over 24k gold plating	24k gold plating	99.996% copper	3 part: brass cage, pure CU contact, stainless steel former CE and IEC 65 compliant		•		•						0		•	
WBT0660Ag	Makrolon™ over platinum plating	platinum plating	pure fine silver	3 part: brass cage, pure Ag contact, stainless steel former CE and IEC 65 compliant		•		•						0		•	
WBT0680Ag	Makrolon™ over platinum plating	platinum plating	pure fine silver	3 part: brass cage, pure Ag contact, stainless steel former CE and IEC 65 compliant		•		•						0			











BINDING POSTS - RoHS COMPLIANT

ILLUSTRATIONS NOT TO SCALE

	Retail
WBT-0702.01 Topline	\$53.00
WBT-0702.01-KIT 2 posts, 1 Torx™ key, boxed	\$110.00

With a 400 ampere continuous current capability, this is the perfect size binding post for demanding applications. A patented clamping mechanism makes it possible for high compression connection of spades and crimped wire ends up to 6mm² (10AWG). By means of a collet chucking device, any 4mm² banana plug can be securely clamped. Milled grooves on both sides of the compression plate provide high strength for connection of spades. No tools are required to provide a secure connection. Finger tightening is all that is required. This connector will not fit on 3/4" or 19mm center to center spacing.

WBT-0702.03 Topline	\$51.00
	l
WBT-0702.03-KIT 2 posts, 1 Torx™ key, boxed	\$106.00

Same as above (WBT-0702.01) but with a glass bead blasted finish in velours chromium. Looks like sand blasted nickel.

WBT-0702.11 Signature	\$64.00
WBT-0702.11-KIT 2 posts, 1 Torx [™] key, boxed	\$132.00

Comparable design as the WBT-0702.01 except it is manufactured using cold rolled 68% copper alloy. The connector is then plated with a single layer of 24k gold to protect against oxidation. Finally, it is polished by hand to give an extreme finish.

WBT-0702.12 Signature	\$64.00
WBT-0702.12-KIT 2 posts, 1 Torx™ key, boxed	\$132.00

This binding post makes use of the same features as the WBT-0702.11 but with a highly polished platinum finish.

CE COMPLIANT

WBT-0710Ag nextgen™ Signature	\$60.00
WBT-0710Ag-KIT	\$244.00
4 posts, WBT™ solder, boxed	Ψ244.00

A 30 ampere continuous current rating makes this connector sufficient for most audio functions. Made with passivated pure fine silver. Spade lugs measuring 6mm, standard 4 mm² banana plugs and wire with a diameter of 6mm² (10AWG) can be accepted. Maximum mounting depth of 4mm without use of puzzle washer. Recommended use with WBT mounting plates on page 17. Can be terminated with 6.1mm / 0.25 inch quick disconnect found on page 15.











BINDING POSTS - RoHS COMPLIANT

ILLUSTRATIONS NOT TO SCALE

CE COMPLIANT	Retail
WBT-0710Cu nextgen™ Topline	\$39.00
WBT-0710Cu-KIT 4 posts, WBT™ solder, boxed	\$160.00

With the same manufacturing design as the WBT-0710Ag but created using 99.996% pure oxygen free copper. The connector is then plated with a single layer of 24k gold to protect against oxidation.

CE COMPLIANT

WBT-0710Cu mC nextgen™ Topline	\$39.00
WBT-0710Cu mC-KIT 4 posts, WBT™ solder, boxed	\$160.00

Brother to the WBT-0710Cu but with a velours chromium tightening nut.

WBT-0730.01 Topline	\$29.00
WBT-0730.01-KIT 4 posts, 2 spacer blocks, 1 Torx [™] key, boxed	\$120.00

A 200 ampere continuous current rating makes this connector sufficient for most functions. Spade connectors are securely held with a patented high compression design. Wire with a diameter of 6mm² (10AWG) can also be accepted. Accepts 4 mm² banana plugs.

WBT-0730.11 Signature	\$38.00
WBT-0730.11-KIT 4 posts, 2 spacer blocks, 1 Torx [™] key, boxed	\$156.00

With the same manufacturing design as the WBT-0730.01 but created using cold rolled 68% copper alloy. The connector is then plated with a single layer of 24k gold to protect against oxidation. Finally, it is polished by hand to give an extreme finish.

٧	\$38.00
4	\$156.00
4	\$156.0

Brother to the WBT-0730.11 but with a highly polished platinum finish.

CE COMPLIANT

WBT-0735 Topline – Safety Line	\$32.00
WBT-0735-KIT 4 posts, 2 spacer blocks, 1 Torx [™] key, boxed	\$132.00

Utilizing a full insulation of Makrolon®, this binding post is part of WBT's safety line and is a CE and IEC compliant version of the WBT-0730.01.













BINDING POSTS - ROHS COMPLIANT

ILLUSTRATIONS NOT TO SCALE

	Retail
WBT-0763 Midline	\$24.00
WBT-0763-KIT	\$100.00
4 posts, WBT™ solder, boxed	

A standard binding post for many high end amplifier and loudspeaker companies. This binding post features a patented rotating collar design that requires only finger tightening to securely fasten a spade. Able to handle 200 amperes of continuous current, this is just the right size binding post for nearly all applications. Set screw not included.

PCB MOUNT

WBT-0764 Midline	\$29.00
WBT-0764-KIT 4 posts, WBT™ solder, boxed	\$120.00

Screw on printed circuit board version of the WBT-0763, can also accept ring terminal lugs.

CE COMPLIANT

WBT-0765 Midline – Safety Line	\$29.00
WBT-0765-KIT 4 posts, WBT™ solder, boxed	\$120.00

Using full insulation of Makrolon®, this binding post is part of WBT's safety line and is a CE and IEC compliant version of the WBT-0763

CE COMPLIANT PCB MOUNT

WBT-0766 Midline – Safety Line	\$32.00
WBT-0766-KIT 4 posts, WBT™ solder, boxed	\$132.00

With the same characteristics as the WBT-0765 except this post is designed for direct mounting on printed circuit board with included bolt and lock washer.

PCB MOUNT

WBT-0780 Economy

\$22.00

WBT's least expensive binding post model featuring a unique finish of velours chromium and is manufactured from brass. Available termination options include crimp, solder and bolt on printed circuit board. Crimp screw and set screw can be purchased separately.

CE COMPLIANT

PCB MOUNT

WBT-0785 Economy - Safety Line

\$24.00

The WBT-0785 is a safety line version of the WBT-0780.



BINDING POSTS - INCLUDES INSULATING WASHER AND SET NUT

ILLUSTRATIONS NOT TO SCALE

		nce Binding		<u> </u>		Teri	mina	tion	,	Ava Mu	ilabl Itich	e m	arkii iel ic	ng c denti	olor: ficat	s fo	r
All t		installed at 90° steps torque = 6.273 Ft Lb			WBT-9404			nt									
BINDING POSTS	Final body finish	External Plating, layers & thickness	Maximum Cable diamater accepted	Metallurgic properties	Special Notes	Solder	Crimp	PCB Mount	Red	Orange	Yellow	Green	Blue	Violet	White	Grey	Black
WBT0702.01	24k gold	nickel free 3 layers Cu 11µm Pd 4µm Au 0.3µm	4mm² banana 1/4" spade 5/16" spade 10 AWG	68% oxygen free copper alloy	locking collet for 4mm² bananas recommended torque for counter nut: 8.5Nm	•	•		•						0		•
WBT0702.03	velours chromium	glass bead blasted 1 layer Ni 5.0µm	4mm² banana 1/4" spade 5/16" spade 10 AWG	68% oxygen free copper alloy	locking collet for 4mm² bananas recommended torque for counter nut: 8.5Nm	•	•		•						0		•
WBT0702.11	24k gold (highly polished)	1 layer Au 0.3µm	4mm² banana 1/4" spade 5/16" spade 10 AWG	68% cold rolled oxygen free copper alloy	locking collet for 4mm² bananas recommended torque for counter nut: 8.5Nm	•	•		•						0		•
WBT0702.12	platinum (highly polished)	1 layer Pt 0.3μm	4mm² banana 1/4" spade 5/16" spade 10 AWG	68% cold rolled oxygen free copper alloy	locking collet for 4mm² bananas recommended torque for counter nut: 8.5Nm	•	•		•						0		•
WBT0710Ag	CE-compliant Tedur™	none	4mm² banana 1/4" spade 5/16" spade 10 AWG	100% pure fine silver passivated	Internal pressure damping ring maximum mounting depth is 4mm	•	•		•						0		•
WBT0710Cu	CE-compliant Tedur™	none	4mm² banana 1/4" spade 5/16" spade 10 AWG	99.996% oxygen free copper plated with 24k Au	Internal pressure damping ring maximum mounting depth is 4mm	•	•		•						0		•
WBT0710Cu mC	CE-compliant Tedur™	none	4mm² banana 1/4" spade 5/16" spade 10 AWG	99.996% oxygen free copper plated with 24k Au	Internal pressure damping ring maximum mounting depth is 4mm	•	•		•						0		•
WBT0730.01	24k gold	nickel free 3 layers Cu 11µm Pd 4µm Au 0.3µm	4mm² banana 1/4" spade 10 AWG	68% oxygen free copper alloy	recommended torque for counter nut: 8.5Nm	•	•		•						0		•
WBT0730.11	24k gold (highly polished)	1 layer Au 0.3μm	4mm² banana 1/4" spade 10 AWG	68% cold rolled oxygen free copper alloy	recommended torque for counter nut: 8.5Nm	•	•		•						0		•
WBT0730.12	platinum (highly polished)	1 layer Pt 0.3µm	4mm² banana 1/4" spade 10 AWG	68% cold rolled oxygen free copper alloy	recommended torque for counter nut: 8.5Nm	•	•		•						0		•
WBT0735	CE-compliant Makrolon™ over 24k gold	nickel free 3 layers Cu 11µm Pd 4µm Au 0.3µm	4mm² banana 1/4" spade 10 AWG	68% oxygen free copper alloy	recommended torque for counter nut: 8.5Nm	•	•		•						0		•
WBT0763	24k gold	3 layers Cu 1.5µm Ni 8.0µm Au 0.2µm	4mm² banana 1/4" spade 10 AWG	52% oxygen free copper alloy	recommended torque for counter nut: 8.5Nm	•	•		•						0		•
WBT0764	24k gold	3 layers Cu 1.5µm Ni 8.0µm Au 0.2µm	4mm² banana 1/4" spade 10 AWG	52% oxygen free copper alloy	recommended torque for counter nut: 8.5Nm recommended torque for PCB bolt, 1.1Nm	•		•	•						0		•
WBT0765	CE-compliant Makrolon™ over 24k gold	3 layers Cu 11µm Ni 4.0µm Au 0.3µm	4mm² banana 1/4" spade 10 AWG	52% oxygen free copper alloy	recommended torque for counter nut: 8.5Nm	•	•		•						0		•

BINDING POST CONTINUED

ILLUSTRATIONS NOT TO SCALE

At	a Glance E	Binding Post (Compariso	on Chart Con	tinued	Terr	nina	tion		Ava Mu	ilabl Iltich	le m nanr	arkir nel ic	ng c denti	olor	s fo	r
All t		installed at 90° steps, torque = 6.273 Ft Lbs			VBT-9404												
BINDING POSTS	Final body finish	External plating, layers & thickness	Maximum cable diamater accepted	Metallurgic properties	Special Notes	Solder	Crimp	PCB Mount	Red	Orange	WolleY	Green	Blue	Violet	White	Grey	Black
WBT0766	CE-compliant Makrolon™ over 24k gold	3 layers Cu 11µm Ni 4.0µm Au 0.3µm	4mm² banana 1/4" spade 10 AWG	52% oxygen free copper alloy	recommended torque for counter nut: 8.5Nm recommended torque for PCB bolt, 1.1Nm	•		•	•						0		•
WBT0780	velours chromium	glass bead blasted 1 layer Ni 5.0µm	4mm² banana 1/4" spade 10 AWG	brass	recommended torque for counter nut: 8.5Nm recommended torque for PCB bolt, 1.1Nm	•	•	•	•						0		•
WBT0785	CE-compliant Makrolon™ over velours chromium	glass bead blasted 1 layer Ni 5.0µm	4mm² banana 1/4" spade 10 AWG	brass	recommended torque for counter nut: 8.5Nm recommended torque for PCB bolt, 1.1Nm	•	•	•	•						0		•

BINDING POST ACCESSORIES - RoHS COMPLIANT



WBT-0715 Extension bolt

\$8.00 Extension piece used with WBT binding posts to accommodate

mounting into material with a thickness from 9mm - 50mm / (0.35" - 2"). Comes with mounting nut and aggressive lock washer. This piece is machined of brass.



WBT-0716 Thick panel mounting kit Gold plated finish	\$15.00
WBT-0719 Thick panel mounting kit Chromium Velours finish	\$15.00

Suggested use requires counter sinking of cabinet with a router or 50mm Forstner drill bit.



1 plastic interior bracket



1 gold-plated brass exterior bracket

1 velours chromium exterior bracket



Retail



2 fan shaped washers

BINDING POST ACCESSORIES CONTINUED

ILLUSTRATIONS NOT TO SCALE

		Retail
1	WBT-0799 Safety Stick	\$0.50
	Specially shaped plastic peg inserts into binding post banana hole. Required to accomplish CE safety conformity (red, white & black).	
	WBT-9404 Spacer Block – 3/4" (19mm) spacing	\$3.00
	Fits all binding posts except WBT-0702 and WBT-0710 series. Plastic insulating spacer block. Available in red, white, or black. Post can adjust in angle every 30 or 45 degrees.	
	WBT-0721 PCB Adapter Block	\$6.00
	Fastens horizontally or vertically to circuit board with included bolt and lock washer. Torx [™] screw fastens jumper wire, other end of lead wire connects to binding post.	
	WBT-9102 Antifatigue Bolt	\$2.00
	Antifatigue bolt with fan shape washer. Used with WBT-0780 and WBT-0785.	
The same of the sa	WBT-9150 Fan Shape Lock Washer	\$1.00
The same of the sa	Recommended addition to all WBT binding posts.	
	WBT-9302 Chrome Plated Counternut, M9 thread	\$1.00
	Specialty nut only available from WBT.	
	WBT-9303 Gold Plated Counternut, M9 thread	\$2.00
	Specialty nut only available from WBT.	
	Replacement T-6 Torx™ Set Screws	\$2.00
	Available 4mm - 8mm lengths. Please specify length when ordering.	
	WBT-QD25	\$0.30
	-	



WBT-9410 \$2.00

To take best advantage of the puzzle washers, at least two should be clipped together. They can be arranged to obtain either 0.75" (19mm) or 1.181" (30mm) spacing. The puzzle washer allows a very tight terminal installation on housings from 0.1mm - 10mm thickness.

Gold plated brass quick disconnect for use with WBT-0710 series binding posts. Allows solder free connection to binding post.



110mm WBT-0540.05 Shown

Retail Price List • Effective January 1, 2007

MOUNTING PLATES & ASSEMBLIES - ROHS COMPLIANT

ILLUSTRATIONS NOT TO SCALE

	Retail
WBT-0510.05 Two post assembly Clear anodized aluminum finish.	\$99.00
WBT-0510.06 Two post assembly Black anodized finish.	\$99.00

Anodized aluminum plate with two WBT-0763 Midline posts. Includes a closed cell foam rubber gasket and 4 wood screws.

WBT-0520.05 Two post ass	sembly	\$106.00
WBT-0520.06 Two post ass	sembly	\$106.00

Anodized aluminum plate with two WBT-0765 safety line posts. Includes a closed cell foam rubber gasket and 4 wood screws.

WBT-0540.05 Two post assembly Clear anodized aluminum finish.	\$136.00
WBT-0540.06 Two post assembly Black anodized finish.	\$136.00

Anodized aluminum plate with two WBT-0710Cu safety line posts. Includes a closed cell foam rubber gasket and 4 wood screws.

Q			Q	
	6	-66	•	150mm
Q	(%		Q	m
			2	

WBT-0541.05 Shown

110mm

WBT-0511.05 Four post assembly Clear anodized aluminum finish.	\$159.00
WBT-0511.06 Four post assembly Black anodized finish.	\$159.00

Anodized aluminum plate with four WBT-0763 Midline posts. Includes a closed cell foam rubber gasket and 6 wood screws.

WBT-0521.05 Four post assembly Clear anodized aluminum finish.	\$172.00
WBT-0521.06 Four post assembly Black anodized finish.	\$172.00

Anodized aluminum plate with four WBT-0765 safety line posts. Includes a closed cell foam rubber gasket and 6 wood screws.

WBT-0541.05 Four post assembly Clear anodized aluminum finish.	\$231.00
WBT-0541.06 Four post assembly Black anodized finish.	\$231.00

Anodized aluminum plate with four WBT-0710Cu safety line posts. Includes a closed cell foam rubber gasket and 6 wood screws.



WBT-0542.05 Shown

Retail Price List • Effective January 1, 2007

MOUNTING PLATES & ASSEMBLIES - RoHS COMPLIANT

ILLUSTRATIONS NOT TO SCALE

	Retail
WBT-0512.05 Four post assembly Clear anodized aluminum finish.	\$165.00
WBT-0512.06 Four post assembly Black anodized finish.	\$165.00
Anodized aluminum plate with four WBT-0763 Midline	posts.

Includes a closed cell foam rubber gasket and 6 wood screws.

WBT-0522.05 Four post assembly Clear anodized aluminum finish.	\$179.00
WBT-0522.06 Four post assembly Black anodized finish.	\$179.00

Anodized aluminum plate with four WBT-0765 safety line posts. Includes a closed cell foam rubber gasket and 6 wood screws.

WBT-0542.05 Four post assembly Clear anodized aluminum finish.	\$238.00
WBT-0542.06 Four post assembly Black anodized finish.	\$238.00

Anodized aluminum plate with four WBT-0710Cu safety line posts. Includes a closed cell foam rubber gasket and 6 wood screws.

110mm	110mm	
	150mm	



(m)	178mm	•
127mm	а	

110mm

WBT-0530.05 Clear anodized aluminum finish.	\$58.00
WBT-0530.06 Black anodized finish.	\$58.00
	·

Punched for 2 posts. Includes a closed cell foam rubber gasket and 4 wood screws.

WBT-0531.05 (Bi-Wire) Clear anodized aluminum finish.	\$76.00
WBT-0531.06 (Bi-Wire) Black anodized finish.	\$76.00

Punched for 4 posts. Includes a closed cell foam rubber gasket and 6 wood screws.

WBT-0532.05 (Bi-Wire) Clear anodized aluminum finish.	\$83.00
WBT-0532.06 (Bi-Wire) Black anodized finish.	\$83.00

Punched for 4 posts. Includes a closed cell foam rubber gasket and 6 wood screws.


Custom Laser engraving of graphics and/or text available for all Mounting Plates. Call for Pricing.



POWER BRIDGE JUMPER - RoHS COMPLIANT

ILLUSTRATIONS NOT TO SCALE





	Retail
WBT-0725 Cu Power Bridge - Safety Line Pure copper, gold plated	\$17.00
WBT-0725 Ag Power Bridge - Safety Line Pure silver, platinum plated	\$34.00
WBT-0726 Economy Power Bridge Pure copper, velour chromium plated Non-insulated and not vibration damped	\$8.00

Designed primarily for the OEM market to meet strict European CE safety standards, the WBT-0725 Cu/Ag Power bridge replaces the brass jumpers found as standard equipment on most speakers.

Uninsulated jumpers are no longer legal in Europe as they pose a shock threat due to lack of insulation. The WBT Power Bridges address this problem as they are fully insulated with Makrolon® plastic for shock protection and, because both terminals are removed at the same time, the "live-wire" situation is avoided. The back of the Power Bridge is damped with an elastomer to minimize vibration.

Power Bridges can be used in conjunction with any WBT™ binding post (except the WBT-0702 series). When purchased with WBT™ posts, Power Bridges make an excellent modification to any bi-wire loudspeaker. Please refer to the diagram to the left for required mounting dimensions. These dimensions are the only that work. The WBT power bridges are not flexible.

Tools





Used for the unassembly and assembly of nextgen series of RCA type plugs. One tool is all that is required.



WBT-0299 RCA Socket Wrench

Specially designed for tightening the metal mounting nut on WBT™ RCA type sockets. Spike on tool fits into hole in mounting nut. Permits tightening without scratching the nut or socket.



WBT-0717 Holding Tool

Used when mounting binding posts. Snaps into the two posts and holds them in alignment. The WBT-0717 also prevents the posts from rotating while tightening the nuts.



WBT-0499 Cutting Shears

Shears cut through fine stranded copper cable up to #5AWG with a cleaving action for a clean even cut. Gold plating protects against corrosion. With a little practice, also good for stripping speaker cable. Retail

\$3.00

\$44.00

\$65.00

\$90.00





ILLUSTRATIONS NOT TO SCALE

Retail



WBT-0403 Crimping Pliers

\$90.00

Crimping pliers with special multiple spike jaw. The only tool designed to correctly crimp WBT $^{\text{TM}}$ crimp sleeves. Gold plating protects against corrosion. Comfortable, platic-coated grip.

WBT-0411 Crimp KIT

\$230.00



Includes one WBT-0403 crimping pliers and an assortment of copper crimp sleeves in a convenient carrying case. Silver sleeves sold separately. Copper sleeves included with the WBT-0411 are as follows:

 20 pcs WBT-0430
 20 AWG (uninsulated)
 20 pcs WBT-0442
 14-13 AWG

 20 pcs WBT-0431
 18-19 AWG (uninsulated)
 20 pcs WBT-0443
 11-12 AWG

 20 pcs WBT-0432
 17 AWG (uninsulated)
 20 pcs WBT-0444
 9-10 AWG

 20 pcs WBT-0433
 15-16 AWG (uninsulated)
 10 pcs WBT-0445
 7-8 AWG



WBT-0488 Torx™ Key

\$6.00

T-6 size fits all WBT™ set screws. For temporary use only.



WBT-0481 Torque Screwdriver

\$160.00

The WBT-0481 is a precision torque screwdriver with an elegant design. Torque is set to 5 dNm for precise tightening of all WBT parts utilizing the Torx[™] T-6 size. 4mm² hole in the end for the attachment of a ground lead, if a static electricity ground is needed. Includes one T-6 Torx[™] bit.



WBT-0490 Torque Screwdriver Set

\$260.00

This kit includes one WBT-0481 Dyna-key along with the WBT-0484 bit assortment in a jewel case for keeping it all together. Additional bits are available separately. (see below)

WBT™ BITS FOR TORQUE SCREW DRIVER



	WBT-0485 SLOT BITS —	WBT-0485 PHILLIPS BITS +	WBT-0485 TORX™ BITS 📥	WBT-0485 HEX BITS
	Available Sizes	Available Sizes	Available Sizes	Available Sizes
	1.5mm	000	Т6	1.3mm — 0.050"
	2.0mm	00	T7	1.5mm — 0.059"
	2.5mm	0	Т8	1.59mm — 1/16"
	3.0mm	1	T10	2.0mm — 5/64"
9	3.5mm*		T15*	2.38mm — 3/32"
	4.0mm*		T20*	2.5mm — 0.098"
				3.0mm*— 0.118"
	Not included in the WBT-04	484 Bit-Set. Special Order Only.		4.0mm — 0.157"

WBT-0484 Bit-Set Bit Set (18 types).	\$120.00
WBT-0485/XXX Choice of any one bit from the above list.	\$9.50

WBT SOLDER

ILLUSTRATIONS NOT TO SCALE

WBT™ 4% SILVER SOLDER (Lead based)

All WBT™ Solder is the highest quality solder with 4% fine silver content. The halogen-free flux is gentle on precious metal surfaces. The melting temperature is extremely low at 180°C / 356°F.

-	
	- 2
WV.	-1
	15
	⊌ v⊟

WBT-0800 Silver Solder 4% Ag

0.9mm diameter

42grams / 0.123 lbs. 10m / 32.8 ft



WBT-0820 Silver Solder 4% Ag

\$49.00

0.8mm diameter 250grams / 0.575 lbs. 73m / 239 ft



WBT-0840 Silver Solder 4% Ag

\$89.00

Retail

\$16.00

1.2mm diameter 500grams / 1.140 lbs. 57m / 187 ft

WBT™ LEAD Free 4% SILVER SOLDER - RoHS COMPLIANT (Tin based)

WBT™ Lead free solder is the highest quality solder with 4% fine silver content. The halogen-free flux is gentle on precious metal surfaces. The melting temperature is easily accomplished at 219°C / 426°F.

6	Chicago, Santana
	WBT
1	
1	

WBT-0805 Silver Solder 4% Ag

Retail \$25.00

0.9mm diameter 42grams / 0.123 lbs. 10m / 32.8 ft



WBT-0825 Silver Solder 4% Ag

\$74.00

0.8mm diameter 250grams / 0.575 lbs. 73m / 239 ft



WBT-0845 Silver Solder 4% Ag

\$143.00

1.2mm diameter 500grams / 1.140 lbs. 57m / 187 ft



CRIMP SLEEVES - ROHS COMPLIANT

ILLUSTRATIONS ARE TO SCALE

WBT™ cable end sleeves are made of special oxygen free copper or pure fine silver. Available in all standard sizes from 0.5mm² - 16mm², also with transparent insulation collar from 1.5mm² - 16mm². Insulated sleeves provide additional cable strain relief. Available in bulk bags, assortments or single pieces. Copper sleeves are 24k gold plated

and silver sleeves	are platinum plat	ed	3 / 11	0 1
and silver siecves	are platificant plat	I.Ou.		Per Each Slee
BT™ Crimp Slee	ves n	nm²	AWG	Retail
└	/BT-0430 0	0.5	#20	\$0.60
		0.75	#19	\$0.60
• w	/BT-0432 1	1.0	#17	\$0.60
W	/BT-0433 1	1.5	#16	\$0.60
W	/BT-0434 2	2.5	#14	\$1.00
w	/BT-0435 4	1.0	#12	\$1.00
w	/BT-0436 6	6.0	#10	\$1.00
w	/BT-0437 1	10.0	#8	\$1.50
w	/BT-0438 1	16.0	#6	\$2.00
BT™ Crimp Slee	ves with Insul	lated	l Collar	
w	/BT-0441 1	1.5	#16	\$1.50
W	/BT-0442 2	2.5	#14	\$1.50
w	/BT-0443 4	1.0	#12	\$2.00
W	/BT-0444 6	6.0	#10	\$2.00
w	/BT-0445 1	10.0	#8	\$2.50
w	/BT-0446 1	16.0	#6	\$3.00
BT™ Silver Crim	p Sleeves witl	h Ins	sulated Collar	
w	BT-0450 1	.5	#16	\$5.00
L w	BT-0451 2	2.5	#14	\$6.00
w	BT-0452 4	1.0	#12	\$7.50
W	BT-0453 6	6.0	#10	\$8.50
	V	VBT-	0470 Crimp Sleeve Assortment	\$245.00
		1 ba	g each of WBT-0430, 31, 32, 33,34, 41 & 42	
	V	VBT-	0471 Crimp Sleeve Assortment	\$229.00
		1 ha	g each of WRT-0/35, 36, 37 & 38	


Assortments are packaged in plastic dispensers as shown.


WD1-0470 Chilip Siceve Assortinent	ΨΣ-10.00
1 bag each of WBT-0430, 31, 32, 33,34, 41 & 42	
WBT-0471 Crimp Sleeve Assortment	\$229.00
1 bag each of WBT-0435, 36, 37 & 38	
WBT-0472 Crimp Sleeve Assortment	\$123.00


1 bag each of WBT-0443, 44, 45 & 46

Various Instructions

RCA TYPE CONNECTOR TIGHTENING INSTRUCTIONS










RCA Socket Mounting Dimensions

WBT-0234





WBT-0274






Various Instructions


WBT-0645 Install Instructions



WARNING! Do not fully tighten knob unless inserted into banana hole.

Binding Post Assembly





Binding post hole cutout dimensions for insulation washer (measurements in mm)



CRIMPING TECHNIQUE

ILLUSTRATIONS NOT TO SCALE

WBT's crimping technique has been designed to ensure a high quality and durable crimp. For the procedure itself, one must strip the desired cable and insert it into the proper size crimp sleeve. Then, carefully place the wire and sleeve into the proper slot on the crimper and apply a powerful squeeze. WBT's unique crimp tool design creates a crescent shaped crimp which forces the wire to flow together, thus creating the illusion of a single strand of wire. Trim the sleeve, including the wire, to the desired length to fit the application. When using one of WBT's solderless connectors, simply loosen the set screw on the connector then insert the crimped end of the cable into the connector, tighten using the TorxTM bit.



Wire is stripped and the appropriate size crimp sleeve is slid onto the strands.



Sleeve is then crimped onto wire with crimping pliers.



The result should look like this.



Use WBT-0499 cutters to trim crimped wire end to fit in WBT™ crimp technique connector.



Crimped cable end ready for use in WBT™ crimp technique connectors.



BC662 6-way Speaker Selector with volume controls \$252 each. 2 Source Inputs (A & B), selectable per channel Power Handling 75 watts RMS Use with 4 or 8 ohm systems

Impedance correction Transformer type volume controls Shown with cover off.



VC126i Volume Control \$34.00 Impedance matching, use with 4 or 8 ohm speakers. 43 watt RMS, 126 watt average. 10 steps



Foculpods Isolation Feet \$20.00 for a set of 4.

Great for isolating vibrations from equipment or speakers.



YAPLUG Angle Banana \$4.50 ea Gold plated brass, set screw for wire and pressure fit for jacket. Threaded pin expands banana for tight fit.



Flared Ports 3" & 4" ID Flared on both ends. 17" long max length. Cut center to fit. 3FLARE \$12.00 each Flange diameter 6 1/4'



2" ID Flared Port Flared on both ends. Use either end as outer flare. 11" long max length, 5.25" flange 2FLARE \$8.80 each



SSV Scan speak vent \$6.00 each Scan-speak aperiodic vents are used in sealed boxes to reduce the system Q of the box. SSV's allow you to reduce your box size by about 25%. Use one up to 1 cf and 2 or more for larger boxes. 4.3" cutout diameter

PEGLOCK Grill Fastener

\$0.25 each for a peg and socket.

Use 3/8" drill for peg & socket.

Nylon, very strong material.



T-Nut & Blk Allen Head Screws 6-32 x 1" \$0.30 each 8-32 x 1" \$0.35 each 10-24 x 1-1/2" \$0.35 each 1/4-20 x 1-3/4" \$0.40 each

HEDLOCK Grill Fastener

\$0.25 each for a ball and socket.

Use 37/64" or 14.5mm for Socket.

Use 7/16" or 11mm for Ball.



YSC Cone Tiptoe \$1.45 each Chrome plated metallic gray color, including t-nut. 5/8" tall with metric M6 shaft (not 1/4-20)



YSC1/4-20 Chrome Tiptoe \$1.45 each YSCG Gold Plate Tiptoe \$1.50 each

Black Chrome or Gold plated, including foot. 5/8" tall with 1/4-20 shaft & insert.



YLC Cone Tiptoe \$2.00 each Chrome plated metallic gray color, including t-nut. 1-3/8" tall with metric M6 shaft (not 1/4-20)



YLC1/4-20 Chrome Tiptoe \$2.00 each. YLCG Gold Plate Tiptoe \$2.10 each.

Chrome or Gold plated. 1-3/8" tall with 1/4-20 shaft and threaded insert



YT Set of 4 Tiptoe \$2.60 set 1/4" tiptoe x 1-3/4" long with threaded inserts and lock nuts. Use pointed or flat end.



YBT Set of 4 Tiptoe \$5.20 set 3/8"-20 tiptoe x 2 1/8" long with threaded inserts and lock nuts. Use pointed or flat end.



YRCA4 RCA Plug \$2.95 each Blue or Red stripe. Gold plated, Crimp or solder. Accepts up to 6mm cable jacket. 4cm long



RCA5 RCA Plug \$5.70 each Red or White stripe. Gold plated, Crimp or Solder. Accepts up to 8mm cable jacket. 5cm lon



YBSC Chrome Tiptoe \$5.65 each YBSCG Gold Tiptoe \$5.85 each 1.5" Tall



YBLCG Gold Tiptoe \$6.35 each 2.15" Tall

Great for heavy speakers, Black Chrome plated brass, 1.25" diameter at base. Tiptoe, 1/4-20 threaded stud, threaded insert, foot pad. Perfect for large speakers or subwoofers. Could be used without tip.




YSCGA Gold Plated Height Adjustable TipToe. \$5.40 Each. 1" (25mm) diameter, 1.1" to 1.38" height. Gold plated foot. Pad for foot & double stick tape to mount.



YRF Rubber Foot \$0.80 each 1.45" OD (37mm) 0.78" Tall (20mm) 1/4" hole (6mm)



Felt Diffraction Ring for tweeters, 1/8" thick; \$2.00 each. 4.37" (111mm) OD 1.62" (41mm) ID



YG-Spade Red or Black \$2.75 each All brass gold plated. Will accept wire with a jacket diameter up to 6mm. Spade opening stepped at 3mm, 5mm & 6mm. Spade blade thickness 2.1mm







LP15 15W 8Ω L-pad \$4.40 ea 3/4" shaft length, 1.6" Ø body LP100 100W 8Ω L-pad \$10.85 ea 3/4" shaft length, 2.45" Ø body



LP50 50Watt 8Ω L-pad \$8.50 each 3/4" long shaft, 2" square body, Attenuation 0 to 40dB. Cast aluminum top plate. Terminal one is ground to speaker and crossover. Terminal 2 to speaker plus. Terminal 3 to crossover T or M plus.



New Hex Socket Screws

- » Black Ox & Wax finish
- » RoHS compliant
- >> Very strong finish and good looking!
- >> Also have several pan head screws with this finish listed in the table above.
- » Made in USA

#6 x 3/4" socket head screw \$0.20 each #8 x 1" socket head screw \$0.24 each #10 x 1-1/8" socket head screw \$0.28 each



CB-CUP Input Cup \$1.85 each Chrome plated posts with plastic knobs and threaded inserts. Accepts banana plugs or 8 Awg. Wire. The cup is 3.15" square with a round 2.7" cut-out hole size.



GB-CUP Input Cup \$2.35 each DB-CUP Input Cup \$3.95 each 2.7" cut-out hole size.



Gold plated posts with plastic knobs All brass gold plated posts with and threaded inserts. Accepts knurled caps. Accepts banana banana plugs or 8 Awg. wire. The plugs or 4 Awg wire. The cup is cup is 3.15" square with a round 3.15" square with a round 2.7" cut-out hole size.



D-CUP Input Cup \$3.95 each All brass gold plated posts with knurled caps. Accepts banana plugs or 4 Awg wire. The cup is 4.14" round with a 3" round hole size.



R-CUP Input Cup \$4.25 each hexagonal caps. Accepts banana Ø)posts with ribbed caps. Accepts caps and straps for plugs or 4 Awg wire. The cup is 4.14" round with a 3" round hole size.



plate is 4.73" long by 1.97" wide. Cut-out, buy it first and decide.



G25-CUP Input Cup \$10.60 each TD-CUP Input Cup \$9.20 each All brass gold plated posts with All brass gold plated (25mm All brass gold plated posts with ribbed bi-wire banana plugs or 2 Awg wire. The applications. Accepts banana plugs or 4 Awg wire. The cup is 4.73" tall by 3.66" wide. Cut-out 3.7" x 2.9".



N-POST Terminal \$0.90 each Chrome plated posts with metal inserted plastic knobs. Accepts 7 Awg wire. 1/2" long shaft. Red or Black.



G-POST Terminal \$1.60 each head. Accepts bananas or 4 Awg head. Accepts bananas or 4 Awg or Black.



G-POSTL Terminal \$1.70 each All brass gold plated with knurled All brass gold plated with knurled wire. Shaft length 1/2". Specify Red wire. Shaft length 1". Specify Red or Black.



HG-POST Terminal \$1.90 each All brass gold plated with Hex head. Accepts bananas or 4 Awg wire. Shaft length 1". Specify Red or Black.



BG-POST Terminal \$2.10 each All brass gold plated with ribbed head. Accepts bananas, spades or 4 Awg wire. Shaft length 1". Specify Red or Black.



All brass gold plated with knurled Gold plated posts with clear plastic head. Accepts bananas, spades or 4 protection. Meets CE regulation. Awg wire. Shaft length 1.65". Specify Red o Black.



YG-POST Terminal \$2.55 each SG-POST Safety Terminal \$1.90 Available in Red or Black. 30mm long shaft. 5mm cable entry hole



EG-SPLUG Banana \$2.45 each. EG-PLUG Banana \$6.50 each. All brass gold plated single banana All brass gold plated dual banana plug. Accepts 6 Awg wire (5mm plug with a standard 34" spacing. Ø). Has two set screws. Specify Accepts 6 awg wire. Red or Black.



Wire is fastened by screw down head.




Computer Aided Crossover Design


Crossover design has significantly evolved in the last decade. In the past you had to start with a theoretical design and then spend weeks tweaking until you came up with a crossover that sounded pretty good, but probably was not as good as it could be. Madisound has now developed the art of crossover design, providing the customer with a fully developed filter system in a fraction of the time necessary using older methods.


Madisound begins by taking all driver response and impedance measurements in our anechoic chamber using the Audio Precision measurement system. We then export this data into the Leap filter analysis program by Linearx. With the Leap program we can plot what would be an ideal curve for each driver, and then use Leap to try different filter values against the actual driver response curves, continually selecting those parts that bring the actual curve to that of the ideal curve. We then look at the total system response curve and select parts to match the ideal system response. The result is a flat response curve, to the limits of the selected driver responses. This method can be repeated for impedance correction to create an ideal impedance magnitude response. The finished design is excellent, and a good value!


We are designing with Leap version 4.6.

The following curves are provided with each Leap design order:









To place an order for a Leap design, Madisound we need to know the following:

- > What drivers are you using? They must be Madisound stock items. (In the case of 3 or 4 way systems, we could just use the woofers technical parameters.)
- > What are your box volumes, or do you wish us to determine them for you?
- > Are the drivers surface mounted, or routed into the cabinet for a flush mount? (Flush recommended)
- What slopes (6dB, 12dB, 18dB, 24dB) would you like us to design for, or would you prefer we choose?
- > Do you prefer a flat response, tapered response or relaxed midrange response?
- > What quality of inductors will you use? We will model using the DCR of the coils.

Leap Design Pricing (Design only, not an assembled crossover)

2-Way Design	\$30.00	Sub /Sat Design	\$35.00	Special requests or projects?
3-Way Design	\$40.00	MTM 2-Way	\$30.00	Ask about pricing.
4-Way Design	\$60.00			

All our cables are manufactured with the same principle which for the first time PHY-HP (Haut parleurs)® respects the works conclusion of Dr. Pierre Johannet, Head of research at the EDF (French National Electricity Cie) about the interface micro discharges = MDI and coming also from two years development at PHY-HP. Those works ex-

plain a lot of things, most of which for many years audiophile people have found by listening, and even more, but shows also why all natural materials perform much better, in audio also than any "modern", "technic" synthetic one.

For example they show how multi wire cables produce so much MDI = oblige mono wire cable how all synthetic material make the same MDI, cotton and lin so few and also have no memory effect how copper when new and clean, performs very close to silver (MDI and listening), but increase in a dramatic way in producing MDI and become awful listening after some days as his surface comes oxide and copper oxide is semi-conductor, in opposition silver oxidized conductivity is as good as silver; this means that it is not necessary to make it massive silver but silvered cooper as it is much cheaper.

And more... These techniques gives extremely natural results, transparency with fullness, sweetness with high definition, with a much larger objective and subjective frequency response (see for instance how high level industry HF is made), and which transmit an astonishing quantity of information. As on, sound, musicality and emotion carried by our cables with very few added perturbations allow a rare level of pleasure.



PHY 1.2 Meter Interconnect Pair with Silver Plated Copper RCA \$480 PHY 1.2 Meter Shielded Interconnect Pair with Silver Plated Copper RCA \$510

3 conductors ø 0,6 mm mono wire cable, silver plated pure recooked copper, insulated by hydrophobic natural cotton, with or without silvered shielding.

Review: http://www.6moons.com/audioreviews/phy/cotton_2.html



PHY Speaker Cable Pairs without Termination

3 Meter Pair \$610 - 4 Meter Pair \$695 - 5 Meter Pair \$760 - 6 Meter Pair \$910 For Terminated Cable Pair Add: \$460.00 to prices above.

 $3 \text{ conductors } \emptyset \text{ 2 = 3,1416 mm2 solid core mono wire cable , silver}$ plated pure recooked copper, insulated by hydrophobic natural cotton.

Terminated cables have PHY banana plugs are made from 40 micron silver plated pure copper.





PHY Speaker Binding Post Each \$39.00

The PHY binding post will accept cable entry or a banana plug. Specify Red or Black. 40 micron silver plated pure copper.



The PHY banana plug is made from 40 micron silver plated pure copper.





PHY RCA Plugs Each \$50.00

40 micron silver plated pure copper

PHY RCA Sockets Each \$43.00

Specify Red or White.

40 micron silver plated pure copper





PHY Mains Power Cable with US Standard and IEC Plugs

- 1 Meter Length \$350
- 2 Meter Length \$400

3 conductors each of ø 1,8 = 2,5 mm2 made of 50 wires flexible cable, silver plated pure recooked copper, insulated by hydrophobic natural cotton



Supra has been manufacturing cables, in-house from their facilities in Sweden, since 1976. Prior to 1976, cables had no identity, they were just "cables". In 1976 **Supra** introduced the "Supra 2.5", beginning a new trend in branded cables.

Supra has since greatly expanded their lines, creating new cables for each new trend in the audio industry. We invite you to visit the **Supra** web site for more information, or download the Supra catalog from our web site: **www.jenving.se** in Sweden.

<u>Item</u>	Description	Price		
Supra Lorad Screened Power Cables: Ice Blue				
LORAD/FT	Lorad cable by the foot	\$4.55		
MD06-US	Power Strip - no cord	\$180.00		
Sword Rif	ilar I itz Spaakar Cabla with (Combicon		

Sword Bifilar Litz Speaker Cable with Combicon Termination by Gas Tight Crimping (cold welded)

Sword 2M	2m Pair with Combicon	\$840.00
Sword 3M	3m Pair with Combicon	\$1,125.00
Sword 4M	4m Pair with Combicon	\$1,410.00

Sword Analog Interconnects with Bifilar Wound Litz Wire and Special Anniversary RCA Terminals

Sword-ISL 1M	1m Pair with RCA	\$685.00
Sword-IXLR 1M	1m Pair with XLR	\$740.00

EFF Analog 75 Ohm Interconnects with PPSL RCA

EFF-ISL 1M	1m Pair with RCA	\$160.00
EFF-ISL 2M	1m Pair with RCA	\$200.00
EFF-IXLR 1M	1m Pair with XLR	\$155.00
EFF-IXLR 2M	2m Pair with XLR	\$195.00

Trico Digital 75 Ohm RCA Video Interconnects

Trico-RCA 1M	1m Each with RCA (3.3')	\$80.00
Trico-RCA 2M	2m Each with RCA (6.6')	\$95.00
Trico-RCA 4M	4m Each with RCA (13.3')	\$125.00
Trico-RCA 6M	6m Each with RCA (20')	\$150.00
Trico-RCA 8M	8m Each with RCA (26.6')	\$180.00
Trico-RCA 15M	15m Each with RCA (49.8')	\$280.00

Speaker Cable by the foot

Classic 1.6	by the foot (15AWG)	\$0.80
Classic 2.5	by the foot (13AWG)	\$1.45
Classic 4.0	by the foot (11AWG)	\$2.15
Rondo 2x2.5	by the foot (2x13AWG)	\$2.15

<u>Item</u>	Description	Price
Rondo 4x2.5	by the foot (4x13AWG)	\$3.35
PLY2.0	by the foot (14AWG)	\$2.75
PLY3.4	by the foot (12 AWG)	\$3.65
PLY3.4/S	by the foot (12AWG) Shielded	\$4.55
HDMI to HDMI Cables		
HDMI 1M	1 Meter Single (3.3')	\$75.00
HDMI 2M	2 Meter Single (6.5')	\$85.00
HDMI 4M	4 Meter Single (13.1')	\$105.00
HDMI 8M	8 Meter Single (26.2')	\$145.00
HDMI 12M	12 Meter Single (39.3')	\$185.00
HDMI 15M	15 Meter Single (49.2')	\$215.00
Supra Connectors		
Banana	2 pairs	\$38.00
Fork XL	2 pairs	\$24.00
Boxcon	1 pair insulated binding post	\$60.00
CombiCon Kit	2 pairs body, 4 spades/bananas	\$80.00

The **Lorad power cables** are very popular, providing a shielded connection to the wall outlet. The MD06-US power strip is also shielded and has no stray fields.

The **Supra Classic** and **Rondo cables** are used for both internal and external wiring. The shielded version is more often used for external wiring, reducing the effects of stray field noise.

Sword cables are made with bifilar litz winding, where an inner set of helically wound wire is run in one direction and an outer set in another direction. This divides the fields in opposing directions, cancelling the magnet field. Sword behaves as a non-inductive and phase stable cable. Sword cables come with interchangeable CombiCon connectors, providing both spade and banana termination.

Supra EFF is one of our best analogue interconnects. Multi test winner and our most sold interconnect. EFF comes terminated with the PPSL RCA plug or XLR plug.

Trico is a 75 Ohm double screened coaxial interconnect cable for digital/ video signals.

Tin vs Silver, Supra cables are plated with a high purity Tin instead of Silver. Tin is of a higher resistance than Silver, so the signal travels through the copper and not on the plating. Tin also has a minimized dialectic effect by acting as a semi-Litz.

GOERTZ SPEAKER CABLES

• GOERTZ HT 14AWG COPPER

Easy to install under carpeting and behind baseboards.

On the spot termination: Termination may be performed using the Goertz Rhodium plated connectors or the G-HT may be notched to form integral spades which will fit into the screw terminals. In both cases no soldering is required. The notching pliers are available to buy in "Accessories."

• GOERTZ MI 1 13AWG COPPER (AG 1 SILVER 12AWG)

The original Goertz cable, MI 1 in 13 gauge (AWG) solid Oxygen Free Copper (OFC) or 12 gauge AG 1 in solid High Purity Silver. The heavy, high purity Oxygen Free Copper (OFC) or solid high purity silver ribbons are sandwiched together, separated only by micro-thin layers of film insulation. The minute amount of active dielectric also provides rapid break-in; now audiophiles don't have to wait tens of hours to break in their cables, Goertz cables produce immediate results!

• GOERTZ MI 2 10AWG COPPER (AG 2 SILVER 9AWG)

MI 2 Heavy 10 gauge OFC copper or 9 gauge AG 2 solid silver cabling for improved bass and power handling over the remarkable Goertz MI 1. Great reviews confirm that this remarkable cable really delivers; superb bass control, vivid mid-range, and excellent high frequency extension combine with rejection of interference and no break-in period. Simply great value.

• GOERTZ MI 3 7AWG COPPER (AG 3 SILVER 7AWG)

Alpha-Core's "Big Boy" 7 gauge speaker cable; the answer for powerful audiophile systems. MI 3 was designed for high power amplifiers driving full range speakers. Perhaps the best speaker cable made today, the MI 3 delivers sublime clarity, dynamics, and definition throughout the audio spectrum. The extreme low DC resistance ensures diaphragm control for tight, powerful bass and mid-range, and the low inductance carries distortion free high frequencies and crucial harmonics for outstanding imaging and depth perception.

- **PYTHON MI 2**, the first Serpent, is electrically and sonically equivalent with the popular **GOERTZ MI2**. It contains four film insulated flat, solid OFC copper conductors sandwiched intimately on top of one another and then twisted and embedded in a cylindrical, solid jacket of high grade polymer. The resin is cast in place to totally support and protect the flat conductor bundle, meaning that **Python** can take any amount of punishment and still sound and look like new.
- BOA cables are larger gauge versions of the Serpent cables.

HT, MI, & AG SPEAKER CABLE PAIR

MODEL	SINGLE per foot	BI-WIRE per foot				
COPPER CABLE "CU"						
HT 'Home Theater' (14AWG)	\$8.39	\$16.77				
MI1 'Center Stage' (13AWG)	\$12.40	\$24.80				
MI2 'Veracity' (10AWG)	\$21.50	\$43.00				
MI3 'Divinity' (7AWG)	\$53.00	\$106.00				
SILVER CAB	LE "AG"					
AG1 'Center Stage' (12AWG)	\$73.20	\$146.40				
AG2 'Veracity' (9AWG)	\$128.70	\$257.40				
AG3 'Divinity' (7AWG)	\$275.60	\$550.00				
Add Termination Cost						
Rhodium Spades, Bananas, Pins	\$40.00	\$63.00				
Silver Spades	\$58.00	\$85.00				

CABLE CONNECTORS

MODEL	PRICE				
RHODIUM SPADES (4)	\$24.00				
RHODIUM BANANAS (4)	\$24.00				
RHODIUM PINS (4)	\$24.00				
SILVER SPADES KIT 1/2" x 5/16" (4)	\$40.00				
SILVER SPADES KIT 5/16" x 5/32" (4)	\$27.00				

PYTHON & BOA CABLE PAIR

MODEL	SINGLE per foot	BI-WIRE per foot					
COPPER CABI	COPPER CABLE "CU"						
PYTHON MI2 (10AWG)	\$28.00	\$28.00					
BOA MI3 (7AWG)	\$69.00	\$69.00					
SILVER CABL	E "AG"						
PYTHON AG2 (9AWG)	\$161.00	\$161.00					
BOA AG3 (7AWG)	\$344.50	\$344.50					
COPPER & SILVER HY	BRID "CU&	kAG"					
PYTHON HYBRID (10AWG)	\$94.50	\$94.50					
BOA HYBRID (7AWG)	\$206.75	\$206.75					
Add Termination Cost							
Rhodium Spades, Bananas, Pins	\$40.00	\$63.00					
Silver Spades	\$58.00	\$85.00					

TO CALCULATE TOTAL PRICE:

- DETERMINE PRICE FOR 1' PAIR IN SINGLE OR BI-WIRE
- MULTIPLY THE LENGTH YOU NEED WITH CORRE-SPONDING PRICE/FOOT PAIR
- ADD THE TERMINATION PRICE
- TOTAL PRICE=[(PRICE/FT. PAIR X LENGTH) + TERMINATION COST]

ALPHA-CORE INTERCONNECTS

• 'TOURMALINE' COPPER

Two thin 18 gauge high purity Oxygen Free Copper (OFC) conductors are sandwiched together, separated only by micro-thin layers of film insulation. The minute amount of active dielectric also provides virtually no break-in!

• 'MICRO PURL', COPPER AND SILVER

The revolutionary Micro Purl is cutting-edge transmission line technology. It contains two 50 microns thick by 2mm wide signal carriers made of solid fine silver or OFC Copper, placed on each side of a copper ground plane. The ultra thin three layer sandwich is then twisted (purled) as it is embedded in a heavy sheath of transparent high grade polymer. The twisting facilitates handling and further enhances EM and RF rejection. Micro Purl is breaking new ground as professional quality microphone and patch cables, and as digital interconnects. AWG 26.

• TQ 2 'TRIODE QUARTZ' SOLID FINE SILVER

The new TQ 2 is made in similar fashion as Micro Purl, by twisting the bundle of solid fine silver conductors and copper ground plane in line with the extrusion of a tough, crystal clear jacket of high grade polymer. The result may be coiled and handled like any other cable and will take considerable punishment without equivalent to AWG 22, and the overall diameter is .32" versus .25" for Micro Purl. The electrical parameters and sonic characteristics are the same as those of TQ 1 except for the fact that the in-line twist has further improved the EMI and RF noise rejection inherent in the low inductance geometry.

• 'SAPPHIRE' SILVER

Two thin 18 gauge 99.99% pure solid fine silver conductors are sandwiched together in the unique Goertz configuration. Impervious to extraneous line frequency and RF fields, with the great ultra clean sound of solid fine silver.

INTERCONNECT CABLE PAIR

TITERCOTTILET CIBELTIAN								
MODEL	0.5M	1M	1.5M	2M	2.5M	3M	4M	5M
COPPER INTERCONNECTS "CU"								
TOURMALINE RCA	\$92.00	\$137.00	\$175.00	\$216.00	\$258.00	\$299.00	\$352.00	\$410.00
TOURMALINE XLR	\$131.00	\$180.00	\$224.00	\$270.00	\$316.00	\$363.00	\$424.00	\$492.00
MICRO PURL CU-RCA	\$52.00	\$78.00	\$93.00	\$121.00	\$149.00	\$166.00	\$196.00	\$257.00
MICRO PURL CU-XLR	\$74.00	\$103.00	\$128.00	\$155.00	\$187.00	\$207.00	\$244.00	\$312.00
		SILVER IN	NTERCON	NECTS "A	.G"			
MICRO PURL AG-RCA	\$85.00	\$127.00	\$152.00	\$197.00	\$243.00	\$270.00	\$320.00	\$419.00
MICRO PURL AG-XLR	\$121.00	\$167.00	\$208.00	\$252.00	\$305.00	\$337.00	\$398.00	\$508.00
TRIODE QUARTZ TQ2 RCA	\$125.00	\$186.00	\$238.00	\$293.00	\$350.00	\$406.00	\$478.00	\$557.00
TRIODE QUARTZ TQ2 XLR	\$178.00	\$245.00	\$304.00	\$366.00	\$428.00	\$492.00	\$576.00	\$668.00
SAPPHIRE RCA	\$193.00	\$341.00	\$487.00	\$619.00	\$652.00	\$685.00	\$914.00	\$1,145.00
SAPPHIRE XLR	\$256.00	\$435.00	\$610.00	\$769.00	\$800.00	\$864.00	\$1,118.00	\$1,340.00

INTERCONNECT TERMINATION

MODEL	PRICE
24 KARAT GOLD PLATED TIP RCA (4)	\$28.00
RHODIUM PLATED XLR (4)	\$37.00
SOLID SILVER RCA AG2K (4)	\$180.00



OTHER ACCESSORIES

MODEL	PRICE
HEAT SHRINK SLEEVES (6)	\$2.00
GOERTZ SPADE CUTTER	\$8.95
SILVER SOLDER 1 LB. SPOOL	\$42.00




Words of Wisdom for Speaker Builders

"For the inexperienced builder...the best single reference available..."

> —Robert M. Bullock, III Contributing Editor, Speaker Builder SEVENTH EDITION

The Loud Speaker Design Cookbook

by Vance Dickason



Publisher's price \$39.95 Madisound Price \$35.00

Twelve Chapters (275 pages, soft bound)

- 0. How Loudspeakers Work
- 1. Closed-Box Low-Frequency Systems
- 2. Vented-Box Low-Frequency Systems
- 3. Passive-Radiator Low-Frequency Systems
- 4. Transmission Line Low-Frequency Systems
- 5. Cabinet Construction: Shape and Damping
- 6. Loudspeaker Baffles: Driver Locations, Separation and other Considerations
- 7. Passive and Active Crossovers
- 8. Loudspeaker Testing
- 9. Cad Software for Loudspeaker Design and Loudspeaker Room Interfacing
- 10. Home Theater Loudspeakers
- 11. Car Audio Loudspeakers
- 12. Two System Designs: Home Theater and a Studio Monitor



by Joseph D'Appolito

- Seven Chapters
- 174 pages

Publishers Price \$34.95 Madisound's Price \$30.00

Testing Loudspeakers is the first comprehensive and solidly authoritative account of just how loudspeakers may be reliably tested. Ultimately, accurate results from testing will lead to better designs. The measurement techniques contained in this book provide all clues you need to refine your speaker's components to improve its performance. The author spells out in his first chapter:

"To my knowledge, there is currently no well-organized tutorial reference on loudspeaker testing for the experienced hobbyist or technician. This book is intended to fill that gap."

Speaker Building 201


A comprehensive course in speaker design. by Ray Alden

Twelve Chapters, (153 pages, soft bound)


Chapters 1 through 10 provide a basic knowledge of speakers and speaker building. Starting with the basic of how a speaker works, to building the correct enclosure for your speaker and basics in speaker crossover design. There is also a chapter on speaker design software and speaker testing.

The Final two chapters have specific details on building 11 different speaker systems

This book has many photos, illustrations and graphs to aid you in understanding the speaker building process.



Madisound's Price \$30.00



Spectra Dynamics

ACOUSTIC PANEL TECHNOLOGY

Deflex Panel and Deflex Subwoofer Panel

Material......

Color......

Surface emulation.....

Defined radius - nominal.

Focal point - nominal....

Thickness at center.....

Max. edge thickness.....

Overall dimensions.....

Density / hardness......

Rebound resilience.....

Standard Panel

Advanced polymer Charcoal grey Spherical concave 200 mm 100 mm 5 mm (maximum) 12 mm 280mm x 210mm 1.36 / < 15° A < 15%


Subwoofer Panel

Advanced polymer Charcoal grey Spherical concave 300 mm 150 mm 12 mm (maximum) 12 mm 340 mm Ø Round 1.36 / < 15° A < 15%


The polymer is specially formulated to absorb shock and vibration, thus minimizing cabinet resonances.

The surface emulation has been carefully designed to help eliminate standing waves.

Independent tests on MLSSA show an energy gain of over 50%.



Foculpod Isolation Feet



"...A marked improvement was obvious from the "...The special surface pattern reduces standing waves to cure boxiness and resonance without killing the vitality of the sound..."

"...expect tighter cleaner bass, crisper articulation, and an increase in liveliness without loss of control..."

"...The result was sharper imaging, wider dynamics and a more natural sound..."

**HI-FI Choice - January 1994*

"...Deflex panels seemed to give greater tightness and control, improved internal clarity, and better pitch definition - all without deadening the sound in any way..."


Audiophile - January 1994

CURRENT PRICE LIST

Standard Panel Sub-woofer Panel Foculpods Weldbond @ \$ 11.00 each
@ \$ 20.00 each
@ \$ 20.00 set of 4
@ \$ 2.70 4 oz. bottle

We recommend Weldbond as an adhesive to attach the Panels. Wash the panel first; let dry; smear Weldbond on panel and cabinet; when tacky, attach.

" THE ONLY CURE FOR BOX NOISE AND STANDING WAVES "



MADISOUND SPEAKER COMPONENTS 8608 UNIVERSITY GREEN P.O. BOX 44283

MADISON, WI 53744-4283 U.S.A. TEL: 608-831-3433 FAX: 608-831-3771

e-mail: madisound@itis.com
Web Page: http://www.itis.com/madisound



Altitude 3500 Integrated Valve Amplifier

The Altitude 3500 is the culmination of many years of development and refinement. Component quality and circuit design have been carefully chosen to deliver the highest quality of musical reproduction, with accurate and emotional delivery of the sound stage.

The Altitude 3500 Integrated valve amplifier features only the best available components with the shortest and cleanest signal paths possible with direct coupling used on the input stages to improve signal transit response.

High quality electrolytic and non electrolytic capacitors have been used throughout the Altitude 3500 amplifier in critical signal areas to ensure instant energy for fast dynamic midrange and top end transients with tight very dynamic bass performance normally not found on valve amplifiers.



By using high voltages on the plates of the output valves, we are able to run them at lower currents, which will result in longer life for the output valves and less reliance on bias adjustment with age.





Specifications:

Conformity

Price

Channels	2-channel
Inputs	(4) CD/Tuner/Aux1/Aux2
Input Impedance	100k ohms
Input Sensitivity	350mV rms @ 1KHz
Output Power	32WPC@1KHz into 8ohm
Output Class	AB1 Push Pull
Output	4 or 8 ohm speaker load
T.H.D.	less than 1%
Frequency Response	15Hz-50 KHz +- 0.5 dB
S/N Ration	89dB/A
Valves	2 x 12AT7 Twin triode
	2 x 12BH7 Twin triode
	4 x EL34B Pentode
E	L34 Output Valves are matched pairs
Chassis	heavy gauge brushed
	aluminum on all sides
Dimensions	350mm*190mm*320mm
Net Weight	18Kgs (39.7lbs)

CE Rating

\$1350.00



Keiga Subwoofer Amplifiers and 2.1 Media Amplifier

 \Rightarrow KG-3100: 50W & (2x) 25W @ 4Ω

 \rightarrow KG-5150: 200 Watts @ 4 Ω

ightharpoonup KG-5230: 300 Watts @ 4 Ω

KG-5230 Sub Amp

The KG-5150 and KG-5230 are plate Subwoofer Amplifiers with Electronic Crossovers for building powered subwoofer systems. These amps have adjustable electronic crossovers and have enough power to deliver good bass without added distortion. We are confident that we now have products that can meet the demands of both home theater or high end audio systems. subwoofers are a versatile addition to your audio system. With the variable crossover and volume control, you can match a subwoofer to any existing system. amplifiers can be used with single or multiple woofer systems (a total impedance of 4 to 8 ohms is recommended). The crossover can be turned off if you are using the amplifier with a system that already has a built in crossover. KG5230 has a 12V DC trigger.

your computer.

Class AB

- KG-5150 Sub Amp Discrete high current drivers and output devices
- Woofer volume control
- 50Hz to 100Hz continuously adjustable low pass 12dB electronic crossover
- Crossover on/off switch
- · Low and High level input, summed to mono signal
- Low and High level all pass output
- · Phase inverter switch
- Master power switch
- Auto power on/off activated by input signal
- 4dB boost @ 25Hz, 15Hz High pass

The **KG-3100 2.1 Amplifier** was developed for small sub/sat systems. The amp is designed to be built into



KG-3100 2.1 Amp

the subwoofer enclosure and then out to the satellite speakers. You can use the built in **electronic crossover** to divide the frequencies between the amp and the The electronic crossover is continuously

variable from **75Hz to 150Hz**. There is a master volume control and a volume control for just the subwoofer. The amplifier will accept either RCA inputs or 3.5mm Mini **Jack inputs**. If you are using the mini jack inputs, you can purchase a separate desktop volume control for use with KG-VC Volume Control



The KG-3100 is the perfect choice to build a system for your computer, MP3 player, portable CD player, office or small apartment.

- X-over LP + HP: 75Hz 150Hz
- Rear plastic cover
- Master & woofer volume controls
- Switchable bass boost 3dB@40Hz
- Auto on control
- GP Binding Posts for Sat. Outs
- Separate KG-VC desktop mini jack volume control for \$15.85.

Specifications:	KG-5150	KG-5230	KG-3100
Power output Watt@ 4 ohms	200	300	50 &2x25
THD	0.05%	0.08%	0.08%
S/N ratio @ rated power	85dB	85dB	76dB
Input sensitivity @ 100Hz - low level	75mV	75mV	80mV
Input sensitivity @ 100Hz - high level	3.5V	3.5V	3.5V
Input impedance	22k ohms	22k ohms	22k ohms
Variable Low Pass Crossover Freq.	50-100Hz	50-100Hz	75-150Hz
Weight	10.5 lbs	14.5 lbs	7.6 lbs
Dimensions W x H inches	11 ^{7/16} x 8 ^{1/4}	9 ^{7/8} x 9 ^{7/8}	7 ^{7/8} x 8 ^{11/16}
Cutout hole W x H inches	10 ^{7/16} x 7 ^{1/4}	8 ^{7/8} x 8 ^{7/8}	6 ^{7/8} x 7 ^{11/16}
AC Voltage	115	115 / 230 switchable	115 / 230 switchable
Price Each	\$169.00	\$225.00	\$142.00



KGND5250 (500W) & **KGND52100** (1000W)

Class D Subwoofer Plate Amplifiers

Madisound is pleased to offer these powerful Class D amplifiers. A Class D amplifier is a switching amplifier that converts a low level analog signal into a high power pulse width modulated output. The KGND52100 is 86% efficient and the KGND5250 is 82% efficient; inherent in the Class D design and the efficient power supply. The 1950 watt peak analog power supply is a cleaner power source than switching power supplies found in most other Class D amplifiers. The Keiga Class D amps also have very low standby power consumption of 1 watt, which meets new European standards. Because of its efficiency, these amps produce very little heat. The Keiga Class D Amps use the ICEPower® modules, developed by Bang @ Olufsen Powerhouse a/s. The amps are equipped with a protective casing on the back, not shown in this picture.



K G N D 5 2 1 0



Features:

- Very high efficiency Class D amplifier; high current Mosfet output devices.
- Low pass frequency adjustable 50~100Hz.
- Woofer level control.
- 180° Phase invert switch.
- Auto on control, switchable.
- Very low standby power.
- Thermal protection
- Master power switch.
- LFE input.
- RCA in/out (out has no crossover).
- Speaker level in/out (out has no crossover).
- IEC power socket.
- LED power indicator.
- AC 115V/230V switchable.

Specifications:	5250	52100
• Power output @ 10% THD, 4 ohms	s 600W	1200W
Power output @ 1% THD, 4 ohms	500W	1000W
• T.H.D.	0.08%	0.08%
• S/N ratio @ rated power	80dB	90dB
• Input sensitivity @ 100Hz		
(RCA) low level	150 mv	190mv
(Speaker) high level	3.5v	4.2v
• Input impedance	$22k \Omega$	$22k \Omega$
• Variable low pass frequency	50~100Hz	50~100Hz
• Efficiency	82%	86%
• Standby power consumption	1W	1W
 Dimensions 		
Width	12"	12"
Height	12"	12"
Depth	4.5"	4.5"
• Weight	9.0kg	13.5kg
• Price Each	\$387	\$545

POWERED SUBWOOFER KITS


Madisound has put together several exceptional subwoofer designs to produce Do-It-Yourself Sub Kits with simple assembly and top quality components. We have chosen drivers from Eclipse and Foster to combine with the clean power of the Keiga amplifier make for an attractive and versatile designs. The cabinets are compact for easy room placement and suitable for home hi-fidelity or for home theater applications. Despite the small box size the low resonance of these subwoofers will allow for clean reproduction of movie soundtrack transients down to 25Hz. The cabinets are professionally finished with solid rounded oak corners, completely assembled, and are already cut and vented. Front baffles are 1" thick, all other sides 3/4". The cabinet comes with a black grill. Your choice of clear or black lacquered oak veneer. (Clear finish shown below). The graphs shown are simulated frequency responses. Actual frequency response will vary depending on the dimensions of the listening environment.

Eclipse Powered Subwoofer Kit

Parts Only, cabinets not available \$215.00




18" deep x 16" tall x 14" wide



MAD1259 Powered Subwoofer Kits





Options:


NHT1259 woofer with KG5150 amp \$502.50 (w/o cab \$307.50) NHT1259 woofer with KG5230 amp \$552.90 (w/o cab \$357.90)

18" deep x 28.25" high x 15.5" wide

DESCRNT IN-WALL & IN-CEILING SPEAKERS

Madisound is pleased to offer Descant architectural sound systems for wall and ceiling installation. We think this is an excellent approach to hi-fi sound, without the requirement of significant space for loudspeaker placement. Descant speakers are a good choice for Audio, Video or Commercial applications.

The spin out clamps allow easy installation. Using the template provided, simply cut a hole in the drywall or paneling. Attach the speaker wire to the input terminals and clamp the wall material between the grill frame and the clamps. **New Construction kits** are available for all but the square flange coaxial for \$19.00 a pair.





TW-625 6.5" 2-Way \$218.00 / pair

The TW-625 is a 2-way speaker using a 6.5" polypropylene cone woofer with a rubber surround. The tweeter has a 1" textile dome. The crossovers are designed with 6dB parts on the woofer and 12dB parts on the tweeter, resulting in 12dB mirrored slopes. Good choice for in wall applications.

Specifications:

Impedance:8 ohmSensitivity:90dBFrequency:55 to 20KHzColor:whitePower :40 WattsX-over freq.:3KHz

Dimension: 12" tall x 8 1/2" wide x 3 1/2" deep

RCX-619 6.5" Coaxial 2-Way \$239 / pair RCX-825 & SCX-825 8" Coaxial 2-Way \$279 / pair

The RCX-825 (round) and SCX-825 (square) coaxial speakers are constructed with an 8" polypropylene cone woofer with rubber surround and a pivotal 1" textile dome tweeter. The crossovers are designed with 12dB parts on the woofer and 6dB parts on the tweeter, resulting in 12dB mirrored slopes.

The RCX-619 (round) has a polypropylene cone with a rubber surround and pivotal ¾" textile dome tweeter. The crossover is 12dB/12dB.

The concentric design of a coaxial speaker makes this systems suitable for mounting in the ceiling. With the tweeter mounted in the center of the woofer, no matter where you are standing in relationship to the speaker, you will be equal distance from both the woofer and tweeter. This system performs equally as well when mounted in the wall.



Specifications RCX-825 & SCX-825:

Impedance: 8 ohm Sensitivity: 88dB Frequency: 45 to 20kHz Color: white Power: 75 Watts X-over freq.: 3.5kHz

Dimensions R800: 10 3/4" diameter x 3 1/2" deep Dimensions SQ800: 10 1/16" square x 3 1/2" deep

Specifications RCX-619:

Impedance: 8 ohm Sensitivity: 89dB Frequency: 65 to 20kHz Color: white

Power: 50 Watts X-over freq.: 3.5kHz

Dimension: 9" diameter x 2 7/8" deep

RCX-619CH \$299.00 Pair

This is a chambered version of the RCX-619. The fire rated plastic chamber will allow this speaker to be used in many installations requiring a fire resistant chamber.



RCX-825CH \$349.00 Pair

This is a chambered version of the RCX-825. The fire rated plastic chamber will allow this speaker to be used in many installations requiring a fire resistant chamber.



DESCANT INDOOR/OUTDOOR ON-WALL SPEAKER OR SHIELDED MONITOR / AV SPEAKER

Madisound is pleased to introduce the Descant On-wall or Shielded Monitor speaker. We developed the TR-525 in response to a need for an on-wall speaker that would be functional, yet uncompromising in sound quality. We experimented with many different loudspeakers until we discovered a weather resistant polymer coated paper cone woofer, that gave us the vocal midrange clarity we were looking for, without sacrificing bass response. The TR-525's versatility allow it to be used for numerous applications.

The weatherproof cabinet with U-shaped mounting bracket and weather resistant loudspeakers allow the TR-525 to be mounted outdoors. Consider using them by the pool, patio or any other area you use for outdoor entertaining. The TR-525 is also suitable for commercial outdoor applications, in theme parks, gardens, etc.

Since the TR-525 is magnetically shielded, you may use it next to a computer or TV screen. Consider using it for your surround sound system or add an amplifier to your computer system and use it as a monitor.



The TR-525 can be used as a monitor speaker, either standing upright or on its side. The fully shielded speaker allows for placement next to your TV or computer monitor. The cabinets are available either all black or all white.



The TR-525 comes with a mounting bracket to allow wall or ceiling mounting. The Bracket can be rotating to direct the speaker to the correct listening location. You may mount the speaker vertically or horizontally.





Specifications:

- Indoor / Outdoor
- Shielded magnets for use near computer monitor or TV screen
- Stand alone or wall/ceiling mount (mounting bracket included)
- 5 1/4" Polymer sealed paper cone woofer
- 3/4" Titanium dome tweeter
- · Durable plastic cabinet with metal grill
- Can be mounted vertically or horizontally
- 10" tall x 7.25" wide (front) 2.75" wide (back) x 6.5" deep
- 6dB/12dB crossover with poly cap on the tweeter
- Nominal 8 ohm impedance
- · 80 watts max. Power handling

TR-525 Price \$299.00 per pair Specify white or black.



ACCUTON by Thiel & Partner



New Label	Old	Description	Ω	Fs Hz	dB	Watt	Box Ltrs	F3	Price Each
	Label	· · ·					Sealed/Vented	Hz	
	Tweeters								
D20N-6-31	D20-6	³ ⁄ ₄ " Diamond Dome Tweeter	6	900	89.5	200			\$2,900.00
D25N-6-34	D25-6	1" Diamond Dome Tweeter	6						\$3,900.00
D30N-6-36	D30-6	1.2" Diamond Dome Tweeter	6	440	90	300			\$5,000.00
D50N-6-39	D50-6	2" Diamond Dome Midrange	6	390	89				\$13,500.00
C25-6-12	C12-6	1" Ceramic Dome Tweeter	6	700	89.5	120			\$226.00
C25N-6-13	C13-6	1" Ceramic Dome, Neo Magnet	6	1250	92	120			\$297.00
C30-6-23	C23-6	1.2" Ceramic Dome Tweeter	6	350	89.5	100			\$262.00
C30N-6-24	C24-6	1.2" Ceramic Dome, Neo Mag.	6	825	92	100			\$345.00
		,	Squ	are Fi	rame	S			
C50-8-44	C44-8	2" Ceramic Dome Midrange	8	390	88.5	100	has sealed cl	namber	\$276.00
C90-6-79	C79-6	3" Ceramic Dome Midrange	6	96	88.5	120	Use 1.5 to 4	sealed	\$339.00
C90-T6-89	C89-T6	5" Ceramic Bass-Midrange	6		89.2		2.5S / 3V	110 / 80	\$368.00
			Rou	und Fr	ame	S			
C153-T8-82	New	5" Ceramic Bass-Midrange	11	33.2	87	130	2.5S / 5V	118 / 70	\$275.00
C173N-T6-90	C90-T6	6.5" Ceramic Mid, Neo Magnet	6	73	93.2	120	2S / 3V	180 / 120	\$614.00
C173-6-92	C92-6	6.5" Ceramic Bass-Midrange	6	29	86	130	29S	49	\$285.00
C173-T6-95	C95-T6	6.5" Ceramic Bass-Midrange	6	32	89.1	130	6.5S / 9V	80 / 57	\$368.00
C173N-T6-96	New	6.5" Ceramic Midrange, Neo. Mag	6	37	93.3	130	3S	225	\$563.00
C220-T6-220	C220-T6	8" Ceramic Woofer	6	20.4	89.6	150	25S / 38V	53 / 36	\$564.00
C220N-T6-220	New	8" Ceramic woofer, Neo Magnet	6	26.7	93.2	150	6S / 15V	115 / 75	\$839.00

D20N-6-31



DOME TWEETER • Response to @100kHz

• ¾" PURE DIAMOND

- · Extremely low harmonic distortion
- High sound propagation
- Ferrofluid loaded
- Flange 82 x 82mm
- Cut-out 64x 64mm
- Depth 56mm

Znom	6	ohm
Re	6.0	ohm
Le@1kHz	0.04	mΗ
fs	900	Hz
Qms	-	
Qes	-	
Qts	-	
Mms	0.09	g
Cms	-	mm/N

Sd	6.0	cm ²
BL	-	N/A
Vas	-	Itrs
Xmax	-	mm peak
VC Ø	18.9	mm
Sensitivity		
1W / 1m	89.5	dB
Nom. Power	200	W
Net weight	430	g



D30N-6-36

Znom

Le@1kHz

Re

fs

Qms Qes Qts

Mms Cms

No Picture Looks like D20-6

440

- 1" PURE DIAMOND DOME TWEETER
- Response to @60kHz
- · Extremely low harmonic distortion
- High sound propagation
- Ferrofluid loaded
- Flange 82 x 82mm
- Cut-out 64x 64mm
- Depth 56mm

6	ohm	Sd	8.4	cm ²
6.0	ohm	BL	-	N/A
0.04	mH	Vas	-	ltrs
40	Hz	Xmax	-	mm peak
-		VC Ø	18.9	mm
-		Sensitivity		
-		1W / 1m	90	dB
0.19	g	Nom. Power	300	W
-	mm/N	Net weight	-	g

No Graph Yet

C25-6-12



Znom ohm Re 6.0 ohm Le@1kHz 0.04 mH fs 700 Hz Qms Qes Qts Mms g

Cms

100.0

95.0

90.0

85.0

75.0

70.0

65.0

60.0

55.0

50.0

mm/N

1000 0

- 1" CERAMIC DOME **TWEETER**
- Response to @30kHz
- Great as supertweeter or in 2-Way system
- Heavy zinc frontplate
- Ferrofluid loaded
- Flange 82 x 82mm
- Cut-out 64 x 64mm

Sd	6.1	cm ²
BL	-	N/A
Vas	-	ltrs
Xmax	-	mm peak
VC Ø	16.4	mm
Sensitivity		
1W / 1m	89.5	dB
Nom. Power	120	W
Net weight	530	a




C25N-6-13



Znom	6	ohm
Re	-	ohm
Le@1kHz	-	mΗ
fs	1360	Hz
Qms	-	
Qes	-	
Qts	-	
Mms	-	g
Cms	-	mm/N

- 1" CERAMIC DOME TWEETER
- High efficiency version
- 4mm Underhung Neodymium magnet
- Heavy zinc frontplate
- Ferrofluid reduced
- Flange 82 x 82mm
- Cut-out 64 x 64mm
- Depth 56mm

Sd	6.1	cm ²
BL	-	N/A
Vas	-	ltrs
Xmax	-	mm peak
VC Ø	16.4	mm
Sensitivity		
2.83V / 1m	92	dB
Nom. Power	120	W
Net weight	-	g



C30-6-23

400 0



Znom 6 ohm Re 6.1 ohm Le@1kHz 0.04 mH fs 350 Hz Qms Qes Qts Mms g mm/N Cms

- 1.2" CERAMIC DOME **TWEETER**
- Wide bandwidth

- Very low resonance
- Ferrofluid loaded
- Flange 106 x106mm
- Depth 67mm

Sd	8.5	cm ²
BL	-	N/A
Vas	-	Itrs
Xmax	-	mm peak
VC Ø	19.4	mm
Sensitivity		
1W / 1m	89.5	dB
Nom. Power	100	W
Net weight	980	g

10000.0

- Response to @23kHz
- Very high resolution

- - Cut-out 89 x 89mm

Sd	8.5	cm ²
BL	-	N/A
Vas	-	ltrs
Xmax	-	mm peak
VC Ø	19.4	mm
Sensitivity		
1W / 1m	89.5	dB
Nom. Power	100	W
Net weight	980	g

C30N-6-24





Znom	6	ohm
Re	-	ohm
Le@1kHz	-	mΗ
fs	835	Hz
Qms	-	
Qes	-	
Qts	-	
Mms	-	g
Cms	-	mm/N

• 1.2" CERAMIC DOME **TWEETER**

- 6mm Underhung Neodymium magnet
- High efficiency version
- Very high resolution
- Ferrofluid loaded
- Flange 82 x 82mm
- Cut-out 64 x 64mm
- Depth 56mm

Sd	8.5	cm ²
BL	-	N/A
Vas	-	Itrs
Xmax	-	mm peak
VC Ø	19.4	mm
Sensitivity		
2.83V / 1m	92	dB
Nom. Power	100	W
Net weight	-	g






C50-8-44




Znom Re 8.2 ohm Le@1kHz 24.6 mΗ 390 fs Hz Qms 1.19 Qes 2.2 Qts .77 1.3 g Mms Cms 0.13 mm/N

- 2" CERAMIC DOME **MIDRANGE**
- Response to @12kHz
- Flat on- and off- axis response from 400 Hz
- Very high resolution
- Ferrofluid loaded
- Flange 106x106mm
- Cut-out 89 x 89mm
- Depth 67mm

Sd	.02	cm ²
BL	3.47	N/A
Vas	.11	Itrs
Xmax	8.0	mm peak
VC Ø	30.4	mm
Sensitivity		
1W / 1m	88.5	dB
Nom. Power	130	W
Net weight	680	g



6.5" CERAMIC MID C173N-T6-90




- Titanium VC former
- Neodymium magnet
- Underhung voice coil
- Double roll surround
- Range 120Hz to 6kHz
- Flange 173mm round

peak

Cms

- Cut-out 152mm
- Depth 90mm

Znom Re Le@1kHz	6 ohm 6.5 ohm - mH	Sd BL Vas	145 11.7	cm² N/A
			8.8	ltrs
fs	73 Hz	Xmax	-	mm
Qms	6.54	VC Ø	55	mm
Qes	.32	Sensitivity		
Qts	.30	2.83V / 1m	93.2	dB
Mms	15.75 g	Nom. Power	120	W
Cms	.3 mm/N	Net weight	1800	g



C90-6-79




Good dispersion up to 5 kHz Very high resolution

3" CERAMIC DOME

MIDRANGE

- Requires 1.5 to 4 liter sealed chamber
- Flange 130x130mm
- Cut-out 116x116mm
- Depth 75mm

Znom	6 ohm	Sd	75.5 cm ²
Re	5.8 ohm	BL	4.96 N/A
Le@1kHz	.12 mH	Vas	3.1 ltrs
fs	96 Hz	Xmax	2.6 mm peak
Qms	.96	VC Ø	37.7 mm
Qes	1.07	Sensitivity	
Qts	.51	1W / 1m	88.5 dB
Mms	7.2 g	Nom. Power	120 W
Cms	.39 mm/N	Net weight	1800 g



C90-T6-89



Znom	6 ohm
Re	5.9 ohm
Le@1kHz	0.4 mH
fs	33.6 Hz
Qms	3.29
Qes	.23
Qts	.215
Mms	9.3 g


2.42 mm/N

Znom	6	ohm			
Re	5.9	ohm			
₋e@1kHz	0.4	mΗ			
S	33.6	Hz			
Qms	3.29				
Qes	.23				
Ots	215				

•	5" CERAMIC BASS-
	MIDRANGE

- Good dispersion up to 5 kHz
- Very high resolution
- Rubber surround
- Titanium VC former
- Flange 130x130mm
- Cut-out 116x116mm
- Depth 75mm

Sd	83.3	cm ²
BL	7.1	N/A
Vas	23.5	Itrs
Xmax	3.1	mm peak
VC Ø	37.7	mm
Sensitivity		
1W / 1m	89.2	dB
Nom. Power	100	W
Net weight	1800	q



C153-T8-82




- 5" CERAMIC BASS-MIDRANGE
- Good response to 3kHz
- Very high resolution
- Rubber surround
- Titanium VC former
- Flange 153 mm
- Cut-out 114mm
- Depth 65mm

C173-6-92


- 6.5" CERAMIC BASS-MIDRANGE
- Good dispersion up to 4 kHz
- Very high resolution
- Rubber surround
- Aluminum VC former
- Flange 173mm
- Cut-out 152mm


Znom	11	ohm
Re	8.9	ohm
Le@1kHz	0.61	mΗ
fs	33.2	Hz
Qms	3.15	
Qes	0.26	
Qts	0.24	
Mms	7.8	g
Cms	2.94	mm/N

Sd	77	cm ²
BL	7.5	N/A
Vas	25.4	Itrs
Xmax	-	mm peak
VC Ø	-	mm
Sensitivity		
1W / 1m	87	dB
Nom. Power	130	W
Net weight	-	g



Sd	133	cm ²
BL	5.1	N/A
Vas	54.8	ltrs
Xmax	4.0	mm peal
VC Ø	39	mm
Sensitivity		
1W / 1m	86	dB
Nom. Power	130	W
Net weight	2450	g





C173-T6-95



- 6.5" CERAMIC BASS-MIDRANGE
- Good dispersion up to 3 kHz
- Very high resolution
- Rubber surround
- Titanium VC former
- Flange 173mm
- Cut-out 152mm

C220-T6-220




- 8" CERAMIC WOOFER
- Low resonance
- High excursion
- Rubber surround
- Titanium VC former
- Flange 222mm
- Cut-out 188mm
- Depth 120mm


Znom	6 ohm
Re	5.9 ohm
Le@1kHz	0.73 mH
fs	32 Hz
Qms	4.0
Qes	.30
Qts	.279
Mms	13.8 g
Cms	1.36 mm/N

Sd	133	cm ²	
BL	8.32	N/A	
Vas	34.2	ltrs	
Xmax	5.0	mm	peak
VC Ø	38	mm	
Sensitivity			
1W / 1m	89.1	dB	
Nom. Power	130	W	
Net weight	2450	g	

∠nom	6	onm
Re	5.9	ohm
Le@1kHz	0.61	mΗ
fs	20.4	Hz
Qms	4.49	
Qes	0.29	
Qts	0.27	
Mms	31.9	g
Cms	1.91	mm/N

Sd	233	cm ²
BL	9.1	N/A
Vas	144	Itrs
Xmax	5.2	mm peak
VC Ø	38	mm
Sensitivity		
1W / 1m	89.6	dB
Nom. Power	150	W
Net weight	2950	g







Audax is now produced by AAC of France.



MADISOUND SPEAKER COMPONENTS, INC. 8608 UNIVERSITY GREEN P.O. BOX 44283

MADISON, WI 53744-4283 U.S.A. TEL: 608-831-3433 FAX: 608-831-3771 e-mail: info@madisound.com Web Page: http://www.madisound.com




Model	Size Description	Ω	Fs Hz	Qts	Vas Ltrs	Xmax mm	Power Watts	dB	Cost Each
	Soft and Hard dome tweeters								
TM010A1	Micro Series 1 0mm polymer dome, 4 ohm, by AAC	4	3000		-	0.25	25	85	\$6.70
TM010A1_Grill	Black or Brown Grill for TM010A1 tweeter	-			-	-	-	-	\$1.55
TW010F1	10mm polymer dome, 74mm round flange	8	3000		-	0.25	25	90	\$5.75
TW025A0	25mm textile dome, 100mm round flange (3.93"), made by AAC	8	1090		-	0.65	55	90	\$28.25
TW025A2	25mm textile dome, 100mm round flange, 4 ohm, by AAC	4	1090		-	-	55	92	\$28.25
TW025A20	25mm Titanium dome, Neodymium magnet, heat sinks	8	1137		-	-	100	93	\$103.25
TW034X0	34mm textile dome, 132mm flange, made by AAC of France	8	800		-	0.25	70	93	\$72.05
	Repair parts for Audax tweete	rs							
RW025A0	Replacement voice coil for TW025A0	8							\$10.50
RW025A2	Replacement voice coil for TW025A2	4							\$10.50
RW034X0	Replacement Voice coil for TW034X0 tweeter	8							\$39.15
	Reference Series Carbon Fiber Cone Driver - Cast F	rame	e, Rubb	er Surr	ound				
HM100C0	4" Carbon Fiber Cone mid/bass, made by AAC of France	8	54	.21	6.4	1.8	40	89	\$81.75
HM130C0	5.25" Carbon Fiber Cone mid/bass, made by AAC of France	8	46	.31	18.1	3	50	90	\$89.20
	Polymer Chassis Woofers								
AP130ZO SALE	Shielded 5.25" Aerogel cone, response 99\$/60V to 2.5kHz	6	57.6	0.41	10.9	2.5	40	87.4	\$19.00
	Professional Speaker								
PR170M0	6.5" Paper Cone midrange, 100dB, made by AAC of France	8	117	0.51	5.5	0.5	100	100	\$83,30

TM010A1



- 10mm Polymer Dome Micro Tweeter
- · Neodymium magnet
- Ultra light and compact
- Ferrofluid cooled
- · Formerless VC
- Flange 29.5mm
- Cut-out 27.8mm
- Depth 14mm
- · Grill sold separately

				_	
Znom	4	ohm	Sd		cm ²
Re	3.4	ohm	BL	1	N/A
Le@1kHz		mΗ	Vas		Itrs
fs	3000	Hz	Xmax	.25	mm peak
Qms	-		VC Ø	10	mm .
Qes	-		Sensitivity		
Qts	-		1W / 1m	85	dB
Mms	0.13	g	Nom. Power DIN	25	W
Cms	-	mm/N	Net weight	0.01	kg




TW010F1



Znom	8	ohm
Re	5.5	ohm
Le@1kHz	.03	mΗ
fs	3000	Hz
Qms	-	
Qes	-	
Qts	-	
Mms	.11	g
Cms	_	mm/N

- 10mm Polymer Dome Tweeter
- Formerless VC
- Ferrofluid cooled
- 1st order above 6K
- Exceptional transient response
- Flange 74mm
- Cut-out 48mm
- Depth 14.4mm

Sd	.03	cm ⁻
BL	1.3	N/A
Vas	-	ltrs
Xmax	0.25	mm peak
VC Ø	10	mm
Sensitivity		
1W / 1m	90	dB
Nom. Power DIN	25	W
Net weight	0.05	kg



TW025A0

Znom

Le@1kHz

Re

fs Qms

Qes

Qts

Mms



1090

4.21

1.3

1

ohm

5.8 ohm

.03 mH

Hz

g

- 25mm Textile Dome Tweeter
- 8 ohms
- Extended response
- Replaceable voice coil

4.91 cm²

90

55

460

N/A

Itrs

0.65 mm peak

mm

dΒ

W


- Aluminum faceplate
- Flange 100mm
- Cut-out 75mm
- Depth 23.5mm

T۱	N	02	25	A	2
----	---	----	----	---	---



- 25mm Textile Dome Tweeter
- 4 ohms
- Extended response
- Replaceable VC
- Aluminum face plate
- Flange 100mm
- Cut-out 75mm
- Depth 23.5mm

Znom	4	ohm	Sd	-	cm ²
Re	-	ohm	BL	-	N/A
Le@1kHz	-	mΗ	Vas	-	ltrs
fs	900	Hz	Xmax	0.65	mm peak
Qms	-		VC Ø	-	mm
Qes	-		Sensitivity		
Qts	-		1W / 1m	93	dB
Mms	-	g	Nom. Power DIN	55	W
Cms	-	mm/N	Net weight	-	kg



Sd

BL

Vas


Xmax

vc ø

Sensitivity

1W / 1m

Nom. Power DIN



TW034X0

Znom

Le@1kHz

Re

fs

Qms

Qes Qts



8

800

5.3 ohm

ohm

mΗ

Hz

- 34mm Textile Dome Tweeter
- \mathbf{E} re
- R
- S p

10.8 cm²

ltrs

0.25 mm peak

mm

dΒ

3.5 N/A

34

93

- F
- Cut-out 106mm
- Depth 29mm

Extended frequency	
esponse	-
Replaceable VC	
Solid aluminum face	
late	4
Flange 132mm	

TW025A20

- 25mm Titanium Dome Tweeter
- Neodymium magnet with heat sinks
- Solid aluminum face plate
- Chambered back
- Flange 100 mm
- Cut-out 76 mm
- Depth 32 mm

Mms Cms	0.5	g mm/N	Nom. Power D Net weight	DIN 70 1180	W g
105.0 - 100.0 - 95.0 - 90.0 - 95.0 - 90.0 -		A		eros T	M
100.0		1000.0)	10000	0.0

Sd

BL

Vas

Xmax


VC Ø

Sensitivity

1W / 1m

Znom	8	ohm	Sd
Re	5.5	ohm	BL
Le@1kHz	-	mΗ	Vas
fs	1137	Hz	Xma
Qms	3.47		VC !
Qes	0.96		Sen
Qts	0.76		2.
Mms	-	g	Non
Cms	-	mm/N	Net

Sd	4.91	cm ²
BL	-	N/A
Vas	-	ltrs
Xmax	-	mm peak
VC Ø	25	mm
Sensitivity		
2.83V / 1m	93	dB
Nom. Power DIN	100	W
Net weight	-	g



HM100C0



- Znom ohm Re 6.4 ohm Le@1kHz .11 mH fs 54 Hz Qms 3.27 Qes 0.22 Qts 0.21 Mms 5.1 g Cms

- 4" Carbon Fiber Cone Mid-bass
- Diecast basket
- Rubber surround
- Kapton VC former
- Venting under spider
- Gold plated terminals
- Flange 110mm square
- Cut-out 94mm
- Depth 57mm

Sd	-	cm ²
BL	6.96	N/A
Vas	6.4	ltrs
Xmax	1.8	mm peak
VC Ø	25	mm
Sensitivity		
1W / 1m	89	dB
Nom. Power DIN	40	W
Net weight	.93	kg


HM130C0




Znom	8	ohm
Re	6.2	ohm
Le@1kHz	.39	mΗ
fs	46	Hz
Qms	3.6	
Qes	.34	
Qts	.31	
Mms	6.9	g
Cms	-	mm/N

- 5.25" Carbon Fiber Cone Mid-bass
- Diecast basket
- Rubber surround
- Kapton VC former
- Venting under spider
- · Gold plated terminals
- Flange 136mm square
- Cut-out 115.44mm
- Depth 65mm

-	cm ²
5.97	N/A
18.1	ltrs
3	mm peak
25	mm
90	dB
50	W
1.4	kg
	18.1 3 25 90 50





Sensitivity Mag - dB SPL_watt (8.8 ohm load) (8.33 oct)(eq) 100 95 90 20 85 80

AP130Z0



ohm

ohm 5.7

mΗ

57.6 Hz

1.48

.57

.41 6.86 g

1.11 mm/N

Znom

Le@1kHz

Re

fs

Qms

Qes

Qts

Mms Cms

- 5.25" **Shielded** Aerogel Cone Bass Midrange
- Suitable for A/V
- Non-resonant polymer chassis
- Rubber surround
- Built in mounting ring
- Flange 143mm
- Cut-out 112mm
- Depth 66 5mm

Depth 00.511111			
Sd		cm ²	
BL	4.72	N/A	
Vas	10.85	Itrs	
Xmax	0.35	mm peak	
VC Ø	25	mm	
Sensitivity			
1W / 1m	87.4	dB	
Nom. Power DIN	40	W	
Net weight	.9	kg	


PR170M0 (100dB)




Znom	8	ohm
Re	6.2	ohm
Le@1kHz	.73	mΗ
fs	117	Hz
Qms	3.16	
Qes	0.61	
Qts	0.51	
Mms	9.17	g
Cms	_	mm/N

- Professional 6.5" Paper Cone Midrange
- Diecast basket
- Flat Foam surround
- Kapton VC former
- Edgewound 40mm VC
- Gold plated terminals
- Flange 190mm square
- Cut-out 145mm
- Depth 76mm

Sd	139	cm ²
BL	8.24	N/A
Vas	5.5	ltrs
Xmax	0.5	mm peak
VC Ø	40	mm
Sensitivity		
1W / 1m	100	dB
Nom. Power DIN	100	W
Net weight	2.5	kg







- 1.25" Micro In-wall
- Designed for installation in single gang box
- 20W RMS power handling
- Frequency range 150Hz -20kHz ± 6dB
- Capable of high SPL for such a small speaker
- 8 ohm impedance
- · Inherently Shielded
- 33mm voice coil Ø
- 84 dB
- (single gang box not included)





Price Each \$43.00

The IWS-Micro is a Sound Contractors dream. This little speaker has a big speaker output. The 3mm peak x-max allows for a lot of cone travel. This speaker has no application boundaries and challenges the imagination for new uses. Here are some ideas we've thought of:

- · Computer surround sound
- Information applications in museums, libraries, etc.
- Theme park rides
- Bathrooms

- Ambient sound in waiting rooms and offices
- Computer monitors
- · Home theater arrays
- Aircraft

S O U N D

NT1-204-8D 3/4" Titanium Dome Tweeter

Specifications:


op to the total of		
Fs	2000	Hz
Nominal Imp.	8	ohms
Power (RMS)	15	W
Re	6.96	ohms
Sens. 1W/1m	88.5	dB
X-max peak	0.6	mm
Mms	0.16	gr
VC diameter	20	mm


Features:

- Frequency 3kHz to 25kHz
- · Titanium dome
- Underhung voice coil
- Neodymium magnet
- Inherently shielded
- Frame: 39mm square
- Overall Depth: 22mm
- Could be rear mounted, 3/4"
- Don't touch the dome!!!



Price Each \$8.75





NURA S O U N D

Specifications:

Specification	115.	
Fs	220	Hz
Nominal Imp.	8	ohms
Power (RMS)	5	W
Re	6.3	ohms
Sens. 1W/1m	78	dB
X-max peak	1.5	mm
Qms	2.1	
Qes	1.1	
Qts	0.7	
Vas	0.04	ltrs
BL	1.9	TM
Mms	0.50	gr
Cms	1155	μ M/N
Sd	5.31	cm ²
Net weight	52.3	g
Max Exc. p2p	6	mm
VC diameter	20	mm


Features:


- · Frequency 220 to 25kHz
- · Titanium dome
- Underhung voice coil
- NRT neodymium magnet system
- · Inherently shielded
- Foam surround
- Frame: 39mm square
- Overall Depth: 22mm

NSW1-205-8A 1" Extended Range



Price Each \$12.20





Specifications:

Specification	1100	
Fs	250	Hz
Nominal Imp.	8	ohms
Power (RMS)	15	W
Re	6.4	ohms
Sens. 1W/1m	84	dB
X-max peak	3	mm
Qms	4.72	
Qes	0.80	
Qts	0.68	
Vas	0.1	ltrs
BL	3.5	TM
Mms	1.04	gr
Cms	390	μ M/N
Sd	13.2	cm ²
Net weight	113	g
Max Exc. p2p	10	mm
VC diameter	33	mm


Features:


- · Frequency 250 to 15kHz
- Titanium dome
- Underhung voice coil
- NRT neodymium magnet system
- · Inherently shielded
- Foam surround
- Frame: 49mm square
- Overall Depth: 29.4mm

NSW2-326-8A 2" Extended Range



Price Each \$16.00







NS3-193-4A/8A & 4A1/8A1

3" Extended Range

Specifications:

-			
	4Ω	Ω 8	
Fs	78	80	Hz
Power (RMS)	20	20	W
Re	3.5	7.6	ohms
Sens. $1W/1m$	80	80	dB
X-max peak	4.75	5	mm
Qms	9.0	8.0	
Qes	0.62	0.73	
Qts	0.58	0.67	
Vas	1.27	1.25	ltrs
BL	3.5	4.7	TM
Mms	4.5	4.3	gr
Cms	925	920	μ M/N
Sd	31	31	cm ²

Features:

Net weight

• Frequency 80 to 7kHz

216

216 g

19.3 mm

· Low distortion


VC diameter 19.3


- Aluminum cone
- Underhung voice coil
- NRT neodymium magnet system
- Inherently shielded
- Rubber surround
- Frame: 105mm
- Depth: 66mm



Price Each \$19.50

Recommended Enclosure for F3 of 85Hz: 3 to 6 liters (0.1 to 0.2 cf)





Specifications:

	4Ω	Ω 8	
Fs	66	59	Hz
Power (RMS)	20	20	W
Re	3.6	6.0	ohms
Sens. 1W/1m	84	83	dB
X-max peak	5.5	5.5	mm
Qms	4.57	6.81	
Qes	0.46	0.45	
Qts	0.42	0.42	
Vas	2.67	3.40	ltrs
BL	4.99	6.12	TM
Mms	7.84	7.64	gr
Cms	753	959	μ M/N
Sd	50.27	50.27	cm ²
Net weight	384	384	g

Features:

Frequency 60 to 6kHz

VC diameter 25.5 25.5 mm


- Low distortion
- Aluminum cone
- Underhung voice coil
- NRT neodymium magnet 100 system
- Inherently shielded
- Rubber surround
- Frame: 105mm
- Depth: 66mm


4" Extended Range

NS4-255-4D1/8D1

Price Each \$34.00

N Please refer to our web site for impedance curves and box alignments.





Specifications


Specifications:			
Fs	25	Hz	
Nominal Imp.	8	ohms	
Power (RMS)	800	W	
Re	5.6	ohms	
Sens. 1W/1m	96	dB	
X-max peak	18	mm	
Qms	4.40		
Qes	0.28		
Qts	0.26		
Vas	475	ltrs	
BL	24.5	TM	
Mms	186	gr	
Cms	218	μ M/N	
Sd	1240	cm ²	
Net weight	13.5	kg	
VC diameter	99.1	mm	
Features:			

- Frequency 25 to 2kHz
- · Low distortion
- Paper/fiberglass/epoxy cone material
- Edgewound aluminum ribbon voice coil
- NRT neodymium magnet
- Inherently shielded
- Polyester Weave surround

NRT18-8 18" Pro Sound Woofer



Price Each \$912.00




F3 of 52Hz in 4.5cf vented box with two 4" Ø vents x 9.5" long, some stuffing

50Watt RMS Continuos 4 ohm 6.2" in diameter, 2.2" tall Fs 40Hz

Peak Force 30lbf (132N) Weight 3 lbs

Price Each \$39.00


Want to feel your music? The Bass Shaker products allow you to



To add bass shakers to your home theater system, they need to be powered by an amplifier (50 to 100 watt recommended) and receive the same signal as your powered subwoofer. No crossover is needed. Bass shakers should be rigidly mounted to the bottom of your seat, whether it your car seat

AST-2B-4 Pro Bass Shaker







Specifications:


- F		
Fs	32	Hz
Nominal Imp.	4	ohms
Power (RMS)	400	W
Re	3.6	ohms
Sens. 1W/1m	83	dB
X-max peak	18	mm
Qms	7.8	
Qes	0.42	
Qts	0.4	
Vas	33	ltrs
BL	13	TM
Mms	103	gr
Cms	236	μ M/N
Sd	317	cm ²
Net weight	7.7	kg
Max Exc. p2p	60	mm
VC diameter	79.4	mm
-		1 F1 TT


- Frequency Fo to 1.5kHz
- Aluminum Cone black
- Underhung voice coil
- · NRT neodymium magnet system
- · Inherently shielded
- Rubber surround
- Frame: 268.2mm
- Cut out: 232.2mm
- Depth: 178.3mm

NS10-794-4A 10" Subwoofer



Price Each \$481.00





Recommended Enclosure for F3 of 30Hz: 1.5 cubic feet with 3" Ø vent by 12" long

Specifications:


Fs	27	Hz
Nominal Imp.	4	ohms
Power (RMS)	400	W
Re	3.5	ohms
Sens. 1W/1m	84	dB
X-max peak	18	mm
Qms	7.1	
Qes	0.45	
Qts	0.43	
Vas	78	ltrs
BL	14	TM
Mms	152	gr
Cms	233	μ M/N
Sd	487	cm ²
Net weight	8.0	kg
Max Exc. p2p	60	mm
VC diameter	79.4	mm
F	T	1 51 TT

- Frequency Fo to 1.5kHz
- Aluminum Cone black
- Underhung voice coil
- NRT neodymium magnet system
- Inherently shielded
- Rubber surround
- Frame: 317mm
- Cut out: 280mm
- Depth: 202mm

NS12-794-4A 12" Subwoofer



Price Each \$565.00




Recommended Enclosure for F3 of 25Hz: 3.5 cubic feet with 4" Ø vent by 12" long

Specifications:


Specification	1100	
Fs	20	Hz
Nominal Imp.	4	ohms
Power (RMS)	800	W
Re	3.3	ohms
Sens. 1W/1m	86	dB
X-max peak	25	mm
Qms	8.0	
Qes	0.4	
Qts	0.37	
Vas	169	ltrs
BL	18	TM
Mms	314	gr
Cms	206	μ M/N
Sd	765	cm ²
Net weight	20.1	kg
Max Exc. p2p	75	mm
VC diameter	99.2	mm
 Frequency 	Fo to	1.5kHz


- Aluminum Cone black
- Underhung voice coil
- NRT neodymium magnet system
- Inherently shielded
- Rubber surround
- Frame: 393.4mm
- Cut out: 352mm
- Depth: 270mm

NS15-992-4A 15" Subwoofer



Price Each \$685.00





Recommended Enclosure for F3 of 22Hz: • 4.5 cubic feet with 4" Ø vent by 15" long


0 U

Specifications:


Fs	20	Hz
Nominal Imp.	4	ohms
Power (RMS)	800	W
Re	3.1	ohms
Sens. 1W/1m	86	dB
X-max peak	25	mm
Qms	7.7	
Qes	0.5	
Qts	0.47	
Vas	322	ltrs
BL	17	TM
Mms	400	gr
Cms	170	μ M/N
Sd	1164	cm ²
Net weight	19.7	kg
Max Exc. p2p	75	mm
VC diameter	99.2	mm
_	_	

- Frequency Fo to 1.5kHz
- Aluminum Cone black
- Underhung voice coil
- NRT neodymium magnet system
- Inherently shielded
- Rubber surround
- Frame: 477mm
- Cut out: 426.4mm Depth: 287.1mm

NS18-992-4A 18" Subwoofer



Price Each \$882.00



Recommended Enclosure for F3 of 35Hz: 4.5 cubic feet sealed and stuffed

Eclipse Woofers by Eminence

Eclipse 10" Polypropylene cone woofer with rubber sur-

round and vented pole piece.

W1038R 10" Poly Cone Woofer								
Fs	18.36							
Impedance	6 ohm							
Mmd	58.4 Grams							
Cms	1207.4 m/n							
Vas	214.9 Liters							
Rscc	4.7 Ω							
Leap Krm	3.439							
Leap Kxm	25.412							
Leap Erm	0.813							
Leap Exm	0.670							
vcL	1.4mH @ 1K							
BI	9.95 Tm							
Qms	4.694							
Qes	0.341							
Qts	0.318							
Xmax	8.0 mm Peak							
SD	0.0354 m ²							
Surround	Rubber							
Magnet	40 oz.							
Voice Coil	2 Inch							
Power Handling	100 watts							
Freq. Response	28—1500 Hz							
Efficiency	88 dB @2.83V							
Price	\$57.00							



Frame Size: 10 1/8" diameter 9 1/8" cutout diameter 4 7/16" depth

Sealed Box Alignment 2 cubic feet F3 of 40Hz Qtc of .7

Vented Box Alignments
QB3 alignment
2.9 cubic feet
F3 of 28Hz
3" diameter x 9" long

Eclipse 12" Polypropylene cone woofer with rubber surround and vented pole piece.

W1238R 12" Poly Cone Woofer							
Fs	21.48						
Impedance	6 ohm						
Mmd	86.5 Grams						
Cms	586.39 m/n						
Vas	236.55 Liters						
Rscc	4.9 Ω						
Leap Krm	3.368						
Leap Kxm	28.125						
Leap Erm	0.868						
Leap Exm	0.738						
vcL	2.84mH @ 1K						
BI	15.38 Tm						
Qms	6.599						
Qes	0.262						
Qts	0.252						
Xmax	8.0 mm Peak						
SD	0.0533 m ²						
Surround	Rubber						
Magnet	40 oz.						
Voice Coil	2 Inch						
Power Handling	150 watts						
Freq. Response	25—1000 Hz						
Efficiency	92 dB @2.83V						
Price	\$61.00						



<u>Frame Size:</u>
12" diameter
11" cutout diameter
5 3/8" depth

Vented Box Alignment 2.0 cubic feet F3 of 35Hz 3" diameter x 6" long w/KG5150 F3 30Hz

Eminence EMI-1550 15" High Efficiency Woofer


EMI-1550 15" P	aper Cone Woofer
Fs	22.54
Impedance	8 ohm
Mms	84.2 Grams
Cms	510.0 m/n
Vas	501.3 Liters
Rscc	6.73 Ω
Leap Krm	5.637
Leap Kxm	15.165
Leap Erm	0.750
Leap Exm	0.700
vcL	4.13mH
BI	19.38 Tm
Qms	10.00
Qes	0.23
Qts	0.23
Xmax	7.15 mm Peak
SD	832 cm ²
Surround	Cloth Accordion
Magnet	67 oz.
Voice Coil	2 Inch, 4 layer, Cu
Power Handling	150 watts
Freq. Response	23—1700 Hz
Efficiency	2.96%
SPL	96.3 dB @2.83V
Flange diameter	389mm (15.3")
Mounting hole	356mm (14")
Depth	146mm (5.75")
Flange thickness	20mm (0.79")
Price	\$91.00

We had this woofer made by Eminence in order to offer an efficient subwoofer for use with high efficiency full range speakers and efficient speaker systems. We worked with Eminence to develop a 15" woofer where efficiency and bass response were equally important, not just power handling. We are very happy with the results.

When using the EMI-1550 with one of our plate amplifiers, we recommend a 3.5 cubic foot box with the 4" flared port 6" long (5" if not using a flared port). For the flared ports that we have, you would connect the front flare to the rear flare and not use the center tube. This box will give you and F3 of 36Hz. Power handling of 150 watts without exceeding the x-max, maximum output of 114.5dB. Using this box with and amplifier that doesn't have a bass boost will result in an F3 of 45Hz.

ill ad a sy ser ill a ser

Another box option for an amplifier without a bass boost would be the Extended Bass Shelf, 4.5 cubic feet with a 4" diameter vent by 5" long (6" if flared port). The F3 is about 40Hz, roll off starts at about 100Hz.





EMINENCE PROFESSIONAL LOUDSPEAKERS Complete specifications available at: www.eminence.com



1013 35											WEED.
Model	Imp. W	Fs Hz	Qts	Vas Ltrs	Power Watts	đВ	Frequency Range	VC Ø Inches	Rec. Box Size ft ³ S / V	Magnet Weight oz	Price Each
			АРТ Н	igh Pow	er Sune	r-Twee	ters				
APT50 driver only, no horn	8	250	-	-	45	105	3.5k-20kHz				\$26.99
APT80 3.4" x 3.4" horn tweeter	8	250	_	-	45	105	3.5k-20kHz	80°	Conical Dispers	sion	\$29.99
APT150 7.5" x 4.5" horn tweeter	8	250	_	_	45	105	3.5k-20kHz		° x 50° Dispers		\$39.99
APT200 5.9" x 5.9" horn tweeter	8	250	_	_	45	105	3.5kHz-20kHz		x 90° Dispersi		\$56.99
APTD25D Replacement Diaphragm		200		l		100	JUNEAU ZONIE	,,,	nyo Bispers.		\$3.99
Compression Dr	ivore &	, ARS	Close	Filled De	alvearho	nata H	orn Flores with	3-Rolt M	ounting		φυνο
ASD1001S screw on type, 1" throat size	8	-	- Glass	-	50	105	2.5k-20kHz	3-Doit W	ounting		\$26.99
PSD2002 bolt on type, 1" throat size	8/16	550	_	_	80	105	1.5k-20kHz				\$56.99
PSD2002S screw on type, 1" throat size	6/16	550	_	_	80	105	1.5k-20kHz				\$56.99
LT250 6.7"W x 6.4"H x 4.2"D Constant Directi			1" thros	t recomn				60°	x 40° Dispersi	ion	\$24.99
SST1 9.8"W x 7.7"H x 5.2"D Constant Directiv									x 40° Dispersi		\$29.99
H290 11.4"W x 6.5"H x 5.9"D Radial horn flare							OVCI TRIIZ		x 40° Dispersi		\$34.99
H295 10.5"W x 4.3"H x 4"D Constant Directivi	•						over 1kHz		x 40° Dispersi		\$29.99
H395 15.6"W x 7.3"H x 6.1"D Constant Directi	•								x 40° Dispersi		\$34.99
13.5 13.6 W X 7.5 11 X 0.1 D Constant Directi	vity non	ii iiaic,						70	X 40 Dispers	1011	φ54.77
ALPHA-6A 6" midrange	8	118	0.54	erican S	tandard 100	93.6	85Hz-6kHz	1.5	0.1-0.2S	20	\$39.99
9	_	73									
ALPHA-8A 8" mid/bass BETA-8A 8" mid/bass	8	58	0.59	17.7 34.5	125 225	94 94	58Hz-5kHz	1.5	0.2-0.25S	20 34	\$44.99 \$54.99
		53					55Hz-4kHz		0.3-0.55V		·
BETA-10A 10" woofer	8		0.49	60.1	250	94	50Hz-4kHz	2	1.9-3.15V	34	\$59.99
BETA-12A-2 12" woofer	8	47	0.46	120.1	250	98	43Hz-3.8kHz	2	1.3-4.9V	34	\$59.99
BETA-12LTA 12" wide range	8	45	0.51	136.3	225	97	45Hz-8kHz	2	2-4.1V	38	\$69.99
BETA-15A 15" woofer	8	35	0.58	334.6	350	95	35Hz-4kHz	2	1.6-2.2S	34	\$69.99
DELTA-10A 10" mid/bass	8	66	0.33	30.5	350	98.8	63Hz-3.7kHz	2.5	0.45-1.35V	56	\$74.99
DELTA-12A 12" woofer	8	55	0.43	81.3	400	98.3	54Hz-5kHz	2.5 0.9-3V		56	\$79.99
DELTA-12LFA 12" woofer, low frequency	8	51	0.47	67.9	500	94.6	44Hz-3kHz	2.5	0.9-3.6V	56	\$94.99
DELTA-15A 15" woofer	8	40	0.53	270.7	400	100	48Hz-4kHz	2.5	2.9-5.7V	56	\$89.99
DELTA-15LFA 15" woofer, low frequency	8	41	0.58	186.1	500	96	42Hz-3.2kHz	2.5	3-5.9V	56	\$99.99
KAPPA-12A 12" woofer	8	45	0.27	112.1	450	99.3	62Hz-4.2kHz	3	1.2-2.2V	80	\$119.99
KAPPA-15A 15" woofer	8	33	0.32	321.3	450	100.5	52Hz-2.3kHz	3	1.6-4V	80	\$124.99
KAPPA-15LFA 15" woofer, low frequency	8	39	0.38	159	600	99	38Hz-2.7kHz	3	2.2-6.8V	95	\$139.99
				Array S							440.00
LA6-CBMR 6.5" midrange, chambered back, tr		460	0.89	0.36	150	98	500Hz-5kHz	1.5	chambered	38	\$49.99
							ubwoofer Enclo			112	4440.00
HL-10 (A/C) 10" Long Stroke Subwoofer	(8/4)	32	0.28	29.2	300	87	Horn Dependent	2.5	Horn,S,V	112	\$129.99
LAB12 12" Long Stroke Subwoofer	6	22	0.38	125.2	400	87.4	Horn Dependent	2.5	Horn,S,V	160	\$154.99
							nd LF for lower				****
Definimax 4012HO 12", High Output	8	46	0.35	59.4	600	94	49Hz-2.5kHz	4	1-2V	109	\$199.99
Definimax 4015LF 15", Low Frequency	8	42	0.50	115.5	700	96	35Hz-1.2kHz	4	3-6V	109	\$269.99
Definimax 4018LF 18", Low Frequency	8	32	0.35	237.9	800	95	36Hz-200Hz	4	4-7V	109	\$299.99
							Extended X-Ma	T *			
DELTA PRO-12A 12" woofer	8	51	0.35	81.7	400	98	50Hz-5kHz	2.5	1.8-2.9V	80	\$109.99
DELTA PRO-15A 15" woofer	8	42	0.40	243.5	400	98	40Hz-4kHz	2.5	2.25-3.75V	80	\$119.99
							round and 3" V		I		
KAPPA PRO-10A 10" woofer	8	46	0.20	52.2	500	96	45Hz-3kHz	3	0.2-0.3V	80	\$119.99
KAPPA PRO-12A 12" woofer	8	37	0.24	121	500	97	35Hz-2.5kHz	3	0.6-0.8V	80	\$129.99
KAPPA PRO-15A 15" woofer	8	47	0.38	167.7	500	100	40Hz-4kHz	3	3.75-6.25V	80	\$139.99
KAPPA PRO-15LF-2 15" woofer, low freq.	8	35	0.31	172.5	600	97.8	38Hz-1.8kHz	3	2.7-5.8V	120	\$154.99
OMECA PRO 154 158		20		GA/SIC				4	2455	100	#400.00
OMEGA PRO-15A 15" woofer	8	39	0.35	196	800	98	35Hz-2kHz	4	3.4-5.6V	109	\$189.99
OMEGA PRO-18A 18" woofer	8	28	0.24	354	800	97	25Hz-2kHz	4	2.2-2.9V	109	\$199.99
SIGMA PRO-18A-2 18" woofer	8	28	0.29	441.2	650	99	41Hz-2.4kHz	3	3.3-7.5V	120	\$159.99
We can special order any E	minen	ce spe	aker, jı	ıst let us	know v	vhat you	u require and w	e'll come	back with a	quote.	



ETON - Model 8.1



MADISOUND SPEAKER COMPONENTS, INC. 8608 UNIVERSITY GREEN P.O. BOX 44283

MADISON, WI 53744-4283 U.S.A. TEL: 608-831-3433 FAX: 608-831-3771 e-mail: info@madisound.com Web Page: http://www.madisound.com



Unit	Description	Ω	fs	dB	Watt	Price Each						
ER-4	Air Motion Ribbon Tweeter - 1.5 to 30kHz	6	490	88	60	\$341.50						
19 SD 1	3/4" Textile Dome Tweeter, dbl. magnet	8	1100	89	80	\$69.80						
25 SD 1	1" Textile Dome Tweeter, dbl. magnet	8	1000	90	100	\$76.60						
	All Eton midranges and woofers feature Kevlar/Nomex Hexacone cones.											
5-880	5" Kevlar Woofer	8	52	87	50	\$120.20						
7-360	7" Kevlar Woofer	8	43	89	100	\$145.50						
7-372	7" Long Throw Kevlar Woofer with heat pipe	8	32	88	80	\$179.40						
8-472	8" Long Throw Kevlar Woofer with heat pipe	8	24	88	90	\$222.60						
8-800	8" Kevlar Woofer	8	36	89	120	\$171.80						
11-581	11" Kevlar Woofer	8	21	91	150	\$343.40						
12-680	12" Kevlar Woofer	8	26	91	200	\$492.60						


Eton Kits engineered by Eton in Germany

All kits include speakers, crossovers ,all brass gold plated input terminals, black screws, port tubes and port tube trim rings, foam dampening pads, Acusta-Stuf (if called for) and Supra Classic internal speaker wire. Cabinet drawings are included. **Cabinets are not available at this time.** We recommend using Deflex panels behind the woofers and within the midrange chambers.

Eton 8.1 Kit: 2-way system using 8-800 woofer and 25SD-1 tweeter. Floor standing.	\$565.00 pr
Eton 8.2 Kit: 3-way system using 8-800 woofer, 5-880 midrange and 19SD-1 tweeter. Floor standing.	\$935.00 pr
Eton 11.2 Kit: 3-way system using 11-581 woofer, 5-880 midrange and 19SD-1 tweeter. Foor standing.	\$1170.00 pr


ETON 8.1 Kit 8" 2-Way Design **ETON 11.2 Kit** • 11" 3-Way Design Cabinets not available Cabinets not Fully assembled available premium crossovers Fully assembled 8-800 woofer premium crossovers 25SD-1 tweeter 11-581 woofer 5-880 midrange All damping materials included 19SD-1 tweeter 39.4" tall 41.3" tall 11.8"deep 13.9" deep 9.6" wide 11.6" wide Tube ø 3" / 5.75" SPI SPI

ETON - Model 11.2 SPL 1 Watt / 1 m - 0°, 30°



ETON 8.2 Kit

- 8" 3-Way Design
- Cabinets not available
- Fully assembled premium crossovers
- 8-800 woofer
- 5-880 midrange
- 19SD-1 tweeter
- 41.75" tall
- 12.6" deep
- 10.25" wide



L1 = 4,7 mH / Copper Wire CUL ø1,4 mm / air

L2 = 0,68 mH / Copper Wire CUL Ø1,0 mm / air L3 = 5,6 mH / Copper Wire CUL Ø1,0 mm / air L4 = 0,33 mH / Copper Wire CUL Ø 0,7 mm air

C1 = 150 MF / bipolar-capacitor / 50 Vac C2 = 6,8 MF / bipolar-Capacitor / 50 Vac C3 = 68 MF / bipolar-capacitor / 50 Vac C4 = 4,7 MF / foil-capacitor (MKP)

R1 = 1,5 Ohm / 4 W

R2 = 5,6 Ohm / 4 W

R3 = 0,75 Ohm / 10 W R4 = 15 Ohm / 4 W

R5 = 2,7 Ohm / 4 W - metaloxid

WO = ETON 8-800/37 HEX / 8 Ohm MD = ETON 5-880/25 HEX / 8 Ohm

TW = ETON 19 SD 1 / 8 Ohm

ER-4




- Air Motion Ribbon Tweeter
- New ribbon design
- High efficiency
- Suitable for center channel
- Flange 110 x 110mm
- Cut-out 90 x 90mm
- Depth 15mm

19 SD-1




- 3/4" Soft Dome Tweeter
- Response to 30 kHz
- Precoated textile dome
- Double magnet
- Vented polepiece
- Aluminum former and chassis
- Flange 110mm
- Cut-out 74mm
- Depth 43mm
- Great sounding tweeter

∠nom	4	onm	50	67	cm
Re	3.5	ohm	BL	-	N/A
Le@1kHz	-	mΗ	Vas	-	Itrs
fs	490	Hz	Xmax	-	mm peak
Qms	-		VC Ø	-	mm
Qes	-		Sensitivity		
Qts	-		1W / 1m	88	dB
Mms	0.66	g	Nom. Power DIN	60	W
Cms	- 1	mm/N	Net weight	-	kg



Znom	8 ohm	Sd	3.9	cm ²
Re	6.3 ohm	BL	-	N/A
Le@1kHz	0.20 mH	Vas	-	ltrs
fs	1100 Hz	Xmax	-	mm peak
Qms	-	VC Ø	19	mm
Qes	-	Sensitivity		
Qts	-	1W / 1m	89	dB
Mms	0.16 g	Nom. Power DIN	80	W
Cms	- mm/N	Net weight	-	kg



25 SD-1




- 1" Soft Dome Tweeter
- Response to 30 kHz
- Pre-coated textile dome
- Double magnet
- Vented pole piece
- Aluminum former and chassis
- Flange 110mm
- Cut-out 74mm
- Depth 43mm


5-880/25HEX



- 5" HEXACONE Bass/ Midrange
- Excellent for small monitors
- Excellent as midrange in multiple-way system
- 3mm X-max
- Flange 156mm
- Cut-out 128mm
 - Depth 70mm

Znom Re	8 ohm 6.8 ohm	Sd BL	6.5	cm² N/A	Znom Re	8 ohm 6.6 ohm	Sd BL	82 4.5	cm² N/A
Le@1kHz	0.28 mH	Vas	-	ltrs	Le@1kHz	0.48 mH	Vas	8.7	ltrs
fs	1000 Hz	Xmax	-	mm peak	fs	52 Hz	Xmax	3	mm peak
Qms	-	VC Ø	25	mm	Qms	2.29	VC Ø	25	mm
Qes	-	Sensitivity			Qes	0.46	Sensitivity		
Qts	-	1W / 1m	90	dB	Qts	0.38	1W / 1m	87	dB
Mms	0.22 g	Nom. Power DIN	100	W	Mms	9.6 g	Nom. Power DIN	50	W
Cms	- mm/N	Net weight	-	kg	Cms	- mm/N	Net weight	-	kg





7-360 / 37HEX



- 7" HEXACONE Bass/ Midrange
- No coloration
- Excellent sound quality
- Rubber surround
- Aluminum diecast basket
- Flange 186mm
- Cut-out 160mm
- Depth 83mm


7-372/32LH




- 7" HEXACONE Woofer
- Constructed with new Heatpipe
- Long throw
- Rubber surround
- Aluminum diecast basket
- Flange 185mm
- Cut-out 151mm
- Depth 89mm

Znom	8	ohm	Sd	137	cm ²
Re	5.6	ohm	BL	7.8	N/A
Le@1kHz	0.64	4 mH	Vas	20.0	ltrs
fs	43	Hz	Xmax	3.0	mm peal
Qms	2.74	4	VC Ø	37	mm
Qes	0.42	2	Sensitivity		
Qts	0.37	7	1W / 1m	89	dB
Mms	18	g	Nom. Power	DIN 100	W
Cms	-	mm/N	Net weight	-	kg

CDI 4 W//4 m						SDI 1 W / 1m	400				
ms	-	mm/N	Net weight	-	kg	Cms	-	mm/N	Net weight	-	kg
lms	18	g	Nom. Power DIN	100	W	Mms	15.6	•	Nom. Power DIN	80	W
ts	0.37	7	1W / 1m	89	dB	Qts	0.27		1W / 1m	88	dB
es	0.42	2	Sensitivity			Qes	0.29)	Sensitivity		
ms	2.74	1	VC Ø	37	mm	Qms	3.78	3	VC Ø	32	mm
	43	Hz	Xmax	3.0	mm peak	fs	32	Hz	Xmax	5.25	mm peak
e@1kHz	0.64	1 mH	Vas	20.0	ltrs	Le@1kHz	0.71	mH	Vas	44	Itrs
е	5.6	ohm	BL	7.8	N/A	Re	7	ohm	BL	6.7	N/A
nom	8	ohm	Sd	137	cm ²	Znom	8	ohm	Sd	137	cm ²





8-472/32 LH



- 8" HEXACONE Woofer
- Constructed with new Heatpipe
- Long throw
- Rubber surround
- Aluminum diecast basket
- Flange 223mm
- Cut-out 186mm
- Depth 108mm

8-800/37HEX



- 8" HEXACONE Woofer
- Excellent sound characteristics
- Outstanding pulse response
- Aluminum diecast basket
- Flange 228mm
- Cut-out 202mm


cm² N/A Itrs


mm peak mm dB W kg

• Depth 96mm

Znom	8	ohm	Sd	219	cm ²
Re	7	ohm	BL	6.7	N/A
Le@1kHz	-	mΗ	Vas	116	Itrs
fs	24	Hz	Xmax	5.25	mm peak
Qms	3.55	;	VC Ø	32	mm
Qes	0.32		Sensitivity		
Qts	0.29	1	1W / 1m	88	dB
Mms	27	g	Nom. Power DIN	90	W
Cms	-	mm/N	Net weight	-	kg

∠nom	8	onm	Sa	235
Re	5.5	ohm	BL	9.3
Le@1kHz	0.69	mH	Vas	45.5
fs	36	Hz	Xmax	3.0
Qms	2.44		VC Ø	37
Qes	0.46		Sensitivity	
Qts	0.39		1W / 1m	89
Mms	31	g	Nom. Power DIN	120
Cms	-	mm/N	Net weight	-





11-581/50HEX



- 11" HEXACONE Woofer
- Low frequency reproduction
- Excellent pulse response
- Aluminum diecast basket
- Flange 280mm
- Cut-out 244mm
- Depth 104mm


12-680/62HEX




- 12" HEXACONE Woofer
- Low frequency reproduction
- Excellent pulse response
- Aluminum diecast basket
- Flange 315mm
- Cut-out 291mm
- Depth 143mm

	Znom8	ohm	Sd	366	cm ²
Re	5.2	ohm	BL	12.4	N/A
Le@1kHz	0.69	mH	Vas	153	Itrs
fs	21	Hz	Xmax	5.0	mm peak
Qms	6.68		VC Ø	50	mm
Qes	0.31		Sensitivity		
Qts	0.30		1W / 1m	91	dB
Mms	67.3	g	Nom. Power DIN	150	W
Cms	-	mm/N	Net weight	-	kg

Znom	8 ohm	Sd	515	cm ²
Re	6.1 ohm	BL	15.6	TM
Le@1kHz	1.45 mH	Vas	150	ltrs
fs	26 Hz	Xmax	6	mm peak
Qms	3.52	VC Ø	62	mm
Qes	0.38	Sensitivity		
Qts	0.34	1W / 1m	91	dB
Mms	92 g	Nom. Power DIN	200	W
Cms	- mm/N	Net weight	-	kg








Visit our web page for more specifications and cabinet designs. www.madisound.com & www.fostex.jp

W 11	т	Г	04	3.7	D	tn.		37	I		
Model	Imp. W	Fs Hz	Qts	Vas Ltrs	Power Watts	dB	Frequency Range	Xmax mm P	Box Liter Sealed/Vented	F3 Hz	Price Each
	***		rlds Firs	st Pure M		n Dome '		11111111	Sealed/ Vented		Lacii
T250D pure magnesium dome	8	'''	lustiis	ure w	150	90	1.5kHz-50kHz				\$263.00
		TWE	ETER -	Patented			e" Full surface di	ive diaphr	agm.		7=00100
FT7RP ribbon tweeter	8				80	93	3.5K-45kHz	•			\$86.60
			FT S	ERIES D	OME TV	VEETE	R				
FT207D dome tweeter, grill, Shielded	8				60	90	3K-40kHz				\$41.60
FT28D dome tweeter	8				40	90	2.5K-50kHz				\$59.00
FT48D dome tweeter	8				50	93	2K-30kHz				\$83.20
TVD4 MYY 1			FTS	ERIES H	1				1		d25 10
FT17H horn tweeter	8				30 50	98.5 100	5K-50kHz 3K-33kHz				\$37.10 \$109.60
FT96H horn super tweeter, alnico magnet	_	CFDI	FS HOL	N TWF) MAGNET				\$109.00
T90A top mount, super tweeter, alnico magnet	8	SEKI	LS HOL	T T VV E	50	106	7K-35kHz				\$146.45
T925A top mount, super tweeter, alnico magnet	8				50	108	6K-40kHz				\$273.25
T500AMK2 top mount, super tweeter, alnico	8				50	110	4K-45kHz				\$756.20
T900A top mount, super tweeter, alnico magnet	8				60	106	5K-38kHz				\$380.40
F SERIES ALNICO MAGNET- Suita	able for	folded	l horn ei	nclosures	Mica co	mposite		iscontinue	d - Get them wh	ile they la	
F120A 4.5" full range, alnico magnet	8	65	0.44	9.87	30	89	Fo-20kHz	1.5	6S/12V	105/58	\$227.15
F200A 8" full range, alnico magnet	8	30	0.32	98.96	80	90	Fo-20kHz	2.0	25S/38V	67/45	\$388.50
FX SERIES - Bio-cellulose cone	made f	rom k	enaf wit		mica con	nposite (inued - Ge		ey last!	
FX120 5" full range	8	70	0.45	8.21	30	89	Fo-20kHz	2.0	5.4S/11V	111/60	\$102.60
							ole for folded hor			I .	
FE108EΣ ; 4" full range	8	77	0.30	5.7	24	90	Fo-23kHz	0.28	Horn	fs	\$88.15
FE168EΣ; 6.5" full range	8	51	0.26	23.7	80	94.5	Fo-21kHz	1.6	Horn	fs	\$144.20
FE208EΣ; 8" full range	8 E CED	42 TEC	0.18	60.1	120	97	Fo-14kHz	1.25	Horn	fs	\$181.70
	E SER	140	0.78	1.293	10	nciosure 88	s, banana pulp co Fo-20kHz	0.4	2-4S	140-135	\$30.10
FE83E 3" full range FE87E 3" full range - Shielded	8	140	0.78	1.03	10	89	Fo-30kHz	0.4	3-5S	125-120	\$31.20
FE103E 4" full range	8	80	0.35	6.89	15	89	Fo-22kHz	0.4	2.4S/3V	158/100	\$38.20
FE107E 4" full range - Shielded	8	80	0.33	5.95	15	90	Fo-22kHz	0.35	2.4S/4V	148/89	\$40.45
FE126E 4.5" full range	8	70	0.25	9.95	45	93	Fo-25kHz	0.35	1.5S/2V	200/165	\$42.75
FE127E 4.5" full range - Shielded	8	70	0.23	9.9	45	91	Fo-20kHz	0.35	6S/12V	114/62	\$45.00
FE166E 6.5" full range	8	50	0.21	45.11	65	94	Fo-22kHz	0.6	4.5S/5V	170/125	\$63.55
FE167E 6.5" full range - Shielded	8	50	0.33	30.2	65	95	Fo-22kHz	0.6	8.4S/18V	118/69	\$65.80
FE206E 8" full range	8	39	0.18	54.5	90	96	Fo-20kHz	1.5	45V	55	\$88.00
FE207E 8" full range - Shielded	8	39	0.26	56.25	90	95	Fo-20kHz	1.5	9S/17V	108/68	\$89.95
FF S	SERIES	S - Suit	able for	folded h	orn enclo	sures, us	ing kenaf fiber c	ones.			
FF85K 3" full range, fiber cone, up/down surr.	8	122	0.47	1.07	10	88	Fo-33kHz	0.55	0.9S/2V	181/94	\$33.45
FF125K 4.5" full range, fiber cone	8	72	0.26	9.12	50	92	Fo-18kHz	0.15	1.5S/2V	195/135	\$41.60
FF165K 6.5" full range, fiber cone	8	40	0.20	48.2	70	94	Fo-17kHz	0.3	4.5S/7V	135/94	\$63.55
FF225K 8" full range, fiber cone	8	38	0.16	79.41	100	96	Fo-14kHz	0.3	Horn	fs	\$98.10
FW137 5.5" woofer, Paper cone - Shielded	0						magnets.	1.0	9S/10V	90/55	\$57.65
FW157 5.5 woofer, Paper cone - Shielded	8	55	0.5	10.2 25.22	75 100	87 89	Fo-8kHz Fo-8kHz	1.0	95/10V 8S/12V	80/55 80/50	\$86.60
1 11107 0.5 woord, 1 aper cone - Smerded	1 0			IES - Hyl				1.3	05/12 V	1 00/30	ψουισο
FW108N 4" wide range woofer	8	55	0.26	4.09	50	86	Fo-10kHz	1.9	0.7S/1V	148/93	\$113.00
FW168N 6.5" woofer	8	40	0.16	14.25	100	89	Fo-9kHz	0.5	4S/5V	200/80	\$145.35
FW208N 8" woofer	8	29	0.2	43.42	100	90	Fo-5kHz	6.5	4.1S/7V	99/68	\$166.15
FW305 12" woofer, 5" voice coil	8	25	0.28	254	125	95	Fo-3.5kHz	4.8	38S/74V	70/44	\$219.00
FW405N 15" woofer	8	27	0.45	392.5	150	92.5	Fo-2.5kHz	7.9	113S/170V	50/37	\$526.80
W400A-HR 16" woofer, alnico magnet	8	25	0.31	310	200	94	Fo-2.5kHz	5.5	90V/120V	45/40	\$2,672.70
FW800N 31.5" super woofer	8	18	0.69	3201	450	96	Fo-1.5kHz	2.3	Inf. Baffle	Fo	\$2,535.75
	T -	I		ATTE	NUATO	R					
R80B L-pad	8				100			nuation 0-4			\$21.95
R82B L-pad	8				200			nuation 0-4			\$38.20
R100T transformer type	8 mmore	ial II-	Нот Т		100 For PA or	Drofoa-	Attenuation		1 1dB steps		\$177.65
H200 Wooden Horn, 2" throat, 240Hz	пппегс						Deep, Natural Ma		not included		\$2268.40
H300 Wooden Horn, 1" throat, 328 Hz							Deep, Natural Ma	•			\$1317.60
H400 Wooden Horn, 1" throat, 455Hz							Deep; Natural Mar	•			\$488.85
D1405 Compression Horn Driver, alnico	8	800		ounds	60	104	850Hz - 20kHz		tanium diaphrag	m	\$273.25
D1400 Compression Horn Drivers, alnico	8	650		ounds	60	104	750Hz - 20kHz		tanium diaphrag		\$469.20
, unico		,	,,,,			-7.		- 11		•	7 - 57 12 0

FOSTEX

Copper Foil/Tin Foil & PPTA Film Capacitor



The Fostex CS capacitors are made from separate layers of Copper Foil, Tin Foil and PPTA Film (poly p-phenylene terepthalamide). The CS caps have solid copper leads. These caps are very densely wrapped, more than twice the weight of similar value capacitors. Non-inductive. 120VAC / 240VDC

<u>Unit</u>	Size mm	Price	<u>Unit</u>	Size mm	Price
0.33	14 Ø x 37	\$24.45	1.50	18 Ø x 62	\$33.45
0.47	16 Ø x 37	\$24.45	2.20	21 Ø x 62	\$40.45
0.68	19 Ø x 37	\$25.55	3.30	25 Ø x 62	\$50.85
1.00	20 Ø x 37	\$28.95			

FOSTEX

Special Edition Kit Book


Fostex has compiled many speaker designs into this spe-

cial edition kit book. The books are written in Japanese. They are filled with different speaker designs of all types. Even if you don't read Japanese, you can still construct the speakers from the drawings and crossover schematics. Most systems are using the Fostex speakers and most are full range, not requiring a crossover.



This is a must have for any full range speaker hobbyist.

Price: \$17.00



FOSTEX

Protective Grills



Metal mesh grills with plastic outer housing. Comes with mounting hardware. We don't have grills for the stamped frame 6" units.

<u>Unit</u>	<u>Description</u>	Price Pair
K308	FE83E, FE87E, FF85K	\$18.55
KG810	FE108EZ, FW108N	\$30.10
K312	FE126E, FE127E, FF125K	\$25.55
KG816	FE168EZ, FW168	\$50.85
KG820	FE208EZ, FW208N	\$68.05

Fostex

HP Sound Reflectors



The HP Sound Reflectors are designed to be used in folded horn enclosures to reduce standing wave problems. When properly placed, the HP Sound Reflectors will reduce resonance peaks in the higher frequencies and cut down on frequency cancellations in the lower frequencies. Made from plastic.

Price per 5 pack: \$50.85

BK-16 Kit



Madisound is pleased to offer the BK-16 folded horn kit. We have chosen the **Fostex FF165K** 6.5" full range for use in the BK-16 cabinet. The **FF165K** has a **Kenaf** fiber cone, inverted foam surround and aluminum dust cap.

The **FF165K** is run full range with a frequency response out to 15kHz. The **T90A** super tweeter has been added to cover the upper frequencies. The **T90A** is a top-mount horn tweeter with an **Alnico magnet**. The tweeter is rolled off on the

low end with a **Fostex Tin & Copper foil capacitor.** The system frequency response is 55Hz to 35kHz at 95dB.

The **BK-16** cabinet is made from **Baltic Birch** plywood and is sold flat, unassembled, unsanded and unfinished. Cabinet dimensions are 9.75" W x 14.75" D x 29" T.

The Kit Includes:

- Pair of Cabinets Flat
- Pair of FF165K Full range
- Pair of T90A horn tweeter
- Pair of DB-cup Input cup
- Pair of Crossovers
- Nordost 2-Flat wire for tweeter
- Instructions

Kit Price: \$750.00 / pair Parts without Cabinets: \$454 /pair Cabinets only: \$148.00 each










FOSTEX T250D \$263.00



- World's First Pure Magnesium Dome Tweeter
- High power magnetic circuit by using a copper plated yoke and top plate, along with a three 90mm ferrite magnets.
- Silver/Copper alloy voice coil wire and internal wiring
- Up down roll tangential surround is used to realize less anti-resonance and superior amplitude characteristic.
- High density resin frame designed to minimize the distance between the tweeter and woofer.
- Frequency range 1.5kHz to 50kHz
- S.P.L. 90dB (1W/1m)
- 8 ohm Impedance







FT7RP \$86.60




FOSTEX

8	ohm
-	ohm
-	mΗ
3000	Hz
-	
-	
-	
-	g
-	mm/N
	-

- RIBBON TWEETER
- 8 ohm impedance
- Frequency response from 3kHz to 45kHz
- 93dB sensitivity at 1w/1m (3.3ft)
- Flange 76mm x 86mm
- Cut-out 50mm
- Depth 32mm

Sd	-	cm ²
BL	-	N/A
Vas	-	ltrs
Xmax	-	mm peak
VC Ø	-	mm
Sensitivity		
1W / 1m	93	dB
Nom. Power	80	W
Net weight	155	q



FT28D \$59.00




- DOME TWEETER
- 8 ohm impedance
- 1kHz to 50kHz frequency response
- 90dB sensitivity at 1w/1m (3.3ft)
- Flange 90mm x 78mm
- Cut-out 70mm
- Depth 32.8mm

FOSTEX

Znom	8	ohm
Re	-	ohm
Le@1kHz	-	mΗ
fs	1000	Hz
Qms	-	
Qes	-	
Qts	-	
Mms	-	g
Cms	-	mm/N

-	cm ²
-	N/A
-	ltrs
-	mm pea
-	mm
90	dB
40	W
528	g
	40



FT207D




FOSTEX

Znom	8	ohm
Re	-	ohm
Le@1kHz	-	mΗ
fs	1000	Hz
Qms	-	
Qes	-	
Qts	-	
Mms	-	g
Cms	-	mm/N
120		

- DOME TWEETER
 - 20mm textile dome
 - Shielded magnet
 - Frequency response from 3kHz to 40kHz
- 90dB sensitivity at 1 w/1 m (3.3 ft)
- Flange 95mm round
- Cut-out 70 mm
- Depth 34.4mm

Sd	-	cm ²
BL	-	N/A
Vas	-	ltrs
Xmax	-	mm peak
VC Ø	-	mm
Sensitivity		
1W / 1m	90	dB
Nom. Power	60	W
Net weight	390	g




FT48D \$83.20



FOSTEX

- DOME TWEETER
- 8 ohm impedance
- 33mm Dome
- Frequency response from 800kHz to 30kHz
- 93dB sensitivity
- Felt front
- Flange 128mm
- Cut-out 90mm
- Depth 38.7mm

Znom	8	ohm	Sd	-	cm ²
Re	-	ohm	BL	-	N/A
Le@1kHz	-	mΗ	Vas	-	ltrs
fs	800	Hz	Xmax	-	mm peak
Qms	-		VC Ø	-	mm
Qes	-		Sensitivity		
Qts	-		1W / 1m	93	dB
Mms	-	g	Nom. Power	50	W
Cms	-	mm/N	Net weight	978	g
			_		_



FT17H \$37.10



Znom ohm Re ohm Le@1kHz mΗ fs 5000 Hz Qms Qes Qts Mms mm/N Cms

- HORN SUPER **TWEETER**
- 8 ohm impedance
- Frequency response from 5kHz to 50kHz
- 98.5dB sensitivity at 1w/1m (3.3 ft)
- Flange 87mm
- Cut-out 63mm
- Depth 38.5mm

Sd	-	cm ²
BL	-	N/A
Vas	-	Itrs
Xmax	-	mm peak
VC Ø	-	mm
Sensitivity		
1W / 1m	98.5	dB
Nom. Power	30	W
Net weight	340	g

\$109.60 FT96H



Fostex

Znom	8	ohm
Re	-	ohm
Le@1kHz	-	mΗ
fs	4000	Hz
Qms	-	
Qes	-	
Qts	-	
Mms	-	g
Cms	-	mm/N

120

110

100

90

80

70

60


50Hz 100

- HORN SUPER **TWEETER**
- 8 ohm impedance
- Frequency response 4kHz to 33kHz
- 100dB sensitivity 1w/1m
- Alnico magnet
- Flange 68mm square
- Cut-out 60mm
- Depth 60mm

Sd	-	cm ²
BL	-	N/A
Vas	-	ltrs
Xmax	-	mm peak
VC Ø	-	mm
Sensitivity		
1W / 1m	100	dB
Nom. Power	50	W
Net weight	600	g

ohm

50K



T90A

Znom Re

fs

Qms Qes Qts Mms

Cms

Le@1kHz

\$146.45

ohm

mΗ

Hz

g mm/N



5000

- HORN SUPER **TWEETER**
- 8 ohm impedance
- Frequency response from 5kHz to 35kHz
- 106dB sensitivity at 1w/1m(3.3ft)
- TOP MOUNT
- Flange 60 mm
- Depth 74.1/87.8 mm

Sd	-	cm ²
BL	-	N/A
Vas	-	Itrs
Xmax	-	mm peak
VC Ø	-	mm
Sensitivity		
1W / 1m	106	dB
Nom. Power	50	W
Net weight	800	g



200

500

1K

2K

FOSTEX

Znom	8	ohm
Re	-	ohm
Le@1kHz	-	mΗ
fs	5000	Hz
Qms	-	
Qes	-	
Qts	-	
Mms	-	g
Cms	-	mm/N

 HORN SUPER **TWEETER**


Impedance


8 ohm impedance

10K

- Frequency response from 5kHz to 40kHz
- 108dB sensitivity at 1w/1m (3.3ft)
- TOP MOUNT
- Flange 82 mm
- Depth 91/108mm

Sd	-	cm ²
BL	-	N/A
Vas	-	Itrs
Xmax	-	mm peak
VC Ø	-	mm
Sensitivity		
1W / 1m	108	dB
Nom. Power	50	W
Net weight	2.0	Kg





T500AMKII \$756.20 ·



4000

110

ohm

Hz

dB


Znom

Sensitivity

1W / 1m

- Horn Super Tweeter
- Pure Magnesium diaphragm
- Silver/Copper VC wire
- Frequency response from 4kHz to 45kHz
- 110dB sensitivity
- Copper terminals
- Solid Brass horn body
- Double alnico magnets

Nom. Power 50 Net weight 5.0 Kg



Recommended x-over frequency more than 7kHz (12dB/Oct.)

F120A \$227.15




FOSTEX

Znom	8	ohm
Re	7	ohm
Le@1kHz	-	mΗ
fs	65	Hz
Qms	3.1	
Qes	.51	
Qts	.44	
Mms	4.7	g
Cms	_	mm/N

- 5" FULL RANGE
- Alnico Magnet
- 8 ohm impedance
- Frequency response from 65Hz to 20kHz
- 89dB sensitivity
- Flange 137 x 123mm **HEXAGONAL**
- Cut-out 103mm
- Depth 88mm

Sd	-	cm ²
BL	-	N/A
Vas	9.87	ltrs
Xmax	1.5	mm peal
VC Ø	-	mm
Sensitivity		
1W / 1m	89	dB
Nom. Power	30	W
Net weight	2.0	Ka




T900A \$380.40



Znom	8	ohm
Re		ohm
Le@1kHz	-	mΗ
fs	-	Hz
Qms	-	
Qes	-	
Qts	-	
Mms	-	g
Cms	-	mm/N

- HORN SUPER **TWEETER**
- 8 ohm impedance
- Frequency response from 5kHz to 38kHz
- 106 dB sensitivity 1 w/1 m
- TOP MOUNT
- Flange 82mm
- Depth 81.8mm/ 98.3mm

ohm	Sd	-	cm ²
ohm	BL	-	N/A
mH	Vas	-	Itrs
Hz	Xmax	-	mm peak
	VC Ø		mm
	Sensitivity		
	1W / 1m	106	dB
g	Nom. Power	60	W
mm/N	Net weight	3.55	Κg



F200A






FOSTEX

8	ohm
7.3	ohm
-	mΗ
30	Hz
2.63	
0.36	
0.32	
18.6	g
-	mm/N
	7.3 30 2.63 0.36 0.32

- 8" FULL RANGE
- Alnico magnet
- 8 ohm impedance
- Frequency response from 30Hz to 20kHz
- 90 dB sensitivity
- Flange 213 X 194mm **HEXAGONAL**
- Cut-out 182 mm
- Depth 123.7 mm

-	cm ²
-	N/A
98.96	Itrs
2.0	mm peak
-	mm
90	dB
80	W
4.4	kg
	2.0 - 90 80



FX120 \$102.60



FOSTEX

Znom	8	ohm
Re	7.3	ohm
Le@1kHz	-	mΗ
fs	70	Hz
Qms	8.4	
Qes	0.47	
Qts	0.45	
Mms	5.3	g
Cms	-	mm/N

- 5" FULL RANGE
- KENAF paper/ fiber composite cone
- 89db sensitivity
- Frequency response from 70 Hz to 20kHz
- Flange 137 x 123mm **HEXAGONAL**
- Cut-out 103 mm
- Depth 54.5 mm

Sd	_	cm ²
BL	-	N/A
Vas	8.21	ltrs
Xmax	2.0	mm peak
VC Ø	-	mm
Sensitivity		
1W / 1m	89	dB
Nom. Power	30	W
Net weight	1.32	kg

$FE108E\Sigma$ \$88.15



Fostex

Znom	8	ohm
Re	6.8	ohm
Le@1kHz	.038	mΗ
fs	77	Hz
Qms	7.79	
Qes	0.32	
Qts	0.3	
Mms	2.7	g
Cms	1.59	mm/N

110

Znom

Le@1kHz

Re

Qms

Qes


Qts

Mms

Cms

- 4" FULL RANGE
- HP shell diaphragm
- Banana pulp cone
- UDR surround
- Frequency response from 77Hz to 23kHz
- 90dB sensitivity
- Flange 128 mm
- Cutout 98mm
- Depth 65mm

Sd	0.005	m²
BL	5.2	N/A
Vas	5.7	Itrs
Xmax	0.28	mm peak
VC Ø	20	mm
Sensitivity		
1W / 1m	90	dB
Nom. Power	24	W
Net weight	1200	g



100 90 80 70 60 50 (dB) 100 200 500 2k 5k 10k

$FE168E\Sigma$ \$144.20



6.8

.056

5.328

0.27

0.26

1.278

8.7

51

ohm

ohm

mΗ

Hz

mm/N

Znom

Re Le@1kHz

fs

Qms

Qes

Qts

Mms

Cms

- 6.5" FULL RANGE
- HP shell diaphragm
- Banana pulp cone
- UDR surround
- Frequency response from 51Hz to 21kHz
- 94.5dB sensitivity
- Flange 190 mm
- Cutout 146mm
- Depth 88mm

Sd BL Vas Xmax	0.0113 8 23.7 1.6	m² N/A Itrs mm peak
VC Ø	30	mm
Sensitivity		
1W / 1m	94.5	dB
Nom. Power	80	W
Net weight	2600	g

FE208E Σ \$181.70



6.4

42

6.19

0.19

0.18

13.3

1.069

0.051

ohm

ohm

mΗ

Hz

mm/N

•	HP	shell	dia	phragr
---	----	-------	-----	--------


8" FULL RANGE


20k

40k

- Banana pulp cone
- UDR surround
- Frequency response from 42Hz to 14kHz
- 97dB sensitivity
- Flange 230 mm
- Cutout 182mm
- Depth 93.5mm

Sd	0.0201	m²
BL	10.8	N/A
Vas	60.1	Itrs
Xmax	1.25	mm peak
VC Ø	35	mm
Sensitivity		
1W / 1m	97	dB
Nom. Power	120	W
Net weight	4800	g





FE83E \$30.10



7.8

127

4.00

0.98

0.79

1.39 0.0012 Hz

mm/N

Znom Re

fs

Qms

Qes

Qts

Mms

Cms

Le@1kHz

- 3" FULL RANGE
- ES banana pulp cone
- · New center cap
- Frequency response from 127 Hz to 20kHz

 m^2


N/A

Itrs

- 88dB sensitivity
- Flange 83mm
- Cut-out 71mm
- Depth 40.2mm

EX:		
ohm	Sd	.0028
ohm	BL	2.98
mΗ	Vas	1.29

Xmax	0.4	mm peak
VC Ø	16	mm
Sensitivity		
1W / 1m	88	dB
Nom. Power	10	W
Net weight	360	g




FE103E \$38.20 • 4" FULL RANGE

- ES banana pulp cone
- New center cap
- 8 ohm impedance
- Frequency response 79.5 Hz to 22kHz
- 89dB sensitivity
- Flange 107mm
- Cut-out 92mm
- Depth 43.6mm

-ostex

∠nom	Ö	onm
Re	7.45	ohm
Le@1kHz	-	mΗ
fs	79.5	Hz
Qms	2.87	
Qes	0.40	
Qts	0.36	
Mms	2.1	g
Cms	0.0019	mm/N

Sd	0.005	m ²
BL	4.42	N/A
Vas	6.90	Itrs
Xmax	0.35	mm peak
VC Ø	20	mm
Sensitivity		
1W / 1m	89	dB
Nom. Power	15	W
Net weight	630	a



FE87E \$31.20




FOSTEX

Znom	8	ohm
Re	7.7	ohm
Le@1kHz	-	mΗ
fs	140	Hz
Qms	3.77	
Qes	1.2	
Qts	0.92	
Mms	1.4	g
Cms	0.0009	mm/N

• 3" **SHIELDED** FULL RANGE

- ES banana pulp cone
- New center cap
- Frequency response from 140 Hz to 30kHz
- 89dB sensitivity
- Flange 83mm
- Cut-out 71mm
- Depth 41.2mm

Sd	.0028	m ²
BL	2.81	N/A
Vas	1.03	Itrs
Xmax	0.4	mm peak
VC Ø	16	mm
Sensitivity		
1W / 1m	89	dB
Nom. Power	15	W
Net weight	288	a



FE107E

Znom Re

fs

Qms

Qes

Qts

Mms

Cms

Le@1kHz

7.6

80

2.56

0.45

0.38

0.0017

2.6

ohm

mΗ

Hz

g


mm/N

\$40.45

• 4" **SHIELDED** FULL RANGE

- ES banana pulp cone
- 8 ohm impedance
- 90dB sensitivity
- Frequency response to 22kHz
- Flange 107mm
- Cut-out 92mm
- Depth 54.7mm

Sd	0.005	cm ²
BL	4.7	N/A
Vas	5.95	ltrs
Xmax	0.35	mm peak
VC Ø	20	mm
Sensitivity		
1W / 1m	90	dB
Nom. Power	15	W
Net weight	550	g



\$42.75 **FE126E**



FOSTEX

Znom	8	ohm
Re	6.9	ohm
Le@1kHz	0.0065	mΗ
fs	70	Hz
Qms	2.96	
Qes	0.27	
Qts	0.25	
Mms	2.9	g
Cms	0.0017	mm/N

- 4.5" FULL RANGE
- ES banana pulp cone
- New center cap
- 93 db sensitivity
- Frequency response from 70 Hz to 25kHz
- Flange 117mm
- Cut-out 103mm
- Depth 61mm

Sd	0.0065	m²
BL	5.92	N/A
Vas	9.95	Itrs
Xmax	0.35	mm peak
VC Ø	20	mm
Sensitivity		
1W / 1m	93	dB
Nom. Power	45	W
Net weight	1010	a

FE127E \$45.00




FOSTEX

Znom	8	ohm
Re	6.5	ohm
Le@1kHz	-	mΗ
fs	70.4	Hz
Qms	3.33	
Qes	0.50	
Qts	0.43	
Mms	6.85	g
Cms	0.0016	mm/N

• 4.5" **SHIELDED** FULL **RANGE**

- ES banana pulp cone
- New center cap
- 91 db sensitivity
- Frequency response from 70.4 Hz to 20kHz
- Flange 117mm
- Cut-out 103mm
- Depth 64.7mm

Sd	0.0067	m²
BL	4.14	N/A
Vas	9.9	Itrs
Xmax	0.67	mm peak
VC Ø	20	mm
Sensitivity		
1W / 1m	91	dB
Nom. Power	45	W
Net weight	574	g



FE166E

50

(dB)

100

90

80

70

60

50

40

7nom

Le@1kHz

Re

fs

Qms

Qes

Qts

Mms

Cms

ohm

ohm

mΗ

mm/N

Hz

50

3.89

0.22

0.21

6.85

0.0018

200

100

\$63.55

500

1k

2k



ES banana pulp cone

10k

- New center cap
- 8 ohm impedance
- 94 db sensitivity
- Frequency response from 50 Hz to 22kHz
- Flange 166mm
- Cut-out 144mm
- Depth 73.2mm

Sd	0.0132	m²
BL	8.33	N/A
Vas	45.11	ltrs
Xmax	0.6	mm peak
VC Ø	25	mm
Sensitivity		
1W / 1m	94	dB
Nom. Power	65	W
Net weight	1600	g

FE167E

Znom

Le@1kHz

7.1

51.5

4.63

0.33

0.31

6.68

0.0015

ohm

mΗ

Hz

mm/N

Re

fs

Qms

Qes

Qts

Mms

Cms

8


20k 40k

\$65.80

• 6" **SHIELDED** FULL **RANGE**

- ES banana pulp cone
- New center cap
- 8 ohm impedance
- Frequency response from 51.5 Hz to 22 kHz
- Flange 166 mm
- Cut-out 144 mm
- Depth 85 mm

Sd	0.0132	m²
BL	6.82	N/A
Vas	35.94	Itrs
Xmax	0.6	mm peak
VC Ø	25	mm
Sensitivity		
1W / 1m	94	dB
Nom. Power	65	W
Net weight	1320	a



110 100 90 80 70 60 16 50 8 (dB) 20 Hz 50 200 100 500 1k 2k 5k 10k 20k 40k

FE206E \$88.00



6.69

39

3.73

0.18

0.18

15.35

0.0009

ohm

ohm

mΗ

Hz

g mm/N

Znom

Le@1kHz

Re

fs

Qms

Qes

Qts

Mms

Cms

- 8" FULL RANGE
- ES banana pulp cone
- · New center cap
- Large 110mm magnet
- Frequency response from 39 Hz to 20kHz

0.0206

11.8

1.5

35

96

90

3350

54.53

 m^2

N/A

Itrs

mm

dΒ

W

g

mm peak

- Flange 208 mm
- Cut-out 182 mm
- Depth 87.5 mm

FOSTEX

\$89.95


FE207E

Znom	8	ohm
Re	6.73	ohm
Le@1kHz	-	mΗ
fs	39	Hz
Qms	3.86	
Qes	.28	
Qts	.26	
Mms	15.02	g
Cms	0.0009	mm/N

• 8" **SHIELDED** FULL **RANGE**

- ES banana pulp cone
- New center cap
- 8 ohm impedance
- Frequency response from 39kHz to 20kHz
- Flange 208 mm
- Cut-out 182 mm
- Depth 104 mm

Sd	0.0206	m²
BL	9.41	N/A
Vas	56.25	ltrs
Xmax	1.5	mm peak
VC Ø	35	mm
Sensitivity		
1W / 1m	95	dB
Nom. Power	90	W
Net weight	2650	g



Sd

BL

Vas

Xmax


VC Ø


Sensitivity

1W / 1m

Nom. Power

Net weight





\$41.60

FF85K \$33.45



- 3" FULL RANGE
- KENAF paper/ fiber composite cone
- U
- A
- Fr fre
- Fl
- Cı
- D

DR surround	
luminum center cap	
requency response	6
om 122 Hz to 32 kHz	The same of the sa
lange 83 mm	
ut-out 71 mm	
epth 49 mm	FOSTEX

Re

fs

FF125K

 4.5" FULL RANG 	iΕ
------------------------------------	----

- KENAF paper/ fiber composite cone
- · 92db sensitivity
- Frequency response from 72 Hz to 18 kHz
- Flange 117 mm
- Cut-out 103 mm
- Depth 60.1 mm

F	0	5	٥	K	
_		_	 		


8	ohm
7.08	ohm
-	mΗ
122	Hz
5.54	
0.52	
0.47	
1.8	g
0.001	mm/N
	7.08 - 122 5.54 0.52 0.47 1.8

Sd	0.0028	m^2
BL	4.33	N/A
Vas	1.07	ltrs
Xmax	0.55	mm peal
VC Ø	20	mm
Sensitivity		
1W / 1m	88	dB
Nom. Power	10	W
Net weight	565	g

Sd BL	0.0028	m² N/A
Vas	1.07	ltrs .
Xmax	0.55	mm peak
VC Ø	20	mm
Sensitivity		
1W / 1m	88	dB
Nom. Power	10	W
Net weight	565	g

																					3									9		
<u>'</u> [Т	Т	1	Τ	T	П	Τ		Γ	T		Γ	T	T	Π	Ţ	Π	_	Τ	T	_		Γ	П	T	Γ	Į		<u> </u>		Т	1
			1	Ť	Ī	I	İ			Ť			T	I	T	T	11		T	Ť			Γ	П	1	T	Ħ	_	F	L	Τ	1
) -				T	Ι		Ī	_	Ļ	4	_	ŀ	1	Ŧ	¥	7	ll	è	7	4	J		Ī,	7	Ŧ	ŀ			~	V		
, [ŀ	ł	ł	f	_		Ι			1		Ι		П		Γ	I			Γ	1	Ī	₹	П	W	.7	Κ.	\setminus	l
, [J	7	٦		Γ	П	V	$\overline{\ \ }$	Γ	Τ		Ī	Ī	Τ	Τ	П	П		T	T		Γ			T	T		I	_	<u>₩</u>	13	30
	٦		J	Ţ	ł	i	Ì		۲	↧	_	1	Ī	Ť	T	П	Ħ		T	1					1	Ī			Ľ	Ľ	Z	1
		Т	٦	T	T	I	T		T	T		Γ	T	Ť	1	7	11	e	10	7	ce		Γ		1	T	I		Г		Т	1
IJΈ			1	Ī	Ţ		Ť		I	Ī	_	I	İ	Ī	ľ	Ш	ľ	G	Ľ	ï					1	Ī	1					1
20	Hz		50)		1	O)	2	00)		5	oc)		11	k		21	ć		5	k		1	a	k	2	0k	4	O





FF165K \$63.55



FOSTEX

Znom Re ohm Le@1kHz mΗ fs 40 Hz Qms 10.92 Qes 0.21 Qts 0.20 Mms 7.8 g mm/N Cms

- 6.5" FULL RANGE
- KENAF paper/ fiber composite cone
- Foam surround
- 94db sensitivity
- Frequency response from 40 Hz to 17 kHz
- Flange 166 mm
- Cut-out 144 mm
- Depth 73.7 mm

Sd	-	cm ²
BL	-	N/A
Vas	48.2	ltrs
Xmax	0.3	mm peak
VC Ø	-	mm
Sensitivity		
1W / 1m	94	dB
Nom. Power	70	W
Net weight	1.6	kg

FF225K \$98.10




Fostex

Znom	8	ohm
Re	6.3	ohm
Le@1kHz	-	mΗ
fs	38	Hz
Qms	3.06	
Qes	0.17	
Qts	0.16	
Mms	17.3	g
Cms	-	mm/N

- 8" FULL RANGE
- KENAF paper/ fiber composite cone
- Foam surround
- 96 db sensitivity
- Frequency response from 38 Hz to 14 kHz
- Flange 208 mm
- Cut-out 182 mm
- Depth 93 mm

Sd	-	cm ²
BL	-	N/A
Vas	79.41	Itrs
Xmax	0.3	mm peak
VC Ø	-	mm
Sensitivity		
1W / 1m	96	dB
Nom. Power	100	W
Net weight	3.72	kg



FW137

Znom

Le@1kHz

Re

fs

Qms

Qes

Qts

Mms

\$57.65

ohm

ohm

mΗ

Hz

0.07

3.58


0.57

0.50

11.7


55

• 5.5" **SHIELDED** WOOFER



- 87 db sensitivity
- Frequency response from 55 Hz to 8 kHz
- Flange 155 mm
- Cut-out 121 mm
- Depth 77 mm

Sd	0.0095	m²
BL	7.06	N/A
Vas	10.2	Itrs
Xmax	1	mm peak
VC Ø	30.4	mm
Sensitivity		
1W / 1m	87	dB
Nom. Power	75	W
Net weight	1.49	kg



FW167

Znom

Le@1kHz

Re

Qms

Qes

Qts

Mms

Cms

\$86.60



7.1

40

2.6

0.40

0.36

14.9

0.0011

.071

ohm

mΗ


Hz


mm/N

• 6.5" **SHIELDED** WOOFER

- Kenaf-Cellgaia Paper
- 89 db sensitivity
- Frequency response from 40 Hz to 6 kHz
- Flange 186 mm
- Cut-out 143 mm
- Depth 96.2 mm

Sd	0.0128	cm ²
BL	8.2	N/A
Vas	25.22	Itrs
Xmax	1.5	mm peak
VC Ø	35.5	mm
Sensitivity		
1W / 1m	89	dB
Nom. Power	100	W
Net weight	2.66	kg





FW108N \$113.00




COSTOX

Znom	8	ohm
Re	6.3	ohm
Le@1kHz	-	mΗ
fs	55	Hz
Qms	8.8	
Qes	0.27	
Qts	0.26	
Mms	6.9	g
Cms	-	mm/N

- 4" WIDE RANGE
- Hybrid pulp cone
- 8 ohm impedance
- 86 db sensitivity
- 1.6" Voice Coil
- · Frequency response from 55 Hz to 10 kHz
- Flange 128 mm
- Cut-out 100 mm
- Depth 72 mm

Sd	-	cm ²
BL	-	N/A
Vas	4.09	Itrs
Xmax	1.9	mm peak
VC Ø	40	mm
Sensitivity		
1W / 1m	86	dB
Nom. Power	50	W
Net weight	1.69	kg



FW208N

Znom

Le@1kHz

Re

Qms

Qes

Qts

Mms

Cms

\$166.15



5.8

29

13.2


0.21

0.20

40

- 8" WOOFER
 - Hybrid pulp cone
 - 8 ohm impedance
 - 90db sensitivity
 - 3" Voice Coil
 - Frequency response from 29 Hz to 5 kHz
 - Flange 230 mm
 - Cut-out 182 mm
 - Depth 94.8 mm

ohm	Sd	-	cm ²
ohm	BL	-	N/A
mΗ	Vas	43.4	ltrs
Hz	Xmax	6.5	mm pea
	VC Ø	81	mm
	Sensitivity		
	1W / 1m	90	dB
g	Nom. Power	100	W
mm/N	Net weight	4.62	k g



\$145.35 **FW168N**




FOSTEX

Znom	8	ohm
Re	5.9	ohm
Le@1kHz	-	mΗ
fs	40	Hz
Qms	15.67	
Qes	0.17	
Qts	0.16	
Mms	28	g
Cms	-	mm/N

• 6.5" WIDE RANGE

- Hybrid pulp cone
- 8 ohm impedance
- 89 db sensitivity
- 2.5" Voice Coil
- Frequency response from 40 Hz to 9 kHz
- Flange 180 mm
- Cut-out 148 mm
- Depth 87 mm

Sd	-	cm ²
BL	-	N/A
Vas	14.25	ltrs
Xmax	0.5	mm peak
VC Ø	65	mm
Sensitivity		
1W / 1m	89	dB
Nom. Power	100	W
Net weight	2.9	kg




FW405N

\$526.80

- 15" WOOFER
- Hybrid pulp cone, fiber + carbon, tree pulp
- 94.7db (2.83V@1M)
- 3" Voice Coil
- Frequency response from 27 Hz to 2.5 kHz
- Flange 395 mm 15.5"
 - Cut-out 350 mm 13.75"

peak

F	-ostex	• Depth 1	62 mm	6.4'
Znom	8 ohm	Sd	0.08	9m²
Re	6.89 ohm	BL	15.7	N/A
Le@1kHz	0.64 mH	Vas	392.5	ltrs
fs	27 Hz	Xmax	7.9	mm
Qms	6.76	VC Ø	80	mm
Qes	0.48	Sensitivity		
Qts	0.45	1W / 1m	92.5	dB
Mms	100.8 g	Nom. Power	150	W
Cms	0.344mm/N	Net weight	10.0	kg(
110				



W400A-HR \$2,672.70 • 15" Woofer



FOSTEX

8	ohm
6	ohm
2.64	mΗ
25	Hz
8.2	
0.32	
0.31	
130	g
0.33	mm/N
	6 2.64 25 8.2 0.32 0.31 130

- Rigid HR radial whizzy hybrid paper cone
- UDR tangential surround and spider
- 94db sensitivity
- 8 ohm impedance
- Flange 395mm
- Cut-out 350mm
- Depth 242mm

_		
Sd	820	cm ²
BL	19.5	N/A
Vas	310	Itrs
Xmax	5.5	mm peak
VC Ø	100	mm
Sensitivity		
1W / 1m	94	dB
Nom. Power	200	W
Net weight	47.18	lb

FW800N \$2,535.75



Znom	8	ohm
Re	6.8	ohm
Le@1kHz	-	mΗ
fs	18	Hz
Qms	8.5	
Qes	0.76	
Qts	0.69	
Mms	440	g
Cms	-	mm/N

110

100


• 31.5" SUPER WOOFER

- Hybrid pulp cone
- 96db sensitivity
- 8 ohm impedance Frequency response
- from 18 Hz to 1.5 kHz
- Flange 800mm
- Cut-out 748mm
- Depth 291mm

	FUSI	
ì	8	ohm
	6.8	ohm

Znom	8	ohm	
Re	6.8	ohm	
Le@1kHz	-	mΗ	
fs	18	Hz	
Qms	8.5		
Qes	0.76		
Qts	0.69		
Mms	440	g	
Cms	-	mm/N	

Sd	-	cm ²
BL	-	N/A
Vas	3201.1	Itrs
Xmax	2.3	mm peak
VC Ø		mm
Sensitivity		
1W / 1m	96	dB
Nom. Power	450	W
Net weight	45.65	lb



R80B

\$21.10



- 8 ohm Attenuator
- Attenuation 0 to 40 db or more
- Input 100 watts
- Flange 50 x 50 mm **SQUARE**
- Depth 71 mm

R82B

\$36.75



- 8 ohm Attenuator
- Attenuation 0 to 40 db or more
- Input 200 watts
- Flange 50 x 50 mm **SQUARE**
- Depth 89 mm





- Transformer type Attenuator
- Attenuation 0 to 21 db (1 db step)
- Input 100 watts
- Flange 88mm x 90mm
- Depth 170mm





H400 Wooden Horn and D1405 Horn Driver. Cutoff frequency of H400 is 455Hz, 1" throat.

Dimensions: 15.59" W x 4.72" T x 8.9" D - Natural Maple

H400 Horn is \$488.85 each (driver not included). D1405 Driver \$273.25 each, D1400 Driver \$469.00 each.

Cabinet plans available on our website. www.madisound.com/fostex.html





Fountek NeoCd3.0M 3" Ribbon

Ribbon Material Ribbon Mass Ribbon dimension

Impedance

Frequency Response

Sensitivity Power Handling

Suggested x-over frequency

SPL vs Freq

Weight **Price Each** Aluminum Alloy

18 mg

8mm x 60mm x 0.02mm

7 ohm

1,400Hz ~ 40,000Hz

95dB/2.83V/m

17W nominal 40W max


2500Hz @ 12dB 560g / 1.28lb

\$89.00



Features:

- Black metal face plate
- Aluminum Alloy ribbon.
- Super strong Neodymium magnet
- Frequency range from 1400Hz to over 40kHz
- Extremely thin foil (0.02mm) for a high degree of signal fidelity and broad frequency response.
- Low distortion and high power handling
- Flat impedance response



Fountek NeoCd2.0M 5" Ribbon

Ribbon Material Ribbon Mass

Ribbon dimension

Impedance

Frequency Response

Sensitivity

Power Handling

Suggested x-over frequency

Weight

Aluminum Alloy

34 mg

8mm x 120mm x 0.02mm

7 ohm


1.200Hz ~ 40.000 Hz

98dB/2.83V/m

20W nominal 50W max

2000Hz @ 12dB

1065g / 2.35lb



Features:

- Black metal face plate
- Aluminum Alloy ribbon.
- Super strong Neodymium magnet for high efficiency.
- Built-in impedance conversion transformer.
- Frequency range from 1200Hz to over 40kHz
- Extremely thin foil (0.02mm) for a high degree of signal fidelity and broad frequency
- Low distortion and high power handling.
- Flat impedance response



Warning:

The ribbon tweeters should always be used with a passive crossover!

Do not test without a capacitor.

Tweeters are repairable at Madisound.

Also available, the larger **Pro Sound** version NeoPro5i, see out web site for details. \$305 ea





Hi-Vi Research Loudspeakers



For complete specifications: www.swanspeaker.com

Node						I			T	I		
RTIL 110mm circular ribbon	Price Each	Hz	Liters	Ø		ďB			Qts	Fs Hz		
RTIL 10mm circular ribbon RTIL3 88mm x10zmm flange 6 10 92 2.5x3.0x40Rt New Noodymium nuguet RTICA 120mm round flange RTCA 120mm round flange 8 30 93 2.5x25x1tz Neodymium nuguet RT2R1 45mm x 16mm rectangular flange 8 30 93 3.4x20x1tz Neodymium nuguet RT2R2A 105mm x 176mm round flange 8 30 93 3.4x20x1tz Neodymium nuguet RT2R2A 105mm x 16mm rectangular flange 8 30 95 3.4x20x1tz Neodymium nuguet RT2R2A 105mm x 16mm rectangular flange 8 30 95 3.4x20x1tz Neodymium nuguet RT2R2A 105mm x 16mm rectangular flange 8 30 95 1.7x27x1tz Neodymium nuguet RT3R1 160mm x 220mm rectangular flange 8 30 95 1.7x27x1tz Neodymium nuguet RT3R1 160mm x 220mm rectangular flange 8 15 90 1.7x27x1tz Neodymium nuguet RT3R1 160mm round flange, shielded 5 1000 - 15 90 3.4x20x1tz Neodymium nuguet RT3R1 160mm round flange, shielded 5 1000 - 15 90 3.4x20x1tz 25 Shielded mapse 0R 116mm round flange, shielded 5 1000 - 15 90 3.4x20x1tz 25 Small flange RT3R2 454mm gaze with chamber 5 1000 - 15 90 3.4x20x1tz 25 Small flange, shielded RT 116mm round flange, shielded 5 1000 - 15 90 3.4x20x1tz 25 Small flange, shielded RT 116mm round flange, shielded 5 1000 - 15 90 3.4x20x1tz 25 Small flange, shielded RT 116mm round flange, shielded 5 1000 - 15 90 3.4x20x1tz 25 Small flange, shielded RT 116mm round flange, shielded 5 7000 - 16 90 3.4x20x1tz 25 Small flange, shielded RT 116mm round flange, shielded 5 7000 - 16 90 3.4x20x1tz 25 Small flange, shielded RT 116mm round flange, shielded 5 800 - 800 93 11412 25 Small flange, shielded RT 116mm round flange, shielded 5 700 - 800 92 1000 7000 7000 7000 7000 7000 7000 700	<u>'</u>					veeters	bbon Tw	amic Ri	Isodyn			
RTICA 120mm round flange	\$31.00	agnet	Neodymium m	1	3.5k-40kHz			-	-	-	4	RT1L 110mm circular ribbon
RT2II 45mm x 166mm recangular flange	\$41.00	agnet	Neodymium m	1	2.5k-30kHz	92	10	-	-	-	6	RT1.3 88mm x 102mm flange
RT2EA (16mm v 176mm ovalish flange	\$36.65	agnet	Neodymium m	1	4.5k-23kHz	94	15	-	-	-	5	RT1C-A 120mm round flange
RTZE-A 105mm x 176mm rovatish flange 8 - 30 93 31-40kHz Neodymium magnet	\$86.65	agnet	Neodymium m	1	2k-27kHz	93	30	-	-	-	8	RT2II 145mm x 166mm rectangular flange
RT2-Pro 220mm x 166mm rectangular flange	\$76.65	agnet	Neodymium m	1	3k-40kHz	93	30	-	-	-	8	RT2C-A 176mm round flange
Technology Part Technology Technolog	\$76.65	agnet	Neodymium m	1	3k-40kHz	93	30	-	-	-	8	RT2E-A 105mm x 176mm ovalish flange
Teaching Time Transport \$149.60	agnet	Neodymium m	1	2.3k-35kHz	99	30	-	-	-	8	RT2-Pro 220mm x 166mm rectangular flange	
Page Page	\$73.30	agnet	Neodymium m	ľ	1.7k-27kHz	95	30	-	-	-	8	RT8II 160mm x 220mm rectangular flange
SD1.1-A 116mm round flange, shielded						eters	me Twe	abric Do	1" F			
QIR 116mm round flange, shielded 6 1000 . . . 15 89 2.5k-20kHz 28 Shielded magnet TNZ8 46mm Ø x 99mm Top Mount 6 1300 . . . 15 90 3k-25kHz 28 Top mount, shielded TNZ8 46mm Ø x 99mm Top Mount 6 1300 . . . 15 90 3k-25kHz 25 Small flange, shielded KI 116mm round aluminum flange, shielded 5 800 . . 60 92 2.5k-25kHz 25 Aluminum face plate 2 2 2 2 2 2 2 2 2	\$5.00	ile dome	Small text	19	4k-20kHz	91/89	15	-	-	2000	4/8	T20 52mm round flange, 20mm dome
TN28 46mm Øx 99mm Top Mount	\$12.50	magnet	Shielded	25	3k-20kHz	91	15	-	-	1200	5	SD1.1-A 116mm round flange, shielded
TN25 54.5mm square with chamber 5 1500 - - 15 90 3k-21kHz 25 Aluminum face plate	\$14.80	magnet	Shielded	28	2.5k-20kHz	89	15	-	-	1000	6	Q1R 116mm round flange, shielded
No. 116mm round aluminum flange, shielded 5 800 5 92 2.5k-25kHz 25 Aluminum face plate 2"Fabric Dome Midranges 2"Fabric Dome Midrange 3"Fabric Dome	\$13.15	, shielded	Top mount	28	3k-25kHz	90	15	-	-	1300	6	TN28 46mm Ø x 99mm Top Mount
DMN-A 116mm round flange with chamber 5 800 - - 60 93 1kHz-10kHz 50 117mm deep bullet ch.	1 \$8.25	e, shielded	Small flange	25	3k-21kHz	90	15	-	-	1500	5	TN25 54.5mm square with chamber
DMN-A 116mm round flange with chamber 5 800 - - - 60 93 1kHz-10kHz 50 43mm Dr. rough dome Small Full Range Speakers Shielded Metal Alloy Cones Small Full Range Speakers Shielded Metal Alloy Cones Small Full Range Speakers Shielded Metal Alloy Cones Small Full Range Speakers Shielded Metal Alloy Cones Small Full Range Speakers Shielded Metal Alloy Cones Small Full Range Speakers Shielded Metal Range Shielded Shim Range Shiel	\$8.55	face plate	Aluminum	25	2.5k-25kHz	92	15	-	-	800	5	K1 116mm round aluminum flange, shielded
DMN-A 116mm round flange with chamber 5 800 - - - 60 93 1kHz-10kHz 50 43mm Dr. rough dome Small Full Range Speakers, Shielded, Metal Alloy Cones Small Full Range Speakers, Shielded, Metal Alloy Cones BIS 36mm square flange, copper color cone 8 220 0.56 0.04 1 79 250Hz-20kHz 19 6 cubic inch 270 AZS 53mm square flange, shielded, silver color 8 152 1.2 0.2 10 78 150Hz-15kHz 25 0.5 - 2 150 U2S 53mm square flange, shielded, aluminum 8 290 1.12 0.1 5 83 245Hz-20kHz 25 0.5 - 2 25 U2.SF-670mm square flange, shielded, aluminum 8 290 1.12 0.1 5 83 245Hz-20kHz 25 0.4 270 2						anges	ne Midra	bric Don	2" Fa			
Small Full Range Speakers, Shielded, Metal Alloy Cones	n. \$26.30	p bullet ch.	117mm deep	50	1kHz-10kHz			-	-	800	5	DMN-A 116mm round flange with chamber
B1S 36mm square flange, copper color cone	e \$23.70	ough dome	43mm D., ro	50	800Hz-10kHz	92	80	-	-	700	5	DMB-A 145mm round flange, shielded
B1S 36mm square flange, copper color cone					Alloy Cones	l, Metal	Shielded	eakers,	ange St	Full R	Small	
B2S 53mm square flange, shielded, copper color 8	\$5.00	270	6 cubic inch	19		1						
U2S 53mm square flange, shielded, aluminum	\$10.30	150	0.5 - 2	25	150Hz-15kHz	78	10	0.2	1.27	153	8	A2S 53mm square flange, shielded, silver color
U.2.5P-6 70mm square flange, shielded, alum. 6	\$10.95	150	0.5 - 2	25	150Hz-15kHz	78	10	0.2	1.2	152	8	B2S 53mm square flange, shielded, copper color
B3S 78mm square flange, shielded, copper color 8 80 0.93 1.6 15 80 80Hz-8kHz 20 0.5 - 2 80	\$10.30	245	0.5 - ~	25	245Hz-20kHz	83	5	0.1	1.12	290	8	U2S 53mm square flange, shielded, aluminum
B3N 90mm round flange, shielded, copper color 8 77 0.86 1.7 15 81 80Hz-8kHz 20 0.5-2 80	\$13.35	270	0.4	25	150Hz-20kHz	86	15	0.8	0.33	110	6	U2.5P-6 70nm square flange, shielded, alum.
"D" Series Mineral Filled Polypropylene Cones, Large Diameter Voice Coils 174mm round flange, cast frame 8 42 0.40 13.5 60 85 40Hz-4kHz 76 7/12 74/42 18.8 243mm round flange, cast frame 8 30 0.38 46.8 150 87 30Hz-2kHz 100 18/31 57/34 18.8+ 243mm round flange, cast frame 8 31 0.40 34.9 150 86 28Hz - 2kHz 100 - /28 - /33 18.8+ 243mm round flange, cast frame 8 20 0.40 211.1 150 87 35Hz-500Hz 100 90/- 35/- "F" Series Kevlar/Paper Cones, Cast Frames, Shielded Magnets, Yellow Cones "F" Series Kevlar/Paper Cones, Cast Frames, Shielded Magnets, Yellow Cones F5 154mm round flange, phase plug 8 52 0.33 7.3 35 86 65Hz-8kHz 25 2/4 111/63 F6 197mm round flange, phase plug 8 45 0.35 16.4 45 88 50Hz-5kHz 25 5/11 92/51 F8 217mm round flange, shielded magnet 8 36 0.39 36.9 60 87 38Hz-3kHz 25 17/30 65/38 "M" Series Magnesium/Aluminum Alloy Cones, Copper Color Cones M4N 116.5mm round flange, shielded magnet 8 47 0.35 11.3 35 87 65Hz-8kHz 25 3.5/6 95/59 M5a 140mm round flange, shielded magnet 8 47 0.35 11.3 35 87 65Hz-3kHz 25 3.5/6 95/59 M5a 140mm round flange, shielded magnet 8 46 0.38 13.6 45 88 50Hz-3kHz 25 3/5 100/63 M6a 174mm round flange 8 30 0.43 50.3 80 87 30Hz-3kHz 25 9/14 86/53 M8a 215mm round flange 8 30 0.43 50.3 80 87 30Hz-1.5kHz 25 9/14 86/53 M8a 215mm round flange, shielded, phase plug 8 57 0.49 8.6 35 86 50Hz-7kHz 25 8/9 82/52 W5 153mm round flange, shielded, phase plug 8 57 0.49 8.6 35 86 50Hz-7kHz 25 8/9 82/52 W6 179mm round flange, shielded 8 40 0.52 25.1 45 86 55Hz-3kHz 25 15/- 55/- Autosound Speakers CF140 4" coaxial speaker with grill 4 30 90 85Hz-23kHz	\$10.65	80	0.5 - 2	20	80Hz-8kHz	80	15	1.6	0.93	80	8	B3S 78mm square flange, shielded, copper color
D6.8 174mm round flange, cast frame	\$10.65	80	0.5 - 2	20	80Hz-8kHz	81	15	1.7	0.86	77	8	B3N 90mm round flange, shielded, copper color
D6.8 174mm round flange, cast frame			ls	ce Coi	e Diameter Voi	s, Larg	ne Cone	ypropyle	led Pol	ral Fil	s Mine	"D" Serie
D8.8+ 243mm round flange, cast frame	\$63.00	74 / 42										
D10.8 299mm round flange, cast frame	\$95.30	57 / 34	18 / 31	100	30Hz-2kHz	87	150	46.8	0.38	30	8	D8.8 243mm round flange, cast frame
"F" Series Kevlar/Paper Cones, Cast Frames, Shielded Magnets, Yellow Cones F5 154mm round flange, phase plug 8 52 0.33 7.3 35 86 65Hz-8kHz 25 2/4 111/63 F6 197mm round flange, phase plug 8 45 0.35 16.4 45 88 50Hz-5kHz 25 5/11 92/51 F8 217mm round flange, phase plug 8 45 0.35 16.4 45 88 50Hz-5kHz 25 5/11 92/51 F8 217mm round flange, phase plug 8 36 0.39 36.9 60 87 38Hz-3kHz 35 17/30 65/38 "M"" Series Magnesium/Aluminum Alloy Cones, Copper Color Cones M4N 116.5mm round flange, shielded magnet 8 69 1.08 4.3 30 82 69-4kHz 20 4/- 73/- M5n 144mm round flange, shielded magnet 8 47 0.35 11.3 35 87 65Hz-3kHz 25 3.5/6 95/59 M	\$123.00	- / 33	- / 28	100	28Hz - 2kHz	86	150	34.9	0.40	31	8	D8.8 + 243mm round flange, cast frame
F5 154mm round flange, phase plug	\$120.00	35 / -	90 / -	100	35Hz-500Hz	87	150	211.1	0.40	20	8	D10.8 299mm round flange, cast frame
F5 154mm round flange, phase plug			nes	ow Coi	Magnets, Yello	hielded	rames, S	, Cast Fi	r Cones	r/Pape	Kevlaı	"F" Series
The first of the	\$36.65	111 / 63										
"M" Series Magnesium/Aluminum Alloy Cones, Copper Color Cones M4N 116.5mm round flange, shielded magnet 8 69 1.08 4.3 30 82 69-4kHz 20 4/- 73/- M5N 144mm round flange, shielded magnet 8 47 0.35 11.3 35 87 53Hz-5kHz 25 3.5/6 95/59 M5a 140mm round flange, shielded magnet 8 48 0.34 11.2 35 87 65Hz-3kHz 25 3/5 100/63 M6a 174mm round flange, shielded magnet 8 46 0.38 13.6 45 88 50Hz-3kHz 25 9/14 86/53 M8a 215mm round flange 8 30 0.43 50.3 80 87 30Hz-2kHz 35 29/40 49/32 Polymer Cone speakers W5 153mm round flange, shielded, phase plug 8 57 0.49 8.6 35 86 50Hz-7kHz 25 8/9 82/52 W5 153mm round flange, shielded, phase plug 8 57 0.49	\$46.30	92 / 51	5 / 11	25	50Hz-5kHz	88	45	16.4	0.35	45	8	F6 197mm round flange, phase plug
M4N 116.5mm round flange, shielded magnet 8 69 1.08 4.3 30 82 69-4kHz 20 4/- 73/- M5N 144mm round flange, shielded magnet 8 47 0.35 11.3 35 87 53Hz-5kHz 25 3.5 / 6 95 / 59 M5a 140mm round flange, shielded magnet 8 48 0.34 11.2 35 87 65Hz-3kHz 25 3 / 5 100 / 63 M6a 174mm round flange, shielded magnet 8 46 0.38 13.6 45 88 50Hz-3kHz 25 9 / 14 86 / 53 M8a 215mm round flange 8 30 0.43 50.3 80 87 30Hz-2kHz 35 29 / 40 49 / 32 M12 313mm round flange 4 27 0.33 81.4 150 93 30Hz-1.5kHz 50 24 / 53 57 / 32 Polymer Cone speakers W5 153mm round flange, shielded, phase plug 8 57 <th< td=""><td>\$66.30</td><td>65 / 38</td><td>17 / 30</td><td>35</td><td>38Hz-3kHz</td><td>87</td><td>60</td><td>36.9</td><td>0.39</td><td>36</td><td>8</td><td>F8 217mm round flange</td></th<>	\$66.30	65 / 38	17 / 30	35	38Hz-3kHz	87	60	36.9	0.39	36	8	F8 217mm round flange
M5N 144mm round flange, shielded magnet 8 47 0.35 11.3 35 87 53Hz-5kHz 25 3.5/6 95/59 M5a 140mm round flange, shielded magnet 8 48 0.34 11.2 35 87 65Hz-3kHz 25 3/5 100/63 M6a 174mm round flange, shielded magnet 8 46 0.38 13.6 45 88 50Hz-3kHz 25 9/14 86/53 M8a 215mm round flange 8 30 0.43 50.3 80 87 30Hz-2kHz 35 29/40 49/32 M12 313mm round flange 4 27 0.33 81.4 150 93 30Hz-1.5kHz 50 24/53 57/32 Polymer Cone speakers W5 153mm round flange, shielded, phase plug 8 57 0.49 8.6 35 86 50Hz-7kHz 25 8/9 82/52 W6 179mm round flange, shielded, phase plug 8 40 0.52 <				ones	Copper Color C	Cones, C	Alloy C	uminum	sium/Al	Magne	eries N	"M" S
M5a 140mm round flange, shielded magnet 8 48 0.34 11.2 35 87 65Hz-3kHz 25 3/5 100/63 M6a 174mm round flange, shielded magnet 8 46 0.38 13.6 45 88 50Hz-3kHz 25 9/14 86/53 M8a 215mm round flange 8 30 0.43 50.3 80 87 30Hz-2kHz 35 29/40 49/32 M12 313mm round flange 4 27 0.33 81.4 150 93 30Hz-1.5kHz 50 24/53 57/32 Polymer Cone speakers W5 153mm round flange, shielded, phase plug 8 57 0.49 8.6 35 86 50Hz-7kHz 25 8/9 82/52 W6 179mm round flange, shielded 8 40 0.52 25.1 45 86 55Hz-3kHz 25 15/- 55/- Autosound Speakers CF140 4" coaxial speaker with grill <	\$17.65	73 / -	4 / -	20	69-4kHz	82	30	4.3	1.08	69	8	M4N 116.5mm round flange, shielded magnet
M6a 174mm round flange, shielded magnet 8 46 0.38 13.6 45 88 50Hz-3kHz 25 9/14 86/53 M8a 215mm round flange 8 30 0.43 50.3 80 87 30Hz-2kHz 35 29/40 49/32 M12 313mm round flange 4 27 0.33 81.4 150 93 30Hz-1.5kHz 50 24/53 57/32 Polymer Cone speakers W5 153mm round flange, shielded, phase plug 8 57 0.49 8.6 35 86 50Hz-7kHz 25 8/9 82/52 W6 179mm round flange, shielded 8 40 0.52 25.1 45 86 55Hz-3kHz 25 15/- 55/- Autosound Speakers CF140 4" coaxial speaker with grill 4 - - 30 90 85Hz-23kHz - - - CF160 6" coaxial speaker with grill	\$25.30	95 / 59	3.5 / 6	25	53Hz-5kHz	87	35	11.3	0.35	47	8	M5N 144mm round flange, shielded magnet
M8a 215mm round flange 8 30 0.43 50.3 80 87 30Hz-2kHz 35 29 / 40 49 / 32 M12 313mm round flange 4 27 0.33 81.4 150 93 30Hz-1.5kHz 50 24 / 53 57 / 32 Polymer Cone speakers W5 153mm round flange, shielded, phase plug 8 57 0.49 8.6 35 86 50Hz-7kHz 25 8 / 9 82 / 52 W6 179mm round flange, shielded 8 40 0.52 25.1 45 86 55Hz-3kHz 25 15 / - 55 / - Autosound Speakers CF140 4" coaxial speaker with grill 4 - - 30 90 85Hz-23kHz - - - CF150 5" coaxial speaker with grill 4 - - - 40 91 60Hz-23kHz - - - CF160 6" coaxial speaker	\$32.65	100 / 63	3/5	25	65Hz-3kHz	87	35	11.2	0.34	48	8	M5a 140mm round flange, shielded magnet
M12 313mm round flange	\$36.00	86 / 53	9 / 14	25	50Hz-3kHz	88	45	13.6	0.38	46	8	M6a 174mm round flange, shielded magnet
Polymer Cone speakers	\$53.30	49 / 32	29 / 40	35	30Hz-2kHz	87	80	50.3	0.43	30	8	M8a 215mm round flange
W5 153mm round flange, shielded, phase plug 8 57 0.49 8.6 35 86 50Hz-7kHz 25 8/9 82/52 W6 179mm round flange, shielded 8 40 0.52 25.1 45 86 55Hz-3kHz 25 15/- 55/- Autosound Speakers CF140 4" coaxial speaker with grill 4 - - 30 90 85Hz-23kHz - - - CF150 5" coaxial speaker with grill 4 - - - 40 91 60Hz-23kHz - - - CF160 6" coaxial speaker with grill 4 - - - 50 92 45Hz-23kHz - - - SP10 246mm round flange, subwoofer 4 34 0.57 17.1 500 84 40Hz-500Hz 76 32 40 In-ceiling and In-wall Speakers	\$133.60	57 / 32	24 / 53	50	30Hz-1.5kHz	93	150	81.4	0.33	27	4	M12 313mm round flange
W6 179mm round flange, shielded 8 40 0.52 25.1 45 86 55Hz-3kHz 25 15/- 55/- Autosound Speakers CF140 4" coaxial speaker with grill 4 - - 30 90 85Hz-23kHz - - - CF150 5" coaxial speaker with grill 4 - - 40 91 60Hz-23kHz - - - CF160 6" coaxial speaker with grill 4 - - - 50 92 45Hz-23kHz - - - SP10 246mm round flange, subwoofer 4 34 0.57 17.1 500 84 40Hz-500Hz 76 32 40 In-ceiling and In-wall Speakers						kers	ne speak	ymer Co	Pol			
Autosound Speakers CF140 4" coaxial speaker with grill 4	\$37.30	82 / 52	8/9	25	50Hz-7kHz					57	8	W5 153mm round flange, shielded, phase plug
CF140 4" coaxial speaker with grill 4 - - - 30 90 85Hz-23kHz - - - CF150 5" coaxial speaker with grill 4 - - - 40 91 60Hz-23kHz - - - CF160 6" coaxial speaker with grill 4 - - - 50 92 45Hz-23kHz - - - SP10 246mm round flange, subwoofer 4 34 0.57 17.1 500 84 40Hz-500Hz 76 32 40 In-ceiling and In-wall Speakers	\$46.60	55 / -	15 / -	25	55Hz-3kHz	86	45	25.1	0.52	40	8	W6 179mm round flange, shielded
CF150 5" coaxial speaker with grill 4 - - - 40 91 60Hz-23kHz - - - CF160 6" coaxial speaker with grill 4 - - - 50 92 45Hz-23kHz - - - SP10 246mm round flange, subwoofer 4 34 0.57 17.1 500 84 40Hz-500Hz 76 32 40 In-ceiling and In-wall Speakers						rs	Speake	utosound	A			
CF160 6" coaxial speaker with grill 4 - - 50 92 45Hz-23kHz - - SP10 246mm round flange, subwoofer 4 34 0.57 17.1 500 84 40Hz-500Hz 76 32 40 In-ceiling and In-wall Speakers	\$30.65	-	-	-	85Hz-23kHz	90	30	-	-	-	4	CF140 4" coaxial speaker with grill
SP10 246mm round flange, subwoofer 4 34 0.57 17.1 500 84 40Hz-500Hz 76 32 40 In-ceiling and In-wall Speakers	\$31.25	-	-	-	60Hz-23kHz	91	40	-	-	-	4	CF150 5" coaxial speaker with grill
In-ceiling and In-wall Speakers	\$34.50	-	-		45Hz-23kHz	92	50	-	-	-	4	CF160 6" coaxial speaker with grill
	\$168.50	40	32	76	40Hz-500Hz	84	500	17.1	0.57	34	4	SP10 246mm round flange, subwoofer
					<u> </u>	peakers	n-wall S	ng and Iı	In-ceili			
VAU-SE O in-centing, two channet - Lacti 0/0 Fotypropyretic cone 00 45 mz-20kmz Fot in-centing mounting	\$145.00	ounting	r in-ceiling mo	Fo	45Hz-20kHz	86	80				8/8	VX6-SC 6" in-ceiling, two channel - Each
VX5-LCR Center channel in-wall - Each 8 Polypropylene cone 80 87 55Hz-22kHz For in-wall mounting	\$145.00	ınting	or in-wall mou	F	55Hz-22kHz	87	80	ie cone	propyler	Poly	8	VX5-LCR Center channel in-wall - Each
VR5-LCR Center channel in-wall - Each 8 Nomex fiber cone 80 85 50Hz-20kHz For in-wall mounting	\$169.00	ınting	or in-wall mou	F	50Hz-20kHz	85	80	r cone	mex fibe	No	8	VR5-LCR Center channel in-wall - Each

RT1L Circular Ribbon • 110mm Round flange

4

5

88

ohm

Watts

dB

Neodymium

0.8 kg

Znom

Nom. Power


2.83V / 1m

Magnet System

Sensitivity

Weight

- Frequency range 3.5k-40kHz
- Isodynamic Ribbon
- Neodymium magnet
- Magnetically shielded
- Flat impedance curve



RT1.3 Ribbon



6

Znom Nom. Power Sensitivity 2.83V / 1m Magnet System

Weight

Watts 10 92 dB Neodymium


0.2 kg

ohm


On axis and 30°

• 88 x 102mm flange

- Frequency range 2.5k-30kHz
- Isodynamic Ribbon
- Neodymium magnet
- Magnetically shielded
- Flat Impedance curve







RT2II Ribbon




Znom 8 ohm Nom. Power 30 Watts Sensitivity 2.83V / 1m 93 dΒ Magnet System Neodymium Weight 0.87 kg

- 160 x 186mm flange
- Frequency range 2k-27kHz

off-axis

- Isodynamic Ribbon
- Neodymium magnet
- · Magnetically shielded
- Flat Impedance curve



RT1C-A Ribbon



Znom 5 ohm Nom. Power 15 Watts Sensitivity dΒ 2.83V / 1m 94

Neodymium

0.2 kg

Magnet System


Weight

• Frequency range 4.5k-23kHz

• Isodynamic Ribbon

• 120mm Round flange

- Neodymium magnet
- · Magnetically shielded
- Flat impedance curve



On axis and 30° off-axis


off-axis On axis and 30°

RT2C-A Ribbon



Znom Sensitivity 8 2.83V / 1m ohm 93 dΒ Nom. Power 30 Magnet Sys-Watts tem

- 176mm Round flange
- Frequency range 3k-40kHz
- Isodynamic Ribbon
- Neodymium magnet
- · Magnetically shielded
- Flat Impedance curve




Znom 8 ohm Nom. Power 30 Watts


ø176

RT2E-A Ribbon

Sensitivity 2.83V / 1m 93 dΒ Magnet System Neodymium

- 105mm x 176mm flange
- Frequency range 3k-40kHz
- Isodynamic Ribbon
- Neodymium magnet
- Magnetically shielded
- Flat Impedance curve





On axis and 30° off-axis

RT2-Pro Ribbon

Znom

Nom. Power

Magnet System

Sensitivity 2.83V / 1m

Weight



8

30

99

ohm

Watts

dB

Neodymium

1.06 kg


- 220 x 166mm flange
- Frequency range 2.3k-35kHz
- Isodynamic Ribbon
- Neodymium magnet
- · Magnetically shielded
- Flat Impedance curve

RT8II Ribbon




Znom 6 ohm Watts Nom. Power 30 Sensitivity 2.83V / 1m 95 dB Neodymium Magnet System Weight 1.1 kg

- 160 x 220mm flange
- Frequency range 1.7k-27kHz
- Isodynamic Ribbon
- Neodymium magnet
- · Magnetically shielded
- Flat Impedance curve







T20-8 Tweeter



- 20mm fabric dome
- 53mm flange
- 36mm cut out
- 10mm depth
- 4 or 8 ohm


Znom	8	ohm
fs	2000	Hz
Nom. Power	15	W
Re	6.8	ohm
VC Ø	20	mm
Sensitivity		
2.83V / 1m	89	dB

SD1.1-A Tweeter





- Fabric dome tweeter
- 116mm flange
- Shielded magnet

B			
	Znom	5	ohm
	fs	1200	Hz
	Nom. Power	15	W
	Re	4.6	ohm
	VC Ø	25	mm
	Sensitivity		
	2.83V / 1m	91	dB
	Weight	1.0	kg









Q1R Tweeter



- Fabric dome tweeter
- 116mm flange
- · Shielded magnet


Znom	6	ohm
fs	1000	Hz
Nom. Power	89	W
Re	5.3	ohm
VC Ø	28	mm
Sensitivity		
2.83V / 1m	89	dB
Weight	0.8	kg

TN28 Tweeter



- Top Mount
- Fabric dome tweeter
- Shielded magnet

	Znom	6	ohm
THE RESERVE	fs	1300	Hz
	Nom. Power	15	W
	Re	5.1	ohm
	VC Ø	28	mm
	Sensitivity		
	2.83V / 1m	90	dB
	Weight	0.14	1 ka



TN25 Tweeter



- Fabric dome tweeter
- 54.5mm square flange
- Shielded, w/ chamber


Znom	5	ohm
fs	1500	Hz
Nom. Power	15	W
Re	4.6	ohm
VC Ø	25	mm
Sensitivity		
2.83V / 1m	90	dB
Weight	0.09 kg	


K1 Tweeter



- Fabric dome tweeter
- 116mm round flange
- Shielded magnet

Znom	5	ohm
fs	800	Hz
Nom. Power	15	W
Re	4.6	ohm
VC Ø	25	mm
Sensitivity		
2.83V / 1m	92	dΒ
Weight	0.9	kg





DMN-A Midrange



- 2" fabric dome
- Chambered back
- Shielded magnet
- 116mm round flange 5 Znom ohm 800 Hz fs Nom. Power 60 W Re 4.3 ohm 50 VC Ø mm Sensitivity 2.83V / 1m 93 dΒ Weight 0.4 kg

DMB-A Midrange




- 2" textured fabric dome
- Shielded magnet
- 145mm round flange

Znom	5	ohm
fs	700	Hz
Nom. Power	80	W
Re	4.3	ohm
VC Ø	50	mm
Sensitivity		
2.83V / 1m	92	dB
Weight	1.6	kg



																	Deg
-			*		-	9 9			10	2		*			1.9	- 83	-
	38	30	*	-		8 B	18	52	32	25	3	2		-	19	237	
	-		1	0	V		- :		-		-			Н			
-	-	1	1	-			1 22 7	(b)		-	-	-		H		- 50	-
-	-		Ė				-			-	-	-		1		250	
_	-	-		1		e e		-	-			*			87	53	
3-1	25	100	-	1	V		324	82	84	200	-33		-	H	692	289	1
See.	:32	9	93		ÿ.		92	192	×	29	0	Q.	4.	-	83.	28	100
	_													Н			
-	-	-	-	-		15			-		-	-		- 1			- 1
-	-	-				(d) (4)	- SW 55	100				-		- +	100	4.5	
	-	-	-	-	-	- (+)	154	(24)	1.04	-	-	+	-		. 55-	- 53	
-	-	-		-		(I) (F)	100			-		-			2.3	-:	



B1S Full Range



8

2

2.57

0.68

0.56

1057

0.5 g

220

ohm

Hz

W

 $\mu M/N$

6.5 ohm

Znom

Nom. Power

fs

Re

Qms

Qes

Qts

Mms

Cms

- cone full range (copper)
- Neodymium magnet
- · Foam surround
- Frequency range 270Hz-20kHz
- 36mm square flange

5

19

79

Rec. 6 cubic inch sealed, f3 270

cm²

0.95 mm peak

mm

dΒ

0.03 kg

2.3 Tm

0.04 ltrs

- 32.5mm cut out
- 13.1mm depth

Sd

BL

Vas

Xmax

VC Ø

Weight

On axis and 30° off-axis

Sensitivity

2.83V / 1m


• 1" magnesium/aluminum A2S Full Range



Znom	8 ohm
fs	153 Hz
Nom. Power	10 W
Re	6.5 ohm
Qms	7.33
Qes	1.53
Qts	1.27
Mms	1.5 g
Cms	707 μM/N
dB spl	

- 2" magnesium/aluminum cone full range (copper)
- Neodymium magnet
- · Rubber surround
- Frequency range 150Hz-15kHz
- Shielded magnet
- 53mm square flange
- 48mm cut out
- 30.5mm depth

Sd	13	cm ²				
BL	2.5	Tm				
Vas	0.2	Itrs				
Xmax	1.5	mm peak				
VC Ø	25	mm				
Sensitivity						
2.83V / 1m	78	dB				
Weight 0.12 kg						
Rec. 0.5-5 liters sealed, f3 150						
		Deer				




B2S Full Range



Znom 8 ohm fs 152 Hz Nom. Power 10 W Re 6.5 ohm Qms 5.69 Qes 1.53 Qts 1.20 Mms 1.6 g Cms 689 $\mu M/N$

- cone full range (copper)
- Neodymium magnet
- · Rubber surround
- Frequency range 150Hz-15kHz
- · Shielded magnet
- 53mm square flange
- 48mm cut out
- 30.5mm depth

BL 2.5 Tm Vas 0.2 ltrs Xmax 1.5 mm pea VC Ø 25 mm Sensitivity 2.83V / 1m 78 dB Weight 0.12 kg Rec. 0.5-5 liters sealed, f3 150								
Xmax 1.5 mm pea VC Ø 25 mm Sensitivity 2.83V / 1m 78 dB Weight 0.12 kg								
VC Ø 25 mm Sensitivity 2.83V / 1m 78 dB Weight 0.12 kg								
Sensitivity 2.83V / 1m 78 dB Weight 0.12 kg	eak							
2.83V / 1m 78 dB Weight 0.12 kg								
Weight 0.12 kg								
8								
Rec. 0.5-5 liters sealed, f3 150								
	Rec. 0.5-5 liters sealed, f3 150							
Deg 18	180							
13	135							




• 2" magnesium/aluminum U2S Full Range



Znom	8 ohm
fs	290 Hz
Nom. Power	5 W
Re	6.5 ohm
Qms	5.17
Qes	1.43
Qts	1.12
Mms	1.2 g
Cms	261 μM/N

- 2" coated aluminum alloy cone full range
- Neodymium magnet
- Transparent surround
- Frequency range 245Hz-20kHz
- Shielded magnet
- 53mm square flange
- 48mm cut out
- 30.5mm depth

Sa	13	cm ⁻
BL	3.0	Tm
Vas	0.1	Itrs
Xmax	1.8	mm peak
VC Ø	25	mm
Sensitivity		
2.83V / 1m	83	dB
Weight	0.1	kg
Rec. Sealed/Oper	n baffle	? 245Hz?



U2.5P-6 Full Range



- 2.5" coated aluminum alloy cone full range
- Neodymium magnet
- Transparent surround
- Frequency range 110Hz-20kHz
- Shielded magnet
- 70mm square flange
- 68mm cut out
- 35mm depth

Znom	6	ohm	Sd	21	cm ²
fs	110	Hz	BL	3.3	Tm
Nom. Power	15	W	Vas	0.8	ltrs
Re	5.2	ohm	Xmax	1.0	mm peak
Qms	1.5		VC Ø	25	mm
Qes	0.43	3	Sensitivity		
Qts	0.33	3	2.83V / 1m	86	dB
Mms	1.69	9 g	Weight	0.14	l kg
Cms	1385	$\mu M/N$	Rec. 0.4 liter seale	ed 270	Hz



B3S Full Range




Znom	8	ohm
fs	80	Hz
Nom. Power	15	W
Re	6.5	ohm
Qms	4.29)
Qes	1.19)
Qts	0.93	3
Mms	3.1	g
Cms	1260	μ M/N
dB spl		

•	3" magnesium/aluminum
	cone full range

- Copper color
- Shielded magnet
- Rubber surround
- Frequency range 80Hz-8kHz
- 78mm square flange
- 70mm cut out
- 53mm depth

Sd	30	cm ²			
BL	2.9	Tm			
Vas	1.6	ltrs			
Xmax	3.0	mm peak			
VC Ø	20	mm			
Sensitivity					
2.83V / 1m	80	dB			
Weight	ight 0.53 kg				
Rec box 0.5-5 liters sealed f3.80					




B3N Full Range



- cone full range
- Copper color
- Shielded magnet
- Rubber surround
- Frequency range 80Hz-8kHz
- 90mm round flange
- 71mm cut out
- 53mm depth

			•
Znom	8 ohm	Sd	30 cm ²
fs	77 Hz	BL	3.1 Tm
Nom. Power	15 W	Vas	1.7 ltrs
Re	6.5 ohm	Xmax	3.0 mm peak
Qms	4.48	VC Ø	20 mm
Qes	1.07	Sensitivity	
Qts	0.86	2.83V / 1m	81 dB
Mms	3.2 g	Weight	0.55 kg
Cms	1320 μM/N	Rec.box 0.5-5 li	iters sealed, f3 80
dB spl			Deg



• 3" magnesium/aluminum M4N Full Range




Znom	8	ohm
fs	69	Hz
Nom. Power	15	W
Re	6.5	ohm
Qms	5.39)
Qes	1.35	5
Qts	1.08	3
Mms	4.8	g
Cms	1080	μM/N

peak

•	4" magnesium/aluminum
	cone full range

- Copper color
- Shielded magnet
- Rubber surround
- Frequency range 70Hz-4kHz
- 116.5mm round flange
- 93mm cut out
- 63mm depth

Sd	53	cm ⁻
BL	3.1	Tm
Vas	4.3	Itrs
Xmax	3.0	mm peak
VC Ø	20	mm
Sensitivity		
2.83V / 1m	82	dB
Weight	0.60) kg
Rec.box 4 liters s	ealed,	f3 73



M5N Midbass



Znom ohm 8 fs 47 Hz Nom. Power 35 Re 6.5 ohm Qms 6.51 0.37 Qes Qts 0.35 10.7 g Mms $\mu M/N$

1051

Cms

Znom

Nom. Power

fs

Re Qms

Qes

Ots

- 5" Magnesium/ Aluminum alloy cone
- Stamped steel frame
- · Rubber surround
- · Shielded magnet
- Frequency response 53Hz-5kHz
- 144mm flange
- 115mm cut out
- 91mm depth

Sd 87 cm ²	Z
BL 7.5 Tm	f
Vas 11.3 ltrs	١
Xmax 2.7 mm peak	F
VC Ø 25 mm	(
Sensitivity	(
2.83V / 1m 87 dB	(
Weight 1.5 kg	Ν
Rec. Box: 6 ltrs, 1"Ø x 2.3" F3 59	(
Deg 180	




D6.8 Midbass

	Znom	8	ohm
	fs	42	Hz
	Nom. Power	60	W
k	Re	6.5	ohm
	Qms	3.81	
	Qes	0.45	5
	Qts	0.40)
	Mms	21.8	g
	Cms	652	μ M/N
3	100 dB spl		

•	7" mineral filled
	polypropylene cone

- · Cast frame
- Rubber surround
- 3" Voice coil
- Frequency range 40Hz-4kHz
- 174mm flange
- 136mm cut out
- 76mm depth

Sd	121	cm ²
BL	9.5	Tm
Vas	13.5	Itrs
Xmax	4.8	mm peak
VC Ø	76	mm
Sensitivity		
2.83V / 1m	85	dB
Weight	1.9	kg
Rec. box 12 ltrs,	1.5"Ø x	5", F3 42
		Deg 180



D8.8 Woofer



8

30

150

ohm

Hz

W

6.5 ohm

1.97

0.46

0.38

- 9" mineral filled polypropylene cone
- Cast frame
- Foam surround
- 4" Voice Coil
- Frequency range 30Hz-2kHz
- 243mm flange
- 202mm cut out

241

100

87

cm²

8.3 mm peak

mm

dB

11.7 Tm

46.8 ltrs

• 96.5mm depth

Sd

BL

Vas

Xmax

VC Ø

Sensitivity

2.83V / 1m

20 L		Fre	-	-	1	10	-	H.	H	- 3	- 31	L	Ŀ	99		П	1	1 3	13	5	Ŀ	E	- 1	Η	- 33	- 11	401	l_,,
**		13	:	1	:	:		: :	I‡	:	- 50	1	:	:	: :	П	31	- 3	:	1:	ŀ	:	: :	H			::	
30	1		i	1.1.5		:		:	ŧ	1	:	:	:	:	:		1	i	:	:	1	:	-	1		i	V	;
40	(8)	+	2	-	-	1	-		1			-	-			11	-	- 10	-	1:	+	H	-	#	V		1	
~_	1	1	1	100				:	1	:	100	:	:	:	:			1	:	1	1	:	1	1	150	1	17	
50	1	1		1,533		:	1111		Ħ	ì		:	1	:					1	1	1:			1	S	-		_
60			:		1	:	-		Or	n ax	is	an	d	3	O,	11	off-ax	kis	1	1.	1	N	1	H	13	0	::	
70	1		:	:	1	t	:	i i	Ħ	9	:	1	t	Н		Ħ	:	1	1	1	h	H	-	Ħ	- 10	1	::	1
	1	1		1111					Ħ	-	1	:	1	1				1	1	1	1	1		Ħ	- 1		1	1
80				-				:	Ŧ	1	1	:	Ŀ	1		M		11		1	Ŀ	1		Ħ		1	::	1
90	-	+		-	1	Ė			1		-		0			Н	1	1	-	1	t	H	-	H	-	-		1
	:	1	:	11.0		:			Ħ	1	1	1	1				1	1	3	1	1	ŀ		Ħ	1	:	::	-
00 L	sp	1	_		_	_	_						_	_	_				_	_	_	_	_			8	Des	
ns						5	4	5		μΜ	/N					ı	Rec.	Box:	3	1	ltr	S,	, 2	2"@	ў x 5	.75	"	F3
ns							5	0.	9	g							Weigl								3.5	_		


Midbass



_	_					
Znom	8	ohm				
fs	52	Hz				
Nom. Power	35	W				
Re	6.5	ohm				
Qms	4.31	l				
Qes	0.36					
Qts	0.33	3				
Mms	11.5	g				
Cms	828	$\mu M/N$				

- 5.5" Kevlar®/Paper cone
- · Phase plug
- Cast frame
- · Rubber surround
- · Shielded magnet
- Frequency range 65Hz-8kHz
- 154mm flange
- 116.5mm cut out
- 89mm depth

Sd	79	cm
BL	8.3	Tm
Vas	7.3	ltrs
Xmax	2.7	mm peak
VC Ø	25	mm
Sensitivity		
2.83V / 1m	86	dB
Weight	1.6	kg
Rec. Box: 4 ltrs,	1"Ø x 4"	F3 63




F6 Midbass



- 7" Kevlar®/Paper cone
- Phase plug
- Cast frame
- Rubber surround
- Shielded magnet
- Frequency response 50Hz-5kHz
- 197mm flange
- 149mm cut out
- 92mm depth

Znom	8 0	ohm	Sd	139	cm ²	
fs	45 H	Ηz	BL	9.	0 Tm	
Nom. Power	45 \	Ν	Vas	16.	4 Itrs	
Re	6.5	ohm	Xmax	4.	3 mm p	eak
Qms	3.91		VC Ø	25	mm	
Qes	0.38		Sensitivity			
Qts	0.35		2.83V / 1m	n 88	dB	
Mms	18.3	9	Weight	2.	1 kg	
Cms	658 µ	ιM/N	Rec Box: 11	trs, 1.5"Ø	x3.75" F	F3 51
100 dB spl			 -1-14	1-1-1-1-1	De	186




F8 Woofer



- 8" Kevlar®/Paper cone
- · Cast frame
- Rubber surround
- Shielded magnet
- Frequency response 38Hz-3kHz
- 239mm flange
- 187mm cut out
- 106mm depth

Znom	8	ohm	Sd	214	cm ²
fs	36	Hz	BL	10.1	Tm
Nom. Power	60	W	Vas	36.9	Itrs
Re	6.5	ohm	Xmax	5.0	mm peak
Qms	1.73	3	VC Ø	35	mm
Qes	0.51		Sensitivity		
Qts	0.39)	2.83V / 1m	87	dB
Mms	35.3	g	Weight	2.9	kg
Cms	567	μ M/N	Rec. Box: 30 ltrs	, 2"Ø x 4	I.3" F3 38
166 dB spl					Deg 186



M5a Midbass

Znom

Re

Qms

Qes

Qts

Mms

Cms

Nom. Power



8

48

35 W

ohm

Hz

6.5 ohm

6.71


0.36

0.34 10.8 g

1038

- 5" Magnesium/ Aluminum alloy cone
- · Cast frame
- Rubber surround
- Shielded magnet
- Frequency response 54Hz-8kHz
- 140mm flange
- 116mm cut out
- 89.2mm depth

Sd	87	cm ²
BL	7.6	Tm
Vas	11.2	Itrs
Xmax	2.7	mm peak
VC Ø	25	mm
Sensitivity		
2.83V / 1m	87	dB
Weight	1.6	kg
Rec. Box: 5 ltrs,	1"Ø x 2.	6" F3 63
		-




M6a Midbass



8	ohm
46	Hz
45	W
6.5	ohm
3.94	1
0.42	2
0.38	3
13.6	g
874	$\mu \text{M/N}$
	46 45 6.5 3.94 0.42 0.38 13.6

- 7" Magnesium / Aluminum alloy cone
- Cast frame
- Rubber surround
- · Shielded magnet
- Frequency response 50Hz-5kHz
- 174mm flange
- 148mm cut out
- 95mm depth

Sd	139	cm ²
BL	7.8	Tm
Vas	21.9	ltrs
Xmax	4.3	mm peak
VC Ø	25	mm
Sensitivity		
2.83V / 1m	88	dB
Weight	2.0	kg
Rec. Box: 14 ltrs,	2"Ø x 5	" F3 53
		Deg



M8a Woofer

Znom

Nom. Power

fs

Re

Qms

Qes

Qts

Mms

Cms



8

30

80

ohm

Hz

W

 μ M/N

6.5 ohm

4.90

0.47

0.43 35.1 g

773

- 8" Magnesium / Aluminum alloy cone
- Cast frame
- · Rubber surround
- Copper color cone
- Frequency response 30Hz-2kHz
- 215mm flange
- 187mm cut out
- 99mm depth

Sd	214	cm ²
BL	9.6	Tm
Vas	50.3	Itrs
Xmax	5.8	mm peak
VC Ø	35	mm
Sensitivity		
2.83V / 1m	87	dB
Weight	2.5	kg
Rec. Box: 40 ltrs,	2" x 5.1	" F3 32
H	111	Deg 189

M12 Woofer



	•	Rubber surround
	•	4 ohm
7	•	Frequency response

• 12" Magnesium /


• Cast frame

Aluminum alloy cone

- 30Hz-1.5kHz
- 336mm flange • 280mm cut out

•	143mm	depth	
---	-------	-------	--

4	ohm	Sd	531	cm ²
27	Hz	BL	16.8	Tm
150	W	Vas	81.4	ltrs
3.4	ohm	Xmax	7.2	mm peak
4.87	7	VC Ø	50	mm
0.36	3	Sensitivity		
0.33	3	2.83V / 1m	93	dB
161.5	g	Weight	8.0	kg
203.2	μM/N	Rec Box: 53 liters	, 3"Ø x	7.5", F3
	·	800 M	-2000	Deg 100



Znom

Re

Qms

Qes

Qts

Mms

Cms

Nom. Power

W5 Midbass



8 ohm Znom 57 Hz Nom. Power 35 W Re 6.5 ohm Qms 3.17 Qes 0.58 Qts 0.49 9.8 g Mms $\mu M/N$ Cms 802

- 5" Super-PPF polymer film cone
- · Cast frame, Shielded
- · Rubber surround
- Phase plug
- Frequency response 50Hz-7kHz
- 153mm flange
- 115mm cut out
- 94mm depth

	•	
Sd	87	cm ²
BL	6.2	Tm
Vas	8.6	Itrs
Xmax	2.5	mm peak
VC Ø	25	mm
Sensitivity		
2.83V / 1m	86	dB
Weight	1.8	kg
Rec. Box: 9 ltr	s, 1.5"Ø x	3.25" F3
	.1.1.1.14	Deg 180


W6 Midbass



- 7" Super-PPF polymer film cone
- · Cast frame
- Shielded magnet
- Frequency response 55Hz-3kHz
- 197mm frame
- 149mm cut out
- 94mm depth

	87	cm ²	Znom	8	ohm
	6.2	Tm	fs	40	Hz
	8.6	Itrs	Nom. Power	45	W
	2.5	mm peak	Re	6.5	ohm
	25	mm	Qms	3.04	ŀ
tivity			Qes	0.64	ļ
3V / 1m	86	dB	Qts	0.52	2
nt	1.8	kg	Mms	17.1	g
3ox: 9 Itrs, 1.	.5"Ø x	3.25" F3	Cms	913	μ M/N
		Deg 180	100 dB spl		

Sa	139	cm
BL	6.7	Tm
Vas	25.1	ltrs
Xmax	4.3	mm peak
VC Ø	25	mm
Sensitivity		
2.83V / 1m	90	dB
Weight	2.5	kg
Rec. Box: 15 ltrs	sealed,	F3 55
		Dog



CF150 5.25" Autosound Coaxial

- Rigid ceramic polypropylene talc cone
- Ferrofluid cooled fabric dome tweeter
- Decorative rubber boot covers the woofer magnet
- Decorative grill included, tweeter grill (also removable)
- Impedance: 4 ohm
- Frequency response: 60Hz to 23kHz
- Nominal power handling: 40W
- Sensitivity: 91dB · Internal crossover
- 138mm frame diameter (5.43")
- 116mm cut out hole size (4.57")
- 62mm depth (2.44")
- Grill dimensions: 158mm x 22mm (6.22" x 0.87")

CF160 6" Autosound Coaxial

- Rigid ceramic polypropylene talc cone
- Ferrofluid cooled fabric dome tweeter
- Decorative rubber boot covers the woofer magnet
- Decorative grill included, tweeter grill (also removable)
- Impedance: 4 ohm
- Frequency response: 45Hz to 23kHz
- Nominal power handling: 50W
- Sensitivity: 92dB
- Internal crossover
- 156.5mm frame diameter (6.16")
- 144mm cut out hole size (5.67")
- 65mm depth (2.56")
- Grill dimensions: 172.5mm x 22mm (6.79" x 0.87")



SP10 Subwoofer



• 10" Subwoofer with double layer mica film cone



VX6-SC 6" 2-way Stereo In-Ceiling - Each



- Dual 19mm fabric dome tweeters with ferrofluid cooling.
- Poly cone woofer with rubber surround, bumped back plate and vented pole piece.
- Level control switch for each tweeter

For Car: 15Hz in 1.1 cubic foot sealed box (with +6dB of cabin gain)

Znom fs Nom. Power Re Qms Qes Qts Mms Cms	4 ohm 34 Hz 500 W 3.4 ohm 4.83 0.65 0.57 235 g 91.4 μΜ/N	Sd BL Vas Xmax VC Ø Sensitivity 2.83V / 1m Weight	363 cm² 16.6 Tm 17.1 ltrs 15.5 mm pk 76 mm 84 dB 13.0 kg
dB			
6 0	wy		
-6	TY M		
-12			
-18			
-24			
-30			
-36			
5 Hz 10	50 100	500 1 K	5 K 10 K 20 K
	Simulate	ed car response	

- Crossover is 6dB on the woofer and 12dB on the tweeter with polymide auto protective switches on the tweeters.
- Tweeters crossover uses a high grade polypropylene capacitor for clearer high frequency response.
- Gold plated push terminals
- Rust proof hardware
- Rust proof aluminum grill, painted white.
- · Paint mask included



- 8.07" cut out hole, cut out template included
- Frame and grills are white

LCY SPLIT RIBBON TWEETERS

The LCY Ribbon tweeter is based on technology well proven by audio pioneers for over half a century but is innovatively designed to satisfy the sophisticated demands of the digital era.

The LCY has a unique design employing twin ribbons of half the length of conventional ribbons in order to control vertical plane dispersion. Thus it reproduces both vertically and horizontally as effectively as voice-coil operated dome tweeters but with the accuracy, elegance and refined timbres of ribbon-tweeter technology. Magnetic flux density is enhanced by the use of our own neodymium magnet system and a sophisticated transformer with parallel multi-wiring oxygen free copper (OFC) has been adopted for superior frequency and power handling and optimal size.



LCY-110

Frequency Response: 2kHz-60kHz Sensitivity: 92dB (2.83V@1M) Nominal Impedance: 8Ω Magnet Type: Neodymium Ribbon Effective Area: 740 mm^2 Ribbon Thickness: 0.006 mm

Ribbon Length: 38mm Nominal Power Handling: 150W


Weight: 1.05kg

Flange Diameter: 110mm

Cut Out: 86mm x 58mm or 99mm Ø

Depth: 86mm

Flange Thickness: 10mm **Price Each: \$199.00**





LCY-108

Frequency Response: 2.2kHz-60kHz Sensitivity: 92dB (2.83V@1M)

Nominal Impedance: 8 Ω Magnet Type: Neodymium Ribbon Effective Area: 740 mm² Ribbon Thickness: 0.006mm Ribbon Length: 38mm

Nominal Power Handling: 150W


Weight: 0.95kg

Flange: 108mm x 108mm

Cut Out: 86mm x 58mm or 99mm Ø

Depth: 86mm

Flange Thickness: 5mm **Price Each: \$184.00**



LCY-108 (2.83V / 1M)



LCY-130

Frequency Response: 1.8kHz-60kHz Sensitivity: 92dB (2.83V@1M)

Nominal Impedance: 8 Ω
Magnet Type: Neodymium

Ribbon Effective Area: 740 mm² Ribbon Thickness: 0.006mm

Ribbon Length: 38mm

Nominal Power Handling: 150W

Weight: 1.15kg

Flange Diameter: 130mm


Cut Out: 86mm x 58mm or 99mm Ø

Depth: 90.5mm

Flange Thickness: 7.5mm


Price Each: \$210.00





LCY SPLIT RIBBON SUPER TWEETERS

Model LCY-100K has been designed specifically bearing in mind the audiophile who already owns a good speaker system. Simple connection of the LCY-100K externally gives immediate enhancement of ultra-high frequencies and brings an already good speaker system into the 21st Century. The units are elegantly designed with integrated stands and will enhance the appearance as well as the performance of any system. Each pair is packed in a rigid aluminium case with handle for secure transportation and shipping.



LCY-100K

Frequency Response: 10kHz or 13kHz -100kHz Crossover: 18dB/oct built-in switchable high pass filter

Sensitivity: (2.83V@1M)

10kHz, 96dB (Switched to the right when viewed from the rear) 13kHz, 92dB (Switched to the left when viewed from the rear) Crossover: Philips MKP Polypropylene capacitors and OFC inductor.


Nominal Impedance: 8Ω Magnet Type: Neodymium Ribbon Effective Area: 375 mm^2 Ribbon Thickness: 0.006 mm Ribbon Length: 25 mm


Nominal Power Handling: 300W


Tweeter Diameter: 84mm Depth: 136mm

Price Each: \$260.00











Viewed from the rear of the LCY-100K super tweeter. When the switch is placed to the left, the unit response will be according to the black line. When the switch is placed to the right, the unit response will be according to the red line.

LCY-K100

Frequency Response: 7kHz-100kHz Sensitivity: 95dB (2.83V@1M) Nominal Impedance: 8 Ω Magnet Type: Neodymium

Ribbon Effective Area: 375 mm² Ribbon Thickness: 0.006mm Ribbon Length: 25mm


Nominal Power Handling: 200W(18dB/7kHz)


Flange Diameter: 90mm

Cut Out: 65mm x 43mm or 70mm Ø

Depth: 67mm

Flange Thickness: 5mm **Price Each: \$156.00**







25NFA, 26NA & 26NAFM 1" neodymium magnet tweeters Compact high efficiency dome tweeters with smooth and

1" neodymium magnet tweeters

extended frequency response. Variable mounting to fit your applications. Ferrofluid cooled for higher power handling.

Technical Data	Symbol	Value	Unit
Nominal Impedance	Z _n	8	Ω
DC Resistance	R _{dc}	6.8	0
Resonant Frequency	f _r	1850	Hz
Rated Power	1r	80	W
SPL 1W/1m		92	db
Total Moving Mass	M _{MS}	0.22	g
Effective Piston Area	SD	6.8	cm ²
Voice Coil Diameter		25	mm
Voice Coil Former		Nomex	
Voice Coil Length		1.5	mm
Voice Coil Layers		2	
Flux Density	В	1.35	Tesla
Force Factor	B_L	2.4	Tm
Gap Height		2	mm
Magnet Diameter		32	mm
Magnet Height		8	mm
Magnet Weight		0.05	kg
Mass of Speaker		0.07	kg

25NFA \$43.00 each 26NA \$37.00 each 25NAFM \$37.00 each

25NFA & 26NA

Flange diameter	48 mm
Cutout hole Ø	46 mm
Depth	10 mm

26NAFM

Flange diameter	67 mm
Cutout hole Ø	48 mm
Depth	10 mm





26NA Aluminum dome

25NFA Textile dome








Hinged Wedge Mount

Wedge Mount

Flush Mount

- Wedge mounting; \$2.00 each (LPGWM)
- Hinged Wedge mounting; \$3.50 each (HWM)
- Flush mounting; \$3.50 each (LPGFM)

26NAFM Flush Mount Tweeter



1" dome tweeter Price \$45.00

25 mm titanium dome tweeter with high efficiency and wide frequency response

- titanium dome
- black aluminum front plate
- double magnet
- vented pole piece
- grill frame



Technical Data	Symbol	Value	Unit
Nominal Impedance	Z _n	8	Ω
DC Resistance	R _{dc}	6.8	Ω
Resonant Frequency	f_r	730	Hz
Rated Power		100	W
SPL 1W/1m		90	db
Total Moving Mass	M_{MS}	0.28	g
Effective Piston Area	S_D	6.8	cm ²
Voice Coil Diameter		25	mm
Voice Coil Former	A	luminun	1
Voice Coil Length		1.5	mm
Voice Coil Layers		2	
Flux Density	В	1.8	Tesla
Force Factor	B_L	3.2	Tm
Gap Height		1.5	mm
Magnet Diameter		72	mm
Magnet Height		2 x 15	mm
Magnet Weight		2 x .25	kg
Mass of Speaker		0.75	kg
Flange diameter		110	mm
Cutout hole diameter		74	mm
Depth		41	mm
	Nominal Impedance DC Resistance Resonant Frequency Rated Power SPL 1W/1m Total Moving Mass Effective Piston Area Voice Coil Diameter Voice Coil Length Voice Coil Length Voice Coil Layers Flux Density Force Factor Gap Height Magnet Diameter Magnet Height Mass of Speaker Flange diameter Cutout hole diameter	Nominal Impedance Z _n DC Resistance R _{dc} Resonant Frequency f _r Rated Power SPL 1W/1m Total Moving Mass M _{MS} Effective Piston Area SD Voice Coil Diameter Voice Coil Length Voice Coil Length Voice Coil Layers Flux Density B Force Factor B _L Gap Height Magnet Diameter Magnet Height Mass of Speaker Flange diameter Cutout hole diameter	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$


51AT 2" midrange dome **No Longer Available**


50 mm metal midrange dome with high efficiency and extraordinarily wide frequency response

- aluminum dome
- rubber surround
- black aluminum front plate
- rear chamber
- vented pole piece
- grill frame



Technical Data	Symbol	Value	Unit
Nominal Impedance	Z _n	8	Ω
DC Resistance	R _{dc}	5.7	Ω
Resonant Frequency	f_r	480	Hz
Rated Power		100	W
SPL 1W/1m		93	db
Total Moving Mass	M_{MS}	1.27	g
Effective Piston Area	S_D	26	cm ²
Voice Coil Diameter		50	mm
Voice Coil Former	A	luminun	1
Voice Coil Length		4.3	mm
Voice Coil Layers		1	
Flux Density	В	1.3	Tesla
Force Factor	B_L	3.7	Tm
Gap Height		3	mm
Magnet Diameter		102	mm
Magnet Height		17	mm
Magnet Weight		0.47	kg
Mass of Speaker		1.2	kg
Flange diameter		140	mm
Cutout hole diameter		105	mm
Depth		46	mm





Madisound 6102				
6.5" Polypropylene				
Woofe	r 4 or 8	Ω		
	6102-4	6102-8		
Fs (Hz)	28.6	30.8		
Rscc (Ω)	3.4	6.3		
VcL(mH@1K)	.403	.552		
Qms	7.28	7.40		
Qes	.27	.37		
Qts	.26	.35		
Mmd (g)	7.87	9.61		
Cms (µm/N)	3590.6	2570.1		
Vas (Ltrs)	77.1	55.2		
Efficiency (dB 2.83V/1m)	92	89		
Xmax	3.5m	m pk		
Power	50 w 12 oz.			
Magnet				
Cone	Black Poly Foam			
Surround				
Voice Coil	1" 2-Laye	er Kapton		

5 9/16" / 2.87"

6 9/16"

\$25.00

Cutout/Depth


Frame

Price



Vented pole piece

	Ver	ited	Sea	aled
	4 Ω	8Ω	4 Ω	8Ω
VB Itrs	18	40	11.4	28
FB Hz	36	30	~	~
F3 Hz	41	33	58	47
Port Diameter	1.5"	2"	Qtc=	Qtc=
Length	4.6"	5.2"	Rg=.4	Rg=.4







MAD1259


High Performance 12" Woofer (4Ω)


Madisound Speakers is pleased to offer the MAD1259 custom made woofer. The unique characteristics of the MAD1259 allow it to be used in a sealed enclosures, producing deep and accurate bass to 25Hz. The large voice coil and long excursion insure that this woofer will provide superior transient response with exceptional power handling. The bumped backplate and raised spider prevent bottoming at maximum excursions; the heavy cast frame minimizes energy transfer to the enclosure; and the polypropylene cone with rubber surround promise long term durability in any environment. This woofer is an exceptional choice for any high-end home or autosound system and can also handle the most demanding A/V system.



Specifications		
Fs	20.13	Hz
Nominal Impedance	4	Ω
Mmd	104.33	Grams
Cms	565.17	m/n
Vas	195.1	Liters
Re	3.524	Ω
Leap Krm	4.033	mΩ
Leap Kxm	11.829	mH
Leap Erm	0.756	
Leap Exm	0.727	
vcL	1.09	mH@1K
Bl	8.472	Tm
Qms	4.413	
Qes	0.663	
Qts	0.576	
Voice Coil Height	34	mm
Air Gap Height	8	mm
Xmax	13.0	mm Peak
SD	0.0493	m ²
Surround	Rubber	
Frame	Cast	
Cone Material	Polypro	opylene
Magnet	59 oz.	
Voice Coil	50 mm	
Music Power	300 Watts	
Sensitivity	89 dB	2.83V/1m
Price	\$150.00	







Simulated Response Curve, 3.0 cubic foot, two MAD1259 woofers in series, compound loaded (piggyback), sealed and stuffed. About 85dB

The MAD1259 is the latest version of the famous NHT1259 woofer. The woofer is still made by Foster, but some of the original parts are no longer available. Since the new driver is not similar enough to the old driver, we have changed the name.



5% off on 4 or more pieces of the same item.



Morel Tweeters									
Model					Imp.	Fs Hz	Nom.	dB	Price
					Ω		Power	2.83V/m	Each
ST1108 Supreme 110mm flange, 28mm	soft dom	e tweete	er, Hexa	tech VC	8	680	220	91.5	\$218.00
ST1308 Supreme 130mm flange, 28mm					8	680	220	91.5	\$231.00
ET448 Elite 72mm flange, 28mm soft dor					8	750	120	92	\$104.00
ET338 Elite 110mm flange, 28mm soft de	ome twe	eter, doi	uble ma	gnet	8	750	200	92.5	\$153.00
ET338-104 Elite 104mm flange, 28mm so	ft dome	tweeter	, double	magnet	8	700	200	92.5	\$146.00
MDT12 28mm dome tweeter w/ Neodymiu	ım magn	net, 2.13	" sq, 0.6	i" deep	8	1000	80	89	\$31.00
MDT20 28mm dome tweeter					8	650	120	90	\$33.00
MDT22 28mm dome tweeter w/ chamber	and neod	lymium	magnet		8	650	80	89	\$33.00
MDT29 28mm dome tweeter					8	900	80	89	\$47.00
MDT30S 28mm dome tweeter					8	700	200	90	\$68.00
MDT32S 28mm dome tweeter with 110mm	m flange	;			8	700	200	90	\$73.00
MDT37 28mm horn loaded dome tweeter					8	700	200	93	\$65.00
MDT39 28mm dome tweeter, chambered					8	750	80	88	\$52.00
MDT40 28mm dome tweeter, Neodymiun	n magnet	t			8	750	120	89	\$72.00
MDT44 28mm dome tweeter, Double Nec	dymium	magne	t		8	750	120	91	\$97.00
R-29 & R-39 Voice Coil for MDT29 & V	oice Coi	l for MI	DT39						\$13.00
R-30 Voice Coil for MDT30S; R-40 Voice	e Coil fo	r MDT4	10						\$18.00
R-32/33 Voice Coil for MDT32S & MDT	33 & Su	preme;	R-37 V	oice Coil f	for MDT	37; R-44 V	oice Coil for MD	T44	\$20.00
			Mi	dranges					
EM1308 Elite 130mm flange, 54mm soft	dome, ne	eodymiu	ım magı	net	8	320	200	88	\$139.00
MDM55 87mm square flange, 54mm soft	dome, n	eodymiı	ım mag	net	8	380	200	90.5	\$86.00
			V	Voofers					
Model	Imp.	Fs	Qts	Vas	Nom.	Efficiency	Box Liters	F3	Price
	Ω	Hz		liters	Power	2.83V/1m	Sealed/Vented	Hz	Each
EM428 Elite 4" Poly cone, Neo. magnet	4 or 8	68	.41	3.5	150	87 (8Ω)	3V / 1S	75 / 130	\$126.00
MW113 4" Poly cone woofer	8	72	.75	4.3	150	87	10S	70	\$84.00
MW144 5" Poly cone woofer	4 or 8	52	.55	8	150	88	8S	67	\$94.00
MW164 6" Doped Paper cone woofer	4 or 8	48	.55	14.3	150	86	20 S	62	\$107.00
MW166 6" Poly cone woofer	4 or 8	48	.58	15.6	150	86	14 to 28 S	57 to 55	\$107.00
MW168 6" Poly cone woofer, low Q	4 or 8	44	.41	16	150	88	14V / 8S	44 / 77	\$107.00
MW265 8" Poly cone woofer, low Q						89	60 to 90S	36 to 35	\$116.00
MW266 8" Doped Paper cone woofer	4 or 8	29	.56	80	150	89	56-100S	38-36	\$116.00
MW1075 10" Poly cone woofer	8	29	.62	123	180	89	90S	35	\$144.00
HU Cast Frame Uniflow Woofers - Neodymium & Ferrite Hybrid Magnet System									
HU521 5" Poly cone bass/midrange	8	46	.37	9.9	160	88	7V/4S	51 / 85	\$124.00
HU531 5" Paper cone bass/midrange	8	46	.37	9.9	180	86	6V/4S	55 / 88	\$127.00
HU621 6" Poly cone woofer	8	43	.38	27	160	90	18V/11S	50 / 80	\$143.00
HU631 6" Poly cone woofer	8	44	.36	16.9	180	88	10V/6S	53 / 86	\$145.00
HU9.1 8" Poly cone woofer	8	30	.36	71	200	89	43V / 25S	36 / 59	\$157.00

 IDR^{TM} Many of the tweeters have been redesigned with the new IDR^{TM} Improved Dispersion Recess face plates. As the name implies, both the on and off axis dispersion of the tweeters in greatly improved.

Hexatech: Hexatech's honeycomb voice coil structure reduces air gaps and increases efficiency by up to 20%. The lightweight structure allows for the quick transient response necessary for accurate music reproduction.

*Acuflex*TM coating: Acuflex is a specially engineered material that ensures good damping, reduces distortion levels and unwanted resonances, and provides crystal clear sound.

External Voice Coil (EVC): Morel's woofer voice coils are three times larger than those found in conventional speakers with the same cone diameter. The extremely light and efficient voice coil optimizes the translation from electrodynamic energy to acoustic energy. This topology also allows for some of the shallowest woofers available.

ST1108 Tweeter

Znom

Le@1kHz

Re

fs Qms Qes Qts Mms

Cms



ohm

Hz

mm/N

5.2 ohm

0.09 mH 680

0.44 g

- 1" textile Acuflex dome **ST1308 Tweeter**
- Neodymium flat pancake magnet
- IDR Face plate
- Rear chamber
- Hexatech VC
- 1400 to 22,000Hz
- Flange 110mm (4.33")
- Cut-out 75mm (2.95")
- Depth 37mm (1.46")

Sd	6.0	cm ²
BL	-	N/A
Vas	-	ltrs
Xmax	0.75	mm peak
VC Ø	28	mm
Sensitivity		
1W / 1m	91.5	dB
Nom. Power DIN	220	W
Net weight	0.45	kg





Znom	8	ohm
Re	5.2	ohm
Le@1kHz	0.09	mH
fs	680	Hz
Qms	-	
Qes	-	
Qts	-	
Mms	0.44	g
Cms	-	mm/N

- 1" textile Acuflex dome
- Neodymium flat pancake magnet
- IDR Face plate
- Hexatech voice coil
- 1400 to 20,000Hz
- Chambered back
- Flange 130mm (5.12")
- Cut-out 104mm (4.09")
- Depth 37mm (1.46")

Sd	6.0	cm ²
BL	-	N/A
Vas	-	ltrs
Xmax	-	mm peak
VC Ø	28	mm
Sensitivity		
1W / 1m	91.5	dB
Nom. Power DIN	220	W

0.52 kg





Net weight

ET448 Tweeter



Znom 8 ohm Re 5.2 ohm Le@1kHz 0.05 mH fs 750 Hz Qms Qes Qts Mms 0.44 g Cms mm/N

- 1" textile Acuflex dome
- Double neodymium magnets
- IDR Face plate
- Rear chamber
- Ferrofluid cooled
- 2,200 to 22,000Hz
- Flange 72mm Ø (2.83")
- Cut-out 44mm Ø (1.73")
- Depth 55mm (2.17")

Depui 33mm (2.17)			
Sd	6.0	cm^2	
BL	2.3	N/A	
Vas	-	ltrs	
Xmax	-	mm peal	
VC Ø	28	mm	
Sensitivity			
1W / 1m	92	dB	
Nom. Power DIN	120	W	
Net weight	0.10	kg	


ET338-104 Tweeter




ohm Znom Re 5.2 ohm Le@1kHz 0.09 mH 700 Hz fs Qms Qes Ots 0.44 g Mms Cms mm/N

- 1" textile Acuflex dome
- Triple magnet
- IDR Face plate
- Replaceable voice coil
- Hexatech voice coil
- 1.800 to 20.000Hz
- · Chambered back
- Flange 104mm (4.09")
- Cut-out 76mm (3.00")
- Depth 63mm (2.48")

Sd	6.0	cm ²
BL	6.3	N/A
Vas	-	ltrs
Xmax	-	mm peak
VC Ø	28	mm
Sensitivity		
1W / 1m	92.5	dB
Nom. Power DIN	200	W
Net weight	1.08	kø





ET338 Tweeter



Znom ohm Re 5.2 ohm Le@1kHz 0.09 mH 700 Hz Qms Qes Qts

Mms Cms

Znom

Le@1kHz

Re

fs

Qms


Qes

0.44 g

mm/N

- 1" textile Acuflex dome
- Triple magnet
- IDR Face plate
- Replaceable voice coil
- Hexatech voice coil
- 1.800 to 20.000Hz
- Chambered back
- Flange 110mm (4.33")
- Cut-out 76mm (3.00")
- Depth 63mm (2.48")

Sd	6.0	cm ²
BL	6.3	N/A
Vas	-	ltrs
Xmax	-	mm peak
VC Ø	28	mm
Sensitivity		
1W / 1m	92.5	dB
Nom. Power DIN	200	W
Net weight	1.08	kg




EM1308 Midrange



Znom	8	ohm
Re	6.2	ohm
Le@1kHz	0.20	mΗ
fs	320	Hz
Qms	0.9	
Qes	1.01	
Qts	0.47	
Mms	3.0	g
Cms	-	mm/N

- 2" textile Acuflex dome
- Hand coated dome
- IDR Face plate
- 500 to 5,000Hz
- Hexatech voice coil
- Gold-plated terminals
- Rear chamber
- Flange 130mm (5.12")
- Cut-out 76mm (3.00")
- Depth 118mm (4.65")

	8	ohm	Sd	28.0	cm ²
	6.2	ohm	BL	5.2	N/A
kHz	0.20	mH	Vas	-	ltrs
	320	Hz	Xmax	1	mm peak
	0.9		VC Ø	54	mm
	1.01		Sensitivity		
	0.47		1W / 1m	88	dB
	3.0	g	Nom. Power DIN	200	W
	-	mm/N	Net weight	0.52	kg



MDT12 Tweeter



ohm

ohm

Hz

 $0.05~\mathrm{mH}$

52

1000

- 1" textile dome tweeter
- Ferrofluid cooled
- Neodymium magnet
- Replaceable voice coil
- Magnetically shielded
- Gold-plated terminals
- Flange 54mm sq (2.13")
- Cut-out 44mm Ø (1.73")

6.0 cm²

2.8 N/A

28

ltrs

mm

mm peak

Depth 15.5mm (0.61")

MDT20 Tweeter



- 1" textile dome tweeter
- Rear chamber
- Replaceable voice coil
- Ferrofluid cooled
- Polymer face-plate
- Low Fs
- Gold plated terminals
- Flange 104mm (4.09")
- Cut-out 73mm (2.87")
- Depth 43mm (1.69")

V								
Qts		-		1W / 1m		89	dB	
Mms		0.47	g	Nom. Power	DIN	80	W	
Cms		-	mm/N	Net weight		0.08	kg	
	Sensitivity	Mag -	dB SPL/watt	(8.0 ohm load)	(0.10	ect)		
		- 1					1	11
100.0	+++							
95.0	11.							
90.0	111			4-11				
85.0	1.11				MT.		~~	
		1 1				1	. \	\ I
90.0	1 1 1 1 1		<i>f</i>				7	1
75.0	4-44							
		1					1	
70.0	11 /	1						7
65.0	1							
					1 1 1		1	- 1
60.0	11							
55.0	4-4					 		
FO 0		1 1			. 1 1 1 1 .	<u> </u>		

Sd

BL


Vas

Xmax

VC Ø

Sensitivity

Znom	8	ohm	Sd	6.0	cm ²
Re	5.2	ohm	BL	3.5	N/A
Le@1kHz	0.05	mH	Vas	-	ltrs
fs	650	Hz	Xmax	-	mm peak
Qms	-		VC Ø	28	mm
Qes	-		Sensitivity		
Qts	-		1W / 1m	90	dB
Mms	0.5	g	Nom. Power DIN	120	W
Cms	-	mm/N	Net weight	0.55	kg




MDT22 Tweeter



Znom ohm Re 5.2 ohm Le@1kHz 0.05 mH Hz fs Qms 0.89 Qes Qts 0.47 g Mms Cms mm/N

- 1" textile dome tweeter
- Neodymium magnet
- Magnetically shielded
- Rear chamber
- Ferrofluid cooled
- Gold-plated terminals
- Replaceable voice coils
- Flange 54mm sq (2.13")
- Cut-out 44mm Ø (1.73")
- Depth 55mm (2.17")


6.0	cm ²
2.8	N/A
-	ltrs
-	mm peak
28	mm
89	dB
80	W
0.09	kg
	28



MDT29 Tweeter



Znom	8	ohm	Sd	6.0	cm ²
Re	5.2	ohm	BL	3.3	N/A
Le@1kHz	0.05	mH	Vas	-	ltrs
fs	900	Hz	Xmax	-	mm peak
Qms	-		VC Ø	28	mm
Qes	-		Sensitivity		
Qts	-		1W / 1m	89	dB
Mms	0.5	g	Nom. Power DIN	80	W
Cms	-	mm/N	Net weight	0.54	kg




MDT30S Tweeter



Znom ohm Re ohm 5.2 Le@1kHz mH 650 Hz fs Qms Qes Ots 0.44 gMms Cms mm/N

- 1" textile dome tweeter
- Hand coated dome
- Ferrofluid cooled
- Replaceable voice coils
- Aluminum face-plate
- Gold-plated terminals
- Rear chamber
- Flange 94mm (3.7")
- Cut-out Ø 73mm (2.87")
- Depth 43mm (1.69")

•		
Sd	6.0	cm^2
BL	3.5	N/A
Vas	-	ltrs
Xmax	-	mm peak
VC Ø	28	mm
Sensitivity		
1W / 1m	90	dB
Nom. Power DIN	200	W
Net weight	0.56	kg



MDT32S Tweeter



Znom	8	ohm
Re	5.2	ohm
Le@1kHz	0.09	mH
fs	650	Hz
Qms	-	
Qes	-	
Qts	-	
Mms	0.44	g
Cms	-	mm/N

1" textile dome tweeter

• 1" textile dome tweeter

Replaceable voice coil

Aluminum face-plate

Gold-plated terminals

Cut-out 78mm (2.83")

Flange 94mm (3.7")


• Depth 27mm (1.06")

Hand treated dome

Ferrofluid cooled

- Hand coated dome
- Ferrofluid cooled
- Replaceable voice coils
- Aluminum face-plate
- Gold-plated terminals
- Rear chamber
- Flange 110mm (4.33")
- Cut-out Ø 73mm (2.87")
- Depth 43mm (1.69")

Sd	6.0	cm ²
BL	3.5	N/A
Vas	-	ltrs
Xmax	-	mm peak
VC Ø	28	mm
Sensitivity		
1W / 1m	90	dB
Nom. Power DIN	200	W
Net weight	0.56	kg




DMS30S Tweeter



Znom 8 ohm
Re 5.2 ohm
Le@1kHz 0.05 mH
fs 650 Hz
Qms Qes Qts Mms 0.44 g
Cms - mm/N

- 1" textile dome tweeter
- · Hand coated dome
- Ferrofluid cooled
- Replaceable voice coil
- Gold-plated terminals
- · Magnetically shielded
- · Rear chamber
- Flange 94mm (3.7")
- Cut-out 73mm (2.87")
- Depth 43mm (1.69")

		2
Sd	6.0	cm ²
BL	3.5	N/A
Vas	-	ltrs
Xmax	-	mm peak
VC Ø	28	mm
Sensitivity		
1W / 1m	90	dB
Nom. Power DIN	200	W
Net weight	0.66	kg




MDT37 Tweeter



Znom	8	ohm
Re	5.2	ohm
Le@1kHz	0.09	mΗ
fs	700	Hz
Qms	-	
Qes	-	
Qts	-	
Mms	0.44	g
Cms	-	mm/N

- 1" textile dome tweeter
- Horn loaded face-plate
- Hexatech voice coil
- Ferrofluid cooled
- Replaceable voice coil
- Gold-plated terminals
- High efficiency
- Flange 94mm (3.7")
- Cut-out 72mm (2.83")
- Depth 54mm (2.28")

Sd	6.0	cm ²
BL	3.5	N/A
Vas	-	ltrs
Xmax	-	mm peak
VC Ø	28	mm
Sensitivity		
1W / 1m	93	dB
Nom. Power DIN	200	W
Net weight	0.56	kσ



MDT39 Tweeter



Znom ohm ohm Re 5.2 Le@1kHz 0.06 mH fs 750 Hz Qms Qes Ots Mms 0.46 gmm/N Cms

- 1" textile dome tweeter
- Compact size
- Neodymium magnet
- Rear chamber
- · Ferrofluid cooled
- Magnetically shielded
- Smooth response
- Flange 54mm sq (2.13")
- Cut-out 44mm Ø (1.73")
- Depth 55mm (2.17")

Sd	7.0	cm ²
BL	2.6	N/A
Vas	-	ltrs
Xmax	-	mm peak
VC Ø	28	mm
Sensitivity		
1W / 1m	88	dB
Nom. Power DIN	80	W
Net weight	0.09	kg

105.0 95.0 95.0 75.0 65.0 1000.0 20000.0


MDT40 Tweeter



Znom	8	ohm
Re	5.2	011111
Le@1kHz	0.05	mH
fs	750	Hz
Qms	-	
Qes	-	
Qts	-	
Mms	0.46	g
Cms	-	mm/N

- 1" textile dome tweeter
- Hexatech voice coil
- Neodymium magnet
- Rear chamber
- Replaceable voice coil
- · Ferrofluid cooled
- · Magnetically shielded
- Flange 54mm sq (2.13")
- Cut-out 44mm Ø (1.73")
- Depth 55mm (2.17")

Sd	7.0	cm ²
BL	2.9	N/A
Vas	-	ltrs
Xmax	-	mm peak
VC Ø	28	mm
Sensitivity		
1W / 1m	89	dB
Nom. Power DIN	120	W
Net weight	0.09	kø



MDT44 Tweeter



Znom	8	ohm
Re	5.1	ohm
Le@1kHz	0.05	mΗ
fs	750	Hz
Qms	-	
Qes	-	
Qts	-	
Mms	0.46	g
Cms	-	mm/N

95.0

85.Q

75.0

65.0

55.0

- 1" textile dome tweeter
- Hexatech voice coil
- Double neodymium magnet - Shielded
- Rear chamber
- Replaceable voice coil
- Ferrofluid cooled
- Flange 54mm sq (2.13")
- Cut-out 44mm Ø (1.73")
- Depth 55mm (2.17")

Sd	7.0	cm ²
BL	4.3	N/A
Vas	-	ltrs
Xmax	-	mm peak
VC Ø	28	mm
Sensitivity		
1W / 1m	91	dB
Nom. Power DIN	120	W
Net weight	0.09	kg

MDM55 Midrange



Znom	8	ohm
Re	6.3	ohm
Le@1kHz	0.19	mΗ
fs	380	Hz
Qms	-	
Qes	-	
Qts	-	
Mms	2.2	g
Cms	-	mm/N

100.0

95.0 90.0

85.0


75.0

65.0

55.0

- 2" textile dome midrange
- Neodymium magnet
- Rear chamber
- Magnetically shielded
- Gold-plated terminals
- Hexatech voice coil
- Flange 87mm sq (3.43")
- Cut-out 75mm Ø (2.95")
- Depth 82mm (3.23")

Sd	28.0	cm ²
BL	5.2	N/A
Vas	-	ltrs
Xmax	1.0	mm peak
VC Ø	54	mm
Sensitivity		
1W / 1m	90.5	dB
Nom. Power DIN	200	W
Net weight	0.3	kg




EM428 4" Mid (MW114S)



Znom ohm ohmRe 5.4 Le@1kHz 0.36 mH 68 Hz 3.03 Qms Qes 0.48 Qts 0.41 Mms 6.55 g Cms 0.88 mm/N

- 4" Damped Polymer Composite cone
- Neodymium magnet
- Hexatech voice coil
- Shielded magnet
- Rubber surround
- Small & powerful
- Flange 118mm (4.64")
- Cut-out 94mm (3.7")
- Depth 58mm (2.28")

Sd	57.0	cm ²	
BL	5.4	N/A	
Vas	3.50	ltrs	
Xmax	3.0	mm peak	
VC Ø	54	mm	
Sensitivity			
1W / 1m	87	dB	
Nom. Power DIN	150	W	
Net weight	0.5	kg	
(8 ohm load) (0.10 oct)			




MW113 4" Woofer



Znom	8	ohm
Re	6.2	ohm
Le@1kHz	0.25	mΗ
fs	72	Hz
Qms	3.13	
Qes	1.03	
Qts	0.75	
Mms	5.54	g
Cms	0.84	mm/N

- 4" Damped Polymer Composite cone
- 54mm Hexatech voice coil
- Rubber surround
- Triple magnet system
- Magnetically shielded
- Flange 118mm (4.64")
- Cut-out 95mm (3.75")
- Depth 58mm (2.28")

Sd	53.0	cm ²
BL	3.98	N/A
Vas	4.3	ltrs
Xmax	3.0	mm peak
VC Ø	54	mm
Sensitivity		
1W / 1m	87	dB
Nom. Power DIN	150	W
Net weight	0.5	kg



MW144 5" Woofer



ohm

Hz

5.2 ohm

2.44

0.71

0.55

13.7 g

0.69 mm/N

52

0.38 mH

Znom

Le@1kHz

Re

Qms

Qes

Qts


Mms

Cms

- 5" Damped Polymer Composite cone
- Double magnet
- Hexatech voice coil
- Vented magnet system
- Rubber surround
- Low magnetic field
- Flange 142mm (5.59")
- Cut out 118mm (4.65")

• Cut-out 118mm (4.65)				
• Depth 52mm (2.04")				
Sd	90.0	cm^2		
BL	6.2	N/A		
Vas	8.0	ltrs		
Xmax	3.5	mm peak		
VC Ø	75	mm		
Sensitivity				
1W / 1m	88	dB		
Nom. Power DIN	150	W		

	90.0	CIII
	6.2	N/A
	8.0	ltrs
	3.5	mm peak
	75	mm
	88	dB
N	150	W
	1.0	kg
		_




Net weight

MW164 6" Woofer



Znom	8	ohm	Sd
Re	6.3	ohm	BL
Le@1kHz	0.66	mH	Vas
fs	48	Hz	Xmax
Qms	2.55		VC Ø
Qes	0.70		Sensitivity
Qts	0.55		1W / 1m
Mms	14.9	g	Nom. Power DIN
Cms	0.69	mm/N	Net weight




MW166 6" Woofer



- 6" Damped polymer composite cone
- Double magnet
- Hexatech voice coil
- Rubber surround
- Low magnetic field
- Ventilated spider
- Flange 160mm (6.3")
- Cut-out 136mm (5.4")
- Depth 67mm (2.63")

Znom	8	ohm	Sd	119.0	cm^2
Re	6.7	ohm	BL	6.84	N/A
Le@1kHz	0.61	mH	Vas	15.6	ltrs
fs	46	Hz	Xmax	4.25	mm peak
Qms	2.79		VC Ø	75	mm
Qes	0.74		Sensitivity		
Qts	0.58		1W / 1m	86	dB
Mms	16.3	g	Nom. Power DIN	150	W
Cms	0.78	mm/N	Net weight	1.1	kg



MW168 6" Woofer



Znom ohm Re 5.2 ohm Le@1kHz 0.51 mH fs 44 Hz 2.09 Qms 0.50 Qes Qts 0.41 14.0 g Mms Cms 0.80 mm/N • 6" Damped polymer composite cone

• 6" Polymer coated paper

Double magnet

Hexatech voice coil Rubber surround

Low magnetic field

Flange 160mm (6.3")

Cut-out 136mm (5.4") Depth 67mm (2.63")

119.0 cm²

6.57 N/A

4.25 mm peak

mm

dB

W

14.34 ltrs

86


150

Ventilated spider

cone

- Double magnet
- Hexatech voice coil
- Rubber surround
- Low magnetic field
- Ventilated spider
- Flange 160mm (6.3")
- Cut-out 136mm (5.4")
- Depth 58mm (2.28")

Sd	119.0	cm ²
BL	6.55	N/A
Vas	16.0	ltrs
Xmax	3.5	mm peak
VC Ø	75	mm
Sensitivity		
1W / 1m	88	dB
Nom. Power DIN	150	W
Net weight	0.80	kg



MW265 8" Woofer



ohm

ohm

Hz 2.79

0.92 mm/N

0.58 mH

30

0.79

0.61 25.5 g

Znom

Le@1kHz

Re

fs

Qms Oes

Qts

Mms

Cms

105.0 100.0 95.0

> 85.0 80.0 75.0

> > 65.0 60.0

Znom

Le@1kHz

Re

fs

Qms Qes

Ots

Mms

Cms

- 8" Damped polymer composite cone
- Rubber surround
- Hexatech voice coil
- Double magnet
- Shallow profile
- Low magnetic field
- Flange 222mm (8.75")
- Cut-out 195mm (7.68")
- Depth 69mm (2.7")

Sd	219.0	cm ²
BL	6.3	N/A
Vas	61	ltrs
Xmax	3.5	mm peak
VC Ø	75	mm
Sensitivity		
1W / 1m	89	dB
Nom. Power DIN	150	W
Net weight	1.2	kg




MW266 8" Woofer

Znom	8	ohm
Re	6.3	ohm
Le@1kHz	0.54	mΗ
fs	29	Hz
Qms	2.45	
Qes	0.73	
Qts	0.56	
Mms	24.9	g
Cms	1.19	mm/N

8" Polymer coated paper cone

- Rubber surround
- Hexatech voice coil
- Double magnet
- Shallow profile
- Low magnetic field
- Flange 222mm (8.75")
- Cut-out 195mm (7.68")
- Depth 69mm (2.7")

Sd	219.0	cm ²
BL	6.25	N/A
Vas	80	ltrs
Xmax	4.25	mm peak
VC Ø	75	mm
Sensitivity		
1W / 1m	89	dB
Nom. Power DIN	150	W



MW1075 10" Woofer



ohm

6.3 ohm

0.83

0.62

32.6 g

0.84 mm/N

0.63 mH 29

Hz 2.48

- 10" Damped polymer composite cone
- Polymer treated foam surround

Sd	324.0	cm ²
BL	6.3	N/A
Vas	123	ltrs
Xmax	4.25	mm peak
VC Ø	75	mm
Sensitivity		
1W / 1m	89	dB
Nom. Power DIN	180	W
Net weight	1.34	kg



90.0

70.0 65.0


55.0


Znom	8	ohm
Re	5.6	ohm
Le@1kHz	0.53	mΗ
fs	46	Hz
Qms	2.24	
Qes	0.46	
Qts	0.37	
Mms	12.2	g
Cms	0.98	mm/N

HU521 5" Uniflow

- 5" Damped polymer composite cone
- Hybrid neodymium / ferrite magnet system
- Low magnetic field
- Hexatech voice coil
- Rubber surround
- Flange 145mm (5.7")
- Cut-out 124mm (4.88")
- Depth 68mm (2.68")

Sd	84.0	cm ²
BL	6.6	N/A
Vas	9.9	ltrs
Xmax	3.5	mm peak
VC Ø	54	mm
Sensitivity		
1W / 1m	88	dB
Nom. Power DIN	160	W
Net weight	1.1	kσ





1000.D

HU531 5" Uniflow



ohm

Hz

6.8 ohm

1.84

0.46

0.37

12.2 g

0.98 mm/N

46

0.63 mH

Znom

Le@1kHz

Re

fs

Qms

Qes

Qts

Mms

Cms

- 5" Damped polymer composite cone
- Hybrid neodymium / ferrite magnet system
- Low magnetic field
- Hexatech voice coil
- Rubber surround
- Flange 145mm (5.7")
- Cut-out 124mm (4.88")

• Depth 68mm (2.68")				
Sd	84.0	cm ²		
BL	7.2	N/A		
Vas	9.9	ltrs		
Xmax	3.5	mm peak		
VC Ø	75	mm		
Sensitivity				
1W / 1m	86	dB		
Nom. Power DIN	180	W		


1.15 kg

HU621 6" Uniflow




- 6" Damped polymer composite cone
- Hybrid neodymium / ferrite magnet system
- Low magnetic field
- Hexatech voice coil
- Rubber surround
- Flange 160mm (6.3")
- Cut-out 141mm (5.55")
- Depth 68mm (2.68")

Znom	8	ohm	Sd	119.0	cm ²
Re	5.6	ohm	BL	5.9	N/A
Le@1kHz	0.53	mΗ	Vas	27.0	ltrs
fs	43	Hz	Xmax	3.5	mm peak
Qms	2.34		VC Ø	54	mm
Qes	0.45		Sensitivity		
Qts	0.38		1W / 1m	90	dB
Mms	10.0	g	Nom. Power DIN	160	W
Cms	1.34	mm/N	Net weight	1.2	kg



Net weight



HU631 6" Uniflow



- 6" Damped polymer composite cone
- Hybrid neodymium / ferrite magnet system
- Low magnetic field
- Hexatech voice coil
- Rubber surround
- Flange 160mm (6.3")
- Cut-out 141mm (5.5")
- Depth 68mm (2.68")

п	UY.	T (0	U.	Ш	W	W



• Hybrid neodymium / ferrite magnet system

• 8" Damped polymer


composite cone


- Hexatech voice coil
- Rubber surround
- Low magnetic field
- Flange 222mm (8.75")
- Cut-out 199mm (7.83")
- Depth 70mm (2.75")

Znom	8 ohm	Sd	219.0 cm ²
Re	6.6 ohm	BL	8.3 N/A
Le@1kHz	0.87 mH	Vas	71.0 ltrs
fs	30 Hz	Xmax	4.25 mm peak
Qms	1.71	VC Ø	75 mm
Qes	0.46	Sensitivity	
Qts	0.36	1W / 1m	89 dB
Mms	23.5 g	Nom. Power DIN	200 W
Cms	1.055mm/N	Net weight	1.42 kg

8	ohm
6.8	ohm
0.63	mΗ
44	Hz
1.66	
0.46	
0.36	
13.6	g
0.96	mm/N
	6.8 0.63 44 1.66 0.46 0.36 13.6

Sd	119.0	cm ²
BL	7.5	N/A
Vas	16.9	ltrs
Xmax	4.25	mm peak
VC Ø	75	mm
Sensitivity		
1W / 1m	88	dB
Nom. Power DIN	180	W
Net weight	1.18	kg








Model	$\frac{Imp.}{\Omega}$	Fs Hz	Qts	Vas Ltrs	Power Watts	dВ	Xmax mm P	Box Liter S ealed/ V ented	F3 Hz	Price Each
			/EETE	RS						
810921: 104 DT 26 72 SF HDS DM (HDS 1" dome)	8	700	T DAN	JOE		93	0.5			\$59.30
830970: 2" aluminum cone full range	4	147.5	L RAN 0.57		60	85	1.7	0.5S	225	\$17.35
830986: 3" aluminum cone full range	8	83.8	0.59		80	83.8	2.0	2.0S	110	\$14.55
HDS EXCLUSIVE SERIES W									110	Ψ11.55
830881: 106 WR 26 81 NWP AL CU PH, Truncated 4"	8	81.2	0.45		c prag, c	84	3.5	1.5S / 2V	130/81	\$61.80
831882: 152 WR 26 90 NWP AL CU PH, 5.75"	8	64.5	0.39	7.2		88.2	3.5	3S / 7V	115/65	\$66.20
830883: 180 WR 33 102 NWP AL CU PH LS, 7"	8	52.3	0.43			87.5	5.5	7S / 10V	87/55	\$76.05
830884: 205 WR 102 NWP AL CU PH LS, truncated, 8"	8	32.4	0.38	68.8		89.3	5.5	28S / 44V	60/39	\$81.50
HDS SERIES PPB WOO	FER	S - Polvi	oropyle	ene cone	. cast fra	me with	raised	spider		
830854 : 106 WR 26 72 PPB AL TV, shielded, truncated, 4"	8	75.7	0.46		,	86.8	3	2.5S / 3V	115/75	\$54.80
830870: 106 WR 26 81 PPB AL, truncated, 4"	8	77.6	0.54	3		87	3	4S	100	\$50.20
830860: 134 WR 26 90 PPB AL, truncated, 5.25"	8	56.1	0.41	10.6		88.3	3.5	5.5S / 8V	95/60	\$50.25
830874 : 164 WR 33 102 PPB AL LS, truncated, 6.5"	8	47.3	0.40	16.7		87.8	5.5	8S / 14V	80/48	\$57.95
830868: 205 WR 33 102 PPM AL 4L LS, truncated, 8"	8	32.5	0.40	63.4		90.1	5.5	28S / 43V	58/37	\$67.70
HDS NOMEX SERIES W	OOF	ERS - N	omex f	iber con	e, cast fr	ame wit	h raise	d spider		
832873 : 134 WR 26 90 NWP AL, truncated, 5.25"	8	58.6	0.38		· -	88.3	3.5	3.7S / 6V	105/65	\$51.70
830875: 164 WR 33 102 NWP AL LS , truncated, 6.5"	8	48.1	0.39	17.6		88.6	5.5	8S / 12V	85/53	\$58.50
830869 : 205 WR 33 102 NWP AL 4L LS , truncated, 8"	8	30.0	0.38	70.3		89.7	4.5	28S / 45V	55/36	\$65.60
SDS WOO	FER	S - Coat	ed Pap	er cone,	stamped	l frame				
830856: Mini Woofer, truncated, shielded, 3.5"	8	62.4	0.35	3.3		85.7	3	see below		\$39.65
830878: Passive Radiator, truncated, 3.5"	Tymph	nany recom	mends u	sing two of	these pass	ive with the	830856	in 3.5 liters.		\$13.20
830887: Mini Woofer, truncated, shielded, 5.25"	8	61.5	0.42	8.6		88.5	3.5	see below		\$37.70
830880 : Passive Radiator, truncated, 5.25"	Tymnp	hany recor	mmends	using two c	of these pas	sives with t	he 83087	8 in 5 liters.		\$14.50
SLS SUBWOOFERS - Ha	rd Pa	aper con	e, stan	iped frai	me, shor	ting ring	, raisec	l spider		
830946 : 182 SWR 39 115 THSX AL 4L, 6.5"	4	36.1	0.31	12.7		86.5	8	11V	45	\$44.85
830667 : 213 SWR 39 115 THSX AL 2L, 8"	8	36.5	0.54	33.1		87.2	8.5	50S / 45V	47/31	\$59.55
830668 : 263 SWR 39 115 THSX AL 4L , 10"	8	33.3	0.51	69.3		88.7	8	75S / 83V	46/30	\$61.95
830669 : 315 SWR 39 134 THSX AL 4L , 12"	8	28.0	0.47			91.2	8	90S / 127V	40/30	\$71.65
XLS LINE SUBWOOFERS	- Ext	ra Long	Stroke		Frame -	Active &	z Passiv	<u>e Drivers</u>		
830452: 269 SWR 51 147 NX ALP 4L XLS (10" woofer)	5	18.6	.17		200	88.4	±12.5	35 w/passive	20	\$168.55
830481 : 10" Passive Radiator 400 gram, threaded hole. Fs 11			100g, Sd	333 cm ² , X	-max 22 m	m, Cms 508				\$82.90
830500 : 308 SWR 51 147 NX ALP 4L XLS (12" woofer)	5	17.8	.21	136.8	200	90.6	<u>+</u> 12.5	42 w/passive	20	\$191.70
830548 : 12" Passive Radiator 425 gram, threaded hole. Fs 10										\$106.00
XXLS LINE SUBV	NOO!	FERS - 1	Extra l	Extra Lo	_	<u>ke - Cast</u>	Frame	!		
830846: 269 SWR 51 147 NWP ALP DVC, 10"	8/8	24.3	0.33		175	91	12.5	50V	30	\$187.90
830843: 269 SWR 51 147 NWP ALP 4L, 10"	8	25	0.44		175	87.2	12.5	60S	40	\$175.80
830842 : 269 SWR 51 147 NWP ALP 4L, 10", use passive	4	19.2	0.19		175	88.4	12.5	20 w/830481	curve	\$172.15
830951 : 269 SWR 51 147 AL ALP4L, 10" Aluminum cone	4	20.8	0.30	103.4	175	90.3	12.5	71V	27	\$175.80
830847 : 308 SWR 51 147 NWP ALP DVC, 12"	8/8	21.8	0.36		175	92	12.5	50S / 80V	43/27	\$208.85
830845 : 308 SWR 51 147 NWP ALP 4L , 12"	8	21.5	0.45		175	88	12.5	90S	34	\$196.55
830844 : 308 SWR 51 147 NWP ALP 4L , 12", use passive	4	17.7	0.20		175	90.3	12.5	33 w/830548	curve	\$193.00
830952 : 308 SWR 51 147 AL ALP4L, 12" Aluminum cone	4	19.1	0.37		175	91.2	12.5	40S / 96V	40/26	\$198.55
AUTOSOUND SPEAKE										
830516 : 100 WR 26 72 CD (4")	4	81.2	0.52		110	89.4	0.5	3S	112	\$32.05
830512 : 130 WR 26 81 CD (5.25")	4	66.2	0.51		110	90.1	2.0	5 to 10S	90	\$36.00
832513: 165 WR 26 90 CD (6.5")	4	48.7	0.45		140	91	2.0	8 to 15S	75	\$39.00
XXLS AUTOSOUND WOOFERS (#100 to
830876: 269 SWR 51 147 NWP ALP 4L (10")	4	39.0	.44		200	92.2	±12.5	15S / 29V	63/35	\$198.40
830877: 308 SWR 51 147 NWP ALP 4L (12")	4	35.0	.49		200	94.3	±12.5	35S / 42V	51/32	\$191.25
LAT 250, Dual coil sub	A / 4		Subwo			01	12	Cooled W- 1 P	المسم	\$50.00
LAT-250: Dual coil subwoofer, 2"	4/4	63	0.64		250	91	<u>+3</u>	Sealed, Vented, B		\$58.00
LAT-500: Dual coil subwoofer, 5" (8/8 ohm or 16/16 ohm)	8/8	28	0.45		250	92	<u>±6.7</u>	60V	30	\$223.00
LAT-700: Dual coil subwoofer, 7"	8/8	24	0.55	110	250	89	<u>+</u> 8	85V/55S	25/36	\$391.00

810921 1" HDS Dome Tweeter



- 104mm flange
- 1" textile dome
- Low compression magnet system, vented
- · Ferrofluid cooled
- Replaceable voice coil
- 79mm cut out
- Preliminary Specs

Znom	8	ohm	Sd	-	cm ²
Re	5.6	ohm	BL	-	N/A
Le	-	mH	Vas	-	ltrs
fs	700	Hz	Xmax	0.5	mm peak
Qms	-		Sensitivity		
Qes	-		2.83V / 1m	93	dB
Qts	-		Longterm Max		
Mms	-	g	System Power	-	W
Cms	-	mm/N	Magnet weight	-	kg



— Impedance — On axis — 30 degrees — 60 degree

830970



Znom	4	ohm
Re	3.8	ohm
Le	0.2	mΗ
fs	147.5	Hz
Qms	3.06	
Qes	0.70	
Qts	0.57	
Mms	1.5	g
Cms	0.76	mm/N

2" Full Range

- Aluminum cone
- Neodymium magnet
- Double venting
- Copper cap on pole piece
- Direct coupled dust cap
- 150 to 20KHz
- 55mm flange
- 50mm cut out
- John Cut Out

•	30.2mm depth	
Sd	13	cn

Su	13	CIII
BL	2.8	N/A
Vas	0.2	ltrs
Xmax		mm peak
Voice Coil Ø		mm
Sensitivity		
2.83V / 1m	85	dB
Power (IEC)	60	W
Magnet weight	0.13	kg

1100 1000 10000 40000

Frequency [Hz]

——Impedance ——On axis ——30 degrees ——60 degrees

830986

Znom

Re

Le

fs

Qms

Qes

Qts

Mms

Cms



8

6.8

0.6

83.8

5.04

0.67

0.59

2.3

1.56

ohm ohm

mΗ


Нz

mm/N

3" Full Range

- Aluminum cone
- Neodymium magnet
- Double venting
- Copper cap on pole piece
- Direct coupled dust cap
- 110 to 15KHz
- 78mm flange
- 72mm cut out
- 47mm depth

Sd	29	cm ²
BL	3.4	N/A
Vas	1.8	ltrs
Xmax	2	mm peak
Voice Coil Ø	25	mm
Sensitivity		
2.83V / 1m	84.2	dB
Power (IEC)	80	W
Magnet weight	0.13	kg



830881

Znom

Re

Le

Qms

Qes

Qts Mms

Cms


fs

4" Exclusive Woofer



- Nomex fiber cone
 - Rubber surround
 - Cast Frame truncated
 - Ventilated raised spider
 - Shorting rings
 - 120.5mm flange
 - 106.5mm truncated
 - 95mm cut out
 - 53.5mm depth

8	ohm	Sd	53	cm ²
5.9	ohm	BL	6.4	N/A
1.0	mH	Vas	2.0	Itrs
1.2	Hz	Xmax	3.5	mm peak
2.31		Voice Coil Ø	26	mm
0.55		Sensitivity		
0.45		2.83V / 1m	84	dB
7.4	g	Power (IEC)		W
0.52	mm/N	Magnet weight	0.31	kg



— Impedance — On axis — 30 degrees — 60 degree

831882 **5.75" Exclusive Woofer**



8

5.9

8.0

64.5

3.85

0.43

0.39

8.8

ohm


ohm

mΗ

Hz

- Nomex fiber cone
- Rubber surround
- Cast frame silver color
- Phase plug
- Ventilated raised spider
- Shorting rings
- 152.5mm flange
- 120.5mm cut out
- 61mm depth

	1	
Sd	87	cm ²
BL	7.0	N/A
Vas	7.2	Itrs
Xmax	3.5	mm peak
Voice Coil Ø	26	mm
Sensitivity		
2.83V / 1m	88.2	dB
Power (IEC)		W
Magnet weight	0.40	kg



On oxis — 30 degrees — 60 degrees


830883

Znom	8	ohm
Re	5.8	ohm
Le	1.3	mΗ
fs	52.3	Hz
Qms	2.79	
Qes	0.50	
Qts	0.43	
Mms	17.7	g
Cms	0.52	mm/N
110		

7" Exclusive Woofer

- · Nomex fiber cone
- Phase plug silver color
- Rubber surround
- Cast frame silver color
- Ventilated raised spider
- Shorting rings
- 180mm flange
- 147mm cut out
- 78mm depth

Sd	134	cm²
BL	8.2	N/A
Vas	13.0	Itrs
Xmax	5.5	mm peak
Voice Coil Ø	33	mm
Sensitivity		
2.83V / 1m	87.5	dB
Power (IEC)		W
Magnet weight	0.68	kg



Frequency [Hz] Onaxis 30 degrees

SH

830884

Znom

Re

Le

fs

Qms

Qes

Qts

Mms Cms

SPL [dB]

8

5.8

1.4

3.00

0.44

0.38 23.7

1.02

32.4

ohm

ohm

mΗ

Нz

mm/N

Znom

Re

Le

fs

Qms

Qes

Qts

Mms

8" Exclusive Woofer

Nomex fiber cone

- Rubber surround Cast frame - silver color
- Ventilated raised spider

221

8.0

68.8

5.5

cm²

N/A

Itrs

mm peak

- Shorting rings
- 225mm flange
- 205mm truncated
- 191mm cut out
- 90.5mm depth

Sd

BL

Vas

Xmax

Voice C Sensitiv		33	mm	
2.83 Power	V / 1m (IEC)	89.3	dB W	
Magne	t weight	0.68	kg	
				128°
				64° 32°
			1	187
	\sim	М.		8° 4°
		MAY	^	

Frequency [Hz] On axis — 30 degrees — 60 degrees

830854

SPL [dB]



Znom	8	ohm
Re	5.3	ohm
Le	0.6	mΗ
fs	75.7	Hz
Qms	2.66	
Qes	0.56	
Qts	0.46	
Mms	5.9	g
Cms	0.76	mm/N


4" PPB Woofer

- Shielded Magnet
- Polypropylene cone
- Rubber surround
- Cast Frame truncated
- Ventilated raised spider
- 120.5mm flange
- 106.5mm truncated
- 95mm cut out

	Ou	00	CITI
	BL	5.1	N/A
	Vas	3.2	ltrs
	Xmax	3	mm peak
	Voice Coil Ø	26	mm
	Sensitivity		
	2.83V / 1m	86.8	dB
	Power (IEC)		W
	Magnet weight	0.39	kg
_			

55


cm²



On axis — 30 degrees — 60 degrees




Znom 8 ohm 5.2 Re ohm Le 0.6 mΗ fs 77.6 Hz



4" PPB Woofer

- Polypropylene cone
- Rubber surround
- Cast Frame truncated
- Ventilated raised spider
- Shorting rings
- 120.5mm flange
- 106.5mm truncated
- 95mm cut out
- 55mm depth

Sd	55	cm ²
BL	4.8	N/A
Vas	3.0	ltrs
Xmax	3	mm peak
Voice Coil Ø	26	mm
Sensitivity		
2.83V / 1m	87.0	dB
Power (IEC)		W
Magnet weight	0.31	kg



On axis 30 degrees

830860




Znom	8	ohm
Re	5.7	ohm
Le	0.6	mΗ
fs	56.1	Hz
Qms	2.41	
Qes	0.50	
Qts	0.41	
Mms	8.1	g
Cms	0.99	mm/N

5.25" PPB Woofer

- Polypropylene cone
 - Rubber surround
 - Cast Frame truncated
 - Ventilated raised spider
 - Shorting rings
 - 152mm flange
 - 134mm truncated
 - 120mm cut out
 - 61.5mm depth

Sd	88	cm ²
BL	5.7	N/A
Vas	10.6	Itrs
Xmax	3.5	mm peak
Voice Coil Ø	26	mm
Sensitivity		
2.83V / 1m	88.3	dB
Power (IEC)		W
Magnet weight	0.4	ka




830874

6.5" PPB Woofer

Polypropylene cone

- Rubber surround
- Cast Frame truncated
- Ventilated raised spider
- Shorting rings
- 182mm flange
- 164mm truncated
- 145mm cut out
- 78mm depth

				1	
Znom	8	ohm	Sd	139	cm ²
Re	6.4	ohm	BL	8.5	N/A
Le	1.2	mΗ	Vas	16.7	ltrs
fs	47.3	Hz	Xmax	5.5	mm peak
Qms	2.73		Voice Coil Ø	33	mm
Qes	0.47		Sensitivity		
Qts	0.40		2.83V / 1m	87.8	dB
Mms	18.1	g	Power (IEC)		W
Cms	0.63	mm/N	Magnet weight	0.68	kg



Onaxis

30 degrees —

60 degrees

830868




Znom	8	ohm
Re	5.5	ohm
Le	1.5	mΗ
fs	32.5	Hz
Qms	4.09	
Qes	0.44	
Qts	0.40	
Mms	25.6	g
Cms	0.94	mm/N

8" PPB Woofer

- Polypropylene cone
- Rubber surround
- Cast Frame truncated
- Ventilated raised spider
- Shorting rings
- 225mm flange
- 205mm truncated
- 190mm cut out
- 91mm depth

Sd	221	cm ²
BL	8.1	N/A
Vas	63.4	Itrs
Xmax	5.5	mm peak
Voice Coil Ø	33	mm
Sensitivity		
2.83V / 1m	90.1	dB
Power		W
Magnet weight	0.68	kg



On axis -30 do groos - 60 do groos

Znom

Re

Le

fs

Qms

Qes

Qts

Mms

Cms

5.25" Nomex Woofer

830875

6.5" Nomex Woofer



6

8.0

58.6

2.39

0.46

0.38

9.1

0.81

ohm

ohm

mΗ

mm/N

Hz

- Nomex fiber cone
- Rubber surround
- Cast frame truncated
- Ventilated raised spider
- Shorting rings
- 152mm flange
- 134mm truncated
- 120mm cut out

• 61.5mm		
Sd	88	cm ²
BL	6.6	N/A
Vas	8.7	ltrs
Xmax	3.5	mm peak
Voice Coil Ø	26	mm
Sensitivity		
2.83V / 1m	88.3	dB
Power (IEC)		W
Magnet weight	0.4	kg

128 6**4**° 32ⁿ

16


ę,



Znom Re Le fs Qms Qes Qts Mms Cms	8 6.4 1.3 48.1 2.67 0.45 0.39 16.6 0.66	ohm ohm mH Hz
Cms	0.66	mm/N

- Nomex fiber cone
- Rubber surround
- Cast frame truncated
- Ventilated raised spider
- Shorting rings
- 182mm flange
- 164mm truncated
- 145mm cut out
- 78mm depth

Sd	139	cm²
BL	8.4	N/A
Vas	17.6	Itrs
Xmax	5.5	mm peak
Voice Coil Ø	33	mm
Sensitivity		
2.83V / 1m	88.6	dB
Power (IEC)		W
Magnet weight	0.68	kg



830869

Znom

Re

Le

fs

Qms

Qes

Qts

Mms

Cms

8

6.6

1.8

30.0

5.7

0.41

0.38

30.6 0.92 mm/N

ohm

ohm

mΗ

Hz

8" Nomex Woofer

=30 degrees ===60 degrees

Frequency [Hz]

Nomex fiber cone

- Rubber surround
- Cast frame truncated
- Ventilated raised spider
- Shorting rings
- 225mm flange
- 205mm truncated
- 190mm cut out

Magnet weight

pth	
235	cm ²
9.1	N/A
70.3	Itrs
4.5	mm peak
33	mm
89.7	dB
	W
	235 9.1 70.3 4.5 33

0.64 kg




830946


Znom	4	ohm
Re	3.4	ohm
Le	1.5	mΗ
fs	36.1	Hz
Qms	6.2	
Qes	0.33	
Qts	0.31	
Mms	35.2	g
Cms	0.55	mm/N

6.5" SLS Woofer

- · Coated Paper cone
- Rubber surround
- Rigid stamped frame
- Ventilated raised spider
- Bumped back plate
- Shorting rings
- 182mm flange, T164
- 148mm cut out
- 84mm depth

Sd	129	cm
BL	8.3	N/A
Vas	12.7	Itrs
Xmax	8	mm peak
Voice Coil Ø	39	mm
Sensitivity		
2.83V / 1m	86.5	dB
Power (IEC)		W
Magnet weight	0.84	ka





Znom

Re

Le

fs

Qms

Qes Qts

Mms

8" SLS Subwoofer

830668

10" SLS Subwoofer



8

5.4

2.1

36.5

7.8 0.59

0.54

33.0

8

5.7

3.1

28.0

6.70

0.51

0.47

75.4

ohm

ohm

mΗ

Hz

ohm


ohm

mΗ

Hz

- Coated Paper cone
- Rubber surround
- Rigid stamped frame
- Ventilated raised spider
- Bumped back plate
- Shorting ring
- 213.5mm flange
- 178mm cut out
- 100mm denth

• 100mm depm			
204	cm ²		
8.3	N/A		
33.1	ltrs		
8.5	mm peak		
39	mm		
87.2	dB		
220	W		
0.87	kg		
	204 8.3 33.1 8.5 39 87.2 220		




Znom	8	ohm
Re	5.6	ohm
Le	3.3	mΗ
fs	33.3	Hz
Qms	4.85	
Qes	0.57	
Qts	0.51	
Mms	51.1	g
Cms	0.45	mm/N

Coated Paper cone

- Rubber surround
- Rigid stamped frame
- Ventilated raised spider
- Bumped back plate
- Shorting ring
- 263mm flange
- 224mm cut out
- 123mm depth

8	ohm	Sd	335	cm ²
5.6	ohm	BL	10.2	N/A
3.3	mH	Vas	69.3	Itrs
33.3	Hz	Xmax	8	mm peak
4.85		Voice Coil Ø	39	mm
0.57		Sensitivity		
0.51		2.83V / 1m	88.7	dB
51.1	g	Power (IEC)		W
0.45	mm/N	Magnet weight	0.87	kg



830669

Znom

Re

Le

fs

Qms

Qes

Qts

Mms

Cms

12" SLS Subwoofer

On arris - 30 degrees - 60 degrees

• Coated Paper cone

- Rubber surround
- Rigid stamped frame
- Ventilated raised spider
- Good sealed or vented
- Bumped back plate
- 315mm flange
- 277mm cut out
- 150mm depth

Sd	540	cm ²
BL	12.2	N/A
Vas	172.4	Itrs
Xmax	8	mm peak
Voice Coil Ø	39	mm
Sensitivity		
2.83V / 1m	91.2	dB
Power (IEC)		W
Magnet weight	1.28	kg



8

5.6

0.9

62.4

3.8

0.38

0.35

6.6

ohm

830856

7nom

Re

Iе

fs

Qms

Qes

Ots

Mms


	•	R
)	•	R
3	•	Sl
	•	Tı


- · Coated Paper cone
- ubber surround

3.5" SDS Mini Woofer

- igid stamped frame
- hielded magnet
- runcated flange
- Use with 830878 passive
- 124mm flange (105 T)
- 93mm cut out
 - 65.8mm depth

ohm	Sd	49	cm ²
ohm	BL	6.2	N/A
mH	Vas	3.3	ltrs
Hz	Xmax	3	mm peak
	Voice Coil Ø	26	mm
	Sensitivity		
	2.83V / 1m	85.7	dB
g	Power (IEC)		W
mm/N	Magnet weight	0.39	kg





On acis — 30 degrees — 60 degrees

Znom

Re

Le

fs

Qms

Qes

Ots

Mms

Cms

Znom

Re

Le

fs

Qms

Qes

Qts

Mms

Cms

8

3.5

4.2

17.8

3.76

0.22

0.21

172.3

ohm

ohm

mΗ

Hz

g 0.46 mm/N

8

3.4

4.3

18.6

2.66

0.18

0.17

139.3

ohm

ohm

mΗ

Hz

0.52 mm/N

10" XLS Subwoofer

- Extra Long Stroke Sub
- Thick Nomex fiber cone
- Cast frame
- Big roll rubber surround
- Works well with 830481 passive in 20 liters
- 269.3mm Ø flange
- 240mm Ø cut out
- 107mm depth

	Ι.	
Sd	333	cm ²
BL	17.5	N/A
Vas	80.2	ltrs
Xmax	12.5	mm peak
Voice Coil Ø	51	mm
Sensitivity		
2.83V / 1m	88.4	dB
Power (IEC)	200	W
Magnet weight	2.42	kg



830481

Znom Re Le		ohm ohm mH
fs	11.2	Hz
Qms	14	
Qes		
Qts		
Mms	400	g
Cms	0.508	3 mm/N


•	Extra Long Stroke
	Passive Radiator

- Thick Nomex fiber cone
- Cast frame

10" XLS 400g Passive

- Big roll rubber surround
- Threaded M5 bolt hole for adding weight
- 269.3mm Ø flange
- 240mm Ø cut out

Sd	333	cm ²
BL		N/A
Vas	80	Itrs
Xmax	22	mm peak
Sensitivity		
2.83V / 1m		dB
Longterm Max		
System Power		W
Magnet weight		kg




830500

12" XLS Subwoofer

- Extra Long Stroke Sub
- Thick Nomex fiber cone
- Cast frame
- Works well with 830548 passive in 40 liters
- Big roll rubber surround
- 308mm Ø flange
- 278mm Ø cut out
- 126mm depth

Sd	462	cm ²
BL	17.6	N/A
Vas	136.8	Itrs
Xmax	12.5	mm peak
Voice Coil Ø	51	mm
Sensitivity		
2.83V / 1m	90.6	dB
Power (IEC)	250	W
Magnet weight	2.42	kg
		obu



One Peerless 830452 10" XLS woofer in 1.0 cubic foot box

830548

Znom

Re

I e

fs

Qms

Qes

Qts

Mms

Cms

12" XLS 425g Passive



10.4

15.2

425

ohm

ohm

mΗ


Hz

0.55 mm/N

- Extra Long Stroke Passive Radiator
- Thick Nomex fiber cone
- Cast frame
- Big roll rubber surround
- Threaded M5 bolt hole for adding weight

- 308mm Ø flange
- 278mm Ø cut out

Sd	466	cm ²
BL		N/A
Vas		Itrs
Xmax	22	mm peak
Sensitivity		
2.83V / 1m		dB
Longterm Max		
System Power		W
Magnet weight		kg



One Peerless 830500 12" XLS woofer in a 1.25 cubic foot enclosure one Peerless 830548 passive radiator and a Madisound KG5230 amplifier with active crossover at 90Hz.



830846 10" XXLS DVC Subwoofer



Specs are with coils in parallel Znom ohm 2.6

1.6

24.3

9.24

0.34

0.33

89.7


ohm

mΗ

Hz

- Extra Extra Long Stroke
- Thick Nomex fiber cone
- Cast frame
- Big roll rubber surround
- Good for 50 liter vented box, 3" port 10" long
- 269.3mm flange
- 240mm cut out
- 137mm denth

13/111111	137 mm depth							
Sd	352	cm ²						
BL	10.1	N/A						
Vas	81.8	Itrs						
Xmax	12.5	mm peak						
Voice Coil Ø	51	mm						
Sensitivity								
2.83V / 1m	91	dB						
Power (IEC)	175	W RMS						
Magnet weight	2.4	kg						



On axis — 30 degrees

830843

Znom

10" XXLS Subwoofer

- Extra Extra Long Stroke
- Thick Nomex fiber cone
- Cast frame
- Big roll rubber surround
- Good for 62 liter sealed box (2.2cf)

cm²

- 269.3mm flange
- 240mm cut out
- 137mm depth

Re	5.8	ohm	BL	12.5	N/A
Le	2.8	mΗ	Vas	86.7	ltrs
fs	25.0	Hz	Xmax	12.5	mm peak
Qms	9.03		Voice Coil Ø	51	mm .
Qes	0.47		Sensitivity		
Qts	0.44		2.83V / 1m	87.2	dB
Mms	79.9	g	Power (IEC)	175	W RMS
Cms	0.51	mm/N	Magnet weight	2.4	kg
110					
100					-128Ω
100					-64Ω
90	- 				-32Ω
SPL [dB]					-16Ω
균 80					8Ω
70					-4Ω
				MILLA	
60			A 7.	WILL	
50				1 / M.\	
10	10	10	1000	10000	40000
			Frequency [Hz]		32Ω
		— Impeda	nce — On axis — 30 degrees — 60 dec	Tees	

Sd

ohm

830842

Re

Le

fs

Qms

Qes

Qts


Mms

10" XXLS Subwoofer

• Extra Extra Long Stroke

- Thick Nomex fiber cone
- Cast frame
- Big roll rubber surround
- Good for use with 830481 Passive in 20 ltrs
- 269.3mm flange
- 240mm cut out
- 137mm depth

			13/111111	acpui	
Znom	4	ohm	Sd	352	cm ²
Re	2.6	ohm	BL	14.9	N/A
Le	4.2	mΗ	Vas	88.4	ltrs
fs	19.2	Hz	Xmax	12.5	mm peak
Qms	8.74		Voice Coil Ø	51	mm
Qes	0.19		Sensitivity		
Qts	0.19		2.83V / 1m	88.4	dB
Mms	133.8	g	Power (IEC)	175	W RMS
Cms	0.52	mm/N	Magnet weight	2.4	kg
110					




830951

10" XXLS Subwoofer



- Extra Extra Long Stroke
- Aluminum cone
- Cast frame
- Big roll rubber surround
- Good for home or car
- 269.3mm flange
- 240mm cut out
- 137mm depth

Znom	4	ohm	Sd	352	cm ²
Re	2.6	ohm	BL	10.2	N/A
Le	1.8	mH	Vas	103.4	Itrs
fs	20.8	Hz	Xmax	12.5	mm peak
Qms	8.40		Voice Coil Ø	51	mm
Qes	0.32		Sensitivity		
Qts	0.30		2.83V / 1m	90.3	dB
Mms	96.7	g	Power (IEC)	175	W RMS
Cms	0.6	mm/N	Magnet weight	2.2	kg
110					



— 30 degrees — 60 degrees

830847 12" XXLS DVC Subwoofer




llel

Specs are	with coils	in parall
Znom	4	ohm
Re	2.5	ohm
Le	1.8	mΗ
fs	21.8	Hz
Qms	10.24	
Qes	0.37	
Qts	0.36	
Mms	110.9	g
Cms	0.48	mm/N
110		

- Extra Extra Long Stroke
- Thick Nomex fiber cone
- Cast frame
- Big roll rubber surround
- Good for 80 liter vented box. 3" vent 8.75" long
- 308mm Ø flange
- 278mm Ø cut out
- 145mm depth

Sd	466	cm ²
BL	10.2	N/A
Vas	144.2	Itrs
Xmax	12.5	mm peak
Voice Coil Ø	51	mm
Sensitivity		
2.83V / 1m	92	dB
Power (IEC)	175	W RMS
Magnet weight	2.4	kg



32Ω

830845

Znom

100

90

80 70

60

Znom

Re Le

12" XXLS Subwoofer

- Extra Extra Long Stroke
- Thick Nomex fiber cone
- Cast frame
- Big roll rubber surround
- Good for 62 liter sealed box (2.2cf)

466

cm²

- 308mm Ø flange
- 278mm Ø cut out
- 145mm depth

	-							
	5.9	ohm		BL		13.1	N/A	١.
	3.6	mΗ		Vas		162.5	Itrs	
	21.5	Hz		Xmax		12.5	mm	peak
	9.68			Voice Coi	١Ø	51	mm	1
	0.47			Sensitivity	/			
	0.45			2.83V /	1m	88	dB	
	101.4	g		Power (IE	(C)	175	W F	RMS
	0.54	mm/N		Magnet w	eight	2.4	kg	
					ПП	Ш	П	Π
1				\mathbb{H}	ш	Ш.,		-128Ω
								-64Ω -32Ω
								-16Ω
	$\uparrow \downarrow \downarrow \downarrow \downarrow$		-111		n A	-	+	-8Ω
				H = V	MYALA			-4Ω
					W W	ML		
					Y W			
0	10	10		1000		10000		40000
			Fre	quency [Hz]			320	

Sd

ohm

830844

SPL [dB]

Znom

Re

Le

fs

Qms

Qes

Qts

80


60

12" XXLS Subwoofer

Frequency [Hz]

-On axis —— 30 degrees —— 60 degrees





- Cast frame
- Big roll rubber surround
- Good for use with 840548 passive in 33 ltrs

466

15.7

156.5

cm²

N/A

32Ω

- 308mm Ø flange
- 278mm Ø cut out
- 145mm depth

Sd

BL

Vas

Xmax Voice Coil Ø Sensitivity	12.5 51	mm peak mm
2.83V / 1m Power (IEC) Magnet weight	90.3 175 2.4	dB W RMS kg
		-128Ω -64Ω -32Ω -16Ω -8Ω -4Ω

-30 degrees ——60 degrees

Mms 155.9 g Cms 0.52 mm/N SPL [dB] Frequency [Hz]

ohm

ohm

mΗ

Hz

2.8

4.2

17.7

8.21

0.20

0.20

830952

12" XXLS Subwoofer



ohm

- Extra Extra Long Stroke
- Aluminum cone
- Cast frame
- Big roll rubber surround


466

cm²

- Good for home or car
- 308mm Ø flange
- 278mm Ø cut out
- 145mm depth

Re	2.6	ohm	BL	10.3	N/A
Le	1.6	mH	Vas	159	Itrs
fs	19.1	Hz	Xmax	12.5	mm peak
Qms	9.29		Voice Coil Ø	51	mm
Qes	0.38		Sensitivity		
Qts	0.37		2.83V / 1m	91.2	dB
Mms	130.6	g	Power (IEC)	175	W RMS
Cms	0.53	mm/N	Magnet weight	2.2	kg
110					

Sd



830516

4" CD Car Woofer

- Poly cone
- Rubber surround
- Peerless Logo
- Four removable mounting tabs
- Extended response
- Response to 9kHz
- 100.5mm flange

 cm^2

N/A

Itrs

mm

dΒ

W

0.23 kg

mm peak

56.5mm depth

Znom	4	ohm	Sd	58
Re	3.4	ohm	BL	4.0
Le	0.5	mΗ	Vas	3.3
fs	78.9	Hz	Xmax	0.5
Qms	3.65		Voice Coil Ø	26
Qes	0.59		Sensitivity	
Qts	0.51		2.83V / 1m	89.4
Mms	5.8	g	Power (IEC)	100
Cms	0.70	mm/N	Magnet weight	0.23
dD				



830512

4	ohm
3.3	ohm
0.6	mΗ
66.2	Hz
3.55	
0.60	
0.51	
10	g
0.58	mm/N
	3.3 0.6 66.2 3.55 0.60 0.51


• Poly cone

- Rubber surround
- Peerless logo

5.25" CD Car Woofer

- Removable mounting
- Smooth response curve
- 130mm flange
- 117mm cut out
- 60mm depth

Sd	91	cm ²
BL	4.8	N/A
Vas	6.6	ltrs
Xmax	2	mm peak
Voice Coil Ø	26	mm
Sensitivity		
2.83V / 1m	90.1	dB
Power (IEC)	110	W
Magnet weight	0.32	kg



832513

80


6.5" CD Car Woofer



- Rubber surround
- Peerless logo
- 6.5" frame size
- Use in door or 0.4cf sealed box
- 165mm flange
- 143.5mm cut out
- 79mm depth

7nom 4 ohm	Ca

Znom Re	4 3.3	ohm ohm	Sd BL	143 5.6	cm² N/A
Le	0.5	mH	Vas	17.7	Itrs
fs	48.7	Hz	Xmax	2	mm peal
Qms	2.51		Voice Coil Ø	26	mm
Qes	0.54		Sensitivity		
Qts	0.45		2.83V / 1m	91	dB
Mms	16.9	g	Power (IEC)	140	W
Cms	0.63	mm/N	Magnet weight	0.40	kg



830876 10" XXLS Car Subwoofer



1.7

1.5

6.79

39.0

ohm

mΗ

Hz

Znom

Re

Le

fs

Qms

- Extra Extra Long Stroke
- Nomex fiber cone
- Decorative logo and magnet cover
- Big roll rubber surround
- Use sealed or vented

333

10.4

23.6

12.5

cm²

N/A

ltrs

mm peak

- 269.3mm Ø flange
- 240mm Ø cut out

(Qes	0.47	Sensitivity		
(Qts	0.44	2.83V / 1m	92.2 dB	
N	Иms	121.1 g	Power (IEC)	200 W	
(Cms	0.14 mm/N	Magnet weigh	t 2.4 kg	
	110				$\overline{}$
	100				1287
	E				64
	~ ° E				32°
	SPL[dB]				169
				1/4 kHH	å.
	70		11111 NV		=
	eo 🗏		HHH VV		
	=			I Dell In	
	50 ↓ 10	100	1000	10000	40000
			Frequency [Hz]		

Sd

BL

Vas

Xmax

impedance — On wais — 30 degrees — 60 degrees


Voice Coil Ø

830877 12" XXLS Car Subwoofer



- Extra Long Stroke Sub
- · Nomex fiber cone
- Decorative logo and magnet cover
- · Big roll rubber surround
- 51mm Ø voice coil
- 308mm Ø flange
- 278mm Ø cut out

Znom Re		ohm ohm	Sd BL	466 10.6	cm² N/A
Le	1.3	mH	Vas	39.9	Itrs
fs	35.0	Hz	Xmax	12.5	mm peak
Qms	7.31		Voice Coil Ø	51	mm
Qes	0.52		Sensitivity		
Qts	0.49		2.83V / 1m	94.3	dB
Mms	156.1	g	Power (IEC)	250	W
Cms	0.13	mm/N	Magnet weight	2.4	kg
110			 	Ш	
100					128 ⁹



LAT-500 Subwoofer

The LAT-500 subwoofer has the power of two 10" woofers in a sleek 5" wide tube design. The LAT is a good choice for both home and autosound systems. Since it is a dual voice coil, you can either use each channel independently or use the speaker for one channel with the coils wired in series or parallel.



These woofers can be used in sealed, vented or bandpass enclosures. Please visit our web site for some enclosure suggestions. Dimensions are 7" wide by 16" long. Cut out is 5.9" wide by 14.9" long.

LAT-500 4 ohm (2x 8 ohm coils in parallel)

4	ohm	Sd	525	cm ²
3.2	ohm	BL	13	N/A
1.5	mH	Vas	81	Itrs
28.0	Hz	Xmax	6.7	mm peak
9.00		Voice Coil Ø	38	mm
0.50		Sensitivity		
0.45		2.83V / 1m	92	dB
160.0	g	Power (IEC)	250	W
0.21	mm/N	Magnet weight	2.72	kg
	3.2 1.5 28.0 9.00 0.50 0.45 160.0	3.2 ohm 1.5 mH 28.0 Hz 9.00 0.50 0.45 160.0 g	3.2 ohm BL 1.5 mH Vas 28.0 Hz Xmax 9.00 Voice Coil Ø 0.50 Sensitivity 0.45 2.83V / 1m 160.0 g Power (IEC)	3.2 ohm BL 13 1.5 mH Vas 81 28.0 Hz Xmax 6.7 9.00 Voice Coil Ø 38 0.50 Sensitivity 0.45 2.83V / 1m 92 160.0 g Power (IEC) 250

LAT-500 8 ohm (2x 16 ohm coils in parallel)

Znom	8	ohm	Sd	525	cm ²
Re	8.1	ohm	BL	23	N/A
Le	4	mH	Vas	81	Itrs
fs	28.0	Hz	Xmax	5.5	mm peak
Qms	9.00		Voice Coil Ø	38	mm
Qes	0.40		Sensitivity		
Qts	0.40		2.83V / 1m	89	dB
Mms	160.0	g	Power (IEC)	250	W
Cms	0.21	mm/N	Magnet weight	2.72	kg

LAT-250 Subwoofer 4/4 Ohm

The LAT-250 was designed to provide good bass response in very narrow enclosures. The LAT250 is an excellent choice as a woofer for flat panel TV speakers. At only 3.5" wide by 10-1/8" long, this driver can fit in some tight spaces and offer the bass response of an 8" woofer. The LAT is a good choice for both home and autosound systems. Since it is a dual voice coil, you can either use each channel independently or use the speaker for one channel with the coils wired in series or parallel. The LAT250 is 4 ohm stereo, 8 ohm mono with coils in series or 2 ohm mono with coils in parallel.



Dimensions: 3.5" Wide by 10-1/8" long 1.5" depth 1.25" protrusion

7nom

2

Band-Pass Single Tuned Enclosure:

- Rear (sealed) chamber volume: 2 liters
- Front (ported) chamber volume: 1liter
- Port tuning: 110Hz
- Port 1.5" diameter by 7.5" long
- F3: 59Hz

Vented Bass-Reflex Enclosure:

- Enclosure volume: 6 liters
- Port tuning: 70Hz

Sd

- Port 2" diameter by 6.75" long
- F3: 60Hz

If you intend to drive the speaker hard, a high pass filter at 55Hz is recommended in order to limit cone excursion.

cm²

LAT-250 4/4 ohm (Measured with coils in parallel for 2 ohm)

ohm

Re	2	ohm	BL	6.8	N/A
Le	0.27	mΗ	Vas	7.8	ltrs
fs	63	Hz	Xmax	3	mm peak
Qms	4.60		Voice Coil Ø	38.5	mm
Qes	0.75		Sensitivity		
Qts	0.64		2.83V / 1m	91	dB
Mms	45.0	g	Power (IEC)	-	W
Cms	0.14	mm/N	Magnet weight	0.56	kg
110					_
100			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
90	1111111	~~~	L+11/1\/ \\		
9	<i>X</i> 11111				- 12θΩ
SPL [dB]					- 64Ω
70					- 32Ω
\w''					- 16Ω
∞ √				1	- 4Ω
50	111111			W\ \d	
10	100		1000 10 Fraguency [Hz]	000	40000

LAT-700 Subwoofer 8/8 ohm

The LAT-500 subwoofer has the power of two 12" woofers in a sleek 7" wide tube design. The LAT is a good choice for both home and autosound systems. Since it is a dual voice coil, you can either use each channel independently or use the speaker for one channel with the coils wired in series or parallel.



These woofers can be used in sealed, vented or bandpass enclosures. See our web site for more info. Dimensions are 8.6" wide by 19.2" long. Cut out is 7.7" wide by 18" long.

LAT-700 4 ohm (2x 8 ohm coils in parallel)

	(- ··· p···· ··· ,		
Znom	4	ohm	Sd	525	cm ²
Re	3.2	ohm	BL	13	N/A
Le	1.5	mΗ	Vas	81	ltrs
fs	28.0	Hz	Xmax	6.7	mm peak
Qms	9.00		Voice Coil Ø	38	mm
Qes	0.50		Sensitivity		
Qts	0.45		2.83V / 1m	92	dB
Mms	160.0	g	Power (IEC)	250	W
Cms	0.21	mm/N	Magnet weight	2.72	kg

PHY TW37 \$960/pair



- Piezo Electric 37mm Paper Cone Tweeter
- · Brass frame
- Internal Crossover
- 98dB
- Frequency response 10kHz-30kHz
- Sold in Matched Pairs



Znom	70	ohm
Sensitivity	98	dB
Ms	0.07	g
Weight	0.42	kg
Diameter	83	mm
Cut out	51	mm
Depth	83	mm



PHY H30LB15 \$1675 • 12" Wide Range




- · Paper cone
- Alnico 3SC magnet
- · Cast Brass frame
- · Shielded magnet
- Designed for use in an open baffle or large sealed box. Plans are available at:

www.tonianlabs.com

16 36	ohm Hz
	—
	W
13.8	ohm
6.60	
0.62	
0.59	
23.1	g
224	ltrs
	36 50 13.8 6.60 0.62 0.59 23.1

VC Ø	35	mm			
Sensitivity	97	dB			
Zmin	14.9	ohm			
Zmax	125	ohm			
Frame diameter	311	mm			
Cut out diameter	270	mm			
Depth	195	mm			
With Silver VC wire \$1880					




PHY H21LB15 \$1205 • 8" Wide Range



Znom	15	ohm
fs	45	Hz
Nom. Power	25	W
Re	12.8	ohm
Qms	6.10	
Qes	0.65	
Qts	0.59	
Mms	9.4	g
Vas	97	Itrs

- Paper cone
- Alnico 3SC magnet
- · Cast Brass frame
- · Shielded magnet
- Designed for use in an open baffle (no-enclosure). Plans are available at: www.tonianlabs.com

VC Ø	25	mm
Sensitivity	98	dB
Zmin	14.4	ohm
Zmax	155	ohm
Frame diameter	234	mm
Cut out diameter	202	mm
Depth	154	mm
With Silver VC w	rire \$140	00




PHY KM30 \$1400



Znom	16	ohm
fs	36	Hz
Nom. Power	50	W
Re	13.8	ohm
Qms	6.60	
Qes	0.62	
Qts	0.59	
Mms	23.2	g
Vas	224	ltrs

- 12" Coaxial Speaker
- Paper cone woofer
- Piezo Paper cone tweeter
- · Cast Brass frame
- · Shielded magnet
- Designed for use in an open baffle or large sealed box. Plans are available at: www.tonianlabs.com

VC Ø 35 mm Sensitivity Zmin 14.9 ohm Zmax 125 ohm Frame diameter 311 mm Cut out diameter 270 mm Depth 195 With Silver VC wire \$2040



RAAL is a company based in Zajecar (Zayechar), eastern Serbia. It is 100% owned and managed by its founder and director, solely creating the company's policy, products, development and strategy.

In an effort to recreate a sound that happened in some other place, in some other time, audio engineers are constantly trying to find the best means to record and reproduce the sound as exactly as possible. If we could have absolutely accurate replica of recorded sound at the end of an audio equipment chain, than the sensation that we would have, would be the same as we actually participated in the recorded event.

Of course, absolute accuracy is not possible. Fortunately enough, it has been proven that it takes a certain level of reproduction accuracy to make the human or animal ears experience no difference to original. Impressive achievement, but with ridiculously expensive and impractical laboratory equipment and conditions.

Our goal is to bring the most of that experience to everyday life.



RAAL 70-10D Ribbon

- Ribbon material: aluminium
- Ribbon dims: (70 x 9.5 x 0.004) mm Ribbon mass: 0.0075 g
- Ribbon area: 6.65 cm sq.
- Gap induction: 0.62 T
- Frequency response: 2 kHz ~ 100 kHz Sensitivity: 92 dB / 1 m / 2.83 V Impedance: 8 Ohm

- Program power handling: 150 W*
- *Recommended crossover: 4th order L-R @ 2800 Hz

Price Each \$324 Price Each with Amorphous Core \$424






RAAL 140-15D Ribbon

- Ribbon material: aluminium
- Ribbon mass: (140 x15 x 0.004) mm Ribbon mass: 0.022 g
- Ribbon area: 21 cm sq.
- Gap induction: 0.51 T
- Frequency response: 500Hz ~ 100 kHz Sensitivity: 95 dB / 1 m / 2.83 V
- Impedance: 8 Ohm
- Program power handling: 200 W* *Recommended crossover: 4th order L-R @ 1600 Hz

Price Each \$538 Price Each with Amorphous Core \$638



Recently, we finished development of Amorphous C-cores transformer application in our ribbons. We are the first to use AMCC's in ribbons for absolutely uncompressed high power transient transfer and, at the same time, even further improving already the best low-level performance in the world today, by decreasing the width of hysteresis compared to HF ferrite cores. For direct coupled tube SE-ribbon, we successfully developed 175:1 ratio, -3dB at 120kHz Amorphous C-core transformers that can carry DC idle current of SET. Impedance conversion is about 30000:1, bringing the 0.1 Ohm ribbon up to 3kOhm, good for plate loading of most triodes in HF.

FEATURES:

- Special **FLATFOIL**® pure Aluminium ribbon
- Special SYMMLEAD® low inductance signal path
- Special **EQUAFIELD®** NdFeB magnetic structure
- Special "non-wave-guide" INOX front plate
- Exceptional vertical dispersion
- Super-fast settling time
- Flat frequency response
- · Low nonlinear distortion
- High signal power handling
- Highest reliability
- **Available for OEM customers: 70-20XR Ribbon Tweeter

EQUAFIELD® technology: The magnetic field in RAAL ribbons is homogenous, in other words the width of the gap is designed to have the same strength at the ribbon edges as at the middle. EQUAFIELD® technology dramatically reduces stress and distortion of the ribbon foil. We've extensively used the FEM and BEM magnetic circuit analysis software to create a precisely-shaped magnetic field that is consistent across the gap width and depth. In order to create such a field with real magnets, very strong NdFeB magnets have been precisely machined into a very special shape prior to magnetization. The process of making the magnetic field homogenous does sacrifice some of the magnet's strength. However this loss of efficiency is eclipsed by the benefits of low stress and low linear and nonlinear distortion.

www.sbacoustics.com

₿ACOUSTĬCS

SB Acoustics was formed to provide an affordable hi-end products to the loudspeaker. This was accomplished by marrying the design talents of Scandinavian Audio Research (Denmark) with the manufacturing expertise of Sinar Baja Electric (Indonesia). SCAR is company composed of many industry veterans responsible for many well known and revolutionary designs and Sinar Baja Electric is a company with more than 27 years of transducer manufacturing experience.

The SB Acoustics speaker line has been carefully engineered by Ulrik Schmidt of Denmark. Ulrik studied at The Engineering College of Odense (IOT), world renowned for their acoustic department. Ulrik has a BSc EE (specialized in Electro-Acoustics) from IOT. Ulrik worked for Scan-speak as an R&D engineer from 1997 until the spring of 2006. In 2006 Ulrik joined the team headed by Lars Goller (formerly directing engineer at Danish Sound Technology) in a new Danish loudspeaker company called Scandinavian Audio Research.

The current line of loudspeakers includes a 1" textile dome tweeter; 5" and 6.5" midbass driver; 10" and 12" bass driver and 15" bass/subwoofer. The line will be expanded to include more tweeter choices; a 4" midbass driver and an 8" woofer. The 4" through 12" woofer line features coated proprietary paper cones with papyrus reed. The 15" woofer has a special Kevlar HoneyComb (KHC) cone for added stiffness and lightness. This KHC has a more natural and warmer sound. All woofers use non-inductive fiberglass voice coil formers.

All the drivers in this line have been engineered to offer the end user many application choices. These drivers will work in many different box alignments and many drivers will do equal duty as woofers or midbass drivers. The cones and surrounds on the 5" and 6.5" woofers have been carefully chosen to provide the best possible midrange reproduction without compromising bass definition. The open structure cast frames minimize reflections, yet provide a solid foundation with minimal vibration to the motor structure.

SB25STC-C000-4


This tweeter features a fabric dome with a large roll surround. The face plate has been optimized to provide a extended frequency response with exception off axis response. The tweeter has a chambered back designed to provide a lower resonance



frequency and reduce back wave reflections from the dome. Careful engineering has resulted in a tweeter with natural sound reproduction without coloration.

Dimensions: 100mm flange diameter; 70mm cut out hole size (notch for terminals); 3mm flange thickness, 34.14mm depth.

Impedance	4 ohm	Free air resonance Fs	680 Hz
DC resistance	3.2 ohm	Sensitivity 2.83V/1M	91 dB
V.C. inductance	0.04 mH	Qms	2.00
Effective cone area	6.2 cm ²	Qes	1.40
V.C. diameter	25.4 mm	Qts	0.80
VC height	1.3	Force factor BL Product	1.7 Tm
Air gap	2.5	Power	120 W
Linear excursion	±1.2 mm	Magnet flux density	1.25 T
Moving mass incl. air	0.3 g	Magnet weight	0.22 kg
_	=	Net weight	0.5 kg



SB15NRX30-8 5"


This 5" woofer features a proprietary composition paper cone with a special coating. The woofer uses a low damping rubber surround for better midrange reproduction. The open structure cast frame has been specially engineered for minimum reflections good air



flow. A extended length copper clad pole piece improves inductance symmetry and lessons modulation distortion.

This driver will get down to 55Hz in a 0.3 cubic foot box with a 1.5" diameter port by 6" long. Frame is 150mm in diameter.

Impedance	8 ohm	Free air resonance Fs	38 Hz
DC resistance	5.7 ohm	Sensitivity 2.83V/1M	88 dB
V.C. inductance	0.14 mH	Qms	4.80
Effective cone area	82 cm ²	Qes	0.35
V.C. diameter	30.5 mm	Qts	0.33
VC height	15	Moving mass incl. air	8.1 g
Air gap	5	Force factor BL Product	5.6 Tm
Linear excursion	±5 mm	Vas	20.7 ltrs
Magnet flux density	1.0 T	Compliance, Cms	2.17 mm/N
Magnet weight	0.54 kg	Mechanical loss, Rm	0.4 kg/s
Net weight	1.48 kg	Power	50 W
100			



SB17NRX35-8 6.5"


This 6.5" woofer features a proprietary composition paper cone with a special coating. The woofer uses a low damping rubber surround for better midrange reproduction. The open structure cast frame has been specially engineered for minimum reflections good air



flow. A extended length copper clad pole piece improves inductance symmetry and lessons modulation distortion.

This driver will get down to 50Hz in a 0.6 cubic foot box with a 2" diameter port by 7" long. Frame is 171mm in diameter.

Impedance	8 ohm	Free air resonance Fs	32 Hz
DC resistance	5.7 ohm	Sensitivity 2.83V/1M	89 dB
V.C. inductance	0.15 mH	Qms	5.00
Effective cone area	118 cm ²	Qes	0.36
V.C. diameter	35.5 mm	Qts	0.34
VC height	16	Moving mass incl. air	11.0 g
Air gap	5	Force factor BL Product	5.9 Tm
Linear excursion	±5.5 mm	Vas	44.5 ltrs
Magnet flux density	1.0 T	Compliance, Cms	2.25 mm/N
Magnet weight	0.54 kg	Mechanical loss, Rm	0.44 kg/s
Net weight	1.56 kg	Power	60 W
100			M 9 *



SB34NRX75-6 12"


This 12" woofer features a proprietary composition paper cone with a special coating. The rubber surround has been carefully chosen to properly dampen the cone movement. The open structure cast frame has been specially engineered for



minimum reflections good air flow. This woofer is a good choice for any high end 3-way speaker system or subwoofer.

This driver will get down to 37Hz in a 2.8 cf sealed box or 28Hz in 3.5 cf with a 3" diameter port by 8" long.

6 ohm	Free air resonance Fs	19 Hz
4.2 ohm	Sensitivity 2.83V/1M	90 dB
1.8 mH	Qms	5.10
508 cm ²	Qes	0.43
75.6 mm	Qts	0.40
28	Moving mass incl. air	99.0 g
6	Force factor BL Product	10.7 Tm
±11 mm	Vas	260 ltrs
±11 mm	Vas	260 ltrs
0.9 T	Compliance, Cms	0.71 mm/N
2.1 kg	Mechanical loss, Rm	2.3 kg/s
5.85 kg	Power	200 W
	4.2 ohm 1.8 mH 508 cm ² 75.6 mm 28 6 ±111 mm 0.9 T 2.1 kg	4.2 ohm 1.8 mH Cycle 1.8 mH Cycle 1.8 mH Cycle 2.8 a Cycle 2.1 kg Cycle



SB29NRX75-6 10"


This 10" woofer features a proprietary composition paper cone with a special coating. The rubber surround has been carefully chosen to properly dampen the cone movement. The open structure cast frame has been specially engineered for



minimum reflections good air flow. This woofer is a good choice for any high end 3-way speaker system.

This driver will get down to 27Hz in a 2.0 cubic foot box with a 3" diameter port by 12" long. Frame is 290mm in diameter.

Impedance	6 ohm	Free air resonance Fs	21 Hz
DC resistance	4.2 ohm	Sensitivity 2.83V/1M	88 dB
V.C. inductance	1.8 mH	Qms	5.70
Effective cone area	312 cm ²	Qes	0.38
V.C. diameter	75.6 mm	Qts	0.35
VC height	28	Moving mass incl. air	78.0 g
Air gap	6	Force factor BL Product	10.7 Tm
Linear excursion	±11 mm	Vas	102 ltrs
Magnet flux density	0.9 T	Compliance, Cms	0.74 mm/N
Magnet weight	2.1 kg	Mechanical loss, Rm	1.8 kg/s
Net weight	5.3 kg	Power	200 W




SB42KHC75-6 15"

This 15" woofer features a Kevlar Honeycomb cone. The rubber surround has been carefully chosen to properly dampen the cone movement. The open structure cast frame has been specially engineered for minimum reflections good



air flow. This woofer is a good choice for any high end 3-way speaker system or subwoofer.

This driver will get down to 32Hz in a 4.5 cubic foot box with a 4" diameter port by 8" long, 50% poly filling.





Model	Imp Ω	Fs Hz	Qts	Vas Ltrs	Power @12dB	dB 283V/m	Xmax mm P	Box Liter S ealed/ V ented	F3 Hz	Price Each
Revelator Series Tweeters										
R2904/7000-00: Premium Ring Radiator - Silver	4	520			160@2.5k	94.5	0.2			\$398.00
R2904/7000-05: Premium Ring Radiator - Black w/silver plug	4	520			160@2.5k	94.5	0.2			\$398.00
R2904/7000-09: Premium Ring Radiator - Black	4	520			160@2.5k	94.5	0.2			\$398.00
D2904/7100-02: Premium Wide Surround Tweeter - Silver	4	520			160@2.5k	94.5	0.2			\$285.00
D2904/7100-03: Premium Wide Surround Tweeter - Black	4	520			160@2.5k	94.5	0.2			\$285.00
D2905/9900 : 1" textile dome, SD-2, LCD, NRC, CDD	8	500			225@2.8k	91	0.4			\$241.00
D2904/9800: 1" aluminum dome, diffuser, SD-2, NRC	4	500			160@2.8k	90	0.1			\$206.00
D2905/9700 : 1" textile dome, SD-2, LCD, NRC	8	500			225@2.8k	89.5	0.4			\$164.00
D2904/6000-00 : 1" dome, neodymium magnet, grill - 60mm flange	4	750			150@2.7k	90	0.25			\$208.00
D2904/6000-0 1: 1" dome, neodymium magnet - 60mm flange	4	750			150@2.7k	90.5	0.25			\$200.00
D3004/6600-00: 1" dome, AirCirc, neodymium magnet	4	520			160@2.5k	92.5	0.2			\$220.00
Rev	elato	or Seri	es Mi	dran	iges					
12M/4631G: 4.5" slit paper cone, neodymium magnet, R3	4	75	0.33	2.4	40@75	89	3.0	0.7 / 1.0	160 / 100	\$285.00
15M/4531K: 5" slit paper cone midrange, Glass former	4	35	0.22	24		90	3.0	3.0 / 5.0	100 / 70	\$222.00
Revelato	r Sei	ries Mi	id/Ba	ss &	Woofers					
15W/4531G: 5" slit paper cone, NRCS, SD-1, R3, Glass former	4	39.5	0.32	16	60	87	6.5	4 / 6	88 / 58	\$223.00
15W/8530K-00 : 5" paper cone, NRCS, SD-1, R3, Glass former	8	30	0.27	28	60	85.5	6.5	5.1 / 7.4	77 / 55	\$212.00
15W/8531K-00 : Same as 15W/8530K-01, but with non-coated mat ap	pearar	nce								\$217.00
15W/8530K-01 : 5" paper cone, NRCS, SD-1, R3, Glass former	8	30	0.35	28	60	84.5	6.5	9.5 / 15	60 / 40	\$212.00
18W/4531G: 7" slit paper cone, SD-1, R3, Glass former	4	33	0.35	42	70	90	6.5	14 / 23	65 / 41	\$232.00
18W/8531G: 7" slit paper cone, SD-1, R3, Glass former	8	28	0.36	59	60	87	6.5	21 / 36	54 / 35	\$225.00
22W/4851T: 8" hard paper cone, SD-1, Titanium former	4	20.5	0.22	127	170	89	9.0	10 / 28	70 / 40	\$344.00
22W/8851T: 8" hard paper cone, SD-1, Titanium former	8	21	0.25	127	170	88	9.0	18 / 34	60 / 38	\$347.00
22W/8857T: 8" Black Aluminum cone, SD-1, Titanium former	8	23	0.30	89	170	89	9.0	14 / 35	60 / 38	\$308.00
26W/8861T: 10" hard paper cone, SD-1, Titanium former	8	19	0.31	234	170	88.5	9.0	55 / 90	40 / 28	\$375.00
26W/4867T: 10" Black Aluminum cone, SD-1, Titanium former	4	18	0.30	223	170	89	9.0	46 / 71	43 / 29	\$339.00
26W/8867T: 10" Black Aluminum cone, SD-1, Titanium former	8	19	0.29	179	170	87	9.0	36 / 57	46 / 31	\$354.00
23W/4557T: 10" Aluminum Cone, SD-1, Titanium former	4	20.5	0.44	43.5	225	83	13	28 / 59	33 / 27	\$385.00
23W/0-00: 10" Aluminum Cone Passive Radiator	F	s 10.5 Hz	z, Sd 23	32 cm ²	, Mms 400g,	Vas 43.5	Ltrs, Qr	ns 11.5, Excursion	<u>+</u> 20mm	\$163.00
Classic Se	ries [Γweete	rs an	d Mi	d/Tweete	r				
D2010/8513: 3/4" dome, chamber, foam on faceplate, ff	8	800			150@4k	90	0.7			\$77.00
D2905/9300 : 1" textile dome, chamber, FF	8	650			150@2.5k	90	0.4			\$129.00
D2905/9500 : 1" textile dome, NRC, FF	8	550			150@2.5k	90	0.4			\$132.00
	Class	ic Seri	es Wo	ofer	S			·		
18W/8535 : 7" carbon paper cone, SD-1, R3	8	26	0.38	72	70	86.5	5.0	30 / 46	48 / 33	\$174.00
18W/8545 : 7" carbon paper cone, SD-1, R3	8	28	0.27	48	100	88	6.5	8 / 15	75 / 46	\$164.00
18W/8545K: 7" carbon paper cone, SD-1, R3, Glass former	8	28	0.28	48	100	87.5	6.5	9 / 19	70 / 42	\$167.00
Replacement voice coils and reconing are available for many Scan-s	speak 1	products.	. Repla	acemei	nts for produ	ets that ca	ın't be re	paired may be avail	able at a di	scount.

Scan-speak is creating a new line of loudspeakers called **Illuminator**. This new line will begin with three tweeters, a 5" and a 6" woofer.

The **Illuminator tweeters** will be available with a 3/4" dome and 1" dome. There will be two versions of the 1" dome, one with a shallow chamber on the back (perhaps more suitable for automotive use) and one with a deeper chamber on the back. The rear chambers have been designed to reduce rear wave reflections and to act as a heat sink. The tweeters have small flange sizes for mounting in tight spaces. The tweeter motors feature neodymium ring magnets and contoured pole pieces for an open flow to the rear chamber. Both sides of the voice coil gap are lined with copper shorting rings that enable brilliant high frequency extension while reducing distortion.

The **Illuminator mid woofers** have exceptionally long throw, producing the bass output of drivers one size up. Both the 5 1/4" and the 6 1/2" have peak a peak x-max of 10mm. This performance is achieved with a patent pending neodymium ring magnet motor that delivers a large force factor. The underhung voice coil is precision wound with CCAW ribbon wire on a titanium former for increased power handling. The vented pole piece has a contoured opening to eliminate any hint of turbulence noise. The uniquely shaped top plate and open frame ensure there is virtually no dynamic compression caused by restriction of the diaphragm back wave.

We will introduce these drivers on our website as they become available. www.madisound.com

SCANSPEAK The Solist SCANSPEAK


Madisound is pleased to offer Solist, a very precise MTM speaker system. We are confident that we have a achieved a speaker that meets or exceeds the expectations of today's discerning Audiophile.


The **Solist** is capable of delivering the most demanding passage without losing the delicacy of every nuance. The Solist immediacy about it that elicits excitement in the listener, yet is never fatiguing. We have listened to the **Solist** on both transistorized amplifiers and tube amplifiers and found both to be pleasing.

The Solist is designed around the popular Scan-speak 18W/8545K carbon/paper cone 7" woofer. This 18W/8545K features a heavily damped and carbon fibre impregnated paper cone that dampens resonances normally associated with stiff cones. The magnet system is the



SD-1 system which eliminates modulation and dynamic distortion, as well as lowering clipping distortion created as the voice coil exceeds its maximum linear excursion. This woofer uses the new Fiber Glass non-conducting high temperature voice coil former, which improves bass





Width 8 3/4"

Height 24" Depth 13 1/2"

response and resolution in the midrange frequencies. A new type of rubber surround combines dynamic linearity with low coloration.

The Solist high frequencies are reproduced by the D2905/9700 tweeter. The D2905/9700 tweeter which uses the same motor as the Revelator tweeter, but with the standard flange. The Revelator motor is state of the art, using SD caps and shorting rings that minimize electrical phase shift. The top plate has been carefully machined to reduce air noises and compression from behind the dome and to assist in cooling the voice coil. The hand coated textile

dome is a refinement of earlier versions and also incorporates a special devise behind the dome to minimize dynamic compression. The 28mm voice coil uses plastic coated aluminum wire on aluminum voice coil former.



No ferrofluid is used in the air gap.

The crossover network was designed using our anechoic chamber, Audio Precision and the Linearx Leap software. The acoustical 18dB bi-wire network yields a seamless response from 40Hz to 20KHz. This Premium uses some 14 awg Goertz Copper Foil crossover inductors, Solen Polypropylene capacitors, Hoyland Musicaps and Eagle resistors.

The cabinets are fully assembled oak veneered MDF with solid rounded oak corners in clear coat or black painted finish. The front and back are black and the front is covered by a full black grill. You can further upgrade the cabinet by installing the Deflex damping pads to reduce cabinet resonances and cut down on internal reflections.

Price per pair without cabinets \$1140.00

Deflex Panel Upgrade: 10 panels and glue: Add \$103.86

Supra Classic wiring is supplied for internal wiring. Cabinets are no longer available for this speaker.

SCANSPEAK

D3004/6600-00 AirCirc 4Ω

The new D3004/660000 builds on the experience of the one-inch R29 ring radiator, resulting in low resonance frequency, but further provides the extended dispersion characteristics of a 3/4-inch dome. Tymphany's unique AirCirc Magnet System — named for the way it optimizes air flow within the chamber – rearranges the traditional




magnet structure from a single magnet to an open magnetic circuit comprised of six separate neodymium slugs. This, in combination with the chamber, results in the elimination of the reflections and resonances that compromise the performance of traditional motors.

TECHNICAL DATA: Sensitivity 2.83V/1M Free air resonance Fs DC resistance V.C. inductance Power 12dB@Hz Effective cone area V.C. diameter V.C. heiaht

92.5dB 520 Hz 3.0 ohm 0.03 mH 160W@2.5K 7 cm² 26 mm 2.1 mm 2.5 mm

Lin. & max. excursion Air gap flux density Force factor BL Product Moving mass incl. air Outside diameter Cutout diameter Flange thickness Depth Screw Circle

±0.2 / ±1.6 mm 2.5 Tm 0.35 g 104 mm 77 mm 5 mm 23 mm 90 mm



R2904/7000-00 4Ω

The R2904/7000 tweeter is the new flagship tweeter in the Scan-speak line. tweeter incorporates many innovative design concepts.

The first notable difference is the use of a phase plug. The dome is attached to the phase plug, so the radiating area is now concentrated around the voice coil.

This offers more control and reduces distortion and loss that occur at the center of the dome on dome tweeters. The phase plug also acts as a wave guide, reducing high frequency cancellations. A specially designed venting system uses a needle to cut down on turbulence in the air cavity. Better dynamics are achieved b using ferrofluid, voice coil cooling is performed venting system and conduction through copper The new SD-2 neodymium magnet system imp transient response.




by the	- 0 0
rings.	
oroves	
	Disabilities and it

TECHNICAL DATA:
Sensitivity 2.83V/1M
Free air resonance Fs
DC resistance
V.C. inductance
Power 12dB@Hz

94.5dB 520 Hz 3.0 ohm 0.01 mH 150W@2.7K

Effective cone area V.C. diameter Lin. & max. excursion Force factor BL Product Moving mass incl. air Net weight

5.6 cm² 28 mm ±0.2 / ±1.6mm 2.8 Tm 0.42 kg



D2904/7100-00 4Ω

The D2904/7100 tweeter is a 1" soft dome with wide surround, using the

same chambering as the Ring Radiator.
The carefully designed dome and surround result in a linear response and an exceptionally good off axis response. Note the smooth roll off on the low end, making this tweeter a good choice for simple slopes


A specially designed venting system uses a needle to cut down on turbulence in the air cavity. Better dynamics are achieved by not using ferrofluid, voice coil cooling is performed by the venting system and conduction through copper The new SD-2 neodymium rings. system improves magnet transient response.



TECHNICAL DATA: Sensitivity 2.83V/1M 94.5dB Free air resonance Fs DC resistance V.C. inductance Power 12dB@Hz

V.C. diameter 520 Hz Lin. & max. excursion 3.0 ohm Force factor BL Product Moving mass incl. air 160W@2.5K Net weight

7 cm² 28 mm ±0.2 / ±1.6mm 2.8 Tm 0.42 kg



SCANSPEAK

D2905/9900 **Revelator Dome Tweeter**

The D2905/9900 is our state of the art tweeter. This "revelation" is a 1" textile dome tweeter that will reach new borders within high-end loudspeaker drive units. The new magnet system with SD caps and rings that eliminate the electrical phase shift. The new chamber design reduces air noises and compression. The 130mm machined aluminum front plate has more controlled directivity (down to 2Khz). The textile dome is hand coated and a special device is placed behind it to reduce dynamic compression.



TECHNICAL DATA:
Sensitivity 2.83V/1M
Free air resonance Fs
DC resistance
V.C. inductance
Power
Effective cone area
V.C. diameter

91dB 500 Hz 4.7 Ω 0.01 mH 225W@2.8kHz BL 8.5 cm

V.C. height Air gap height

Lin. & max. excursion Air gap flux density Moving mass incl. air

3.5 Tm 0.45 g 0.8 kg

 $\pm 0.4/ \pm 1.5 \text{ mm}$

28 mm Net weight V.C. diameter

SCANSPEAK

D2904/9800 4Ω

The D2904/9800 is a high-end 1" aluminum dome tweeter. The magnet system uses the Symmetric Drive technology that almost eliminates electrical phase shift. The specially designed chamber reduces air noise and compression. The geometry of the dome causes the "break-up" to appear beyond the audible range. A specially designed diffusor is used to equalize the response in the upper octave. tweeter has a very clear and open sound.




TECHNICAL DATA: Sensitivity 2.83V/1M Free air resonance Fs DC resistance V.C. inductance Power 12dB@Hz Effective cone area V.C. diameter V.C. height Air gap height

90dB 500 Hz 3.5 ohm 0.01 mH 160W@2.8K 8.5 cm² 28 mm

Lin. & max. excursion Air gap flux density Force factor BL Product Moving mass incl. air Net weight Vas Qms Qes

+0.1 / +1.5 mm 2.8 Tm 0.50 g 0.7 kg




D2905/9700 1" Dome Tweeter

The D2905/9700 uses the same hand coated dome and voice coil of the D2905/9500, but uses the motor system of the Revelator. The Symmetric Drive technology eliminates almost all electrical phase shift. The carefully machined top plate minimize air noise and compression. Copper caps act as heat conductors. High power handling is achieved without ferrofluid and is achieved without ships in a chief. improves micro-dynamic linearity. The tweeter has excellent dynamic and detailing capability.



89.5dB 500 Hz 4.7 Ω	Lin. & max. excursion Air gap flux density BL	±0.4/ ±1.5 r - 3.5 Tm
0.01 mH	Moving mass incl. air	0.45 g
225W@2.8kHz	Net weight	0.7 kg
8.5 cm ²	Vas	-
28 mm	Qms	-
-	Qes	-
-	Qts	-
	500 Hz 4.7 Ω 0.01 mH 225W@2.8kHz 8.5 cm ²	500 Hz Air gap flux density 4.7 Ω BL 0.01 mH Moving mass incl. air 225W@2.8kHz Net weight 8.5 cm² Vas 28 mm Qms - Qes



D2904/6000-01 4Ω


The D2904/6000-01 tweeter has a coated textile dome and a neodymium magnet system. speaker uses a compact self shielding Symmetric Drive magnet system, utilizing three powerful neodymium magnets. The cavity under the voice coil is coupled to the chamber through eight holes in the top plate. Pure cotton is used as damping material. The textile diaphragm is carefully hand coated. reproduction is very dynamic and open, with low levels of compression. Perfect for A/V. Also available with grill D2904/6000-00.

ECHNICAL DATA:	
Sensitivity 2.83V/1M	90.50
ree air resonance Fs	750 H
OC resistance	3.5 o
/.C. inductance	0.02
Power 12dB@Hz	150V

dB Ηz hm 150W@2.7K

Effective cone area V.C. diameter Lin. & max. excursion Force factor BL Product Moving mass incl. air Net weight

8 cm² 28 mm ±0.25 / ±1.3mm 2.7 Tm 0.13 kg




SCANSPEAK

12M/**4631G** 4Ω Revelator 4.5" Midrange

The 12M/4631G is a Revelator driver using the "slit cone" technology. Some of the slits are used to control cone resonance and the other set of slits add rigidity. This speaker also has the new dynamic linear suspension for lower compression and higher linearity. Every facet of this driver is designed to reduce resonance in all structures. neodymium magnet has been chosen to reduce the depth, yet increase the magnetic energy. The short field length of a neodymium magnet also allows this driver to by used for A/V.



TECHNICAL DATA:		V.C. height	-
Sensitivity 2.83V/1M	89dB	Air gap height	-
Free air resonance Fs	75 Hz		
DC resistance	3.2Ω	Lin. & max. excursion	±3/ ±7 m
V.C. inductance	0.22 mH	Air gap flux density	-
Power	40W	BL	5.3 Tm
Effective cone area	49 cm ²	Moving mass incl. air	6.5 q
V.C. diameter	38 mm	Net weight	0.51 kg




SCANSPEAK

15M/4531K-00 4 Ω

The 15M/4531K-01 is a 5 1/2" Revelator midrange. It features a slit-paper non-resonant cone and dust cap structure, dynamic linear suspension, SD-1 magnet system, "Grasshopper" cast chassis with maximized air flow, glass fiber voice coil former and resonance terminating mounting system. The 15M/4531K is intended for use as a midrange, with a usable frequency range between 100Hz and 6kHz. As you can see from the response curve, this speaker has a lot of energy in the upper frequency range.



TECHNICAL DATA:			
Sensitivity 2.83V/1M	90 dB	Lin. & max. excursion	±3 & ±8mm
Free air resonance Fs	35 Hz	Air gap flux density	-
DC resistance	3.5 ohm	Force factor BL Product	6.0 Tm
V.C. inductance	0.17 mH	Moving mass incl. air	11 g
Power 12dB@Hz	60W	Net weight	1.6 kg
Effective cone area	95 cm ²	Vas	24 ltrs
V.C. diameter	38 mm	Qms	4.8
V.C. height		Qes	0.24
Air gap height	-	Qts	0.22
COL CIPY			



15S/8530K-01 - Magnetically Shielded

The 15S/8530K-01 is a 5 1/2" Revelator mid/woofer. It features a non-resonant cone and dust cap structure, dynamic linear suspension, SD-1 magnet system, "Grasshopper" cast chassis with maximized air flow and resonance terminating mounting system. Less resonance in all structures, lower compression and higher linearity, faster termination of excess energy and higher sound pressure capability make the 15W have more musical and dynamic capability than any other 5 ½" we know of. Shielded for use near a CRT.



TECHNICAL DATA:
Sensitivity 2.83V/1M
Free air resonance Fs
DC resistance
V.C. inductance
Power 12dB@Hz
Effective cone area
V.C. diameter
V.C. height
Air gap height

SPL [dB]

84.5dB 30 Hz 5.8 ohm 0.35 mH 60W 95 cm² 38 mm

Lin. & max. excursion Air gap flux density Force factor BL Product Moving mass incl. air Net weight Vas Oms Qes Qts

±6.5 & ±9mm 13 g 1.3 kg 28 ltrs 4.9 0.38 0.35



The 15W/4531G-01 is a 5 1/2" Revelator mid/woofer.

15W/**4531G-00 4** Ω


It features a slit-paper uncoated non-resonant cone and dust cap structure, dynamic linear suspension, SD-1 magnet system, "Grasshopper" cast chassis with maximized air flow, glass fiber voice coil former and resonance terminating mounting system. The 15W/4531G provides a more extended frequency response than it's brothers, but still fantastic bass down to the mid 50's in a vented enclosure. This version is only available in 4 ohm.



TECHNICAL DATA:
Sensitivity 2.83V/1M
Free air resonance Fs
DC resistance
V.C. inductance
Power 12dB@Hz
Effective cone area
V.C. diameter
V.C. height
Air gap height

39.5 Hz 3.4 ohm 0.25 mH 60W 95 cm² 38 mm

Lin. & max. excursion ±6.5 & ±9mm Air gap flux density Force factor BL Product 5.7 Tm Moving mass incl. air 13 g 1.6 kg Net weight 16 ltrs Vas Qms 4.6 0.34 Qes Qts 0.32



SCANSPEAK

15W/8530K-00/01

The 15W/8530K-01 is a 5 1/2" Revelator mid/woofer. It features a non-resonant cone and dust cap structure, dynamic linear suspension, SD-1 magnet system, "Grasshopper" cast chassis with maximized air flow and resonance terminating mounting system. Less resonance in all structures, lower compression and higher linearity, faster termination of excess energy and higher sound pressure capability make the 15W have more musical and dynamic capability than any other 5 ½" we know of. Wonderful bass in a small box!



TECHNICAL DATA:
Sensitivity 2.83V/1M
Free air resonance F
DC resistance
V.C. inductance
Power 12dB@Hz
Effective cone area
V.C. diameter
V.C. height
Air gap height

85 5/84 5dB 30 Hz 5.8 ohm 0.35 mH 60W 95 cm² 38 mm

Lin & max excursion Air gap flux density Force factor BL Product 7/6.1 Tm Moving mass incl. air Net weight Vas Qms Qes

13 g 1.6/1.3 kg 28 ltrs 4.9 0.29/0.38 0.27/0.35

+6.5 & +9mm

Ots

SCANSPEAK

18W/4531G 4Ω

The 18W/4531G-00 is a 7" Revelator mid/woofer. It features a non-resonant cone and dust cap structure, dynamic linear suspension, SD-1 magnet system, "Grasshopper" cast chassis with maximized air flow and resonance terminating mounting system. Less resonance in all structures, lower compression and higher linearity, faster termination of excess energy and higher sound pressure capability. The 18W/4531G should have an F3 of about 65Hz sealed and 40Hz vented.




TECHNICAL DATA: Sensitivity 2.83V/1M Free air resonance Fs DC resistance V.C. inductance Power Effective cone area V.C. diameter VC height Air gap

90dB 33 Hz 3.4 ohm 0.3 mH 70W 150 cm² 38 mm

Lin. & max. excursion Air gap flux density Force factor BL Product Moving mass incl. air Net weight Vas Qms Oes Qts

 $\pm 6.5 / \pm 11 \text{ mm}$

5.7 Tm 17.5 g 1.75 kg 42 Itrs 5.2 0.38 0.35



18W/8531G 8Ω

The 18W/8531G-00 is a 7" Revelator mid/woofer. It features a non-resonant cone and dust cap structure, dynamic linear suspension, SD-1 magnet system, "Grasshopper" cast chassis with maximized air flow and resonance terminating mounting system. resonance in all structures, lower 1 compression and higher linearity, faster termination of excess energy and higher sound pressure capability. The 18W/8531G should have an F3 of about 50Hz sealed and 35Hz vented.




TECHNICAL DATA:
Sensitivity 2.83V/1M
Free air resonance Fs
DC resistance
V.C. inductance
Power
Effective cone area
V.C. diameter
VC height
Air gap

87dB 27.5 Hz 5.8 ohm 0.35 mH 70W 150 cm² 38 mm

Lin. & max. excursion $\pm 6.5 / \pm 11 \text{ mm}$ Air gap flux density Force factor BL Product 6.7 Tm Moving mass incl. air Net weight Vas Qms Qes Ots

15.5 g 1.75 kg 61 ltrs 5.0 0.39 0.36



18W/16531G 16 Ω

The 18W/16531G-00 is a 7" Revelator mid/woofer. It features a non-resonant cone and dust cap structure, dynamic linear suspension, SD-1 magnet system, "Grasshopper" cast chassis maximized air flow and resonance terminating mounting system. Less resonance in all structures, lower compression and higher linearity, faster termination of excess energy and higher sound pressure capability. This is a 16 ohm woofer, a perfect choice for multiple woofer systems.




TECHNICAL DATA: Sensitivity 2.83V/1M Free air resonance Fs DC resistance V.C. inductance Power Effective cone area V.C. diameter VC height Air gap

83dB 27 Hz 12.2 ohm 0.6 mH 60W 150 cm² 38 mm

Lin. & max. excursion Air gap flux density Force factor BL Product Moving mass incl. air Net weight Vas Qms Qes

 $\pm 6.5 / \pm 11 \text{ mm}$ 9 4 Tm 18 g 1.75 kg 61.5 ltrs 4.7 0.42 0.39



SCANSPEAK

Ots

SCANSPEAK

22W/4851T 4Ω

The 22W/4851T is a new addition to the Revelator line. This robust 8" woofer was designed to provide deep and accurate bass in a small enclosure. This woofer features a 2" voice coil on a titanium former, a low loss linear suspension and symmetric drive motor. The deep set hard paper cone is attached to the frame with a minimal reflection rubber surround. The 9mm X-max insures good linear travel.

We suggest a 1.2 cubic foot enclosure with a 2"Ø vent by 8" long for and F3 of 50Hz.



TECHNICAL DATA:
Sensitivity 2.83V/1M
Free air resonance F
DC resistance
V.C. inductance
Power
Effective cone area
V.C. diameter
VC height
Air gap

TECHNICAL DATA

89 dB 20.5 Hz 3.7 ohm 0.3 mH 170 W 220 cm² 50 mm

Lin. & max. excursion Air gap flux density Force factor BL Product 8.2 Tm Moving mass incl. air Net weight Vas Qms Oes Ots

 $\pm 9 / \pm 14 \text{ mm}$ 32.5 g 3.6 kg 127 ltrs 52 0.23 0.22

22W/8851T 8Ω

The 22W/8851T is a new addition to the Revelator line. This robust 8' woofer was designed to provide deep and accurate bass in a small enclosure. This woofer features a 2" voice coil on a titanium former, a low loss linear suspension and symmetric drive motor. The deep set hard paper cone is attached to the frame with a minimal reflection rubber surround. The 9mm X-max insures good linear travel.

We suggest a 1.2 cubic foot enclosure with a 2.5"Ø vent by 8" long for and F3 of 38Hz.



TECHNICAL DATA: Sensitivity 2.83V/1M 88 dB Free air resonance Fs 21 Hz 6.2 ohm DC resistance V.C. inductance 0.35 mH Power 170 W Effective cone area 220 cm² V.C. diameter 50 mm VC height Air gap


Lin. & max. excursion Air gap flux density Force factor BL Product 9.9 Tm Moving mass incl. air Net weight Vas Qes Qts

0.26 0.25

 $\pm 9 / \pm 14 \text{ mm}$

31 g 3.6 kg

127 ltrs




22W/8857T 8


The 22W/885TT is a new addition to the Revelator line. This robust 8" the Revelator line. woofer was designed to provide deep and accurate bass in a small enclosure. This woofer features a 2" voice coil on a titanium former, a low loss linear suspension and symmetric drive motor. The deep set black aluminum cone is attached to the frame with a minimal reflection rubber surround. The 9mm X-max insures good linear travel.

We suggest a 1.2 cubic foot enclosure with a 2" Ø vent by 8" long for and F3 of 38Hz.



TECHNICAL DATA: Sensitivity 2.83V/1M Free air resonance Fs DC resistance V.C. inductance Power Effective cone area	86 dB 23 Hz 6.2 ohr 0.35 m 170 W 220 cm
V.C. diameter	50 mm
VC height	-
Air gap	_





26W/8861T 8Ω


The 26W/8861T is a new addition to the Revelator line. This robust 10" woofer was designed to provide deep and accurate bass in a small enclosure. This woofer features a 2" voice coil on a titanium former, a low loss linear suspension and symmetric drive motor. The deep set hard paper cone is attached to the frame with a minimal reflection rubber surround. The 9mm X-max insures good linear travel.

We suggest a 2.75 cubic foot enclosure with a 3"Ø vent by 9.5" long for and F3 of 30Hz.



TECHNICAL DATA:	
Sensitivity 2.83V/1M	88.5 dB
Free air resonance Fs	19 Hz
DC resistance	6.2 ohm
V.C. inductance	0.35 mH
Power	170 W
Effective cone area	320 cm ²
V.C. diameter	50 mm
VC height	-
Air gap	-

Lin. & max. excursion	±9 / ±14 mm
Air gap flux density	-
Force factor BL Product	9.9 Tm
Moving mass incl. air	43.5 g
Net weight	3.7 kg
Vas	234 ltrs
Qms	5.2
Qes	0.33
Ote	0.31



SCANSPEAK

26W/4867T 4Ω

The 26W/4867T a new black Aluminum cone woofer. Aluminum is a good material for subwoofer cones, very stiff and light. These cones reduce distortion and also help cool the voice coil, by conducting heat away from the coil. This woofer has a low loss suspension for increased bass response and the SD-1 motor system for less intermodulation distortion. Very rigid cast frame, large windows.

We recommend a 2.5 cubic foot enclosure with a 3" diameter vent by 10" long, the F3 would be about 29Hz.



TECHNICAL DATA: Sensitivity 2.83V/1M
Free air resonance Fs
DC resistance
V.C. inductance
Power
Effective cone area
V.C. diameter
VC height
· O Holgin

Air gap

89 dB 18 Hz 3.7 ohm 0.25 mH 170 W 320 cm² 50 mm

Lin. & max. excursion Air gap flux density Force factor BL Product Moving mass incl. air Net weight Vas Qms **Qes**

 $\pm 9 / \pm 14 \text{ mm}$ 8.3 Tm 51 g 3.7 kg 223 Itrs 5.8 0.31

0.30

SCANSPEAK

26W/8867T 8Ω


The 26W/8867T a new black Aluminum cone woofer. Aluminum is a good material for subwoofer cones, very stiff and light. These cones reduce distortion and also help cool the voice coil, by conducting heat away from the This woofer has a low loss suspension for increased bass response and the SD-1 motor system for less intermodulation distortion. Very rigid cast frame, large windows.


We recommend a 2.3 cubic foot enclosure with a 3" diameter vent by 11" long, the F3 would be about 29Hz.



87 dB
19 Hz
5.8 ohn
0.4 mH
170 W
320 cm
50 mm
-
-

Lin. & max. excursion $+9/\pm14$ mm Air gap flux density Force factor BL Product 11.2 Tm 57 g 3.7 kg Moving mass incl. air Net weight 179 ltrs Vas Qms 4.5 0.31 Qes 0.29





23W/**4557T** 4Ω

The 23W/4557T is a very high end subwoofer, designed to be used with a passive radiator in a small enclosure. This sub has a very rigid aluminum cone, low loss rubber surround and cast frame. The passive radiator is similar, but with a weight attached to the bass of the cone. The 23W/4557T is using the SD-1 motor system. There are gold plated binding posts and the woofer is covered by a decorative rubber cap.


Frequency response with the passive is down to 25Hz. One cubic foot sealed has an F3 of 33Hz.



Sensitivity 2.83V/1M	82 dB
Free air resonance Fs	20.5 Hz
DC resistance	3.45 ohm
V.C. inductance	0.45 mH
Power	225 W
Effective cone area	232 cm ²
V.C. diameter	50 mm
VC height	-
Air gap	-

TECHNICAL DATA:

Lin. & max. excursion ±13 / ±20 mm Air gap flux density Force factor BL Product 9.3 Tm Moving mass incl. air 101 g Net weight 4.6 kg Vas 45.6 ltrs Qms 48 0.52 Oes Qts




23W/0-00 Passive

This is the passive radiator intended for use with the 23W/4557T active woofer. We recommend putting both in a 1.0 cubic foot enclosure. should yield a bass response down to 25Hz. The woofer should still be linear at 180 watts and have an output of about 104dB.

The curve below is a simulation of the woofer and passive radiator in a 1.0 cubic foot box. This was done in Bass Box Pro by Harris Technologies.



TECHNICAL DATA:			
Sensitivity 2.83V/1M	- dB	max. excursion	±20 mm
Free air resonance Fs	10.5 Hz	Air gap flux density	-
DC resistance	- ohm	Force factor BL Product	- Tm
V.C. inductance	- mH	Moving mass incl. air	400 g
Power	- W	Net weight	1.2 kg
Effective cone area	232 cm ²	Vas	43.5 ltrs
V.C. diameter	- mm	Qms	11.5
VC height	-	Qes	-
Air gap	-	Qts	-



SCANSPEAK

SCANSPEAK

D2008/8512

Double chambered 3/4" damped textile dome tweeter. The voice coil is a precision wound aluminum wire with a 27 strand tinsel braid for a lower The magnet system is a resonance. special high flux ferrite with vented pole plates. The surround of the diaphragm is damped to reduce distortion.

This tweeters extremely response, low distortion and dispersion make it an attractive choice for any speaker system.



TECHNICAL DATA:	
Characteristic sensitivity	90dB 1W/1m
Free air resonance fs	800 Hz
DC resistance	5.8 ohm
V.C. inductance	0.08 mH
Power 12db@Hz	150W@4K
Effective cone area	3.8 cm ²
V.C. diameter	19.0 mm

V.C. height

0 Hz 3 ohm 08 mH 0W@4K 3 cm² 19.0 mm 3 2 mm Air gap height 1.6 mm

Lin. & max. excursion Air gap flux density Force factor BL Product Moving mass incl. air Net weight Vas Qms Oes

 $\pm 0.8 / \pm 1.2 \text{ mm}$ 1.6 T 1.8 Tm

D2010/8513

Similar to the D2008, but with several improvements, a foam impregnated front face plate and a lower resonance. Double chambered 3/4" damped textile dome tweeter with the same diaphragm and voice coil as the D2008.

The lower resonance of this driver will allow it to be crossed over lower than most other 3/4" dome tweeters, yet retain the low distortion and clarity of a 3/4" dome. We recommend a steeper x-over slope be used when the x-over point is below 3KHz.



TECHNICAL DATA:	
Sensitivity 2.83V/1M	
Free air resonance Fs	
DC resistance	
V.C. inductance	
Power 12dB@Hz	
Effective cone area	
V.C. diameter	
V.C. height	

Air gap height


90dB 800 Hz 5.7 ohm 0.07 mH 150W@4K 3.8 cm² 19 mm

Lin. & max. excursion Air gap flux density Force factor BL Product Moving mass incl. air Net weight Qms

0.25 g 0.4 kg

2.4 Tm

±0.7 / ±1.2 mm



Qts

Qes

Ots


D2905/9300 1" Dome Tweeter

The D2905/9300 is a 1" textile dome tweeter with a very flat frequency response and low distortion. The D2905/9300 achieves a lower resonance and increased clarity by using several coatings of damping material on the dome and chambering behind the dome. Both these damping factors and the use of a light magnetic fluid, reduce the resonances as much as possible, while reducing compression affects. tweeters linear response and openness make it a good choice for any system.



TECHNICAL DATA:	
Sensitivity 2.83V/1M	90dB
Free air resonance Fs	650 Hz
DC resistance	4.7 ohm
V.C. inductance	0.08 mH
Power 12dB@Hz	150W@2
Effective cone area	8.5 cm ²
V.C. diameter	28 mm
V.C. height	-
Air gap height	-

3 Hz ohm mH W@2.5K cm²	Lin. & max. excursion Air gap flux density Force factor BL Product Moving mass incl. air Net weight Vas Qms Qes	±0.4 / ±1.5 mm - 3.5 Tm 0.45 g 0.7 kg
	Qts	-



D2905/9500 1" Dome Tweeter


The D2905/9500 is similar to the D2905/9300, but with non-resonant chamber. The optimized pole piece geometry reduces flow resistance and the anti-resonator-plug in the rear chamber eliminates turbulence. A light ferrofluid is used in the air gap to ensure optimal linear mechanical behavior and minimal micro-dynamic non-linearity. tweeter has a smooth transparent sound and very low levels of distortion. A perfect choice for any high end system.



TECHNICAL DATA:
Sensitivity 2.83V/1M
Free air resonance Fs
DC resistance
V.C. inductance
Power 12dB@Hz
Effective cone area
V.C. diameter
V.C. height
Air gap height

90dB 550 Hz 4.7 ohm 0.08 mH 150W@2.5K 8.5 cm² 28 mm

Lin. & max. excursion $\pm 0.4 / \pm 1.5 \text{ mm}$ Air gap flux density Force factor BL Product 3.5 Tm Moving mass incl. air 0.45 g Net weight 0.7 kg Vas Qms Qes Qts



SCANSPEAK

D3806/8200 1.5" Dome Mid/Tweeter

D3806/8200 is a dome midrange/tweeter. The magnet system incorporates the Symmetric Drive technology. The pole piece is vented technology. The pole piece is vented and damped by a porous foam pad for correct tuning and coupling of the rear chamber. The surround is partially covered by a front ring to minimize distortion and improve phase response. The low resonance allows for a low crossover point. The frequency response in smooth and the tweeter has good dispersions dispersion s.



TECHNICAL DATA:
Sensitivity 2.83V/1M
Free air resonance Fs
DC resistance
V.C. inductance
Power 12dB@Hz
Effective cone area
V.C. diameter
V.C. height
Air gan height

Hz

Lin. & max. excursion	
Air gap flux density	
Force factor BL Product	;
Moving mass incl. air	(
Net weight	
Vas	
Qms	
Qes	
Qts	

n. & max. excursion	±0.4 / ±1 mm
ir gap flux density	-
orce factor BL Product	3.8 Tm
loving mass incl. air	0.90 g
et weight	1.2 kg
as	-
ms	-
es	-
rts	-

SCANSPEAK

18W/8535 7" Carbon/Paper Woofer

The 18W/8535 woofer features the SD-1 magnet system which almost eliminates modulation and dynamic distortion and reduce clipping when the drivers is taken beyond linear excursion. The carbon fiber filled paper cone is impregnated and coated to damp resonance. The low loss rubber surround combines dynamic linearity with low coloration. The smaller magnet increases the Qts making this driver a good choice for a sealed enclosure.



15.5 g


2.5 kg

0.45

0.38

72 liters

 $\begin{array}{ll} \text{Lin. \& max. excursion} & \pm 5 \, / \, \pm 10 \; \text{mm} \\ \text{Force factor BL Product} & 5.7 \; \text{Tm} \end{array}$ Moving mass incl. air Net weight Vas Qms Qes **Qts**



18W/8542 7" Paper Cone Woofer

This 7" woofer features a coated paper cone that delivers very smooth and warm reproduction with excellent detailing. We recommend this driver for high quality 2-way systems of bass reflex design. This driver has the SD magnet magnesium cast system, frame, aluminum former and wire. surround is a double coated foam material with long term stability.



18W/8543 7" Poly Cone Woofer

The 18W/8543 is a Polypropylene cone woofer, that provides a deep and tight bass combined with excellent midrange clarity. This driver will perform well in a 2-way bass reflex system. The frame is cast magnesium with a resonance free PVC/rubber surround. The long throw all aluminum voice coil is joined to the basket with a linear spider.



TECHNICAL DATA:
Sensitivity 2.83V/1M
Free air resonance fs
DC resistance
V.C. inductance
Power
Effective cone area
V.C. diameter

V.C. height

Air gap height

89dB 30 Hz 5.5 ohm 0.2 mH 70W 143 cm² 42 mm 19 mm


Lin. & max. excursion Air gap flux density Force factor BL Product Moving mass incl. air Net weight Vas Qms Qes


 $\pm 6.5 / \pm 10 \text{ mm}$ 7.8 Tm 15 g 2.4 kg 49 ltr 1.70 0.26

TECHNICAL DATA: Sensitivity 2.83V/1M Free air resonance fs DC resistance V.C. inductance Power Effective cone area V.C. diameter V.C. height Air gap height

88 5dB 30 Hz 5.5 ohm 0.2 mH 80W 143 cm² 42 mm 19 mm 6 mm

Lin. & max. excursion $\pm 6.5 / \pm 10 \text{ mm}$ Air gap flux density Force factor BL Product 7.8 Tm Moving mass incl. air 15 g 2.4 kg Net weight 49 liters Vas Qms 1.40 0.26 Qes Ots 0.22





SCANSPEAK

SCANSPEAK

18W/8545

7" Carbon fibre Paper Woofer

This 7" features the heavily damped and carbon fibre impregnated paper cone that dampens resonances normally associated with stiff cones. The magnet system is the new SD-1 system which eliminates modulation and dynamic distortion, as well as clipping distortion created as it exceeds its maximum linear excursion. These designs all together make a drive unit with a very "open" sound with excellent detailing combined with low coloration and very precise imaging. Cast frame, rubber surround.



TECHNICAL DATA:
Sensitivity 2.83V/1M
Free air resonance Fs
DC resistance
V.C. inductance
Power
Effective cone area
V.C. diameter
V.C. height
Air gan height

88dB 28 Hz 5.5 ohm 0.4 mH 100W 145 cm² 42 mm 19 mm 6 mm

Lin. & max. excursion Force factor BL Product Moving mass incl. air Net weight Vas Qms Qes Ots

 $\pm 6.5 / \pm 10$ mm 8.0 Tm 20 g 2.3 kg 48 liters 2.30

Air gap height

18W/8545K 7" Carbon fibre Paper Woofer


This 7" features the heavily damped and carbon fibre impregnated paper cone that dampens resonances normally associated with stiff cones. The magnet system is the new SD-1 system which eliminates modulation and dynamic distortion, as well as clipping distortion created as it exceeds its maximum linear excursion. This driver uses a fiberglass voice coil former. This is also a good

driver for autosound applications.

Try it in a 1/2 cubic foot box with a 1.5" diameter vent by 5.2" long, f3 48Hz.



TECHNICAL DATA: Sensitivity 2.83V/1M Free air resonance Fs DC resistance V.C. inductance Power Effective cone area V.C. diameter V.C. height	87.5dB 28 Hz 5.5 ohm 0.4 mH 100W 145 cm ² 42 mm 19 mm	Lin. & max. excursion Force factor BL Product Moving mass incl. air Net weight Vas Qms Qes Qts	±6.5 / ±10mm 8.2 Tm 20.5 g 2.4 kg 48 liters 5.20 0.30 0.28
Air gap height	6 mm	Gio	0.20



18W/8546 7" Kevlar Woofer

This new 7" Kevlar cone magnesium cast frame woofer features the new SD-1 magnet system, that eliminates modulation and dynamic distortion, as well as lowering clipping distortion caused when the driver exceeds it's linear excursion. The new magnet system coupled with a new non resonant low loss linear suspension, gives you a drive unit with a very "open" sound with excellent dynamic range and detailing combined with low coloration and very precise imaging.




TECHNICAL DATA:
Sensitivity 2.83V/1M
Free air resonance F
DC resistance
V.C. inductance
Power
Effective cone area
V.C. diameter
V.C. height

Air gap height

88dB 22 Hz 5.5 ohm 0.4 mH 100W 145 cm² 42 mm 19 mm 6 mm

Lin. & max. excursion
Force factor BL Product
Moving mass incl. air
Net weight
Vas
Qms
Qes
Qts

±6.5 / ±10 mm 8.0 Tm 18.5 g 2.4 kg 84 liters 1.70 0.22 0.19



21W/8554 8" Kevlar Woofer


This 8" cast magnesium/Aluminum frame woofer features a hand coated cast Kevlar cone with a hand coated foam surround. The magnet system uses the patented SD copper cap and symmetrically shaped pole piece for lower distortion. The damped cone and surround offer a good balance between clarity and tonal balance.

This driver is fast and accurate even with the most demanding transients. A good choice for any high end system.



TECHNICAL DATA: Sensitivity 2.83V/1M Free air resonance Fs DC resistance V.C. inductance Power Effective cone area V.C. diameter V.C. height Air gap height

90dB 23 Hz 5.5 ohm 0.2 mH 110W 220 cm² 42 mm 19 mm 6 mm Lin. & max. excursion Force factor BL Product 8.0 Tm 8.0 Tm 20.5 g
Net weight 2.4 kg
Vas 160 liters
Qms 1.70
Qes 0.25
Qts 2.2 full mm 8.0 Tm 20.5 g
1.70
0.25



SCANSPEAK

21W/8555 & 21W/8555-01

This 8" features a very stiff paper cone, heavily impregnated to reduce resonance's normally associated with stiff cones. The magnet system is the new SD-1 system which eliminates modulation and dynamic distortion, as well as clipping distortion created as it exceeds its maximum linear distortion. The low-loss rubber surround is designed for better dynamic capability, detailing and less compression. Both the 21W/8555 and 21W/8555-01 will perform well either sealed or vented.



TECHNICAL DATA:
Sensitivity 2.83V/1M
Free air resonance Fs
DC resistance
V.C. inductance
Power
Effective cone area
V.C. diameter
V.C. height
Air gap height
01 0

 $\begin{array}{c} 87 \, / \, 87.5 \ dB \\ 20 \, / \, 19 \ Hz \\ 5.5 \, \Omega \\ 0.4 \, / \, 0.6 \ mH \\ 100W \\ 220 \ cm^2 \\ 42 \ mm \\ 19 \ mm \\ 6 \ mm \end{array}$

Lin. & max. excursion mm

BL 8.2 / 9.3Tm

Moving mass incl. air
Net weight 2.40 kg
Vas 136 ltr

Qms 4.50 / 4.80

Qes 0.33 / 0.27

Qts 5.4 ± 12


8.2 / 9.3Tm

32 / 36 g


2.40 kg
136 ltr

0.33 / 0.27

0.31 / 0.26



Driver Dimensions in Millimeters											
Unit A B C D											
R2904/7000, D2904/7100	104	5.9	30.9	70							
D2008/8512	92	3	38	69							
D2010/8513	98	5	41	69							
D2904/6000-00/01	59.5	3	29	41							
D2904/9800	104.5	3	43	74							
D2904/9400SE	104.5	3	41	74							
D2905/9300, 9500, 9700	104.5	3	41	74							
D2905/9900	130	5	48	90							
D3806/8200	125	4	45	92							
12M/4631G	115.5	3	48.4	92							
13M/8636, 8640, 4535	130	6	48	100							
15S/8530K-01	148	6	77	125							
15W's	148	6	71	125							
18S/8535	177	4	80	158							
18S/8531G	182	5.5	86.2	158							
18W/4531G, 8531G, 16531G	182	5.5	77	156							
18W/8535, 8543, 8545/K, 8546	177	4	70	158							
21W/8554	222	5	77	192							
21W/8555's	222	5	81	192							
22W/8851T	222	7	111	194							
23W/4557T / Passive	255	6	135/73	225							
25W's	255	6	86	228							



25.4mm = 1"
28.3 liters = 1 cubic foot
1 cubic foot = 1728 cubic inches
Box Volume = L x W x H

We can assist you with your speaker design.

SEAS THOR KIT



THOR is the new top-of-the-line loudspeaker kit from SEAS. It is a full range, floor-standing system that provides the very highest level of acoustic performance.

This kit uses two W18E001 woofers and a single T25CF002 "MILLENNIUM" tweeter mounted in a D'Appolito configuration.

The enclosure uses a newly developed transmission line configuration, derived both from sophisticated computer modeling, and extensive experimentation. The line is tapered, and filled with Dacron stuffing. The two W18E001 woofers excite the line at slightly different points, smoothing the response and increasing the range of

bass output. Usable in-room bass response extends well into the low 30Hz range. Our cabinets are 45 ½" T x 9" W x 14 ¼" D.

The crossover network is conventional except for a parallel circuit which suppresses the response peak due to the magnesium cone. The crossover frequency is 2.5kHz. Nordost 2-Flat wire supplied with kit.

THOR was designed by Dr. Joseph D'Appolito, who is world-renowned for his pioneering work on MTM-based loudspeaker configurations.

Pair with cabinets \$1955 (Black Oak, Walnut)
Pair with Sycamore or Mutenye \$2141
Price per pair w/o cabinets \$1365

Upgraded crossovers (Goertz coils, Musicaps) Add \$245

SEAS FROY MK3 KIT



The FROY MK3 is a new and improved version of the original FROY kit; utilizing the latest drive unit technologies from the Excel product line. This kit uses two W15CY001 woofers and a single T25CF002 "MILLENNIUM" tweeter mounted in a D'Appolito configuration.

The cabinet is a bass reflex design with the vent placed in the rear. This directs any potential vent noises away from the listener, and allows for minimum baffle area in the front. The port tube is constructed of two MDF boards which also serve as additional bracing for the cabinet. Our cabinet is 18 ½" T x 8" W x 11 ½" D.

The crossover network is conventional except for a parallel circuit which suppresses the response peak due to the magnesium cone. The crossover frequency is 2.2kHz.

The FROY Mk3 was designed by Murray Zeligman, who also designed the original FROY kit. Murray offers the following comments.

"The vented box is tuned about 15% lower than the ubiquitous QB3 alignment to yield a better damped bass response. Several hundred hours of laboratory testing and listening have gone into this system. You literally can't tell where the woofers leave off and the tweeter begins."

Price per pair without cabinets \$1120.00

SEAS ODIN MK3 KIT



The Odin Mk3 is a completely redesigned version of the very popular Odin kit, utilizing the latest drive unit technologies from the Excel product line. This kit uses two W18E001 woofers and a single T25CF002 "MILLENNIUM" tweeter mounted in a D'Appolito configuration.

The cabinet is a bass reflex design with the vent placed in the rear. This directs any potential vent noises away from the listener, and allows for minimum baffle area in the front. The port tube is supported by an internal baffle which helps maintain equal air flow on each end of the tube, and also serves as

additional cabinet bracing. The port tuning frequency is 31Hz. Cabinet dimensions are 22" T x 9 $\frac{1}{2}$ " W x 14 $\frac{1}{4}$ " D.

The crossover network is conventional except for a parallel circuit which suppresses the response peak due to the magnesium cone. The crossover frequency is 2.5kHz.

The Odin Mk3 was designed by Dr. Joseph D'Appolito, and was developed as a companion kit to the Thor transmission line system. It is equally transparent, a true audiophile speaker. A premium crossover is also available and is well worth the spatial highs it delivers.

Pair with cabinets \$1745 (Cherry, Clear or Black Oak)
Pair with Sycamore or Mutenye \$1795
Price per pair w/o cabinets \$1365

Upgraded crossovers (Goertz coils, Musicaps) Add \$245.00

SEAS LOKI KIT



8" W x 15" T x 11" D

The Seas Loki kit features a 7" coaxial speaker, where the tweeter is coincidently mounted at the base of the woofer cone. The type of configuration allows the listener to hear the sound emanating from the tweeter and woofer at the same time, from any listening position.

In a conventional system, depending on where you are listening from, you may here the individual components at different times, since you are physically at a different distance from each

speaker component. This delay time, as small as it is, is perceivable by the listener. This is why most multiple loudspeaker systems have a "sweet spot", where the speaker sounds best. The Loki sounds fantastic from a very large listening area, there is virtually no sweet spot.

This little speaker is a big performer and will surprise you with its big speaker sound stage. We suggest considering it for Home Theater (it is also magnetically shielded), computer speakers, satellite speakers for a subwoofer or just as stand alone book shelf speakers.

The cabinets are made from 3/4" MDF (1" front baffle) with real wood veneer. They are finished on all sides and come with a black grill on the front. The kit includes; the Seas T18RE/XFCTV2 (H1333) coaxial loudspeaker, the finished cabinets, an input cup with gold plated brass terminals, the crossover with air core inductors and polypropylene capacitors, screws, wire and instructions.

Price Each with cabinets \$281.00
Natural Cherry (not red), Maple or Black Painted Ash
Price Each w/o cabinets \$185.00



Model	Size Description	Ω	Fs Hz	Qts	Vas Liters	X-max mm Peak	VC Ø mm	Power Watts	Sens. 1W/1m db	Cost Per Unit
	Exotic Full Range	€								
F8 X1-04	4	31	.39	146	2.1	26	35	96	\$930.00	
F8 X1-08 8" full range, alnico magnet, open weave spider			32	.44	143	2.1	26	35	93	\$930.00
		V	oice C	oils						
T25CF 002 (E0011)	25CF 002 (E0011) Millennium tweeter, 25mm Sonotex, Hexadym magnet						26	90	89	\$224.30
T25C 001 (E0006)	Millennium tweeter, 25mm Sonotex, Hexadym magnet 6 500 H9929 \$38.90 Seas Excel tweeter, Last call, discontinued 6 700 H9920 \$36.50							90	91	\$103.55
T29AF 001 (E0039)	29mm Alum/Magn. alloy dome tweeter with chamber	6	500		938 \$3		26	100	92	\$214.35
T29CF 001 (E0038)	29mm Sonotex fabric dome tweeter, with chamber	6	550	H9	939 \$3	32.75	26	90	93	\$209.80
T29CF 002 (E0040)	Crescendo tweeter, 29mm Sonotex, Hexadym magnet	6	500	H9'	939 \$3	32.75	26	90	92.5	\$335.90
T29MF 001 (E0047)	Magnum 29mm Magnesium dome, Neo magnet	4	500				26	90	92	\$241.85
EXCEL Premiur	m Magnesium Cone Woofers with Copper Pho	se	Plugs	(EO	026 F	nas Al	um./l	Лад.А	Alloy c	cone)
W12CY 001 (E0021)	4.5" magnesium cone woofer with copper phase plug	8	45	.36	6	3	26	70	84	\$174.70
W15CH 001 (E0037)	5.5" magnesium cone woofer, copper phase plug, Neo	8	38	.42	14	4	26	70	85	\$218.65
W15CY 001 (E0015)	5.5" magnesium cone woofer with copper phase plug	8	38	.36	14	4	26	70	85.5	\$162.40
W16NX 001 E0049-04	6" magnesium cone woofer with copper phase plug	4	37	.33	15	7	39	80	88	\$225.35
W16NX 001 E0049-08	6" magnesium cone woofer with copper phase plug	8	39	.35	14	7	39	80	85	\$219.45
W18E 001 (E0018)	7" magnesium cone woofer with copper phase plug	8	34	.42	30	5	39	100	86	\$196.80
W18E 001/TV (E0027)	Magnetically shielded version of W18E-001	8	29	.29	56	5	39	100	87.5	\$203.65
W18EX 001 (E0017)	Larger magnet version of W18E-001	8	34	.26	30	5	39	100	88	\$199.80
W22EX 001 (E0022)	8" magnesium cone woofer with copper phase plug	8	25	.34	98	5	39	120	88	\$232.55
W26FX 001 (E0026)	10" aluminum alloy cone with copper phase plug	8	20	.35	162	7	51	150	87	\$341.70
W2017 001 (E0020)						-		100	07	Q041.70
M1 FOLL 000 (F00 42)	EXCEL Premium Nextel Cone Midrange &							70	00.5	610470
M15CH 002 (E0043)	5" Nextel cone midrange, Neodymium magnet	6	67	.40	6	3	26	70	88.5	\$194.60
W12CY 003 (E0044)	4.5" Nextel coated paper, phase plug, wide range	8	60	.36	4	3	26	70	85.5	\$160.40
W15LY 001 (E0041)	5.5" Nextel coated paper cone woofer, phase plug	8		49 .45 12 5 40 .34 24 7			26 39	60 80	86.5	\$151.25
W18NX 001 (E0042)	7" Nextel coated paper cone woofer, phase plug	8	40					90	87.5	\$196.60
W22NY 001 (E0045)	8" Nextel coated paper cone woofer, phase plug	8	33	.30	87	7	39 51	100	90 89	\$240.20 \$328.55
W26FX 002 (E0046)	10" Nextel coated paper cone woofer, phase plug	_		.39	07	/	01	100	09	\$320.00
00745/0 (117000)	Prestige Line Twee	T .			0.40.00	.1.70	10.5	00	-00	00435
22TAF/G (H1283)	22mm aluminum/magnesium alloy dome tweeter, grill	6	1100		940 \$2		19.5	80	92	\$34.15
27TAFNC/G (H1397)	27mm aluminum dome, neodymium magnet, grill	4	1170		Repa		26	90	90	\$31.75
27TFFNC/G (H1396)	27mm textile dome, neodymium magnet, grill	4	1170		Repa		26	80	91	\$31.75
27TFFNC/CG H1406	27mm textile dome, truncated flange, neo, grill	4	1170	IVOI	Repa	Irable	26	80	91	\$32.00
27TDFNC/GW H1461	27mm titanium dome, neodymium magnet, grill	6	750				26	100	91.5	\$89.05
27TTFNC/GW H1462	27mm textile dome, neodymium magnet, gril	6	750				26	90	90.5	\$91.95
27TBCD/GB-DXT H1499	27mm alum/mag alloy dome with DXT lens	6	900	LIO	020 ¢1	0 15	26	55	92	\$52.15
27TBC/G (H1147)	27mm alum./Magnesium dome tweeter, Chmb, no FF	6	550		932 \$1 932 \$1		26 26	55 90	92 91.5	\$42.65 \$43.20
27TBFC/G (H1212) 27TDF (H1211)	27mm alum./Magnesium dome tweeter, Chmb, w/ FF 27mm coated textile dome tweeter, w/ FF	6	900		932 \$1 933 \$1		26	90	91.5	\$32.80
27TDC (H1149)	27mm textile dome tweeter, chambered, non-FF						26	55	90	\$39.90
27TDFC (H1189)	27mm textile dome tweeter, chambered, W/ FF	· · · · · · · · · · · · · · · · · · ·			26	90	90	\$40.40		
` ′		6	550 800		933 \$1 933 \$1		26	90	89.5	\$40.40
27TDFC/TV (H1210) 27TFFC (H0881)	Shielded 27mm textile dome tweeter, w/ FF 27mm coated textile dome tweeter w/chamber	6	550		933 Ş1 918 \$1		26	80	91	\$38.75
29TAF/W (H1322)	29mm Aluminum/Magnesium alloy dome, w/ elastomer	6	950		941 \$2		26	100	91.5	\$48.55
29TFF/W (H1318)	29mm fabric dome, with elastomer wave guide front	6	950		941 \$2 942 \$2		26	90	92	\$43.90
Z/111/VV (IIIO10)					, 42 Y2	-2.20		,,,	12	V-10.70
MCV10DC (P1304)	Prestige Line Midranges at					0.0	24	110	04	¢57.00
MCA12RC (H1304)	4.5" coated paper cone midrange, natural rubber surr.	8	68	.56	5	0.9	26	110	86	\$57.80
MCA15RCY (H1262)	5" coated paper cone midrange, natural rubber surr.	8	51	.25	12	1.7	26	100	89.5 86	\$67.50
CA12RCY (H1152)	4.5" coated paper cone woofer, raised spider	8	57	.31	5	3	26	l ou	80	\$63.25

Model	Size Description	Ω	Fs Hz	Qts	Vas Liters	X-max mm Peak	VC Ø mm	Power Watts	Sens. 1W/1m db	Cost Per Unit
L12RCY/P (H1207)	4.5" Aluminum cone woofer with phase plug	8	50	.29	5	3	26	70	85.5	\$69.15
CA15RLY (H1216)	5" coated paper cone mid/woofer	8	44	.34	14	5	26	60	87.5	\$65.75
ER15RLY (H1455)	5" Reed/Paper pulp cone mid/woofer	8	44	.32	15	5	26	60	87.5	\$69.05
L15RLY/P (H1141)	5" aluminum cone woofer, phase plug, raised spider	8	44	.35	12	5	26	80	86	\$74.55
L16RN-SL (H1480)	6" aluminum cone woofer, copper rings, long stroke	8	36	.46	19	6	39	80	84	\$86.25
CA18RLY (H1217)	6.5" coated paper cone woofer for sealed boxes	8	43	.40	37	5	26	80	90	\$68.15
CA18RNX (H1215)	7" coated paper cone woofer, raised spider	8	36	.31	33	6	39	80	88.5	\$75.05
ER18RNX (H1456)	7" Reed/Paper pulp cone woofer, raised spider	8	37	.32	32	6	39	80	88.5	\$77.55
L18RNX/P (H1224)	7" aluminum cone woofer, phase plug, raised spider	8	36	.31	30	6	39	100	88	\$86.30
P18RNX/P (H1350)	7" Polypropylene cone woofer, phase plug, raised spider	8	43	.33	25	6	39	80	89	\$77.90
CA22RNX (H1288)	8" coated paper cone woofer, bumped back plate	8	29	.41	97	6	39	80	89.5	\$87.75
L22RN4X/P (H1208)	8" alum. cone woofer, raised spider, bumped, 4 layer	8	21	.27	93	7	39	125	86.5	\$95.70
L22RNX/P (H1252)	8" aluminum cone woofer, raised spider, bumped BP	8	23	.32	112	6	39	110	88	\$91.85
CA26RFX (H1305)	10" coated paper cone, raised spider, bumped back	8	29	.34	129	7	51	100	90.5	\$150.30
CA26RE4X (H1316)	10" coated paper cone, raised spider, 4 layer voice coil	8	25	.28	164	4	39	80	91	\$118.40
L26RFX/P (H1209)	10" Aluminum cone woofer, raised spider, Bumped BB	8	20	.33	171	7	51	125	88	\$165.10
SP18R (H9944)	6.5" passive radiator, threaded bolt for adding weight		26		41	9.5				\$43.15
SP22R (H9945)	8" passive radiator, threaded bolt for adding weight		22		138	10				\$59.90
SP26R (H9946)	10" passive radiator , threaded bolt for adding weight		22		214	12.5				\$87.70
Prestige Line Coaxial Drivers - The tweeter is mounted at the base of the woofer cone (coincidental).										
T18REX/FXC (H1353)	7" coaxial, clear cone, raised spider, coincidental, new adaptive surround	76 W8	T1.2K W29	.22	W 47.9	W 3	T26 W39	T90 W90	T88.5 W87	\$152.35
T18RE/XFCTV2 (H1333) (Shielded)				\$158.60						
Seas designed crossover for the T18RE Coaxial Speakers, using 16AWG on woofer, Poly Caps on tweeter, Eagle on tweeter \$36.50						\$36.50				

Exotic F8 X1-04

The Exotic F8 is a full range 8-inch driver designed for smooth, wide frequency response, high sensitivity, and low distortion. The special paper cone is embedded with papyrus fibers to optimize stiffness and damping. An optimally matched whizzer cone extends high frequency response beyond 10kHz. A totally new and proprietary spider design dramatically improves the performance of this critical suspension part. The magnet system uses an Alnico V ring magnet for high sensitivity, excellent stability, and low distortion. See more info online.



Nominal Impedance	4	Ohms	Voice coil resistance	3.0	Ohms
Recom. frequency range	30-20000	Hz	Voice coil inductance	0.05	mH
Short term max. power	100	W	Force factor	4.2	N/A
Long term max. power	35	W	Free air resonance	31	Hz
Sensitivity (1W/1m)	96	dB	Moving mass	10.5	g
			Suspension compliance	2.5	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	0.57	Ns/m
Voice coil height	7.8	mm	Effective piston area	222	sq. cm
Air gap height	12	mm	•		•
Linear coil travel (p-p)	4.2	mm	Vas	146	Liters
Max. coil travel (p-p)	14	mm	Qms	4.24	
Magnet weight	0.8	Kg	Qes	0.43	
Total weight	2.6	Kg	Qts	0.39	
1					





Exotic F8 X1-08

The Exotic F8 is a full range 8-inch driver designed for smooth, wide frequency response, high sensitivity, and low The special paper cone is distortion. embedded with papyrus fibers to optimize stiffness and damping. An optimally matched whizzer cone extends high frequency response beyond 10kHz. A totally new and proprietary spider design dramatically improves the performance of this critical suspension part. The magnet system uses an Alnico V ring magnet for high sensitivity, excellent stability, and low distortion. See more info online.



Nominal Impedance	8	Ohms	Voice coil resistance	5.7	Ohms
Recom. frequency range	30-20000	Hz	Voice coil inductance	0.07	mH
Short term max. power	100	W	Force factor	5.25	N/A
Long term max. power	35	W	Free air resonance	32	Hz
Sensitivity (1W/1m)	93	dB	Moving mass	10	g
			Suspension compliance	2.5	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	0.57	Ns/m
Voice coil height	7.8	mm	Effective piston area	222	sq. cm
Air gap height	12	mm	•		•
Linear coil travel (p-p)	4.2	mm	Vas	143	Liters
Max. coil travel (p-p)	14	mm	Qms	4.20	
Magnet weight	.8	Kg	Qes	0.50	
Total weight	2.6	Kg	Qts	0.44	





Excel T25CF-002 E0011

The "Millennium" This 25mm dome tweeter features the proprietary SONOTEX fabric dome. You can expect extremely precise, realistic reproduction and excellent acoustic performance and consistency from the T25CF-002. Equipped with flexible lead-out wires, underhung voice coil for low distortion, tinsel leads, gold plated terminals, and Neodymium based HEXADYM magnet system. Low viscosity magnetic fluid is used for cooling and high power handling. Its low free air resonance is below that of most dome tweeters. Unique molded zinc rear chamber eliminates unwanted interior resonances.



Nominal Impedance	6	Ohms	Voice coil resistance	4.6	Ohms
	-				
Recom. frequency range	2000-25000	Hz	Voice coil inductance	0.05	mH
Short term max. power	200	W	Force factor	3.1	N/A
Long term max. power	90	W	Free air resonance	500	Hz
Sensitivity (1W/1m)	89	dB	Moving mass	0.37	g
			Suspension compliance	-	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	-	Ns/m
Voice coil height	1.5	mm	Effective piston area	7	sq. cm
Air gap height	2.5	mm			
Linear coil travel (p-p)	1.0	mm	Vas	-	Liters
Max. coil travel (p-p)	-	mm	Qms	-	
Magnet weight	.29	Kg	Qes	-	
Total weight	0.36	Kg	Qts	-	


Frequency [Hz]


Excel T25C-001 E0006

This 25mm dome tweeter features the proprietary SONOTEX fabric dome. SONOTEX is only manufactured by Seas and is pre-coated 4 times with a damping/sealing material, resulting in excellent acoustic performance and consistency. The T2CF5-001 has a silver wire voice coil, tinsel leads and gold plated terminals. A wide polymer surround is used to give added stability without magnetic fluid. The T25CF-001 has a double magnet, one added in reverse for use in A/V systems. The complex shape chamber reduces resonance and interior reflections.



Nominal Impedance	6	Ohms	Voice coil resistance	4.6	Ohms
Recom. frequency range	2000-25000	Hz	Voice coil inductance	0.05	mH
Short term max. power	200	W	Force factor	3.5	N/A
Long term max. power	90	W	Free air resonance	700	Hz
Sensitivity (1W/1m)	91	dB	Moving mass	0.33	g
			Suspension compliance	-	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	-	Ns/m
Voice coil height	1.5	mm	Effective piston area	7	sq. cm
Air gap height	2.0	mm			
Linear coil travel (p-p)	0.5	mm	Vas	-	Liters
Max. coil travel (p-p)	-	mm	Qms	-	
Magnet weight	0.34	Kg	Qes	-	
Total weight	0.80	Kg	Qts	-	





Excel T29CF-001 E0038

Excel T29AF-001 E0039 The T29AF001 is a High End, High

Efficiency 29mm aluminum/magnesium alloy dome tweeter. An optimally shaped dome and a wide SONOMEX surround, both manufactured by SEAS, ensure excellent performance and consistency. A powerful magnet system based on axially magnetized NdFeB ring magnets. A generously underhung voice coil with flexible lead-out wires ensures low distortion. A 6mm precision machined aluminum front plate, Nextel painted. injection molded rear chamber made from zinc eliminates unwanted chamber wall resonances




Nominal Impedance	6	Ohms	Voice coil resistance	4.7	Ohms	
Recom. frequency range 2	2000-22000	Hz	Voice coil inductance	0.05	mH	
Short term max. power	220	W	Force factor	3.9	N/A	
Long term max. power	100	W	Free air resonance	500	Hz	
Sensitivity (1W/1m)	92	dB	Moving mass	0.39	g	
			Suspension compliance	-	mm/N	
Voice Coil Diameter	26	mm	Suspension mech. resistance	-	Ns/m	
Voice coil height	1.5	mm	Effective piston area	8	sq. cm	
Air gap height	2.5	mm				
Linear coil travel (p-p)	0.5	mm	Vas	-	Liters	
Max. coil travel (p-p)	-	mm	Qms	-		
Magnet weight	0.053	Kg	Qes	-		
Total weight	0.67	Kg	Qts	-		

The T29CF001 is a High End, High Efficiency 29mm fabric dome tweeter with a wide surround. An optimally shaped dome and a wide SONOMEX surround, both manufactured by SEAS, ensure excellent performance and consistency. A powerful magnet system based on axially magnetized NdFeB ring magnets. A generously

underhung voice coil with flexible lead-out wires ensures low distortion. A 6mm precision machined aluminum front plate, Nextel painted. injection molded rear chamber made from zinc eliminates unwanted chamber wall resonances



Nominal Impedance	6	Ohms	Voice coil resistance	4.7	Ohms
Recom. frequency range 2000-	25000	Hz	Voice coil inductance	0.05	mH
Short term max. power	200	W	Force factor	3.9	N/A
Long term max. power	90	W	Free air resonance	550	Hz
Sensitivity (1W/1m)	93	dB	Moving mass	0.35	g
			Suspension compliance	-	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	-	Ns/m
Voice coil height	1.5	mm	Effective piston area	8	sq. cm
Air gap height	2.5	mm	-		_
Linear coil travel (p-p)	0.5	mm	Vas	-	Liters
Max. coil travel (p-p)	-	mm	Qms	-	
Magnet weight	0.053	Kg	Qes	-	
Total weight	0.67	Kg	Qts	-	




	100	50	
	95-		
	90-	40	
-	85		Ī
- E	, 80-	30	Impedance Johm
P J	75		nce
SP	70-	20	<u></u>
-	65	1 /	_
	60-	V 10	
	55-		
	50- 10		
	10	1 000 10 000 Frequency [Hz]	

Excel T29CF-002 E0040

The T29CF002, "CRESCENDO" is an Ultra High End 29mm soft dome tweeter. An optimally shaped dome with wide Sonomex surround. A high efficiency HEXADYM magnet system, based on 6 radially magnetized NdFeB magnet blocks, provide efficient ventilation and damping of cavities behind the dome, surround and voice coil. Inherently shielded. Generously underhung voice coil with flexible lead out wires. A 6mm precision machined aluminum front plate, Nextel painted. injection molded rear chamber made from zinc eliminates unwanted chamber wall resonances



6	Ohms	Voice coil resistance	4.7	Ohms
00-25000	Hz	Voice coil inductance	0.05	mH
200	W	Force factor	3.5	N/A
90	W	Free air resonance	500	Hz
92.5	dB	Moving mass	0.35	g
		Suspension compliance	-	mm/N
26	mm	Suspension mech. resistance	-	Ns/m
1.5	mm	Effective piston area	7	sq. cm
2.5	mm	_		-
0.5	mm	Vas	-	Liters
-	mm	Qms	-	
0.053	Kg	Qes	-	
0.66	Kg	Qts	-	
	00-25000 200 90 92.5 26 1.5 2.5 0.5	00-25000 Hz 200 W 90 W 92.5 dB 26 mm 1.5 mm 2.5 mm 0.5 mm 0.053 Kg	00-25000 Hz Voice coil inductance 200 W Force factor 90 W Free air resonance 92.5 dB Moving mass Suspension compliance Suspension mech. resistance 1.5 mm Effective piston area 2.5 mm Vas - mm Qms 0.053 Kg Qes	00-25000 Hz Voice coil inductance 0.05 200 W Force factor 3.5 90 W Free air resonance 500 92.5 dB Moving mass 0.35 Suspension compliance - - 26 mm Suspension mech. resistance - 1.5 mm Effective piston area 7 2.5 mm Vas - - mm Qms - 0.053 Kg Qes -




Excel W12CY-001 E0021

This 4.5" woofer features a light, yet stiff magnesium cone for bass precision and midrange detail. The cone is attached to the magnesium cast frame by a natural rubber surround that shows no sign of midrange (edge) resonance. Heavy copper coils mounted above and below the T-shaped pole piece reduce non linear and intermodulation distortion. The raised spider keeps the voice coil from bottoming out and also reduces noise caused by mechanical distortion. A large magnet system is used for improved sensitivity and transient response.



Nominal Impedance	8	Ohms	Voice coil resistance	5.6	Ohms
Recom. frequency range	60-3500	Hz	Voice coil inductance	0.43	mH
Short term max. power	200	W	Force factor	5.4	N/A
Long term max. power	70	W	Free air resonance	45	Hz
Sensitivity (1W/1m)	84	dB	Moving mass	7.5	g
			Suspension compliance	1.7	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	0.87	Ns/m
Voice coil height	12	mm	Effective piston area	50	sq. cm
Air gap height	6.0	mm	_		_
Linear coil travel (p-p)	6.0	mm	Vas	6	Liters
Max. coil travel (p-p)	9	mm	Qms	2.50	
Magnet weight	0.42	Kg	Qes	0.42	
Total weight	1.21	Kg	Qts	0.36	




Excel T29MF-001 E0047

The T29MF-001 "Magnum" is a new magnesium dome tweeter with a special neodymium magnet system. This is the tweeter of choice for those who seek extremely precise and realistic sound reproduction. This tweeter uses the Seas patented Hexadym neodymium radial magnet system. The magnesium dome moves the breakup beyond the audible frequency range. Other features are; underhung voice coil, large Sonomax surround, low viscosity magnet fluid, 6mm machine aluminum face plate, zink injection molded rear chamber, inherently shielded.



Nominal Impedance	4	Ohms	Voice coil resistance	2.5	Ohms
Recom. frequency range 20	00-25000	Hz	Voice coil inductance	0.03	mH
Short term max. power	200	W	Force factor	3.0	N/A
Long term max. power	90	W	Free air resonance	500	Hz
Sensitivity (1W/1m)	92	dB	Moving mass	0.35	g
			Suspension compliance	-	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	-	Ns/m
Voice coil height	1.1	mm	Effective piston area	8	sq. cm
Air gap height	2.5	mm	_		-
Linear coil travel (p-p)	1.4	mm	Vas	-	Liters
Max. coil travel (p-p)	-	mm	Qms	-	
Magnet weight	53	g	Qes	-	
Total weight	0.61	Kg	Qts	-	




Excel W15CH-001 E0037

The W15CH-001 is a 5" cone driver developed for use as a woofer or woofer/midrange. The extremely stiff, yet light magnesium cone delivers tremendous bass precision and midrange detail. This speaker has an acoustically transparent basket and a natural rubber surround. This woofer has the patented Hexadym magnet system, based on 6 radially magnetized Neodymium blocks. Heavy copper rings mounted above and below the T-shaped pole piece reduce non-linear and intermodulation distortion. A solid copper phase plug improves heat conduction.



*					
Nominal Impedance	8	Ohms	Voice coil resistance	5.5	Ohms
Recom. frequency range	50-3000	Hz	Voice coil inductance	0.49	mH
Short term max. power	200	W	Force factor	5.1	N/A
Long term max. power	70	W	Free air resonance	38	Hz
Sensitivity (1W/1m)	85	dB	Moving mass	9.5	g
			Suspension compliance	1.8	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	0.91	Ns/m
Voice coil height	14	mm	Effective piston area	75	sq. cm
Air gap height	6.0	mm			
Linear coil travel (p-p)	8.0	mm	Vas	14	Liters
Max. coil travel (p-p)	14	mm	Qms	2.58	
Magnet weight	0.06	Kg	Qes	0.50	
Total weight	0.80	Kg	Qts	0.42	




Excel W15CY-001 E0015

This 5" woofer features a light, yet stiff magnesium cone for bass precision and midrange detail. The cone is attached to the magnesium cast frame by a natural rubber surround that shows no sign of midrange (edge) resonance. Heavy copper coils mounted above and below the T-shaped pole piece reduce non linear and intermodulation distortion. The raised spider keeps the voice coil from bottoming out and also reduces noise caused by mechanical distortion. A large magnet system is used for improved sensitivity and transient response.



Nominal Impedance	8	Ohms	Voice coil resistance	5.5	
Recom. frequency range	50-3000	Hz	Ohms		
Short term max. power	200	W	Voice coil inductance	0.49	mΗ
Long term max. power	70	W	Force factor	5.5	N/A
Sensitivity (1W/1m)	85.5	dB	Free air resonance	38	Hz
			Moving mass	9.5	g
Voice Coil Diameter	26	mm	Suspension compliance	1.8	-
Voice coil height	14	mm	mm/N		
Air gap height	6.0	mm	Suspension mech. resistance	1.06	
Linear coil travel (p-p)	8.0	mm	Ns/m		
Max. coil travel (p-p)	14	mm	Effective piston area	75	sq.
Magnet weight	0.42	Kg	cm		
Total weight	1.35	Kg			




Excel W16NX-001 E0049-08

This 6" woofer has a machined and surface treated magnesium cone. The unique radial reinforced rubber surround reduces resonances and prevents surround breakup at large excursions. Heavy copper rings above and below the T-shaped pole pieces reduce non linear and modulation distortion and increase overload margins. A copper phase plug reduces compression do to temperature and eliminated cavity resonance from inside the former. The raised spider keeps the voice coil from bottoming out and also reduces noise caused by mechanical distortion. Extended bass shelf gives f5 of 40Hz.



Nominal Impedance	8	Ohms	Voice coil resistance	6.2	Ohms
Recom. frequency range	45-2500	Hz	Voice coil inductance	0.41	mH
Short term max. power	250	W	Force factor	7.3	N/A
Long term max. power	80	W	Free air resonance	39	Hz
Sensitivity (1W/1m)	85	dB	Moving mass	13.9	g
			Suspension compliance	1.2	mm/N
Voice Coil Diameter	39	mm	Suspension mech. resistance	1.64	Ns/m
Voice coil height	20	mm	Effective piston area	94	sq. cm
Air gap height	6.0	mm	*		•
Linear coil travel (p-p)	14.0	mm	Vas	14	Liters
Max. coil travel (p-p)	22	mm	Qms	2.16	
Magnet weight	0.64	Kg	Qes	0.41	
Total weight	2.15	Kg	Qts	0.35	




Excel W16NX-001 E0049-04

This 6" woofer has a machined and surface treated magnesium cone. The unique radial reinforced rubber surround reduces resonances and prevents surround breakup at large excursions. Heavy copper rings above and below the T-shaped pole pieces reduce non linear and modulation distortion and increase overload margins. A copper phase plug reduces compression do to temperature and eliminated cavity resonance from inside the former. The raised spider keeps the voice coil from bottoming out and also reduces noise caused by mechanical distortion. Extended bass shelf gives f5 of 40Hz.



4	Ohms	Voice coil resistance	3.0	
45-2500	Hz	Ohms		
250	W	Voice coil inductance	0.25	mH
80	W	Force factor	5.3	N/A
88	dB	Free air resonance	37	Hz
		Moving mass	14.8	g
39	mm	Suspension compliance	1.3	
20	mm	mm/N		
6.0	mm	Suspension mech. resistance	1.34	
14.0	mm	Ns/m		
22	mm	Effective piston area	94	sq.
0.64	Kg	cm		
2.15	Kg			
	45-2500 250 80 88 39 20 6.0 14.0 22 0.64	45-2500 Hz 250 W 80 W 88 dB 39 mm 20 mm 6.0 mm 14.0 mm 22 mm 0.64 Kg	45-2500 Hz Ohms	45-2500 Hz Ohms 250 W Voice coil inductance 0.25




Excel W18E-001 E0018

This 7" woofer features a light, yet stiff magnesium cone for bass precision and midrange detail. The cone is attached to the magnesium cast frame by a natural rubber surround that shows no sign of midrange (edge) resonance. Heavy copper coils mounted above and below the T-shaped pole piece reduce non linear and intermodulation distortion. The raised spider keeps the voice coil from bottoming out and also reduces noise caused by mechanical distortion. A large magnet system is used for improved sensitivity and transient response.



Nominal Impedance	8	Ohms	Voice coil resistance	6.1	Ohms
Recom. frequency range	40-2500	Hz	Voice coil inductance	0.65	mH
Short term max. power	250	W	Force factor	6.6	N/A
Long term max. power	100	W	Free air resonance	34	Hz
Sensitivity (1W/1m)	86	dB	Moving mass	15.5	g
			Suspension compliance	1.4	mm/N
Voice Coil Diameter	39	mm	Suspension mech. resistance	1.2	Ns/m
Voice coil height	16	mm	Effective piston area	126	sq. cn
Air gap height	6.0	mm	•		•
Linear coil travel (p-p)	10.0	mm	Vas	30	Liters
Max. coil travel (p-p)	19	mm	Oms	2.91	
Magnet weight	0.42	Kg	Oes	0.49	
Total weight	1.75	Kg	Ots	0.42	




Excel W18E-001/TV E0027

This **shielded magnet** 7" woofer features a light, yet stiff **magnesium cone** for bass precision and midrange detail. The cone is attached to the magnesium cast frame by a natural rubber surround that shows no sign of midrange (edge) resonance. Heavy copper coils mounted above and below the T-shaped pole piece reduce non linear and intermodulation distortion. The raised spider keeps the voice coil from bottoming out and also reduces noise caused by mechanical distortion. This speaker has been optimized for use in home theater systems or used near CRT's.



Nominal Impedance	8	Ohms	Voice coil resistance	5.9	Ohms
Recom. frequency range	40-2500	Hz	Voice coil inductance	0.4	mH
Short term max. power	250	W	Force factor	7.2	N/A
Long term max. power	100	W	Free air resonance	29	Hz
Sensitivity (1W/1m)	86.5	dB	Moving mass	14.4	g
-			Suspension compliance	2.1	mm/N
Voice Coil Diameter	39	mm	Suspension mech. resistance	1.4	Ns/m
Voice coil height	16	mm	Effective piston area	126	sq. cm
Air gap height	6.0	mm	-		-
Linear coil travel (p-p)	10.0	mm	Vas	47	Liters
Max. coil travel (p-p)	19	mm	Qms	2.27	
Magnet weight	0.42	Kg	Qes	0.33	
Total weight	1.75	Kg	Qts	0.29	




Excel W22EX-001 E0022

This 8" woofer features a light, yet stiff magnesium cone for bass precision and midrange detail. The cone is attached to the magnesium cast frame by a natural rubber surround that shows no sign of midrange (edge) resonance. Heavy copper coils mounted above and below the T-shaped pole piece reduce non linear and intermodulation distortion. The raised spider keeps the voice coil from bottoming out and also reduces noise caused by mechanical distortion. A larger magnet system is used for improved sensitivity, transient response and lower Qts.



Nominal Impedance	8	Ohms	Voice coil resistance	6.1	Ohms
Recom. frequency range	30-2000	Hz	Voice coil inductance	0.61	mH
Short term max. power	300	W	Force factor	8.1	N/A
Long term max. power	120	W	Free air resonance	25	Hz
Sensitivity (1W/1m)	88	dB	Moving mass	26.2	g
			Suspension compliance	1.5	mm/N
Voice Coil Diameter	39	mm	Suspension mech. resistance	2.06	Ns/m
Voice coil height	16	mm	Effective piston area	220	sq. cm
Air gap height	6.0	mm	_		-
Linear coil travel (p-p)	10.0	mm	Vas	98	Liters
Max. coil travel (p-p)	21	mm	Qms	2.14	
Magnet weight	0.64	Kg	Qes	0.41	
Total weight	2.2	Kg	Qts	0.34	




Excel W18EX-001 E0017

This 7" woofer features a light, yet stiff magnesium cone for bass precision and midrange detail. The cone is attached to the magnesium cast frame by a natural rubber surround that shows no sign of midrange (edge) resonance. Heavy copper coils mounted above and below the T-shaped pole piece reduce non linear and intermodulation distortion. The raised spider keeps the voice coil from bottoming out and also reduces noise caused by mechanical distortion. A larger magnet system is used for improved sensitivity, transient response and lower Qts.



Nominal Impedance	8	Ohms	Voice coil resistance	6.1	Ohms
Recom. frequency range	40-2500	Hz	Voice coil inductance	0.65	mH
Short term max. power	250	W	Force factor	8.4	N/A
Long term max. power	100	W	Free air resonance	34	Hz
Sensitivity (1W/1m)	88	dB	Moving mass	15.5	g
			Suspension compliance	1.4	mm/N
Voice Coil Diameter	39	mm	Suspension mech. resistance	1.94	Ns/m
Voice coil height	16	mm	Effective piston area	126	sq. cm
Air gap height	6.0	mm			
Linear coil travel (p-p)	10.0	mm	Vas	30	Liters
Max. coil travel (p-p)	19	mm	Qms	1.8	
Magnet weight	0.64	Kg	Qes	0.30	
Total weight	2.15	Kg	Qts	0.26	




Excel W26FX-001 E0026

This 10" woofer features a light, yet stiff aluminum alloy cone for stiffness in providing bass precision. Heavy copper rings mounted above and below the T-shaped pole piece reduce non linear and intermodulation distortion and increase overload margin. The raised spider keeps the voice coil from bottoming out and also reduces noise caused by mechanical distortion. Power handling is improved by using a high temperature 2" voice coil and by the solid copper phase plug conducting heat away from the voice coil. Optimized for ported enclosures.



Nominal Impedance	8	Ohms	Voice coil resistance	6.3	Ohms
Recom. frequency range	20-1000	Hz	Voice coil inductance	1.43	mH
Short term max. power	400	W	Force factor	10.7	N/A
Long term max. power	150	W	Free air resonance	20	Hz
Sensitivity (1W/1m)	87	dB	Moving mass	56.3	g
			Suspension compliance	1.1	mm/N
Voice Coil Diameter	51	mm	Suspension mech. resistance	3.21	Ns/m
Voice coil height	20	mm	Effective piston area	330	sq. cm
Air gap height	6.0	mm			
Linear coil travel (p-p)	14.0	mm	Vas	162	Liters
4.17	35	mm	Qms	2.34	
	3.0		Qes	0.41	
Total weight	4.2		Qts	0.35	
Air gap height Linear coil travel (p-p) Max. coil travel (p-p) Magnet weight	6.0 14.0 35 3.0	mm mm	Suspension mech. resistance Effective piston area Vas Qms Qes	3.21 330 162 2.34 0.41	2




Excel M15CH-002 E0043

The M15CH-002 is a 5" Nextel coated paper cone midrange, capable of the most neutral and transparent sound reproduction. The low distortion and low mechanical noise generated by this driver set a new standard for midrange units. The Hexadym magnet system is designed to keep cavity resonances and sound reflection to a minimum. Copper rings are employed to reduce non-linear and modulation distortion. A solid copper phase plug enhances the performance of the rings and conducts heat away from the voice coil. The cast frame with large windows is designed for quiet operation and air flow.



Nominal Impedance	6	Ohms	Voice coil resistance	4.9	Ohms
Recom. frequency range	60-3500	Hz	Voice coil inductance	0.43	mH
Short term max. power	200	W	Force factor	5.3	N/A
Long term max. power	70	W	Free air resonance	67	Hz
Sensitivity (1W/1m)	88.5	dB	Moving mass	6.75	g
			Suspension compliance	0.8	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	1.77	Ns/m
Voice coil height	12	mm	Effective piston area	75	sq. cm
Air gap height	6	mm	•		•
Linear coil travel (p-p)	6	mm	Vas	6.0	Liters
Max. coil travel (p-p)	14	mm	Qms	1.70	
Magnet weight (Neodymium)	0.06	Kg	Qes	0.52	
Total weight	0.8	Kg	Qts	0.40	




Excel W15LY-001 E0041

The W15LY-001 is a paper cone with a unique Nextel coating, for smooth response and low distortion. The new Adaptive Surround provides greater damping in the upper frequencies and less damping for bass frequencies. A large magnet and copper clad aluminum voice coil provide good excursion, low distortion and good transient response. Heavy copper rings mounted above and below the T-shaped pole pieces reduce non-linear and intermodulation distortion. Large windows in the cast basket, above and below the voice coil reduce air flow noise and ventilate the voice coil.



Nominal Impedance	8	Ohms	Voice coil resistance	5.7	
Recom. frequency range	50-4000	Hz	Ohms		
Short term max. power	250	W	Voice coil inductance	0.3	mH
Long term max. power	60	W	Force factor	4.6	N/A
Sensitivity (1W/1m)	86.5	dB	Free air resonance	49	Hz
			Moving mass	6.28	g
Voice Coil Diameter	26	mm	Suspension compliance	1.7	-
Voice coil height	16	mm	mm/N		
Air gap height	6	mm	Suspension mech. resistance	0.93	
Linear coil travel (p-p)	10	mm	Ns/m		
Max. coil travel (p-p)	20	mm	Effective piston area	75	sq.
Magnet weight	0.42	Kg	cm		•
Total weight	1.20	Κα			




Excel W12CY-003 E0044

The W12CY-003 is a 4.5" paper cone with a unique Nextel coating, for smooth response and low distortion. The new Adaptive Surround provides greater damping in the upper frequencies and less damping for bass frequencies. A large magnet and copper clad aluminum voice coil provide good excursion, low distortion and good transient response. Heavy copper rings mounted above and below the T-shaped pole pieces reduce non-linear and intermodulation distortion. Large windows in the cast basket, above and below the voice coil reduce air flow noise and ventilate the voice coil.



Nominal Impedance	8	Ohms	Voice coil resistance	5.5	Ohms
Recom. frequency range	60-3500	Hz	Voice coil inductance	0.41	mH
Short term max. power	200	W	Force factor	5.5	N/A
Long term max. power	70	W	Free air resonance	60	Hz
Sensitivity (1W/1m)	85.5	dB	Moving mass	6.1	g
			Suspension compliance	1.2	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	1.03	Ns/m
Voice coil height	12	mm	Effective piston area	50	sq. cm
Air gap height	6	mm			
Linear coil travel (p-p)	6	mm	Vas	4.0	Liters
Max. coil travel (p-p)	9	mm	Qms	2.30	
Magnet weight	0.42	Kg	Qes	0.44	
Total weight	1.3	Kg	Qts	0.36	




Excel W18NX-001 E0042

The W18NX-001 is a paper cone with a unique Nextel coating, for smooth response and low distortion. The new Adaptive Surround provides greater damping in the upper frequencies and less damping for bass frequencies. A large magnet and copper clad aluminum voice coil provide good excursion, low distortion and good transient response. Heavy copper rings mounted above and below the T-shaped pole pieces reduce non-linear and intermodulation distortion. Large windows in the cast basket, above and below the voice coil reduce air flow noise and ventilate the voice coil.



Nominal Impedance	8	Ohms	Voice coil resistance	6.3	Ohms
Recom. frequency range	30-3000	Hz	Voice coil inductance	0.43	mH
Short term max. power	250	W	Force factor	7.0	N/A
Long term max. power	80	W	Free air resonance	40	Hz
Sensitivity (1W/1m)	87.5	dB	Moving mass	13.7	g
			Suspension compliance	1.2	mm/N
Voice Coil Diameter	39	mm	Suspension mech. resistance	1.77	Ns/m
Voice coil height	20	mm	Effective piston area	126	sq. cm
Air gap height	6	mm	_		_
Linear coil travel (p-p)	14	mm	Vas	24	Liters
Max. coil travel (p-p)	22	mm	Qms	2.08	
Magnet weight	0.64	Kg	Qes	0.41	
Total weight	2.15	Kg	Qts	0.34	




Excel W22NY-001 E0045

The W22NY-001 is a paper cone with a unique Nextel coating to provide stiffness and reduce distortion. A large magnet with a bumped back plate, together with a CCAW voice coil, allow for good excursion with low distortion and excellent transient response. Heavy copper rings mounted above and below the T-shaped pole pieces reduce non-linear and intermodulation distortion. A chrome plated brass phase plug reduces temperature variations in the voice coil and reduces cavity resonances. Large windows in the cast basket, reduce air flow noise and ventilate the voice coil.



8	Ohms	Voice coil resistance	6.1	Ohms
30-3000	Hz	Voice coil inductance	0.61	mH
250	W	Force factor	8.8	N/A
90	W	Free air resonance	33	Hz
90	dB	Moving mass	20.0	g
		Suspension compliance	1.2	mm/N
39	mm	Suspension mech. resistance	2.60	Ns/m
20	mm	Effective piston area	220	sq. cm
6	mm	_		-
14	mm	Vas	72	Liters
21	mm	Qms	1.73	
3.00	Kg	Qes	0.36	
3.6	Kg	Qts	0.30	
	30-3000 250 90 90 39 20 6 14 21 3.00	30-3000 Hz 250 W 90 W 90 dB 39 mm 20 mm 6 mm 14 mm 21 mm 3.00 Kg	30-3000 Hz	30-3000 Hz




Seas 22TAF/G H1283

The 22TAF/G is a High Definition metal dome tweeter with wide, coated fabric surround. The relatively small voice coil diameter and the wide surround combine the high frequency behavior of a ¾" dome with the low frequency characteristics of a 1" dome. A large ferrite magnet gives high efficiency. The dome is precision formed from an aluminum/magnesium alloy for low mass and high rigidity and stability. The pre-coated surround material gives high consistency and excellent stability. The VC is ferrofluid cooled. An acoustically open Hexagrid protects the dome diaphragm.



Nominal Impedance	6	Ohms	Voice coil resistance	4.9	Ohms
Recom. frequency range 25	00-30000	Hz	Voice coil inductance	0.05	mH
Short term max. power	180	W	Force factor	3.3	N/A
Long term max. power	80	W	Free air resonance	1100	Hz
Sensitivity (1W/1m)	92	dB	Moving mass	0.23	g
			Suspension compliance	-	mm/N
Voice Coil Diameter	19.5	mm	Suspension mech. resistance	-	Ns/m
Voice coil height	1.5	mm	Effective piston area	5.9	sq. cm
Air gap height	2	mm	•		•
Linear coil travel (p-p)	0.5	mm	Vas	-	Liters
Max. coil travel (p-p)	-	mm	Qms	-	
Magnet weight	0.25	Kg	Qes	-	
Total weight	0.50	Kg	Ots	-	




Excel W26FX-002 E0046

The W26FX-002 is a paper cone with a unique Nextel coating to provide stiffness and reduce distortion. A 2" diameter high temperature with black anodized coil former is incorporated for high power handling and reduced power compression. Heavy copper rings mounted above and below the T-shaped pole pieces reduce non-linear and intermodulation distortion. A chrome plated brass phase plug reduces temperature variations in the voice coil and reduces cavity resonances. Large windows in the cast basket, reduce air flow noise and ventilate the voice coil.



Nominal Impedance	8	Ohms	Voice coil resistance	6.2	Ohms
Recom. frequency range	30-1000	Hz	Voice coil inductance	0.81	mH
Short term max. power	300	W	Force factor	10.9	N/A
Long term max. power	100	W	Free air resonance	31	Hz
Sensitivity (1W/1m)	89.0	dB	Moving mass	42.4	g
			Suspension compliance	0.6	mm/N
Voice Coil Diameter	51	mm	Suspension mech. resistance	3.52	Ns/m
Voice coil height	20	mm	Effective piston area	330	sq. cm
Air gap height	6	mm	_		-
Linear coil travel (p-p)	14	mm	Vas	87	Liters
Max. coil travel (p-p)	35	mm	Qms	2.55	
Magnet weight	3.00	Kg	Qes	0.47	
Total weight	4.5	Kg	Qts	0.39	




Seas 27TAFNC/G H1397

Compact design neodymium magnet tweeter for high quality small cabinet speakers or autosound applications. Critically designed aluminum/magnesium alloy dome with good dispersion above 10kHz. A wide roll surround together with double chamber magnet system results in a low fundamental frequency. The magnet system is inherently shielded, allowing use in A/V systems. The diffusor is designed to compensate for a slight roll off towards 20kHz and also to reduce resonance above 20kHz. The voice coil is immersed in magnetic fluid. Pressure fit installation.



0					
Nominal Impedance	4	Ohms	Voice coil resistance	2.7	Ohms
Recom. frequency range 25	00-30000	Hz	Voice coil inductance	0.03	mH
Short term max. power	200	W	Force factor	1.9	N/A
Long term max. power	90	W	Free air resonance	1170	Hz
Sensitivity (1W/1m)	90	dB	Moving mass	0.30	g
			Suspension compliance	-	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	-	Ns/m
Voice coil height	1.1	mm	Effective piston area	7.5	sq. cm
Air gap height	2.0	mm	•		•
Linear coil travel (p-p)	0.9	mm	Power ratings with 12dB filter	at 2500F	łz
Max. coil travel (p-p)	-	mm	The aluminum dome has sligh	tly better	power
Magnet weight	0.01	Kg	handling than the textile dome, because the		
Total weight	0.1	Kg	aluminum helps conduct heat	away fron	n the VC.




Seas 27TFFNC/G H1396

Compact design neodymium magnet tweeter for high quality small cabinet speakers or autosound applications. The diaphragm is vacuum formed from a precoated fabric for greater consistency. The coating has been carefully selected to result in a smooth frequency response and a high degree of stability against changes in temperature and humidity. A wide roll surround together with double chamber magnet system results in a low fundamental frequency. The magnet system is inherently shielded, allowing use in A/V systems. The voice coil is immersed in magnetic fluid. Pressure fit installation.



Nominal Impedance	4	Ohms	Voice coil resistance	2.7	Ohms
Recom. frequency range 2:	500-30000	Hz	Voice coil inductance	0.03	mH
Short term max. power	200	W	Force factor	1.9	N/A
Long term max. power	80	W	Free air resonance	1170	Hz
Sensitivity (1W/1m)	91	dB	Moving mass	0.26	g
			Suspension compliance	-	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	-	Ns/m
Voice coil height	1.1	mm	Effective piston area	7.5	sq. cm
Air gap height	2.0	mm	-		-
Linear coil travel (p-p)	0.9	mm	Power ratings with 12dB filter	@ 25001	Ηz
Max. coil travel (p-p)	-	mm	-		
Magnet weight	0.01	Kg			
Total weight	0.1	Kg			




Seas 27TFFNC/CG H1406

Compact design neodymium magnet tweeter for high quality small cabinet speakers or autosound applications. The diaphragm is vacuum formed from a precoated fabric for greater consistency. The coating has been carefully selected to result in a smooth frequency response and a high degree of stability against changes in temperature and humidity. A wide roll surround together with double chamber magnet system results in a low fundamental frequency. The magnet system is inherently shielded, allowing use in A/V systems. The voice coil is immersed in magnetic fluid. Truncated face plate.



Nominal Impedance	4	Ohms	Voice coil resistance	2.7	Ohms
Recom. frequency range 2500	-30000	Hz	Voice coil inductance	0.03	mH
Short term max. power	200	W	Force factor	1.9	N/A
Long term max. power	80	W	Free air resonance	1170	Hz
Sensitivity (1W/1m)	91	dB	Moving mass	0.26	g
			Suspension compliance	-	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	-	Ns/m
Voice coil height	1.1	mm	Effective piston area	7.5	sq. cm
Air gap height	2.0	mm			
Linear coil travel (p-p)	0.9	mm	Power ratings with 12dB filter	@ 2500H	Iz
Max. coil travel (p-p)	-	mm			
Magnet weight	0.01	Kg			
Total weight	0.1	Kg			



Frequency [Hz]

Seas 27TTFNC/GW H1461

This is a 27mm titanium dome tweeter with a soft polymer surround. The dome and surround material give high consistency and excellent stability against variations in air humidity. The titanium dome is protected by a hexagrid grill with acoustic lense. The voice coil is wound on a perforated aluminum former and immersed in magnet fluid for increased power handling. A powerful high grade neodymium ring magnet is coupled with an extruded aluminum heat sink for better heat transfer and increased power handling.



Seas 27TDFNC/GW H1462


This is a 27mm textile dome tweeter with a soft polymer surround. The dome and surround material give high consistency and excellent stability against variations in air humidity. The textile dome is protected by a hexagrid grill. The voice coil is wound on a perforated aluminum former and immersed in magnet fluid for increased power handling. A powerful high grade neodymium ring magnet is coupled with an extruded aluminum heat sink for better heat transfer and increased power handling.



Nominal Impedance	6	Ohms	Voice coil resistance	4.9	Ohms
Recom. frequency range	2500-25000	Hz	Voice coil inductance	0.05	mH
Short term max. power	230	W	Force factor	3.9	N/A
Long term max. power	100	W	Free air resonance	750	Hz
Sensitivity (1W/1m)	91.5	dB	Moving mass	0.32	g
			Suspension compliance	-	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	-	Ns/m
Voice coil height	1.5	mm	Effective piston area	7.0	sq. cm
Air gap height	2.0	mm	*		•
Linear coil travel (p-p)	0.5	mm	Vas	-	Liters
Max. coil travel (p-p)	-	mm	Qms	-	
Magnet weight	53	g	Qes	-	
Total weight	0.29	Kg	Ots	-	

100	50
95	
90-	W **
85	
⊕ 80	30 da
SPL [dB]	mpedance [ohm]
70-	20 9
65	
60	10
55	
50 - 10	1 000 Frequency [Hz] 10 000

Nominal Impedance	6	Ohms	Voice coil resistance	4.9	Ohms
Recom. frequency range	2500-30000	Hz	Voice coil inductance	0.05	mH
Short term max. power	220	W	Force factor	3.9	N/A
Long term max. power	90	W	Free air resonance	750	Hz
Sensitivity (1W/1m)	90.5	dB	Moving mass	0.31	g
			Suspension compliance	-	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	-	Ns/m
Voice coil height	1.5	mm	Effective piston area	7.0	sq. cm
Air gap height	2.0	mm			
Linear coil travel (p-p)	0.5	mm	Vas	-	Liters
Max. coil travel (p-p)	-	mm	Qms	-	
Magnet weight	53	g	Qes	-	
Total weight	0.29	Kg	Qts	-	




Seas 27TBCD/GB-DXT H1499

27TBCD/GB-DXT is a High Definition aluminum/magnesium alloy dome tweeter with DXT® lens. A fine mesh grid protects the diaphragm. Stiff and stable rear chamber with optimal acoustic damping allows the tweeter to be used with moderately low crossover frequencies. This revolutionary DXT® tweeter addresses the major issues regarding directivity control in traditional loudspeaker designs. DXT® solves several well-know issues regarding; directivity control, off-axis response, integration with midrange units and baffle diffraction.



Nominal Impedance	6	Ohms	Voice coil resistance	4.8	Ohms
Recom. frequency range 2	2000-25000	Hz	Voice coil inductance	0.05	mH
Short term max. power	150	W	Force factor	3.7	N/A
Long term max. power	55	W	Free air resonance	900	Hz
Sensitivity (1W/1m)	92	dB	Moving mass	0.33	g
			Suspension compliance	-	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	-	Ns/m
Voice coil height	1.5	mm	Effective piston area	7.5	sq. cm
Air gap height	2.0	mm	•		•
Linear coil travel (p-p)	0.5	mm	Power ratings with 12dB filter	@ 2500H	Iz
Max. coil travel (p-p)	-	mm	_		
Magnet weight	0.35	Kg			
Total weight	0.64	Kg			




Seas 27TBFC/G H1212 The H1212 is an aluminum / magnesium

The H1212 is an aluminum / magnesium alloy dome tweeter. The special wide and soft polymer surround, initially designed to give stability without using ferro fluid, adding ferro fluid has also produced a desirable result. The dome is protected by a hexagrid metal grill, which also supports an acoustic lens to control the roll off frequencies. The voice coil is wound on a perforated aluminum former to help reduce air flow noise. The flange is made from glass fiber reinforced plastic.



Nominal Impedance	6	Ohms	Voice coil resistance	4.8	Ohms
Recom. frequency range 1500-2	0000	Hz	Voice coil inductance	0.05	mH
Short term max. power	220	W	Force factor	3.5	N/A
Long term max. power	90	W	Free air resonance	550	Hz
Sensitivity (1W/1m)	91.5	dB	Moving mass	0.34	g
			Suspension compliance	-	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	-	Ns/m
Voice coil height	1.5	mm	Effective piston area	7.0	sq. cm
Air gap height	2.0	mm	-		_
Linear coil travel (p-p)	0.5	mm	Vas	-	Liters
Max. coil travel (p-p)	-	mm	Qms	-	
Magnet weight	0.25	Kg	Qes	-	
Total weight	0.5	Kg	Ots	-	




Seas 27TBC/G H1147

The H1147 is an aluminum / magnesium alloy dome tweeter with a wide soft polymer surround, designed to give stability without using ferro fluid. The dome is protected by a hexagrid grill, which also supports an acoustic lens which tailors the high frequency roll off. The voice coil is wound on a perforated aluminum former in order to reduce air flow noise. A stiff and stable rear chamber allows for a lower resonance frequency and lower crossover point. The face plate is made from glass fiber reinforced plastic.



Nominal Impedance	6	Ohms	Voice coil resistance	4.8	Ohms
Recom. frequency range	2000-25000	Hz	Voice coil inductance	0.05	mH
Short term max. power	150	W	Force factor	3.5	N/A
Long term max. power	55	W	Free air resonance	600	Hz
Sensitivity (1W/1m)	92	dB	Moving mass	0.33	g
			Suspension compliance	-	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	-	Ns/m
Voice coil height	1.5	mm	Effective piston area	7.0	sq. cm
Air gap height	2.0	mm			-
Linear coil travel (p-p)	0.5	mm	Vas	-	Liters
Max. coil travel (p-p)	-	mm	Qms	-	
Magnet weight	0.25	Kg	Qes	-	
Total weight	0.52	Kg	Qts	-	




Frequency [Hz]

Seas 27TDF H1211

The 27TDF is a low viscosity ferrofluid cooled tweeter with a High Definition pre-coated fabric dome and special wide soft polymer surround. The dome and surround materials give excellent stability against variations in air humidity. The voice coil is wound on an aluminum former with adequate ventilating holes to eliminate air flow noise. The chassis is precision molded glass reinforced plastic and offers optimum radiation.



Nominal Impedance	6	Ohms	Voice coil resistance	4.8	Ohms
Recom. frequency range 2500	-25000	Hz	Voice coil inductance	0.05	mH
Short term max. power	200	W	Force factor	3.5	N/A
Long term max. power	90	W	Free air resonance	900	Hz
Sensitivity (1W/1m)	91	dB	Moving mass	0.37	g
			Suspension compliance	-	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	-	Ns/m
Voice coil height	1.5	mm	Effective piston area	7.5	sq. cm
Air gap height	2.0	mm			
Linear coil travel (p-p)	0.5	mm	Vas	-	Liters
Max. coil travel (p-p)	-	mm	Qms	-	
Magnet weight	0.25	Kg	Qes	-	
Total weight	0.50	Kg	Qts	-	



Frequency [Hz] Frequency [Hz]


SPL [dB]

Seas 27TDC H1149

The 27TDC is a non-ferrofluid tweeter with a High Definition pre-coated fabric dome and soft polymer surround. This tweeter has been especially designed to operate without ferrofluid. The dome and surround materials give excellent stability against variations in air humidity. The voice coil is wound on an aluminum former with adequate ventilating holes to eliminate air flow noise. A stiff and stable rear chamber with optimal acoustic damping allows the 27TDC to be used with moderately low crossover frequencies. The chassis is precision molded glass reinforced plastic and offers optimum radiation.



Nominal Impedance	6	Ohms	Voice coil resistance	4.8	Ohms
Recom. frequency range	2000-25000	Hz	Voice coil inductance	0.05	mH
Short term max. power	150	W	Force factor	3.5	N/A
Long term max. power	55	W	Free air resonance	550	Hz
Sensitivity (1W/1m)	90	dB	Moving mass	0.30	g
-			Suspension compliance	-	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	-	Ns/m
Voice coil height	1.5	mm	Effective piston area	7.0	sq. cm
Air gap height	2.0	mm			
Linear coil travel (p-p)	0.5	mm	Vas	-	Liters
Max. coil travel (p-p)	-	mm	Qms	-	
Magnet weight	0.25	Kg	Qes	-	
Total weight	0.50	Kg	Qts	-	




Seas 27TDFC H1189

The 27TDFC is a low viscosity ferrofluid cooled tweeter with a High Definition pre-coated fabric dome and wide soft polymer surround. The dome and surround materials give excellent stability against variations in air humidity. The voice coil is wound on an aluminum former with adequate ventilating holes to eliminate air flow noise. A stiff and stable rear chamber with optimal acoustic damping allows the 27TDFC to be used with moderately low crossover frequencies. The chassis is precision molded glass reinforced plastic and offers optimum radiation.



Nominal Impedance	6	Ohms	Voice coil resistance	4.8	Ohms
Recom. frequency range	1500-25000	Hz	Voice coil inductance	0.05	mH
Short term max. power	220	W	Force factor	3.5	N/A
Long term max. power	90	W	Free air resonance	550	Hz
Sensitivity (1W/1m)	90	dB	Moving mass	0.37	g
			Suspension compliance	-	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	-	Ns/m
Voice coil height	1.5	mm	Effective piston area	7.5	sq. cm
Air gap height	2.0	mm			
Linear coil travel (p-p)	0.5	mm	Vas	-	Liters
Max. coil travel (p-p)	-	mm	Qms	-	
Magnet weight	0.25	Kg	Qes	-	
Total weight	0.50	Kg	Qts	-	



Seas 27TDFC/TV H1210

The 27TDFC/TV is a low viscosity ferro fluid cooled tweeter with a High Definition pre-coated fabric dome and soft polymer surround. The dome and surround materials give excellent stability against variations in air humidity. The voice coil is wound on an aluminum former with ventilating holes to eliminate air flow noise. The shielded magnet system allows the tweeter to be used in proximity to video display screens or TV sets. The chassis is precision molded glass reinforced plastic and offers optimum radiation.




Nominal Impedance	6	Ohms	Voice coil resistance	4.8	Ohms
Recom. frequency range 2		Hz	Voice coil inductance	0.05	mH
Short term max. power	220	W	Force factor	2.8	N/A
Long term max. power	90	W	Free air resonance	800	Hz
Sensitivity (1W/1m)	89.5	dB	Moving mass	0.37	g
, , , , , , , , , , , , , , , , , , , ,			Suspension compliance	-	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	-	Ns/m
Voice coil height	1.5	mm	Effective piston area	7.5	sq. cm
Air gap height	2.0	mm	•		•
Linear coil travel (p-p)	0.5	mm	Vas	-	Liters
Max. coil travel (p-p)	-	mm	Qms	-	
Magnet weight	0.4	Kg	Qes	-	
Total weight	0.5	Kg	Qts	-	

Seas 29TAF/W H1322

The 29TAF/W aluminum/magnesium alloy dome tweeter with wide, pre-coated fabric surround. The dome and surround are made in house for excellent consistency. The voice coil is wound on an aluminum former with adequate venting holes to eliminate noise from internal air flow. Low viscosity magnetic fluid and flexible lead-out wires ensure high power handling. Two part front plate with smooth, slightly elliptical wave guide made from elastomer provide excellent high frequency response and dispersion. The wave guide conceals the magnet system screws.



Nominal Impedance	6	Ohms	Voice coil resistance	4.7	Ohms
Recom. frequency range 2200-25	000	Hz	Voice coil inductance	0.05	mH
Short term max. power	220	W	Force factor	3.5	N/A
Long term max. power	100	W	Free air resonance	950	Hz
Sensitivity (1W/1m)	91.5	dB	Moving mass	0.39	g
			Suspension compliance	-	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	-	Ns/m
Voice coil height	1.5	mm	Effective piston area	8	sq. cm
Air gap height	2.0	mm	-		_
Linear coil travel (p-p)	0.5	mm	Vas	-	Liters
Max. coil travel (p-p)	-	mm	Qms	-	
Magnet weight (0.25	Kg	Qes	-	
Total weight (0.53	Kg	Qts	-	




Seas 29TFF/W H1318

The 29TFF/W is a High Definition fabric dome tweeter with integrated wide surround. The ediaphragm is made in house from pre-coated fabric for consistency. The voice coil is wound on an aluminum former with adequate venting holes to eliminate noise from internal air flow. Low viscosity magnetic fluid and flexible lead-out wires ensure high power handling. Two part front plate with smooth, slightly elliptical wave guide made from elastomer provide excellent high frequency response and dispersion. The wave guide conceals the magnet system screws.



Nominal Impedance	6	Ohms	Voice coil resistance	4.7	Ohms
Recom. frequency range 2200-2	25000	Hz	Voice coil inductance	0.05	mH
Short term max. power	200	W	Force factor	3.5	N/A
Long term max. power	90	W	Free air resonance	950	Hz
Sensitivity (1W/1m)	92	dB	Moving mass	0.35	g
			Suspension compliance	-	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	-	Ns/m
Voice coil height	1.5	mm	Effective piston area	8	sq. cm
Air gap height	2.0	mm	_		_
Linear coil travel (p-p)	0.5	mm	Vas	-	Liters
Max. coil travel (p-p)	-	mm	Qms	-	
Magnet weight	0.25	Kg	Qes	-	
Total weight	0.53	Kg	Qts	-	




Seas MCA15RCY H1262

The MCA15RCY is a 5" coated paper cone midrange. The classical paper cone gives a smooth and extended frequency response with a controlled roll off. The large magnet and light cone provide high sensitivity, low distortion and good transient response. The stiff injection molded basket has large windows and a raised spider to reduce sound reflection and air flow noise.

The frequency response extends to 10,000 Hz, indicating this driver is not overly damped and will have good upper midrange response.



Nominal Impedance	8	Ohms	Voice coil resistance	5.8	Ohms
Recom. frequency range	100-4000	Hz	Voice coil inductance	0.73	mH
Short term max. power	300	W	Force factor	6.8	N/A
Long term max. power	100	W	Free air resonance	51	Hz
Sensitivity (1W/1m)	89.5	dB	Moving mass	7.1	g
			Suspension compliance	1.4	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	1.53	Ns/m
Voice coil height	9.4	mm	Effective piston area	80	sq. cm
Air gap height	6.0	mm			
Linear coil travel (p-p)	3.4	mm	Vas	12	Liters
Max. coil travel (p-p)	14	mm	Qms	1.57	
Magnet weight	0.42	Kg	Qes	0.30	
Total weight	1.3	Kg	Qts	0.25	




Seas MCA12RC H1304

The MCA12RC is a 4.5" coated paper cone midrange with a mechanically matching natural rubber surround. The result is an unusually smooth midrange response. The stiff injection molded basket has large windows and a raised spider to reduce sound reflection and air flow noise. A 1" high temperature voice coil wound on an aluminum former ensured high power handling capacity.

The frequency response extends to 10,000 Hz, indicating this driver is not overly damped and will have good upper midrange response.



Nominal Impedance	8	Ohms	Voice coil resistance	6.3	Ohms
Recom. frequency range	400-5000	Hz	Voice coil inductance	0.31	mH
Short term max. power	400	W	Force factor	4.2	N/A
Long term max. power	110	W	Free air resonance	68	Hz
Sensitivity (1W/1m)	86	dB	Moving mass	5.58	g
			Suspension compliance	1.2	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	0.85	Ns/m
Voice coil height	5.8	mm	Effective piston area	55	sq. cm
Air gap height	4.0	mm			
Linear coil travel (p-p)	1.8	mm	Vas	5	Liters
Max. coil travel (p-p)	-	mm	Qms	2.42	
Magnet weight	0.25	Kg	Qes	0.74	
Total weight	0.66	Kg	Qts	0.56	




Seas CA12RCY H1152

Natural rubber surround and hand coated paper cone with coated fabric dust cap, reduce resonances and distortion. A large magnet system and a symmetrical driving force accomplished through a special coil winding technique for the voice coil give excellent linearity. A very large magnet system provides a reasonable efficiency and a low Q. Extremely stiff and stable injection molded metal basket keeps the critical components in perfect alignment. Large windows in the basket both above and below the spider reduce sound reflection, air flow noise and cavity resonance to a minimum.



Nominal Impedance	8	Ohms	Voice coil resistance	6.4	Ohms
Recom. frequency range	45-5000	Hz	Voice coil inductance	1.05	mH
Short term max. power	200	W	Force factor	6.35	N/A
Long term max. power	60	W	Free air resonance	57	Hz
Sensitivity (1W/1m)	86	dB	Moving mass	6.1	g
			Suspension compliance	1.3	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	1.04	Ns/m
Voice coil height	12	mm	Effective piston area	55	sq. cm
Air gap height	6.0	mm			
Linear coil travel (p-p)	6.0	mm	Vas	5	Liters
Max. coil travel (p-p)	9.0	mm	Qms	2.17	
Magnet weight	0.42	Kg	Qes	0.36	
Total weight	1.21	Kg	Qts	0.31	




Seas L12RCY/P H1207

The L12RCY/P is a 4.5" mini woofer with an aluminum cone, light yet stiff. The aluminum cone, coupled with the low loss rubber surround, show no sign of cone edge resonance and distortion associated with soft cones. On the other hand, cone breakup at higher frequencies call for special attention in the crossover design work. A bullet shaped phase plug reduces compression due to temperature variations in the voice coil, avoids resonance problems which would occur in the volume between the dust cap and pole piece and increases long term power handling. Raised spider VC ventilation.



Nominal Impedance	8	Ohms	Voice coil resistance	5.5	Ohms
Recom. frequency range	55-3500	Hz	Voice coil inductance	0.76	mH
Short term max. power	200	W	Force factor	6.1	N/A
Long term max. power	70	W	Free air resonance	50	Hz
Sensitivity (1W/1m)	85.5	dB	Moving mass	6.8	g
			Suspension compliance	1.5	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	0.94	Ns/m
Voice coil height	12	mm	Effective piston area	50	sq. cm
Air gap height	6.0	mm	*		•
Linear coil travel (p-p)	6.0	mm	Vas	5	Liters
Max. coil travel (p-p)	9.0	mm	Qms	2.34	
Magnet weight	0.42	Kg	Qes	0.33	
Total weight	1.21	Kg	Qts	0.29	




Seas ER15RLY H1455

The 5" ER15RLY features a new edge coated Reed/Paper pulp cone. The careful selection of cone, surround and spider has produced a driver with an smooth extended frequency response. The Large magnet system, together with a very long and light weight copper clad aluminum voice coil allow good excursion with low distortion and good transient response. A 0.3 cubic foot box with a 1.5" diameter vent by 5" long will give you a 3dB down point of 58Hz.



Nominal Impedance	8	Ohms	Voice coil resistance	5.6	Ohms
Recom. frequency range	50-4000	Hz	Voice coil inductance	0.73	mH
Short term max. power	250	W	Force factor	5.5	N/A
Long term max. power	60	W	Free air resonance	44	Hz
Sensitivity (1W/1m)	87.5	dB	Moving mass	7.6	g
			Suspension compliance	1.7	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	1.43	Ns/m
Voice coil height	16	mm	Effective piston area	80	sq. cm
Air gap height	6.0	mm	-		-
Linear coil travel (p-p)	10	mm	Vas	15.0	Liters
Max. coil travel (p-p)	20	mm	Qms	1.55	
Magnet weight	0.42	Kg	Qes	0.41	
Total weight	1.29	Kg	Ots	0.32	




Seas CA15RLY H1216

This 5.5" woofer was developed for use as a long throw high fidelity woofer or woofer/midrange. The CA15RLY is a coated paper cone with extended frequency range and controlled roll off. The large magnet system, together with a very long and light CCAW voice coil allow good excursion with low distortion and good transient response. The basket is a stable injection molded metal, with large windows both above and below the spider, to reduce sound reflection, air flow noise and cavity resonance. An 8 liter box can give you an F3 of 54Hz.



Nominal Impedance	8	Ohms	Voice coil resistance	5.5	Ohms
Recom. frequency range	50-4000	Hz	Voice coil inductance	0.76	mH
Short term max. power	250	W	Force factor	5.4	N/A
Long term max. power	60	W	Free air resonance	47	Hz
Sensitivity (1W/1m)	87	dB	Moving mass	8.2	g
			Suspension compliance	1.4	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	1.5	Ns/m
Voice coil height	16	mm	Effective piston area	80	sq. cm
Air gap height	6.0	mm	-		-
Linear coil travel (p-p)	10.0	mm	Vas	12.0	Liters
Max. coil travel (p-p)	20	mm	Qms	1.70	
Magnet weight	0.42	Kg	Qes	0.48	
Total weight	1.29	Kg	Qts	0.37	




Seas L15RLY/P H1141

This 5.5" woofer features a light, yet stiff aluminum cone, with a low loss rubber surround and magnesium cast frame. This driver shows no sign of the familiar 500-1500Hz cone edge resonance and distortion associated with soft cones. On the other hand, cone breakup at higher frequencies require special crossover attention. The phase plug gives low compression due to temperature variations in the voice coil, high power handling capacity and eliminates resonance which would otherwise occur in the volume between the dust cap and the pole piece. Raised Spider.



Nominal Impedance	8	Ohms	Voice coil resistance	5.5	Ohms
Recom. frequency range	45-3000	Hz	Voice coil inductance	0.84	mH
Short term max. power	200	W	Force factor	5.7	N/A
Long term max. power	80	W	Free air resonance	44	Hz
Sensitivity (1W/1m)	86	dB	Moving mass	8.1	g
			Suspension compliance	1.6	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	1.12	Ns/m
Voice coil height	16	mm	Effective piston area	75	sq. cm
Air gap height	6.0	mm	-		-
Linear coil travel (p-p)	10.0	mm	Vas	12	Liters
Max. coil travel (p-p)	20	mm	Qms	2.10	
Magnet weight	0.42	Kg	Qes	0.43	
Total weight	1.28	Kg	Qts	0.35	
· -		-			




Seas L16RN-SL H1480

L16RNX is a 5" High Fidelity woofer with an injection molded metal chassis, intended for bass reflex and transmission line designs. Stiff, yet light aluminum cone and low loss rubber surround show no sign of the familiar 500-1500 Hz cone edge resonance and distortion associated with soft cones. A bumped back plate in the magnet system, together with the very long and light weight copper clad aluminum voice coil, allow extreme coil excursion with low distortion. A heavy copper ring below the T-shaped pole piece reduces non linear and modulation distortion.



Nominal Impedance	8	Ohms	Voice coil resistance	6.1	Ohms
Recom. frequency range	45-2000	Hz	Voice coil inductance	0.68	mH
Short term max. power	250	W	Force factor	6.2	N/A
Long term max. power	80	W	Free air resonance	36	Hz
Sensitivity (1W/1m)	84	dB	Moving mass	14.8	g
• • • • • • • • • • • • • • • • • • • •			Suspension compliance	1.3	mm/N
Voice Coil Diameter	38	mm	Suspension mech. resistance	1.41	Ns/m
Voice coil height	18	mm	Effective piston area	104	sq. cm
Air gap height	6.0	mm	•		•
Linear coil travel (p-p)	12.0	mm	Vas	19	Liters
Max. coil travel (p-p)	22	mm	Oms	2.47	
Magnet weight	0.42	Kg	Oes	0.56	
Total weight	1.40	Kg	Qts	0.46	
		-	-		




Seas CA18RNX H1215

This 7" driver was designed for use as a long throw hi-fi woofer or bass/midrange unit. The classical coated paper cone gives a smooth extended frequency response with a controlled roll off. The large magnet system provides good transient response. The bumped back plate, together with the very long and light weight copper clad aluminum voice coil allow for extreme coil excursion with low distortion. The stiff injection molded cast frame has large windows both above and below the spider, to reduce sound reflection, air noise and cavity resonance. An Fs of 45 Hz can be achieved in an 18 ltr



Nominal Impedance	8	Ohms	Voice coil resistance	5.8	Ohms
Recom. frequency range	45-3000	Hz	Voice coil inductance	1.2	mH
Short term max. power	250	W	Force factor	7.2	N/A
Long term max. power	80	W	Free air resonance	35	Hz
Sensitivity (1W/1m)	88.5	dB	Moving mass	14	g
			Suspension compliance	1.4	mm/N
Voice Coil Diameter	39	mm	Suspension mech. resistance	1.72	Ns/m
Voice coil height	18	mm	Effective piston area	136	sq. cm
Air gap height	6.0	mm			
Linear coil travel (p-p)	12	mm	Vas	33	Liters
Max. coil travel (p-p)	22	mm	Qms	1.90	
Magnet weight	0.64	Kg	Qes	0.37	
Total weight	1.91	Kg	Qts	0.31	




Seas CA18RLY H1217

The CA18RLY is a classical coated paper cone woofer, but with a new high tech basket. The injection molded basket features large windows and a raised spider to reduce sound reflection, air flow noise and cavity resonance. The high temperature and light weight voice coil is wound on an aluminum former. This speaker has a natural rubber surround. The higher Qts of this driver makes it suitable for a sealed box of about 1/2 to 3/4 of a cubic foot and a resulting 3dB down point of 65Hz.



Nominal Impedance	8	Ohms	Voice coil resistance	5.8	Ohms
Recom. frequency range	35-2500	Hz	Voice coil inductance	1.03	mH
Short term max. power	250	W	Force factor	5.6	N/A
Long term max. power	80	W	Free air resonance	43	Hz
Sensitivity (1W/1m)	90	dB	Moving mass	8.8	g
			Suspension compliance	1.6	mm/N
Voice Coil Diameter	26	mm	Suspension mech. resistance	1.2	Ns/m
Voice coil height	16	mm	Effective piston area	136	sq. cm
Air gap height	6	mm			
Linear coil travel (p-p)	10	mm	Vas	37	Liters
Max. coil travel (p-p)	20	mm	Qms	2.19	
Magnet weight	0.42	Kg	Qes	0.48	
Total weight	1.41	Kg	Qts	0.40	




Seas ER18RNX H1456

The 7" ER18RNX features a new edge coated Reed/Paper pulp cone. The careful selection of cone, surround and spider has produced a driver with an smooth extended frequency response. The large magnet system with bumped back plate, together with a very long and light weight copper clad aluminum voice coil allow good excursion with low distortion and good transient response. A copper shorting ring in the magnet system reduces non linear on modulation distortion. A 0.65 cubic foot box with a 25" diameter vent by 6" long will give you a 3dB down point of 52Hz.



Nominal Impedance	8	Ohms	Voice coil resistance	5.9	Ohms
Recom. frequency range	45-3000	Hz	Voice coil inductance	0.67	mH
Short term max. power	250	W	Force factor	7.2	N/A
Long term max. power	80	W	Free air resonance	37	Hz
Sensitivity (1W/1m)	88.5	dB	Moving mass	14	g
			Suspension compliance	1.3	mm/N
Voice Coil Diameter	39	mm	Suspension mech. resistance	2.2	Ns/m
Voice coil height	18	mm	Effective piston area	136	sq. cm
Air gap height	6	mm	_		_
Linear coil travel (p-p)	12	mm	Vas	32	Liters
Max. coil travel (p-p)	22	mm	Qms	1.58	
Magnet weight	0.64	Kg	Qes	0.39	
Total weight	1.91	Kg	Qts	0.32	




Seas L18RNX/P H1224

7" aluminum cone woofer. The stiff cone coupled with the low loss rubber surround shows no sign of cone edge resonance and distortion associated with soft cones. Tremendous bass precision. A bullet shaped phase plug reduces compression due to temperature variations in the voice coil, avoids resonance problems which would occur in the volume between the dust cap and pole piece and increases long term power handling. Large magnet for good efficiency. Raised Spider and bumped back plate for increased power handling and lower mechanical distortion.



Nominal Impedance	8	Ohms	Voice coil resistance	5.8	Ohms
Recom. frequency range	40-2500	Hz	Voice coil inductance	1.06	mH
Short term max. power	250	W	Force factor	7.2	N/A
Long term max. Power	100	W	Free air resonance	36	Hz
Sensitivity (1W/1m)	88	dB	Moving mass	13.6	g
			Suspension compliance	1.4	mm/N
Voice Coil Diameter	39	mm	Suspension mech. resistance	1.56	Ns/m
Voice coil height	18.0	mm	Effective piston area	126	sq. cm
Air gap height	6.0	mm			
Linear coil travel (p-p)	12.0	mm	Vas	30	Liters
Max. coil travel (p-p)	22.0	mm	Qms	2.09	
Magnet weight	0.64	Kg	Qes	0.36	
Total weight	1.92	Kg	Qts	0.31	




Seas CA22RNX H1288

A hand coated paper cone and matching natural rubber surround produce a well behaved roll off characteristic and reduce potential resonance problems. A long voice coil wound on an aluminum former gives low distortion and high power handling. The large magnet system provides high efficiency and good transient response. A bumped backplate in the magnet system allow maximum utilization of the long voice coil without mechanical limitation. Large windows in the basket both above and below the spider reduce sound reflections, air flow noise and cavity resonance.



•					
Nominal Impedance	8	Ohms	Voice coil resistance	6.1	Ohms
Recom. frequency range	30-3000	Hz	Voice coil inductance	1.0	mH
Short term max. power	250	W	Force factor	7.0	N/A
Long term max. power	80	W	Free air resonance	29	Hz
Sensitivity (1W/1m)	89.5	dB	Moving mass	20.9	g
			Suspension compliance	1.4	mm/N
Voice Coil Diameter	39	mm	Suspension mech. resistance	2.05	Ns/m
Voice coil height	18	mm	Effective piston area	230	sq. cm
Air gap height	6	mm	-		_
Linear coil travel (p-p)	12	mm	Vas	97	Liters
Max. coil travel (p-p)	26	mm	Qms	2.04	
Magnet weight	0.64	Kg	Qes	0.52	
Total weight	2.2	Kg	Qts	0.41	




Seas P18RNX/P H1350

7" Polypropylene cone woofer, coupled with a high loss rubber surround. Tremendous bass precision. A bullet shaped phase plug reduces compression due to temperature variations in the voice coil, avoids resonance problems which would occur in the volume between the dust cap and pole piece and increases long term power handling. Large magnet for good efficiency. Raised Spider and bumped back plate for increased power handling and lower mechanical distortion. This driver is an excellent choice for use in a satellite speaker or stand alone bookshelf speaker.



Nominal Impedance	8	Ohms	Voice coil resistance	5.7	Ohms
Recom. frequency range	45-3000	Hz	Voice coil inductance	1.0	mH
Short term max. power	250	W	Force factor	7.0	N/A
Long term max. Power	80	W	Free air resonance	43	Hz
Sensitivity (1W/1m)	89	dB	Moving mass	12.2	g
-			Suspension compliance	1.12	mm/N
Voice Coil Diameter	39	mm	Suspension mech. resistance	1.46	Ns/m
Voice coil height	18.0	mm	Effective piston area	126	sq. cm
Air gap height	6.0	mm			-
Linear coil travel (p-p)	12.0	mm	Vas	24.9	Liters
Max. coil travel (p-p)	22.0	mm	Qms	2.26	
Magnet weight	0.64	Kg	Qes	0.39	
Total weight	1.92	Kg	Qts	0.33	




Seas L22RN4X/P H1208

The L22RN4X/P is an 8" aluminum cone woofer, very light and stiff. The stiff cone provides tremendous bass precision. The aluminum cone and low loss rubber surround show no sign of the familiar 500-1500Hz cone edge resonance. The high temperature voice coil on aluminum former provide excellent power handling. The phase plug reduces compression due to temperature variations in the voice coil, and eliminates resonances that can occur in the gap between the dust cap and pole piece. The resonance at higher frequencies require some special crossover work. 4 Layer Voice Coil



Nominal Impedance	8	Ohms	Voice coil resistance	6.1	Ohms
Recom. frequency range	20-1000	Hz	Voice coil inductance	3.76	mH
Short term max. power	300	W	Force factor	10.7	N/A
Long term max. power	125	W	Free air resonance	21	Hz
Sensitivity (1W/1m)	86.5	dB	Moving mass	40	g
			Suspension compliance	1.4	mm/N
Voice Coil Diameter	39	mm	Suspension mech. resistance	1.76	Ns/m
Voice coil height	20	mm	Effective piston area	220	sq. cm
Air gap height	6.0	mm	_		-
Linear coil travel (p-p)	14.0	mm	Vas	93	Liters
Max. coil travel (p-p)	21.0	mm	Qms	3.13	
Magnet weight	0.64	Kg	Qes	0.29	
Total weight	2.2	Kg	Qts	0.27	
-		-	-		




Seas L22RNX/P H1252

The L22RNX/P is an 8" aluminum cone woofer, very light and stiff. The stiff cone provides tremendous bass precision. The aluminum cone and low loss rubber surround show no sign of the familiar 500-1500Hz cone edge resonance. The high temperature voice coil on aluminum former provide excellent power handling. The phase plug reduces compression due to temperature variations in the voice coil, and eliminates resonances that can occur in the gap between the dust cap and pole piece. The resonance at higher frequencies require some special crossover work. 2 Layer Voice Coil



Nominal Impedance	8	Ohms	Voice coil resistance	6.0	Ohms
Recom. frequency range	25-1000	Hz	Voice coil inductance	1.43	mH
Short term max. power	300	W	Force factor	8.15	N/A
Long term max. power	110	W	Free air resonance	23	Hz
Sensitivity (1W/1m)	88	dB	Moving mass	27	g
			Suspension compliance	1.8	mm/N
Voice Coil Diameter	39	mm	Suspension mech. resistance	2.01	Ns/m
Voice coil height	18	mm	Effective piston area	220	sq. cm
Air gap height	6.0	mm	•		•
Linear coil travel (p-p)	12.0	mm	Vas	112	Liters
Max. coil travel (p-p)	21.0	mm	Qms	2.07	
Magnet weight	0.64	Kg	Qes	0.38	
Total weight	2.2	Kg	Qts	0.32	




Seas CA26RFX H1305

A classical hand coated paper cone and matching natural rubber surround produce a well behaved roll off characteristic and reduce potential resonance problems. A 2" high temperature voice coil with black anodized aluminum coil former gives high power handling and reduced power compression. A large magnet system gives good sensitivity and transient response. A bumped backplate in the magnet system allow maximum excursion. Large windows in the basket both above and below the spider reduce reflection, air flow noise and cavity resonance. 51mm VC Ø, 7mm x-max



Nominal Impedance	8	Ohms	Voice coil resistance	6.3	Ohms
Recom. frequency range	30-1000	Hz	Voice coil inductance	1.95	mH
Short term max. power	300	W	Force factor	10.7	N/A
Long term max. power	100	W	Free air resonance	29	Hz
Sensitivity (1W/1m)	90,5	dB	Moving mass	36.1	g
			Suspension compliance	0.8	mm/N
Voice Coil Diameter	51	mm	Suspension mech. resistance	3.4	Ns/m
Voice coil height	20	mm	Effective piston area	350	sq. cm
Air gap height	6	mm			
Linear coil travel (p-p)	14	mm	Vas	129	Liters
Max. coil travel (p-p)	35	mm	Qms	2.14	
Magnet weight	3.0	Kg	Qes	0.40	
Total weight	4.5	Kg	Qts	0.34	




Seas CA26RE4X H1316

A classical manually coated paper cone and matching natural rubber surround produce a smooth response and reduce potential resonance problems. A four layer voice coil provides a well behaved roll off characteristic. A large magnet system gives good sensitivity and transient response. Extremely stiff and stable injection molded metal basket keeps the critical components in perfect alignment. Large windows in the basket both above and below the spider reduce sound reflection, and keep air flow noise and cavity resonance to a minimum.



39mm voice coil Ø, 4mm x-max

Nominal Impedance	8	Ohms	Voice coil resistance	6.1	Ohms
Recom. frequency range	30-1500	Hz	Voice coil inductance	3.08	mH
Short term max. power	300	W	Force factor	11.6	N/A
Long term max. power	80	W	Free air resonance	25	Hz
Sensitivity (1W/1m)	91	dB	Moving mass	38.5	g
_			Suspension compliance	1.1	mm/N
Voice Coil Diameter	39	mm	Suspension mech. resistance	1.66	Ns/m
Voice coil height	14	mm	Effective piston area	350	sq. cm
Air gap height	6	mm			
Linear coil travel (p-p)	8	mm	Vas	164	Liters
Max. coil travel (p-p)	20	mm	Qms	3.99	
Magnet weight	0.64	Kg	Qes	0.30	
Total weight	2.17	Kg	Qts	0.28	




Seas L26RFX/P H1209

This 10" woofer features a light, yet stiff aluminum cone for stiffness in providing bass precision. Large windows both above and below the spider in the injection molded metal basket help reduce air flow noise, sound reflections and cavity resonance. The low loss rubber surround shows no sign of the familiar edge resonance. Cone breakup at higher frequencies need to be addressed in the crossover design. A 2" diameter high temperature voice coil with black anodized aluminum former gives high power handling and reduce compression. The phase plug helps eliminate resonances.



Nominal Impedance	8	Ohms	Voice coil resistance	6.3	Ohms
Recom. frequency range	20-1000	Hz	Voice coil inductance	1.83	mH
Short term max. power	300	W	Force factor	10.7	N/A
Long term max. power	125	W	Free air resonance	20	Hz
Sensitivity (1W/1m)	88	dB	Moving mass	53	g
			Suspension compliance	1.2	mm/N
Voice Coil Diameter	51	mm	Suspension mech. resistance	3.3	Ns/m
Voice coil height	20	mm	Effective piston area	330	sq. cm
Air gap height	6.0	mm			
Linear coil travel (p-p)	14.0	mm	Vas	171	Liters
Max. coil travel (p-p)	35	mm	Qms	2.15	
Magnet weight	3.0	Kg	Qes	0.39	
Total weight	4.05	Kg	Qts	0.33	



Seas SP18R H9944

This 6.5" passive radiator is intended for use as an alternative to the vented port in a bass reflex cabinet. In many applications a traditional port may produce air noise which is often improved by use of a passive radiator instead.

The cone is equipped with a 4mm screw to which you can easily affix added mass.

For optimum performance the passive radiator should be mounted vertically. This is especially important when significant additional mass is used. Polypropylene cone, rubber surround, and injection molded zinc frame.



Nominal Impedance		Ohms	Voice coil resistance		Ohms
Recom. frequency range		Hz	Voice coil inductance		mH
Short term max. Power		W	Force factor		N/A
Long term max. power		W	Free air resonance	26	Hz
Sensitivity (1W/1m)		dB	Moving mass	21.5	g
			Suspension compliance	1.74	mm/N
Voice Coil Diameter		mm	Suspension mech. resistance		Ns/m
Voice coil height		mm	Effective piston area	130	sq. cm
Air gap height		mm			
Linear coil travel (p-p)		mm	Vas	41	Liters
Max. coil travel (p-p)	19	mm	Qms		
Magnet weight		Kg	Qes		
Total weight	.30	Kg	Qts		

		Passive radiate	or chart SP17R		
»					Additional weight in grammes
			Passive radiator		
				<u> </u>	
1 " S					
n					
25					
20					
15				+	
ž 10 I	D 16		9L 40	50 63	79 100
		Cubinet stee in its	res		

Seas SP26R H9946


This 10" passive radiator is intended for use as an alternative to the vented port in a bass reflex cabinet. In many applications a traditional port may produce air noise which is often improved by use of a passive radiator instead.

The cone is equipped with a 4mm screw to which you can easily affix added mass.

For optimum performance the passive radiator should be mounted vertically. This is especially important when significant additional mass is used. Polypropylene cone, rubber surround, and injection molded zinc frame.



Nominal Impedance		Ohms	Voice coil resistance		Ohms
Recom. frequency range		Hz	Voice coil inductance		mH
Short term max. power		W	Force factor		N/A
Long term max. Power		W	Free air resonance	22	Hz
Sensitivity (1W/1m)		dB	Moving mass	42	g
			Suspension compliance	1.25	mm/N
Voice Coil Diameter		mm	Suspension mech. resistance		Ns/m
Voice coil height		mm	Effective piston area	350	sq. cm
Air gap height		mm	*		•
Linear coil travel (p-p)		mm	Vas	214	Liters
Max. coil travel (p-p)	25	mm	Qms		
Magnet weight		Kg	Qes		
Total weight	65	Kσ	Ots		



Seas SP22R H9945

This 8" passive radiator is intended for use as an alternative to the vented port in a bass reflex cabinet. In many applications a traditional port may produce air noise which is often improved by use of a passive radiator instead.

The cone is equipped with a 4mm screw to which you can easily affix added mass.

For optimum performance the passive radiator should be mounted vertically. This is especially important when significant additional mass is used. Polypropylene cone, rubber surround, and injection molded zinc frame.



Nominal Impedance		Ohms	Voice coil resistance		Ohms
Recom. frequency range		Hz	Voice coil inductance		mH
Short term max. power		W	Force factor		N/A
Long term max. Power		W	Free air resonance	22	Hz
Sensitivity (1W/1m)		dB	Moving mass	28	g
			Suspension compliance	1.87	mm/N
Voice Coil Diameter		mm	Suspension mech. resistance		Ns/m
Voice coil height		mm	Effective piston area	230	sq. cm
Air gap height		mm			
Linear coil travel (p-p)		mm	Vas	138	Liters
Max. coil travel (p-p)	20	mm	Qms		
Magnet weight		Kg	Qes		
Total weight	.45	Kg	Qts		

Passive radiator chart SP21R


55 50 46 40	Y WYY					/ / / / / / / /			_			1/1/			Į ,	Ļ									Additional weight in grammes
233				K	*		\geq				1	\geq				Ë				_			=	-	
50	_		-	T -:	1		\geq	8	氢	\equiv		-		=	\geq							-	-		
25	Ē.,	-		he rad		-		=	È	×			11/1		Ξ										
20							-	Ē	<u>+</u>	I		=		=	7										
15	_		-	-								==		==	Ë		Ξ	Ē					-		
,,]		10	Ė	30	Ė	- 2	Ξ		E	1	-		ļ=	sn .	=	-	-		Ę	-	Ŀ				

Seas T18REX/XFC H1353

A PP/TPX based cone matches ideally with an **adaptive rubber surround**. The result is an outstandingly smooth frequency response from the mid woofer. A coaxially arranged pre-coated fabric dome high frequency unit with a low resonance frequency, integrates with the cone driver to a point source. The cone of the woofer acts as a horn loading for the tweeter, and the chassis of the dome unit represents the throat of this horn. This unshielded version is ideal for smaller enclosures. F3 of 60Hz in 0.3 cubic foot enclosure with a 1.5" diameter vent by 5" long. Crossover available separately.



Twee	eter/Woofer		Voice coil resistance	4.8/6.1	Ohms
Nominal Impedance	6/8	Ohms	Voice coil inductance	0.05/0.7	mH
Recom. frequency range	40-25000	Hz	Force factor	2.3/7.5	N/A
Short term max. power	220/250	W	Free air resonance	1200/29	Hz
Long term max. power	90/80	W	Moving mass	0.3/13.6	g
Sensitivity (1W/1m)	88.5/87	dB	Suspension compliance	-/2.38	mm/N
Voice Coil Diameter	26/39	mm	Suspension mech. resistar	rce -/-	Ns/m
Voice coil height	1.5/12	mm	Effective piston area	7.0/120	sq. cm
Air gap height	2.0/6.0	mm			
Linear coil travel (p-p)	0.5/6.0	mm	Vas	-/47.9	Liters
Max. coil travel (p-p)	-/20	mm	Qms	-/1.50	
Magnet weight	-/0.64	Kg	Qes	-/0.26	
Total weight		Kg	Qts	-/0.22	





Seas T18RE/XFCTV2 H1333

A PP/TPX based cone matches ideally with an **adaptive rubber surround**. The result is an outstandingly smooth frequency response from the mid woofer. A coaxially arranged pre-coated fabric dome tweeter with a low resonance frequency, integrates with the cone driver to a point source. The cone of the woofer acts as a horn loading for the tweeter, and the chassis of the dome unit represents the throat of this horn. A compensation magnet and a shielding cup is mounted on the woofer magnet system to eliminate magnetic stray fields, hence the unit can be used very close to CRT's in audio/video applications.




Twee	eter/Woofer		Voice coil resistance	4.8/6.1	Ohms
Nominal Impedance	6/8	Ohms	Voice coil inductance	0.05/0.79	mH
Recom. frequency range	30-25000	Hz	Force factor	2.3/6.8	N/A
Short term max. power	220/250	W	Free air resonance	1200/26	Hz
Long term max. power	90/80	W	Moving mass	0.3/13.7	g
Sensitivity (1W/1m)	88.5/87	dB	Suspension compliance	-/2.7	mm/N
Voice Coil Diameter	26/39	mm	Suspension mech. resistar	nce -/1.45	Ns/m
Voice coil height	1.5/12	mm	Effective piston area	7.0/120	sq. cm
Air gap height	2.0/6.0	mm	•		•
Linear coil travel (p-p)	0.5/6.0	mm	Vas	-/52	Liters
Max. coil travel (p-p)	-/20	mm	Qms	-/1.63	
Magnet weight	-/0.84	Kg	Qes	-/0.31	
Total weight	1.91	Kg	Qts	-/0.26	





Crossover for All Coaxials \$36.50 each.



	 ∪	
↑		
-	<u>~</u>	

1" = 25.4mm = 2.54cm

Driver Dimensions in millimeters, from smallest t	o iargest size.	25.4mm = 1	= 2.54cm	
Unit	A	В	C	D
	mm	mm	mm	mm
(H0625) / (H1396)&(H1397)	60 / 53	2.1 / 0.5	18 / 21.5	45.9 / 46
(H1406) (truncated flat part 54.7mm)	70.5	4	21.6	46
(H1283), *(H1461	97.7	3.5	24, *30.5	73, *66
(H1210), (H1213)	103.8	3.5	28.4	74.5
(H0881), (H1147), (H1149), (H1212), (H1189)	103.8	3.5	39.5	74.8
(H0831), (H1211)	103.8	3.6	24.4	74.8
(H1322), H(1318), *(H1499)	103.8	6	24.5, *59.3	73
(E0038), (E0039), (E0040)	110.3	5.5	37.5	75
(E0006), (E0036), *(E0011), (E0047)	110.4	6.3	53, *35	75
(E0021), (H1207), (H1152), *(H1304)	120.4	5	58.5, *55.5	95.8
(E0015), (H1455),(H1141), (H1216), (H1262), *(E0041)	146	4.2	67.3, *75.5	112
(E0037), (E0043)	146	4.2	77	112
(E0049), (H1480)	146	5	73.5	126
(H9928) passive radiator	170.4	3.8	42.5	145.3
(H1350),(E0018), (E0017), (H1224), (H1215), (H1456) *(E0042)	176	5.2	80, *81	145.2
(H1143), (E0027)	176	5.2	100.3	145.2
(H1144), (H1333), *(H1353)	176	5.2	100.5, *84	145.2
(H9901) passive radiator	215.4	4.7	51	186.8
(E0022), (E0045), (H1208), (H1252), (H1288)	221.4	5.5	90	186.4
(H9902) passive radiator	261.2	4.2	58	229
(E0046),(E0026), (H1209), (H1305), *(H1316)	269	5.8	107.5, *100.5	232.2

Driver Dimensions in millimeters from smallest to largest size 25 4mm - 1" - 2 54cm

Seas

In the late 1920s, at the Norwegian Institute of Technology (NTH), the first Norwegian electrodynamic loudspeaker drivers were designed. Ever since, Norwegian engineers have been leading the technology race in driver design. From its founding in 1950 as a spin-off of the Norwegian radio manufacturers Radionette and Tandberg, SEAS has been dedicated to creating loudspeakers with superior sound reproduction.

A company owned by its employees, SEAS takes pride in the drivers it has tailored to meet specific customer demands and in the major role it plays in creating the "sound experience" of the contemporary Hi-Fi market.


W14RC25-S-08 \$19.40



Silver Flute

- 5-1/2"
- Shielded Magnet
- Wool Cone
- Cast Frame
- 25mm VC Ø
- Rubber Surround
- F3 of 75Hz in 0.32 ft³ sealed enclosure

Re	7.3	Ohms	BL	5.76	TM
Sensitivity	87	dB	X-max	3.5	mm
Power	60	watts	Le @ 1kHz	0.79	mΗ
Fs	43.5	Hz	Frame Ø	142	mm
Qms	3.37		Cutout Ø	122	mm
Qes	0.46		Depth	75	mm
Qts	0.40		Krm	0.967	mΩ
Vas	18.9	Ltrs	Kxm	11.129	mΗ
Mms	7.63	g	Erm	0.875	
Cms	1757.5	μ M/N	Exm	0.697	
Sd	0.0087	M ²	Box Rec.: 9 lite	ers sealed	
ALIDIO D	DECICION . MA	4D00F 0 00			




W17RC38-04 \$24.60




Silver Flute

- 6-1/2"
- Wool Cone
- Cast Frame
- 38mm VC Ø
- Rubber Surround
- Vented Pole Piece
- F3 of 75Hz in 0.21 ft³ vented

Re	3.7	Ohms	BL	7.31	TM
Sensitivity	91.5	dB	X-max	5	mm
Power	80	watts	Le @ 1kHz	0.53	mΗ
Fs	37.5	Hz	Frame Ø	167	mm
Qms	1.52		Cutout Ø	147	mm
Qes	0.28		Depth	75	mm
Qts	0.24		Krm	1.370	mΩ
Vas	25.6	Ltrs	Kxm	17.805	mΗ
Mms	17.4	g	Erm	0.818	
Cms	1036.1	μ M/N	Exm	0.599	
Sd	0.0132	M ²	Box Rec.: 6 lite	ers vented 1.5	" Øx 5.5"L




W17RC38-S-04 \$30.70





- Wool Cone
- Shielded Magnet
- Cast Frame
- 38mm VC Ø
- Rubber Surround
- F3 of 50Hz in 0.48 ft³ vented

Re	3.7	Ohms	BL	6.02	TM
Sensitivity	90	dB	X-max	5	mm
Power	80	watts	Le @ 1kHz	0.51	mΗ
Fs	43.1	Hz	Frame Ø	167	mm
Qms	1.83		Cutout Ø	147	mm
Qes	0.42		Depth	93	mm
Qts	0.34		Krm	1.025	mΩ
Vas	22.4	Ltrs	Kxm	15.716	mΗ
Mms	15.1	g	Erm	0.844	
Cms	903.8	μ M/N	Exm	0.607	
Sd	0.0132	M ²	Box Rec.: 14 li	ters vented 2"	Øx 5.6"L




W17RC38-08 \$24.60



Silver Flute

- 6-1/2"
- Wool Cone
- Cast Frame
- 38mm VC Ø
- Rubber Surround
- Vented Pole Piece
- F3 of 60Hz in 0.42 ft³ vented enclosure

Re	7.3	Ohms	BL	8.26	TM
Sensitivity	89	dB	X-max	5	mm
Power	80	watts	Le @ 1kHz	0.94	mΗ
Fs	40.5	Hz	Frame Ø	167	mm
Qms	1.52		Cutout Ø	147	mm
Qes	0.36		Depth	75	mm
Qts	0.29		Krm	2.001	mΩ
Vas	28.2	Ltrs	Kxm	36.187	mΗ
Mms	13.57	g	Erm	0.836	
Cms	1140.0	μ M/N	Exm	0.582	
Sd	0.0132	M ²	Box Rec.: 12 lt	rs, 2" Ø V x 6"	L




W17RC38-S-08 \$30.70



Silver Flute

- 6-1/2"
- Wool Cone
- Shielded Magnet
- Cast Frame
- 38mm VC Ø
- Rubber Surround
- F3 of 54Hz in 0.46 ft³ vented enclosure

Re	7.3	Ohms	BL	8.33	TM
Sensitivity	88	dB	X-max	5	mm
Power	80	watts	Le @ 1kHz	0.89	mΗ
Fs	41.3	Hz	Frame Ø	167	mm
Qms	1.45		Cutout Ø	147	mm
Qes	0.40		Depth	93	mm
Qts	0.31		Krm	2.424	mΩ
Vas	24.3	Ltrs	Kxm	30.319	mΗ
Mms	15.1	g	Erm	0.815	
Cms	982.3	μ M/N	Exm	0.597	
Sd	0.0132	M ²	Box Rec.: 13 I	trs, 2" Ø V x 6-	1/4" L




W20RC38-04 \$31.20



Silver Flute

- 8"
- Wool Cone
- Cast Frame
- 38mm VC Ø
- Rubber Surround
- Vented Pole Piece
- F3 of 60Hz in 0.53ft³ vented enclosure

Re	3.7	Ohms	BL	7.9	TM
Sensitivity	93.7	dB	X-max	5	mm
Power	100	watts	Le @ 1kHz	0.52	mΗ
Fs	31.0	Hz	Frame Ø	203	mm
Qms	1.51		Cutout Ø	183	mm
Qes	0.27		Depth	86	mm
Qts	0.23		Krm	1.324	mΩ
Vas	72.3	Ltrs	Kxm	17.644	mΗ
Mms	23.7	g	Erm	0.819	
Cms	1111.3	μ M/N	Exm	0.596	
Sd	0.0214	M^2	Box Rec.: 15	liters, 2" ØV x 3	3.75" L



W20RC38-08 \$31.20




Silver Flute

- 8"
- Wool Cone
- Cast Frame
- 38mm VC Ø
- Rubber Surround
- Vented Pole Piece
- F3 of 60Hz in 0.64 ft³ vented enclosure

Re

Re	7.3	Ohms	BL	10.1	IМ
Sensitivity	91	dB	X-max	5	mm
Power	100	watts	Le @ 1kHz	0.92	mΗ
Fs	30.8	Hz	Frame Ø	203	mm
Qms	1.30		Cutout Ø	183	mm
Qes	0.28		Depth	86	mm
Qts	0.23		Krm	1.65	m Ω
Vas	83.3	Ltrs	Kxm	32.793	mΗ
Mms	20.9	g	Erm	0.853	
Cms	1281.1	μ M/N	Exm	0.591	
Sd	0.0214	M ²	Box Rec.: 16 I	itrs, 2" Ø V x 4'	' L



W20RC38-S-08 \$38.95



7.3

Silver Flute

- 2"
- Wool Cone
- Cast Frame
- 38mm VC Ø
- Rubber Surround
- **Shielded** magnet
- F3 of 45Hz in 1 ft³ vented enclosure


7.57

TM

Sensitivity	88	dB	X-max	5	mm
Power	100	watts	Le @ 1kHz	0.92	mΗ
Fs	29.5	Hz	Frame Ø	203	mm
Qms	1.81		Cutout Ø	183	mm
Qes	0.53		Depth	103	mm
Qts	0.41		Krm	1.754	mΩ
Vas	84.7	Ltrs	Kxm	25.339	mΗ
Mms	22.3	g	Erm	0.849	
Cms	1302.1	μ M/N	Exm	0.620	
Sd	0.0214	M^2	Box Rec.: 30 I	itrs, 2" Ø V x 3.	75" L
+110				A	P 1

BL

Ohms





Tymphany Vifa Line www.tymphany.com



Model #	Description	Ω	Price
V-	Line "XT" High Performance Speake	rs	
XT19TD00	3/4" Ring Radiator tweeter	4	\$39.40
XT25SC50	Small Shielded 1" ring radiator	4	\$33.40
XT25TG30	1" Ring Radiator tweeter	4	\$48.20
XT18WH09	7" Wood fiber cone mid/bass	8	\$70.80
XT18WO09	7" Wood fiber cone mid/bass	8	\$82.00
V-Line	e "PL" Premium Speaker and Classic	Serie	S
DX25TG05	1" Fabric dome tweeter	4	\$27.75
D19TD05	¾" Polymer dome tweeter	8	\$15.20
D25AG35	1" Aluminum dome, chambered	6	\$33.85
D27TG35	1" Fabric dome tweeter, chambered	6	\$28.15
D27TG45	1" Fabric dome tweeter, bulged fp	6	\$28.25
D26NC55	1" Fabric dome neo., w/heat sinks	6	\$28.90
D26NC05	1" Fabric dome, neo., grill	6	\$28.50
VFM	Flush mount kit; D25AC/D26NC	ea	\$3.10
VWM	Wedge mount kit; D25AC/D26NC	ea	\$2.35
H26TG35	Horn 1" Fabric dome tweeter	6	\$30.35
D75MX41	3" Fabric dome midrange	8	\$76.05
PL11MH09	4 1/2" Paper cone midrange	8	\$54.90
PL11WG09	4 ½" Paper cone mid/bass	4/8	\$47.35
PL11WH09	4 ½" Paper cone mid/bass	4/8	\$54.00
PL14WJ09	5 ½" Paper cone mid/bass	4/8	\$64.55

Model #	Description	Ω	Price
PL18WO09	7" Paper cone mid/bass	4/8	\$76.05
PL22WR09	8" Paper cone woofer	4/8	\$97.45
PL26WR09	10" Paper cone woofer	4/8	\$107.90
V-Lin	ne TG Series Full Range Glass Fiber (Cones	
TG9FD10	3.5" Full Range	4	\$29.50
TG9FSD10	Shielded 3.5" Full Range	4/8	\$33.95
All items li	sted below are in stock, but being dis	sconti	nued.
,	Vifa "Classic" Tweeters (discontinued)	
D26TG05	1" Fabric dome tweeter	6	\$21.70
D27SG05	Shielded 1" Fabric dome tweeter	6	\$28.15
D27TG05	1" Fabric dome tweeter	6	\$21.90
Vifa "	Classic" Mid/Bass & Woofers (discon-	tinued	1)
M13SG09	Shielded 5" Paper cone mid/bass	8/16	\$42.00
P13WH00	5" Poly cone mid/bass	8	\$43.75
P17SJ00	Shielded 6.5" Poly cone mid/bass	8	\$58.60
P17WJ00	6.5" Poly cone mid/bass	4/8	\$45.20
P21WO20	8" Poly cone woofer	8	\$63.30
P21WO39	8" Poly cone woofer	8	\$64.80

Vifa Big A/V Kit



22" T x 9 1/4" W x 13 3/4" D

The Big A/V is a shielded Audio/Video speaker using a 1" textile dome tweeter and two 6.5" poly cone woofers in a D'Appolito arrangement. The speakers offers fantastic imaging and depth, delivering accurate voicing as well as impressive bass. Even if

you're not prepared to go for the complete surround sound system, the Big A/V will deliver enough bass and excitement to greatly enhance your movie experience.

The cabinet is oak veneered with solid oak corners in either a clear finish or a black painted finish. A black grill covers the front and the back is painted black. The kit comes with the assembled cabinets, loudspeakers, all brass gold plated input cups, assembled crossovers, foam pads, wool stuffing and screws.

The kit can be ordered with either the Vifa D27SG05 tweeter or the Seas T25CF-001 Excel tweeter. See web for more info.

Big A/V with D27SG-05 tweeter without cabinets: \$187.50 each (Cabinet not available) Big A/V with T25CF-001 tweeter without cabinets: \$246.87 each (Cabinet not available)

Vifa Studio Kit



The Studio is a small monitor type speaker using the new Vifa XT ring radiator tweeter and the Vifa Premium Line 5" woofer. A 6" passive radiator is used on the back to tune the enclosure and extend the bass response. The frequency range is from 45Hz to 20kHz with very impressive bass for such a small

12" T x 8" W x 10 1/4" D speaker.

The new XT tweeter has exceptional clarity and detail, but at the same time being warm and non-intrusive. The woofer is a coated paper cone with a new type of termination to the rubber surround. The woofer frame is cast magnesium and is optimized for low distortion. A paper cone woofer offers the most natural and vivid midrange reproduction.

The cabinet is oak veneered with solid oak corners in either a clear or black stained oak finish. A black grill covers the front and the back of the cabinet is painted black. The kit comes with the assembled cabinets, loudspeakers, all brass gold plated input cups, assembled crossovers, foam pads, wool stuffing and screws.

Price per Pair without Cabinets: \$315.00 (Cabinets not available)


XT19TD00-04



- 19mm Dual concentric diaphragm
- Non-reflective dual chamber
- Controlled directivity
- Wave-guide center plug
- copper-clad aluwire VC
- Flange 94mm
- Cutout 68.5mm

Znom Re Le@1kHz fs Qms Qes Qts Mms	681.9 2.39 0.82 0.61	
Mms	0.61	а
Sd	4.55	

1.7	Tm
-	ltrs
0.35	mm peak
19	mm
89	dB
	W
	g
	0.35 19




XT25TG30-04



- 25mm Dual concentric diaphragm
- Non-reflective dual chamber
- Controlled directivity
- Wave-guide center plug
- copper-clad aluwire VC and braided leads
- Flange 104mm
- Cutout 73.5mm, D 41mm

Znom	4	ohm
Re	3.0	ohm
Le@1kHz	-	mΗ
fs	500	Hz
Qms	2.50	
Qes	0.71	
Qts	0.55	
Mms	.30	g
Cms	-	mm/N

Sd	5.4	cm ²
BL	2.5	Tm
Vas	0.02	ltrs
Xmax	0.5	mm peak
VC Ø	25	mm
Sensitivity		
2.83V / 1m	91.5	dB
Nom. Power DIN	140	W
Magnet weight	240	a




XT25SC50-04



Znom	4	ohm
Re	3.1	ohm
Le@1kHz	0.04	mΗ
fs	950	Hz
Qms	-	
Qes	-	
Qts	-	
Mms	.30	g
Cms	-	mm/N

- 25mm Dual concentric diaphragm
- Ring formed chamber
- Controlled directivity
- Heat sink on magnet
- Gasket
- Wave-guide center plug
- Neodymium magnet
- Flange 65mm
- Cutout 46.2mm, D 21mm

Sd	6.0	cm ²
BL	2.3	Tm
Vas	-	ltrs
Xmax	0.5	mm peak
VC Ø	25	mm
Sensitivity		
2.83V / 1m	92.5	dB
Nom. Power DIN	80	W
Magnet weight	-	g




XT18WH09-08



Znom	8	ohm
Re	5.5	ohm
Le@1kHz	0.54	mΗ
fs	38	Hz
Qms	1.83	
Qes	0.46	
Qts	0.37	
Mms	10.7	g
Rm	1.4	Ns/m

- 7" Wood fiber cone mid-woofer
- Phase integrated dust cap
- Low resonance multi-roll surround
- Airflow optimized low distortion chassis and magnet system
- Flange 180mm
- Special installation inst.

Sd	129	cm ²
BL	5.5	Tm
Vas	39	Itrs
Xmax	5	mm peak
VC Ø	25	mm
Sensitivity		
2.83V / 1m	87	dB
Nom. Power DIN	-	W
Magnet weight	415	g



XT18WO09-08

Znom

Le@1kHz

Re

fs Qms

Qes

Qts

Rm

Mms



ohm

Hz

5.8 ohm

5.87

0.39

0.37

11.1 g


0.43 Ns/m

38

0.54 mH

- 7" Wood fiber cone mid-woofer
- Phase integrated dust cap
- Low resonance multi-roll surround
- Airflow optimized low distortion chassis and magnet system
- Flange 180mm
- Special installation inst.

Sd	129	cm ²
BL	6.2	Tm
Vas	38	Itrs
Xmax	4.5	mm peak
VC Ø	25	mm
Sensitivity		
2.83V / 1m	88	dB
Nom. Power DIN	-	W
Magnet weight	698	g



DX25TG05-04

Znom

Le@1kHz

Re

Qms

Qes

Qts

Mms

Cms




650

•	1" Fabric high dispersion
	dome tweeter

- Low compression chamber design
- Light weight voice coil
- High power handling
- High Sensitivity
- Flange 104mm
- Cut-out 75mm
- Depth 26mm

4	ohm	Sd	7.0	cm²
2.75	ohm	BL	2.2	Tm
	mH	Vas	-	ltrs
50	Hz	Xmax	-	mm peak
4.32		VC Ø	25	mm
0.79		Sensitivity		
0.67		2.83V / 1m	93.5	dB
0.42	g	Nom. Power DIN	-	W
-	mm/N	Magnet weight	240	g




D75MX-41-08



- 3" dome midrange
- Precoated fabric diaphragm
- Low moving mass
- Internal ferrite magnet
- Very linear impedance
- Flange 152m3m
- Cutout 120.7mm
- Depth 31.5mm

Znom	8	ohm	Sd	55	cm ²
Re	5.9	ohm	BL	4.7	Tm
Le@1kHz	-	mΗ	Vas	-	ltrs
fs	350	Hz	Xmax	-	mm peak
Qms	-		VC Ø	76	mm
Qes	-		Sensitivity		
Qts	-		2.83V / 1m	92	dB
Mms	3.1	g	Nom. Power DIN	80	W
Cms	-	mm/N	Magnet weight	240	g
7.5					



PL11WG-09-08




Znom	8	ohm
Re	5.6	ohm
Le@1kHz	.61	mΗ
fs	69	Hz
Qms	2.20	
Qes	0.60	
Qts	0.47	
Mms	5.9	g
Cms	-	•

- PREMIUM LINE 4.5" mid-woofer
- Non-resonant cone
- Very flat response
- Rigid magnesium basket
- Long linear excursion
- Gold plated terminals
- Flange 125mm
- Cut-out 101mm
- Depth 59mm

Sd

Ou	00	OIII
BL	4.9	Tm
Vas	4.25	ltrs
Xmax	3	mm peak
VC Ø	25	mm
Sensitivity		
2.83V / 1m	85	dB
Nom. Power DIN	35	W
Magnet weight	8.5	OZ.



PL14WJ-09-08



ohm

5.8 ohm

.49 mH

2.20

0.46

0.38

8.2 g - mm/N

Hz

Znom

Le@1kHz

Re

fs

Qms

Qes

Qts

Mms

Cms

Znom

Le@1kHz

Re

fs

Qms

Qes

Qts

Mms

Cms

- PREMIUM LINE 5" mid-woofer
- Non-resonant cone
- Very flat response
- Rigid magnesium basket
- Long linear excursion
- Gold plated terminals
- Flange 149mm
- Cut-out 115mm
- Depth 71mm

80	cm ²
5.5	Tm
13	Itrs
3	mm peak
32	mm
86	dB
50	W
14.5	OZ.
	5.5 13 3 32 86 50

PL18WO-09-08



Znom	8	ohm
Re	5.8	ohm
Le@1kHz	.85	mΗ
fs	39	Hz
Qms	2.46	
Qes	0.40	
Qts	0.34	
Mms	17.5	g
Cms	-	mm/N


SPL [dB]

16 8

• PREMIUM LINE 7" woofer

- Non-resonant cone
- Very flat response
- Rigid magnesium basket
- Long linear excursion
- Gold plated terminals
- Flange 180mm
- Cut-out 145mm
- Depth 84mm

Sd	132	cm ²
BL	7.8	Tm
Vas	25	Itrs
Xmax	4	mm peak
VC Ø	40	mm
Sensitivity		
2.83V / 1m	87	dB
Nom. Power DIN	100	W
Magnet weight	24.7	OZ



PL22WR-09-08



ohm

Hz

g

mm/N

5.9 ohm

2.7 mH

5.65

0.37

0.34

27

43

- PREMIUM LINE 8" woofer
- Non-resonant cone
- Very flat response
- Rigid magnesium basket
- · Long linear excursion
- Gold plated terminals
- Flange 225mm
- Cut-out 185mm
- Depth 99mm

Sd	224	cm ²
BL	10.9	Tm
Vas	56	Itrs
Xmax	4	mm peak
VC Ø	50	mm
Sensitivity		
2.83V / 1m	85.5	dB
Nom. Power DIN	125	W
Magnet weight	37	oz


PL26WR-09-08



Znom ohm 8 Re 5.9 ohm Le@1kHz 2.7 mΗ fs 27 4.33 Qms Qes 0.43 0.39 Qts Mms 51 mm/N Cms

- PREMIUM LINE 10" woofer
- Non-resonant cone
- Very flat response
- Rigid magnesium basket
- Long linear excursion
- Gold plated terminals
- Gold plated terminal
- Flange 271mm
- Cut-out 232mm
- Depth 107mm

Sd BL	337 10.9	cm² Tm
Vas	110	Itrs
Xmax	4	mm peak
VC Ø	50	mm
Sensitivity		
2.83V / 1m	87	dB
Nom. Power DIN	125	W
Magnet weight	37	OZ



SPL [dB]

90

80

70

16.0

60

0.0

16.0

50

10.0

50

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.0

10.

TG9FD10-04

Znom Re

fs

Qms

Qes Qts

Mms Rm

Le@1kHz



3.2 ohm

Hz

Ns/m

0.12 mH 82

2.90 0.70

0.56 2.45 g

- 3 1/2" Full Range
- NRSC Glass Fiber Cone
- Copper cap on pole piece
- Polymer Chassis
- Frequency Response 100Hz to 10kHz
- Flange 98mm Square
- Cut-out 78.5mm
- Depth 38mm
- Flange Thickness 3.2mm

Sd	38	cm ²
BL	2.4	Tm
Vas	3.15	ltrs
Xmax	2.6	mm peak
VC Ø	20	mm
Sensitivity		
2.83V / 1m	85.5	dB
Nom. Power DIN	-	W
Magnet weight	105	g




TG9FSD10-04

Znom	4	ohm
Re	3.2	ohm
Le@1kHz	0.12	mΗ
s	82	Hz
Qms	2.90	
Qes	0.70	
Qts	0.56	
Mms	2.45	g
Rm	-	Ns/m

• 3 1/2" Full Range

- NRSC Glass Fiber Cone
- Copper cap on pole piece
- Polymer Chassis
- Frequency Response 100Hz to 10kHz
- Flange 98mm Square
- Cut-out 78.5mm
- Depth 38mm
- Shielded Magnet

Sd	38	cm ²
BL	2.4	Tm
Vas	3.15	ltrs
Xmax	2.6	mm peak
VC Ø	20	mm
Sensitivity		
2.83V / 1m	85.5	dB
Nom. Power DIN	-	W
Magnet weight	105	g



SPL [dB] 35 છ 16.63

TG9FSD10-08



Znom ohm Re 6.3 ohm Le@1kHz 0.12 mH fs 87 3.08 Qms Qes 0.87 Qts 0.68 Mms 2.2 Ns/m Rm

- 3 1/2" Full Range
- NRSC Glass Fiber Cone
- Copper cap on pole piece
- Polymer Chassis
- Frequency Response 100Hz to 10kHz
- Flange 98mm Square
- Cut-out 78.5mm
- Depth 38mm
- Shielded Magnet


Sinciaca	viasii	Ct
Sd	38	cm ²
BL	2.95	Tm
Vas	3.1	ltrs
Xmax	2.6	mm peak
VC Ø	20	mm
Sensitivity		
2.83V / 1m	82.5	dB
Nom. Power DIN	-	W
Magnet weight	105	a


D19TD-05-08



- 3/4" dome tweeter
- High loss diaphragm
- Magnetic fluid
- High power version
- Good dispersion
- Flange 94mm
- Cut-out 68mm
- Depth 23mm

Znom	8	ohm	Sd	4.2	cm ²
Re	6.2	ohm	BL	2.6	Tm
Le@1kHz	-	mΗ	Vas	-	ltrs
fs	1700	Hz	Xmax	-	mm peak
Qms	-		VC Ø	19	mm
Qes	-		Sensitivity		
Qts	-		2.83V / 1m	89	dB
Mms	0.2g		Nom. Power DIN	80	W
Cms	-	mm/N	Magnet weight	105	g





D25AG-35-06



Znom 6 ohm
Re 4.6 ohm
Le@1kHz mH
fs 850 Hz
Qms Qes Qts Mms 0.3 g

mm/N

Cms

SPL [dB]

32 ss

Znom

Le@1kHz

Re

fs

Qms

Qes

Ots

Mms

- 1" dome tweeter
- Aluminum alloy diaphragm
- Magnetic fluid
- Double chamber
- Piston movement to above 20 hz
- Flange 104mm
- Cut-out 74.3mm
- Depth 40mm

Sd	7.1	cm ²
BL	3.3	Tm
Vas	-	Itrs
Xmax	-	mm peak
VC Ø	25	mm
Sensitivity		
2.83V / 1m	90	dB
Nom. Power DIN	100	W
Magnet weight	240	g


D27SG-05-06



Znom Re Le@1kHz fs Qms Qes Qts Mms	6 4.6 - 1000 - - - .3	ohm ohm mH Hz
Cms	-	mm/N

- 1" dome tweeter
- Shielded magnet
- Coated fabric with silk diaphragm
- Double magnet
- Linear response front plate, neutral design
- Flange 104mm
- Cut-out 79.3mm
- Depth 41.7mm

Sd	7.1	cm²
BL	2.7	Tm
Vas	-	Itrs
Xmax		mm peak
VC Ø	26	mm
Sensitivity		
2.83V / 1m	92	dB
Nom. Power DIN	80	W
Magnet weight	432	kg



D27TG-05-06



ohm

mΗ

Hz

4.6 ohm

2.15

1.19

0.77

0.3 g

1000

- 1" dome tweeter
- Coated fabric with silk diaphragm
- Linear response front plate, neutral design

7.1 cm²

26

92

Tm

Itrs

mm

dB

W

mm peak

- Magnetic fluid
- Flange 104mm
- Cut-out 73.5mm
- Depth 31.5mm

Nom. Power DIN 100

Sd

BL

Vas

Xmax

VC Ø

Sensitivity 2.83V / 1m

vee	ter		D27TG-35-06	
	1.1	*11		

Frequency [Hz]




Znom	6	ohm
Re	4.6	ohm
Le@1kHz	-	mΗ
fs	650	Hz
Qms	0.95	
Qes	0.77	
Qts	0.43	
Mms	.3	g
Cms	-	mm/N

- 1" dome tweeter
- Coated fabric with silk diaphragm
- Linear response frontplate, neutral design
- Magnetic fluid
- Braids and rear chamber
- Flange 104mm
- Cut-out 73.5mm
- Depth 55mm

Sd	7.1	cm
BL	2.7	Tm
Vas	-	ltrs
Xmax	-	mm peak
VC Ø	26	mm
Sensitivity		
2.83V / 1m	91	dB
Nom. Power DIN	100	W
Magnet weight	240	g

Frequency [Hz]



SPL [dB]

90

90

16.0

16.0

10.0

20.0

50.0

10.0

20.0

50.0

10.0

20.0

50.0

10.0

20.0

50.0

10.0

20.0

50.0

10.0

20.0

50.0

10.0

20.0

50.0

10.0

20.0

50.0

10.0

20.0

50.0

10.0

20.0

50.0

10.0

20.0

50.0

10.0

20.0

50.0

10.0

20.0

50.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

10.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

20.0

D27TG-45-06




Znom Re ohm 4.6 Le@1kHz mΗ 650 fs Hz Qms 0.95 Qes 0.77 Qts 0.43 Mms .3 g

Cms

- 1" dome tweeter
- · Coated fabric with silk diaphragm
- · Linear response frontplate
- · Magnetic fluid
- Braids and rear chamber
- Diameter 104mm
- Cut-out 73.5mm
- Depth 55mm

Sd	7.1	cm ²
BL	-	Tm
Vas	-	Itrs
Xmax		mm peak
VC Ø	26	mm
Sensitivity		
2.83V / 1m	91	dB
Nom. Power DIN	100	W
Magnet weight	240	g



mm/N

H26TG-35-06




Znom	6	ohm
	-	
Re	4.6	ohm
Le@1kHz	-	mΗ
fs	940	Hz
Qms	-	
Qes	-	
Qts	-	
Mms	.33	g
Cms	-	mm/N

- 1" imp.transformer
- Chambered
- Fabric diaphragm
- Butterfly VC assembly
- Improved air load on diaphragm
- · Magnetic fluid
- Flange 104mm
- Cut-out 73.5mm

 Depth 	57.5mm
---------------------------	--------

Sd	7.1	cm ²
BL	3.3	Tm
Vas	-	Itrs
Xmax	-	mm peak
VC Ø	25	mm
Sensitivity		
2.83V / 1m	96	dB
Nom. Power DIN	100	W
Magnet weight	240	g




D26NC-55-06



- 1" textile dome tweeter
- Neodymium magnet
- Heat sink for increased power handling and lower distortion
- · Ferrofluid cooled
- Truncated face plate
- Flange 70mm (54Trun.)
- Cut-out 49.2mm
- Depth 23mm

Znom	6	ohm
Re	4.6	ohm
Le@1kHz	0.05	mΗ
fs	1500	Hz
Qms	1.48	
Qes	2.29	
Qts	0.90	
Mms	0.33	g
Cms	-	mm/N

Sd	7.1	cm ²
BL	2.5	Tm
Vas	-	ltrs
Xmax	0.25	mm peak
VC Ø	25	mm
Sensitivity		
2.83V / 1m	91	dB
Nom. Power DIN	50	W
Magnet weight	0.01	kg




M13SG-09-08



Znom	8	ohm
Re	5.6	ohm
Le@1kHz	-	mΗ
fs	54	Hz
Qms	1.50	
Qes	0.46	
Qts	0.35	
Mms	6.5	g
Cms	-	mm/N

- 5" woofer
- Magnetically shielded
- Very smooth frequency response
- High damping rubber surround
- Good for bass reflex
- Flange 140mm
- Cut-out 112.3mm
- Depth 73.6mm

80	cm ²
5.2	Tm
12	ltrs
2	mm peak
25	mm
88	dB
35	W
344	g
	5.2 12 2 25 88



P13WH-00-08

Znom

Le@1kHz

Re

fs

Qms

Qes

Qts

Mms

Cms



60

1.38

0.43

0.33

7.5 g

ohm

ohm


mΗ

Hz

mm/N

- 5" Mineral filled polycone
- Rubber surround
- Magnesium basket
- · Smooth roll off
- Neutral midrange
- Vented pole piece
- Flange 140mm
- Cut-out 112.3mm
- Depth 64.5mm

Sd	86	cm ²
BL	6.0	Tm
Vas	10	Itrs
Xmax	4	mm peak
VC Ø	25	mm
Sensitivity		
2.83V / 1m	88	dB
Nom. Power DIN	40	W
Magnet weight	415	g



P17SJ-00-08




Znom	8	ohm
Re	5.6	ohm
Le@1kHz	.84	mΗ
fs	41	Hz
Qms	1.28	
Qes	0.48	
Qts	0.35	
Mms	12	g
Cms	-	mm/N

•	6-1	/2"	woofer
---	-----	-----	--------

- · Magnesium basket
- Mineral filled polycone
- Rubber surround
- Smooth response
- · Magnetically shielded
- Flange 170mm
- Cut-out 145.8mm
- Depth 93.1mm

Sd	136	cm ²
BL	6	Tm
Vas	33	ltrs
Xmax	4.5	mm peak
VC Ø	32	mm
Sensitivity		
2.83V / 1m	87/87	dB
Nom. Power DIN	20	W
Magnet weight	721	g



P17WJ-00-08



- 6-1/2" woofer
- · Magnesium basket
- Mineral filled polycone
- Rubber surround
- Smooth response
- Ideal for bass reflex
- Flange 170mm
- Cut-out 145.5mm
- Depth 75.1mm

P21WO-20-08



- 8" woofer
- Magnesium basket
- Mineral filled poly cone

cm² Tm

Itrs mm peak

mm

dΒ

W

g


- Rubber surround
- Flat response
- Ideal for bass reflex
- Flange 215mm
- Cut-out 186.5mm
- Depth 80.4

Znom	8 ohm
Re	5.8 ohm
Le@1kHz	.55 mH
fs	37 Hz
Qms	1.55
Qes	0.45
Qts	0.35
Mms	14 g
O	/A I

Sd	136	cm²
BL	6.5	Tm
Vas	34.7	ltrs
Xmax	4.5	mm peak
VC Ø	32	mm
Sensitivity 2.83V / 1m Nom. Power DIN Magnet weight	88 70 415	dB W g

Cms	-	mm/N	Magne	t weight 4	·15 g	
SPL [dB]						
90						
80						
70 32.0				M		
60 85-				V		
50 20 5	0 100	200 5	i00 1K	2K 5K	10K 20K	40K

Znom	8 ohm	Sd 23	5
Re	5.7 ohm	BL	7.4
Le@1kHz	0.9 mH	Vas 113	3
fs	28 Hz	Xmax	4
Qms	1.6	VC Ø 40	0
Qes	0.41	Sensitivity	
Qts	0.33	2.83V / 1m 9	1
Mms	22.5 g	Nom. Power DIN 80	0
Cms	- mm/N	Magnet weight 698	8




P21WO-39-08



- 8" Polypropylene cone woofer
- Rubber surround
- Cast magnesium frame
- Long throw / low distortion motor
- Good for vented boxes
- Flange 215.2mm
- Cut-out 186.5mm
- Depth 82.1mm

Znom	8 ohm	Sd	235.0	cm ²
Re	5.5 ohm	BL	8.5	Tm
Le@1kHz	1.0 mH	Vas	85	ltrs
fs	26 Hz	Xmax	6.0	mm peak
Qms	2.38	VC Ø	40	mm
Qes	0.44	Sensitivity		
Qts	0.37	2.83V / 1m	88	dB
Mms	32.0 g	Nom. Power DIN	80	W
Cms	- mm/N	Magnet weight	0.7	kg




D26NC-05-06




Znom	6	ohm
Re	4.6	ohm
Le@1kHz	-	mΗ
fs	1800	Hz
Qms	-	
Qes	-	
Qts	-	
Mms	.27	g
Cms	-	mm/N

- 1" textile dome autosound tweeter
- Compact construction
- Butterfly VC assembly
- Magnetic fluid
- Metal grill
- Neodymium magnet
- Flange 45mm
- Cut-out 45mm
- Depth 22mm

Sd	7.1	cm ²
BL	2.5	Tm
Vas	-	Itrs
Xmax	-	mm peak
VC Ø	25	mm
Sensitivity		
2.83V / 1m	91.5	dB
Nom. Power DIN	30	W
Magnet weight	11	g










Home Theater Speakers from Madisound & Vifa

If you have been looking for Home Theater speakers that are better than the current choices on the market, Madisound and Vifa have some good news for you. Vifa has designed exceptional shielded high fidelity loudspeakers for this purpose, and Madisound has matched these drivers with precise crossovers and beautiful oak veneer cabinets.


The following designs were developed using Madisound's anechoic chamber, Audio Precision measurement and Leap analysis. All three speakers use the Vifa M13SG09, a 13cm paper cone, cast frame woofer. The tweeter is the D27SG05, which is also shielded and has a 27mm textile dome. The cabinets are no longer available, so these are truly DIY now. Everything you need to complete the system is included and the crossovers are pre-assembled.

Precut cabinets are no longer available for these systems.



Nominal Impedance:

Frequency range ±3dB: 55Hz to 35KHz - Vented



Pdf fill in form.



Return Policy: We will accept returns of purchases for refund if items are in unused condition, without evidence of mounting or soldering, for a period of 45 days after purchase. Product received in damaged condition should be reported immediately, and the original shipping carton should be retained for UPS inspection. Defective products should be returned with a note explaining the problem, and a daytime phone number to reach you for additional information. Package returns carefully; manufacturers will not warranty damaged products. We handle most warranty claims directly, and will usually exchange defective units within two weeks of return. Disputes over driver performance will be handled through the manufacturer.

			Check	here if the shippin	g address is the	same.
Sold to:			Ship to:			
			1			
Email:			Daytime	Phone:		
		(Into			مسماسيات سامسم	
Quantity	Dagari		mational	Customers must		
Qualitity	Descri	ption			Unit Price	Total Price
Shipping ch	arges are exactly what UPS or the				Sub-total	
	ervice charges us, there are no ad-			5.5% Sales T	Tax (WI only)	
	kaging or handling fees. We ask			Charges <i>Estimate</i>	(add 10%)	
_	nclude 10% for shipping, we will	H	awaii & Ul	PS Blue add 20 %		
bill you or i	refund to you any difference.				TOTAL	
Shipping	on International Orders will be quoted	after the	e boxes h	ave been weighed.	We ship FedEx	or UPS Intl.
		PAY	MENT			
☐ Visa	MasterCard, Discover; #			Fv	pires	
,	2.				/ /	′ /
CHE	CK (personal checks must clear befo	re shipp	oing)	Commencent		
	u.	11	<i>5</i> /	Comments:		
C.O.1	D. Money Order / Certified Check				1	
				Money O	rder	

Click on the plus sign within the box to the left in order to expand this bookmark.