

Car Audio Loudspeakers



**“design innovation
achieves superior sound quality
in an automotive environment”**

McIntosh has been developing and producing loudspeakers for over 25 years. Many of these systems have been awarded patents for their unique technology and design. Our focus has been dedicated to one simple philosophy, to create speakers capable of reproducing music as accurate as possible with superior imaging and the lowest possible distortion.

Mobile sound systems face unique challenges. Higher ambient noise levels typically demand greater output levels from small diameter drivers and the environment itself subjects speakers to excessive heat, moisture and vibration. LD/HP® technology, a patented McIntosh design, allows speakers to operate at high excursion and high output with no substantial increase in distortion. In addition, McIntosh utilizes special structural materials to ensure great resistance to heat, UV and moisture. The result is a speaker with unsurpassed clarity and dynamic capability.

This proven technology, together with a number of technical innovations has resulted in car audio loudspeakers that are meeting the performance challenges which are specific to the environment of a car.

**Patented LD/HP® Driver
High Excursion, Low Distortion Design
High Temperature Voice Coil Formers
Gold-Plated Terminals
Magnetic Fluid Cooling
Butyl Rubber Surround
Strontium Magnets
Die-Cast Aluminum Frame
Protective Metal Grille**

A Tradition of Excellence



McIntosh Laboratory, Inc. 2 Chambers Street, Binghamton, New York 13903-2699
Tel (607) 723-3512 • US Toll-Free (800) 538-6576 • Fax: (607) 724-0549 • www.mcintoshlabs.com

For the Consumer's Protection: In order to ensure the highest level of customer satisfaction, "new" McIntosh products may only be purchased over-the-counter or delivered and installed by an Authorized McIntosh Dealer. McIntosh products that are purchased over the Internet, by phone or mail order are presumed to be "used" and do not qualify for any McIntosh Warranty. McIntosh does not warrant, in any way, products that are purchased from anyone who is not an Authorized Dealer or products that have had their serial number altered or defaced.

Car Audio Loudspeakers

MSS530

5 1/4" woofer/midranges, 1" tweeter drivers,
MN530 crossover networks



DESCRIPTION	FREQUENCY RESPONSE	SENSITIVITY	IMPEDANCE	POWER HANDLING	MAGNET
	80Hz to 20kHz	85dB	4Ω	120w	Strontium, Neodymium
CONE MATERIAL	SURROUND	MOUNTING DIAMETER/DEPTH		WEIGHT	
Woofer: Mica-filled polypropylene Tweeter: soft-dome	Rubber	Woofer 6.56" (16.7cm)/2.75" (7.0cm) Tweeter 2.12" (5.4cm)/.56" (1.4cm)		8.6 lbs. (3.9kg.)	

MSS630

6 1/2" woofer/midranges, 1" tweeter drivers,
MN630 crossover networks



FREQUENCY RESPONSE	SENSITIVITY	IMPEDANCE	POWER HANDLING	MAGNET
80Hz to 20kHz	85dB	4Ω	120w	Strontium, Neodymium
CONE MATERIAL	SURROUND	MOUNTING DIAMETER/DEPTH		WEIGHT
Woofer: Mica-filled polypropylene Tweeter: soft-dome	Rubber	Woofer 7.62" (19.4cm)/3" (7.6cm) Tweeter 2.12" (5.4cm)/.56" (1.4cm)		9.5 lbs. (4.3kg.)

Crossover Networks



MN530

Crossover networks
for use in
MSS530 system

MN630

Crossover networks
for use in
MSS630 system

DESCRIPTION	CROSSOVER FREQUENCY	LOW-PASS SLOPE	HIGH-PASS SLOPE	DIMENSIONS HxWxD	WEIGHT
Crossover networks for use in MSS530 system	2400Hz	12dB/ octave	12dB/ octave	5.2" x 2.7" x 1.4" (132cm x .686cm x .34cm)	1.6 lbs. (0.7kg.)
Crossover networks for use in MSS630 system	2500Hz	12dB/ octave	12dB/ octave	5.2" x 2.7" x 1.4" (132cm x .686cm x .34cm)	1.6 lbs. (0.7kg.)